

FCC ID: 2BLBN-JH2001

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in KDB 447498 D01 V06 and 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm², P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale, $\pi = 3.1416$;

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m

d_{Meas} is the measurement distance, in m

Test Result of RF Exposure Evaluation

For BT

Field strength (dBuV/m)	EIRP (dBm)	Max tune-up (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
84.47	-10.69	0.0853	0.00002	1.0	PASS

Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
2.4G WIFI	16.598	45.69	0.01144	1.0	PASS
5G WIFI	15.768	37.74	0.00945	1.0	PASS
WCDMA BAND 2	24.62	289.73	0.09135	1.0	PASS
WCDMA BAND 5	22.83	191.87	0.05161	0.549	PASS
LTE BAND 2	22.83	191.87	0.01962	1.0	PASS
LTE BAND 4	22.85	192.75	0.05185	1.0	PASS
LTE BAND 5	22.83	191.87	0.05161	0.549	PASS
LTE BAND 12	22.84	192.31	0.01967	1.0	PASS
LTE BAND 66	22.84	192.31	0.02784	0.466	PASS

Remark: antenna gain:

BT EDR: 1.0dBi

WIFI 2.4G: 1.0dBi

WIFI 5G: 2.0dBi

WCDMA BAND 2: 1.31dBi

WCDMA BAND 5: -2.89dBi

LTE Band 2: 1.31dBi

LTE Band 4: 1.31dBi

LTE Band 5: -2.89dBi

LTE Band 12: -1.38dBi

LTE Band 66: 1.31dBi

For Simultaneous transmitting, 1): The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.00002/1 + 0.01144/1 + 0.09135/1 = 0.10281 < 1$ Since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in the device is ≤ 1.0 , the EUT is considered to satisfy MPE compliance for simultaneous transmission operations.