

FCC TEST REPORT

FCC ID: 2BLEA-YC621

Report No. : SSP24090130-1E

Prepared For : Guangdong Yicheng Technology Co., Ltd

Product Name : Wireless magnetic power bank 5000mAh

Model Name : YC621

FCC Rule : FCC Part 15 Subpart C

Date of Issue : 2024-10-22

Prepared By : Shenzhen CCUT Quality Technology Co., Ltd.



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	Guangdong Yicheng Technology Co., Ltd Room 1001, No. 247 Huaide Road, Humen Town, Dongguan City, Guangdong Province,523927, China
Manufacturer:	Guangdong Yicheng Technology Co., Ltd Room 1001, No. 247 Huaide Road, Humen Town, Dongguan City, Guangdong Province,523927, China
Product Name:	Wireless magnetic power bank 5000mAh
Brand Name:	-
Main Model:	YC621
Series Models:	-
Test Standard:	FCC Part 15 Subpart C ANSI C63.10-2013
Date of Test	2024-09-12 to 2024-09-15
Test Result:	PASSED
Tested Engineer	<u>Colin Chen</u> (Colin Chen)
Project Manager:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)

Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.

CONTENTS

1. General Information.....5

 1.1 Product Information5

 1.2 Test Setup Information.....6

 1.3 Compliance Standards.....7

 1.4 Test Facilities.....7

 1.5 List of Measurement Instruments8

 1.6 Measurement Uncertainty8

2. Summary of Test Results9

3. Antenna Requirement10

 3.1 Standard and Limit.....10

 3.2 Test Result.....10

4. Conducted Emissions11

 4.1 Standard and Limit.....11

 4.2 Test Procedure.....11

 4.3 Test Data and Results12

5. Radiated Emissions15

 5.1 Standard and Limit.....15

 5.2 Test Procedure.....15

 5.3 Test Data and Results17

6. Occupied Bandwidth26

 6.1 Standard and Limit.....26

 6.2 Test Procedure.....26

 6.3 Test Data and Results26

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2024-10-22	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Wireless magnetic power bank 5000mAh
Trade Name:	-
Main Model:	YC621
Series Models:	-
Rated Voltage:	Input (Type-c port):5V/3A, 9V/2A Output (Type-c port):5V/3A, 9V/2.22A, 12V/1.67A (20W Max) Output (Wireless charging): 5W, 7.5W, 10W, 15W (15W Max)
Battery:	19.25Wh (5000mAh, 3.85V)
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	

Wireless Specification	
Wireless Standard:	Wireless charging
Operating Frequency:	110.5KHz-205kHz,
Modulation:	ASK
Antenna Gain:	0dBi
Type of Antenna:	Coil Antenna
Type of Device:	<input checked="" type="checkbox"/> Portable Device <input type="checkbox"/> Mobile Device <input type="checkbox"/> Modular Device

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	Wireless charging 15W	-	
TM2	Wireless charging 10W	-	
TM3	Wireless charging 7.5W	-	
TM4	Wireless charging 5W	-	
TM5	Wireless charging 15W+Chargiing	-	
TM6	Wireless charging 10W+Chargiing	-	
TM7	Wireless charging 7.5W+Chargiing	-	
TM8	Wireless charging 5W+Chargiing	-	
Note: All modes have been tested and only the worst mode Wireless charging 15W and Wireless charging 15W+Chargiing data is represented in the report.			
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
Dummy load	YBZ	YBZ-001	N/A
Adapter	UGREEN	CD289	90324

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Conducted RF Testing					
RF Test System	MWRFTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209	Radiated Emissions	Passed
FCC Part 15.215(c)	Occupied Bandwidth	Passed
<p>Passed: The EUT complies with the essential requirements in the standard</p> <p>Failed: The EUT does not comply with the essential requirements in the standard</p> <p>N/A: Not applicable</p>		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an Coil antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Standard and Limit


According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

- Attenuation: 10dB
- Start Frequency: 0.15MHz
- Stop Frequency: 30MHz
- IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.


4.3 Test Data and Results

Based on all tested mode data, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case TM5 as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions


Tested Mode:	TM5
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2220	46.07	9.25	55.32	62.74	-7.42	QP	P	
2 *	0.2220	38.03	9.25	47.28	52.74	-5.46	AVG	P	
3	0.4110	29.80	9.38	39.18	57.63	-18.45	QP	P	
4	0.4110	23.62	9.38	33.00	47.63	-14.63	AVG	P	
5	0.8520	31.60	9.39	40.99	56.00	-15.01	QP	P	
6	0.8520	21.44	9.39	30.83	46.00	-15.17	AVG	P	
7	2.8095	29.46	9.50	38.96	56.00	-17.04	QP	P	
8	2.8095	26.97	9.50	36.47	46.00	-9.53	AVG	P	
9	7.9485	28.21	9.57	37.78	60.00	-22.22	QP	P	
10	7.9485	26.76	9.57	36.33	50.00	-13.67	AVG	P	
11	27.2355	25.95	10.08	36.03	60.00	-23.97	QP	P	
12	27.2355	22.48	10.08	32.56	50.00	-17.44	AVG	P	

Test Plots and Data of Conducted Emissions

Tested Mode:	TM5
Test Voltage:	AC 120V/60Hz
Test Power Line:	Live
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1905	42.78	9.39	52.17	64.01	-11.84	QP	P	
2	0.1905	37.39	9.39	46.78	54.01	-7.23	AVG	P	
3	0.2220	46.17	9.43	55.60	62.74	-7.14	QP	P	
4 *	0.2220	38.56	9.43	47.99	52.74	-4.75	AVG	P	
5	0.8520	34.53	9.58	44.11	56.00	-11.89	QP	P	
6	0.8520	24.53	9.58	34.11	46.00	-11.89	AVG	P	
7	3.0930	29.08	9.69	38.77	56.00	-17.23	QP	P	
8	3.0930	25.99	9.69	35.68	46.00	-10.32	AVG	P	
9	4.6905	25.54	9.75	35.29	56.00	-20.71	QP	P	
10	4.6905	22.58	9.75	32.33	46.00	-13.67	AVG	P	
11	11.1885	29.45	9.75	39.20	60.00	-20.80	QP	P	
12	11.1885	25.59	9.75	35.34	50.00	-14.66	AVG	P	

5. Radiated Emissions

5.1 Standard and Limit

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:


Frequency of Emission (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: The more stringent limit applies at transition frequencies.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure


Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz



Block Diagram of Radiated Emission Above 1GHz


- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW \geq RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

Based on all mode tested data, the EUT complied with the FCC Part 15.209 standard limit for a wireless device, and with the worst case TM1 and TM5 as below:


Test Data of Radiated Emissions from 9kHz to 30MHz

Test Mode:	TM5	Phase:	Coplaner
Test Voltage:	Wireless charging 15W+Chargiing		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0154	15.13	35.39	50.52	123.84	-73.32	QP	100	0	P	
2	0.0352	13.77	32.37	46.14	116.66	-70.52	QP	100	0	P	
3	0.0720	16.89	26.21	43.10	110.45	-67.35	QP	100	0	P	
4 *	0.1165	37.82	25.53	63.35	106.27	-42.92	QP	100	0	P	
5	0.2970	26.11	25.81	51.92	98.15	-46.23	QP	100	0	P	
6	0.3501	26.30	25.79	52.09	96.72	-44.63	QP	100	0	P	


Test Mode:	TM5	Phase:	Coaxial
Test Voltage:	Wireless charging 15W+Chargiing		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0352	16.30	32.37	48.67	116.66	-67.99	QP	100	360	P	
2	0.0413	12.36	30.63	42.99	115.27	-72.28	QP	100	360	P	
3	0.0629	17.92	26.93	44.85	111.62	-66.77	QP	100	360	P	
4	0.0950	16.37	25.77	42.14	108.04	-65.90	QP	100	360	P	
5 *	0.1165	37.51	25.53	63.04	106.27	-43.23	QP	100	360	P	
6	0.2757	26.70	25.80	52.50	98.79	-46.29	QP	100	360	P	


Test Data of Radiated Emissions from 9kHz to 30MHz

Test Mode:	TM1	Phase:	Coplaner
Test Voltage:	Wireless charging 15W		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0112	20.27	35.82	56.09	126.60	-70.51	QP	100	360	P	
2	0.0352	14.77	32.37	47.14	116.66	-69.52	QP	100	360	P	
3	0.0721	16.89	26.21	43.10	110.44	-67.34	QP	100	360	P	
4	0.0953	17.49	25.77	43.26	108.01	-64.75	QP	100	360	P	
5 *	0.1167	40.82	25.53	66.35	106.26	-39.91	QP	100	360	P	
6	0.4587	23.97	25.68	49.65	94.37	-44.72	QP	100	360	P	

Test Mode:	TM1	Phase:	Coaxial
Test Voltage:	Wireless charging 15W		
Remark:			



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	0.0105	22.61	35.89	58.50	127.16	-68.66	QP	100	0	P	
2	0.0300	15.88	33.83	49.71	118.05	-68.34	QP	100	0	P	
3	0.0352	16.30	32.37	48.67	116.66	-67.99	QP	100	0	P	
4	0.0629	17.92	26.93	44.85	111.62	-66.77	QP	100	0	P	
5	0.0950	16.37	25.77	42.14	108.04	-65.90	QP	100	0	P	
6 *	0.1167	40.51	25.53	66.04	106.26	-40.22	QP	100	0	P	

Note:

Pre-scan in the all of mode, the worst case in of was recorded.


Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

Margin = Reading - Limit.

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM5
Test Antenna Polarization:	Horizontal
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	111.7380	33.18	-10.70	22.48	43.50	-21.02	QP	100	342	P	
2	127.6645	33.78	-9.05	24.73	43.50	-18.77	QP	100	302	P	
3 *	162.0414	43.27	-8.05	35.22	43.50	-8.28	QP	100	359	P	
4	251.1804	40.03	-9.95	30.08	46.00	-15.92	QP	100	61	P	
5	271.3246	38.14	-9.29	28.85	46.00	-17.15	QP	100	32	P	
6	411.8240	32.63	-5.32	27.31	46.00	-18.69	QP	100	91	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM5
Test Antenna Polarization:	Vertical
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	43.2017	26.67	-8.27	18.40	40.00	-21.60	QP	100	0	P	
2	128.5630	31.02	-8.98	22.04	43.50	-21.46	QP	100	258	P	
3	165.4866	36.63	-8.37	28.26	43.50	-15.24	QP	100	247	P	
4	228.4904	29.44	-11.22	18.22	46.00	-27.78	QP	100	54	P	
5	392.0951	26.13	-5.83	20.30	46.00	-25.70	QP	100	16	P	
6 *	787.8513	30.47	1.36	31.83	46.00	-14.17	QP	100	258	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz


Tested Mode:	TM1
Test Antenna Polarization:	Horizontal
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	119.3945	39.44	-9.81	29.63	43.50	-13.87	QP	200	11	P	
2	173.8135	40.09	-9.45	30.64	43.50	-12.86	QP	200	61	P	
3 !	355.4273	47.91	-7.19	40.72	46.00	-5.28	QP	100	83	P	
4 *	411.8240	47.59	-5.32	42.27	46.00	-3.73	QP	100	94	P	
5	515.4374	42.37	-3.10	39.27	46.00	-6.73	QP	100	124	P	
6	787.8513	35.72	1.36	37.08	46.00	-8.92	QP	200	186	P	

Test Plots and Data of Radiated Emissions from 30MHz to 1GHz

Tested Mode:	TM1
Test Antenna Polarization:	Vertical
Remark:	



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	38.6160	38.88	-8.52	30.36	40.00	-9.64	QP	100	360	P	
2 *	59.0476	47.19	-9.81	37.38	40.00	-2.62	QP	100	207	P	
3	118.6014	46.47	-9.91	36.56	43.50	-6.94	QP	100	355	P	
4	177.5092	37.90	-10.11	27.79	43.50	-15.71	QP	100	207	P	
5 !	425.0280	47.49	-5.06	42.43	46.00	-3.57	QP	100	13	P	
6	787.8513	32.89	1.36	34.25	46.00	-11.75	QP	100	13	P	

Note 1: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: For 9kHz-30MHz, Distance extrapolation factor = 40 log (specific distance/test distance)(dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

Note 4: Level = Reading + Factor, Margin = Level - Limit.

6. Occupied Bandwidth

6.1 Standard and Limit

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, section 6.9, the emission bandwidth test method as follows.

- 1) Remove the antenna from the EUT and connect to the spectrum analyzer via a low loss RF cable.
- 2) Set the spectrum analyzer to any one measured frequency within its operating range.
- 3) Set RBW = 1% of the 20 dB bandwidth, VBW = RBW.
- 4) Set Sweep = Auto, Detector function = peak, Trace = max hold.
- 5) Set a reference level on the measuring instrument equal to the highest peak value.
- 6) Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level.

Record the frequency difference as the emission bandwidth.

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.




Test Setup Block Diagram

6.3 Test Data and Results

Test Frequency	20dB Bandwidth	99% Bandwidth
158.8kHz	101Hz	170Hz

Test Plots of Occupied Bandwidth



***** END OF REPORT *****