

## 8.5 POWER LINE CONDUCTED EMISSIONS

### 8.5.1 Applicable Standard

According to FCC Part 15.207(a)

### 8.5.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.5.3 Test Configuration

Test according to clause 6.3 conducted emission test setup

### 8.5.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.  
Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
Repeat above procedures until all frequency measured were complete.


### 8.5.5 Test Results

Temperature : 25.1°C  
Humidity : 45 %


ATM Pressure:: 1011 mbar  
Test Engineer: XZC

**Pass**

The all voltage have been tested, and the worst result recorded was report as below.



Site Conduction #1				Phase:	L1	Temperature: 26.9			
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	41.59	10.01	51.60	79.00	-27.40	QP	
2		0.1500	20.90	10.01	30.91	66.00	-35.09	AVG	
3		0.1660	40.03	10.03	50.06	79.00	-28.94	QP	
4		0.1660	20.33	10.03	30.36	66.00	-35.64	AVG	
5		0.1860	38.17	10.03	48.20	79.00	-30.80	QP	
6		0.1860	20.45	10.03	30.48	66.00	-35.52	AVG	
7		0.3580	32.32	9.98	42.30	79.00	-36.70	QP	
8		0.3580	20.88	9.98	30.86	66.00	-35.14	AVG	
9		0.4380	38.08	9.94	48.02	79.00	-30.98	QP	
10		0.4380	28.46	9.94	38.40	66.00	-27.60	AVG	
11		0.7020	24.77	10.01	34.78	73.00	-38.22	QP	
12		0.7020	15.79	10.01	25.80	60.00	-34.20	AVG	



Site Conduction #1				Phase: <i>N</i>		Temperature: 26.9		
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dB	Detector	Comment
1	*	0.1500	39.82	10.01	49.83	79.00	-29.17	QP
2		0.1500	19.44	10.01	29.45	66.00	-36.55	AVG
3		0.1944	34.43	10.03	44.46	79.00	-34.54	QP
4		0.1944	17.25	10.03	27.28	66.00	-38.72	AVG
5		0.3660	30.22	9.97	40.19	79.00	-38.81	QP
6		0.3660	17.35	9.97	27.32	66.00	-38.68	AVG
7		0.4380	36.07	9.94	46.01	79.00	-32.99	QP
8		0.4380	25.26	9.94	35.20	66.00	-30.80	AVG
9		0.7060	22.49	10.01	32.50	73.00	-40.50	QP
10		0.7060	12.74	10.01	22.75	60.00	-37.25	AVG
11		1.9420	18.81	9.97	28.78	73.00	-44.22	QP
12		1.9420	8.91	9.97	18.88	60.00	-41.12	AVG

## 8.6 ANTENNA APPLICATION

### 8.6.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 8.6.2 Result

Temperature : 25°C  
Humidity : 60 %

ATM Pressure:: 1011 mbar  
Test Engineer: XXH

#### PASS

The EUT is integrated antenna, Ant1: 3.27dBi, Ant2: 3.27dBi.

- Antennas use a permanently attached antenna which is not replaceable.
- Not using a standard antenna jack or electrical connector for antenna replacement
- The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

## Detail of factor for radiated emission:

Frequency(MHz)	Ant_F(dB)	Cab_L(dB)	Preamp(dB)	Correct Factor(dB)
0.009	20.6	0.03	\	20.63
0.15	20.7	0.1	\	20.8
1	20.9	0.15	\	21.05
10	20.1	0.28	\	20.38
30	18.8	0.45	\	19.25
30	11.7	0.62	27.9	-15.58
100	12.5	1.02	27.8	-14.28
300	12.9	1.91	27.5	-12.69
600	19.2	2.92	27	-4.88
800	21.1	3.54	26.6	-1.96
1000	22.3	4.17	26.2	0.27
1000	25.6	1.76	41.4	-14.04
3000	28.9	3.27	43.2	-11.03
5000	31.1	4.2	44.6	-9.3
8000	36.2	5.95	44.7	-2.55
10000	38.4	6.3	43.9	0.8
12000	38.5	7.14	42.3	3.34
15000	40.2	8.15	41.4	6.95
18000	45.4	9.02	41.3	13.12
18000	37.9	1.81	47.9	-8.19
21000	37.9	1.95	48.7	-8.85
25000	39.3	2.01	42.8	-1.49
28000	39.6	2.16	46.0	-4.24
31000	41.2	2.24	44.5	-1.06
34000	41.5	2.29	46.6	-2.81
37000	43.8	2.30	46.4	-0.3
40000	43.2	2.50	42.2	3.5

--- End of Report ---

## 声 明

## Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效。  
1. This report is invalid without the signature of the authorized approver and "special seal for testing".
2. 未经许可本报告不得部分复制。  
2. This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责。  
3. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用。  
4. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外。  
5. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检验报告若有异议，请于收到报告之日起 20 日内提出。  
6. Objections shall be raised within 20 days from the date receiving the report.