

承認書

APPROVAL SHEET

客 户
:

品 名 规 格 YD-001-PCB A n t e n n a -1.13-L200MM-IPEX 一代
DESCRIPTION:

料 号
PART NO.: PCB Antenna

客 户 料 号
CUS PART NO.:

日 期 2024.8.19
D A T E:

呈样签章

工 程 ENGINEERING DEPARTMENT	品 保 Q C DEPARTMENT	业 务 SALES DEPARTMENT

客户承认签章

工 程 ENGINEERING DEPARTMENT	品 保 Q C DEPARTMENT	采 购 PURCHASING DEPARTMENT

联系电话: ✖ 承认书一式三份, 惠蒙贵司承认签章

✖ Approval in duplicate, please signed by your company.


manufacturer:Shenzhen Yunding Communication Electronics Co., Ltd.

Add.: 2nd Floor, Building A, No. 51 Xingang Road, Chang'an Town,

Dongguan City, Guangdong Province


1. 测试项目与设备 Test items and equipment

	测试项目	设备
1. S11 参数 (S-parameter)	1. 回波损耗 (Return Loss) 2. 电压驻波比 (VSWR)	网络分析仪: Agilent E5071B HP 8753D
2. 有源测试 (Active)	1. 发射功率 (TRP) 2. 接收灵敏度 (TIS)	1. 暗室: ETS 7x4x3 m (3D) Chamber ETS 5x3x3 m (3D) Chamber 2. 综合测试仪: Agilent 8960 E5515B x2 StarPoint SP6011 Cmw500
3. 无源测试 (Passive)	1. 天线增益 (Gain) 2. 天线效率 (Efficiency)	1. 暗室: ETS 7x4x3 m (3D) Chamber ETS 5x3x3 m (3D) Chamber 2. 网络分析仪: Agilent E5071B HP 8753D




2. 天线性能 Antenna performance

SWR




3. 天线效率与增益 Antenna efficiency and gain

Freq (MHz)	Effi (%)	Gain (dBi)
2400	50.95	2.57
2410	50.35	2.48
2420	51.21	2.46
2430	53.88	2.59
2440	56.87	2.76
2450	59.47	2.83
2460	60.02	2.73
2470	60.23	2.63
2480	60.97	2.62
2490	62.93	2.71
2500	63.47	2.79



4. 天线结构图：



电器技术参数 Electrical technical parameters

电 性 能 指 标		Electrical Specifications	
频率范围	2400~2500MHz	Frequency Range	2400~2500MHz
电压驻波比	≤2.0	VSWR	≤2.0
输入阻抗	50 Ω	Input Impedance	50 Ω
增益	2.83DBI	Gain	2.83DBI
机 械 指 标		Mechanical Specifications	
工作温度	-40℃~+85℃	Working Temperature	-40℃~+85℃
工作湿度	20~80%	Working Humidity	20~80%

环境性能测试（Environment performance test）：

项目	测试条件	测试结果
储存环境	在没有指定的情况下测试温度、湿度、气压如下： 1. 温度为-30℃~+80℃ 2. 相对湿度为45%-85% 3. 气压为86kpa-106kpa	电气机械性能正常
高低温试验	在70℃与-40℃之间进行5次循环，然后在正常条件下1-2H，检查外观质量。	尺寸应满足规定并应满足于机械、电气性能
耐恒定湿热试验	相对湿度95±3%，试验温度：40℃.持续2H作用后，试品取出后5min之内测定电气性能，试品在正常条件下1-2H，检查外观质量	尺寸应满足规定并应满足于机械、电气性能
振动试验	振频范围10-55HZ，位移幅值：0.35MM，加速度幅值：50.0M/S，扫频循环次数：30次	电气机械性能正常
跌落试验	1M高空按照互相垂直的轴方向自由跌落3次	电气机械性能正常

Project	Test condition	Test results
Storage environment	Test temperature, humidity, pressure without stated condition as follwings:1.Temperature: -30℃ ~ +80℃ ;2.Relative humidity: 45%-85%;3,Pressure: 86kpa-106kpa	Electrical and mechanical performance normal
High and low temperature test	Having 5 times cycle between -40℃ to 70℃,Then in common condition 1-2 hours test exterior quality.	Measurement satisfied with electrical and mechanical performance normal.
Resistance constant hot and humid test	Relative humidity:95±3%,Test temperature: 40℃,last 2 hours ,put it after 5 min test the electrical function .Test products during common condition 1-2 hours ,Then test exterior quality.	Measurement satisfied with electrical and mechanical performance normal.
Vibration test	Vibrate Frequency:10-55HZ; Distance :0.35mm;Acceleration :50.0m/s;Sweep frequency cycle:30 times	Electrical and mechanical performance normal
Fall test	From 1m height fall down 3 times freely (vertical direction)	Electrical and mechanical performance normal