

FCC Test Report

Report No.: 2405A41406EB

Applicant: Zhuhai Glory Technology Co., Ltd

Address: 8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai,
Guangdong, China

Product Name: WIRELESS NETWORK CAMERA

Product Model: GL-228CGA-S1V1CY

Multiple Models: N/A

Trade Mark: N/A

FCC ID: 2BMPT-228CGA-S1V1CY

Standards: FCC CFR Title 47 Part 15C (§15.247)

Test Date: 2024-12-10 to 2025-01-18

Test Result: Complied

Report Date: 2025-01-23

Reviewed by:

Frank Yin

Approved by:

Jacob Kong

Frank Yin
Project Engineer

Jacob Kong
Manager

Prepared by:

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen,
Guangdong, People's Republic of China



This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”

Announcement

1. This test report shall not be reproduced except in full, without the written approval of World Alliance Testing & Certification (Shenzhen) Co., Ltd
2. The results in this report apply only to the sample tested.
3. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.
4. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

Revision History

Version No.	Issued Date	Description
00	2025-01-23	Original

Contents

1	General Information	4
1.1	Client Information	4
1.2	Product Description of EUT	4
1.3	Antenna information	4
1.4	Related Submittal(s)/Grant(s).....	5
1.5	Measurement Uncertainty	5
1.6	Laboratory Location.....	5
1.7	Test Methodology	5
2	Description of Measurement.....	6
2.1	Test Configuration.....	6
2.2	Test Auxiliary Equipment	7
2.3	Interconnecting Cables.....	7
2.4	Block Diagram of Connection between EUT and AE	7
2.5	Test Setup.....	7
2.6	Test Procedure	9
2.7	Measurement Method.....	11
2.8	Measurement Equipment	11
3	Test Results	13
3.1	Test Summary.....	13
3.2	Limit	14
3.3	AC Line Conducted Emissions Test Data.....	15
3.4	Radiated emission Test Data.....	17
3.5	RF Conducted Test Data	57
3.5.1	6dB Emission Bandwidth and 99% Occupied Bandwidth.....	57
3.5.2	Maximum Conducted Peak Output Power.....	57
3.5.3	Power Spectral Density.....	58
3.5.4	100 kHz Bandwidth of Frequency Band Edge	58
3.5.5	Duty Cycle.....	58
4	Test Setup Photo.....	68
5	E.U.T Photo	69

1 General Information

1.1 Client Information

Applicant:	Zhuhai Glory Technology Co., Ltd
Address:	8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, China
Manufacturer:	Zhuhai Glory Technology Co., Ltd
Address:	8F, Bldg 7, No. 178 Dingxing Road, Tangjiawan Town, Zhuhai, Guangdong, China

1.2 Product Description of EUT

The EUT is WIRELESS NETWORK CAMERA that contains 2.4G WLAN radio, this report covers the full testing of the 2.4G WLAN radio.

Sample Serial Number	2VKL-1 for CE&RE test, 2VKL-2 for RF conducted test (assigned by WATC)
Sample Received Date	2024-12-09
Sample Status	Good Condition
Frequency Range	2412MHz - 2462MHz(802.11b, g, n-HT20) 2422MHz - 2452MHz(802.11n-HT40)
Maximum Conducted Peak Output Power	22.74dBm
Modulation Technology	DSSS, OFDM
Antenna Gain [#]	2.55dBi
Spatial Streams [#]	1T1R
Power Supply	DC 12V from AC Adapter
Adapter Information	N/A
Modification	Sample No Modification by the test lab

1.3 Antenna information

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
Device Antenna information:	
The Wi-Fi antenna is an external antenna which with unique antenna connector. Please see product external photos for details.	

1.4 Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s)

1.5 Measurement Uncertainty

Parameter		Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
AC Power Lines Conducted Emissions		±3.14dB
Emissions, Radiated	Below 30MHz	±2.78dB
	Below 1GHz	±4.84dB
	Above 1GHz	±5.44dB
Emissions, Conducted		1.75dB
Conducted Power		0.74dB
Frequency Error		150Hz
Bandwidth		0.34%
Power Spectral Density		0.74dB
Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.		

1.6 Laboratory Location

World Alliance Testing & Certification (Shenzhen) Co., Ltd

No. 1002, East Block, Laobing Building, Xingye Road 3012, Xixiang street, Bao'an District, Shenzhen, Guangdong, People's Republic of China

Tel: +86-755-29691511, Email: ga@watc.com.cn

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 463912, the FCC Designation No. : CN5040.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0160.

1.7 Test Methodology

FCC CFR 47 Part 2

FCC CFR 47 Part 15

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

Unless otherwise stated there are no any additions to, deviations, or exclusions from the method

2 Description of Measurement

2.1 Test Configuration

Operating channels:					
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442	/	/
3	2422	8	2447	/	/
4	2427	9	2452	/	/
5	2432	10	2457	/	/
According to ANSI C63.10-2013 chapter 5.6.1 Table 11 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:					
802.11b, 802.11g, 802.11n-HT20					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	6	2437	11	2462
802.11n-HT40					
Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
3	2422	6	2437	9	2452

Test Mode:				
Transmitting mode:		Keep the EUT in continuous transmitting with modulation		
Exercise software [#] :		SecureCRT 8.3		
Mode	Worst-case Data rate	Power Level Setting [#]		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	30	30	30
802.11g	6Mbps	40	40	40
802.11n-HT20	6.5Mbps	40	40	40
802.11n-HT40	13.5Mbps	40	40	40
The exercise software and the maximum power setting that provided by manufacturer.				

Worst-Case Configuration:
For radiated emissions, EUT was investigated in three orthogonal orientation, the worst-case orientation was recorded in report
For AC power line conducted emission and radiated emission 9kHz-1GHz and above 18GHz were performed with the EUT transmits at the channel with highest output power as worst-case scenario.

For radiated emissions below 30MHz, three antenna orientations (parallel, perpendicular, ground-parallel) were tested, only record the worse case test data in report.


2.2 Test Auxiliary Equipment

Manufacturer	Description	Model	Serial Number
C.SA Electronics(Dongguan)Co.,Ltd	AC adapter	CS-1201000	unknown

2.3 Interconnecting Cables

Manufacturer	Description	Length(m)	From	To
C.SA	DC cable	1.2	Adapter	EUT


2.4 Block Diagram of Connection between EUT and AE



Note: for reference only, the actual connection setup used for testing please refer to the test photos.

2.5 Test Setup


1) Conducted emission measurement:




Note: The 0.8 m distance specified between EUT/AE/PSU and AMN/AAN, is applicable only to the EUT being measured. If the device is AE then it shall be >0.8 m.

2) Radiated emission measurement:


Below 30MHz (3m SAC)




30MHz-1GHz (3m SAC)



1GHz-18GHz(3m FAC)





2.6 Test Procedure

Conducted emission:

1. The E.U.T is placed on a non-conducting table 40cm from the vertical ground plane and 80cm above the horizontal ground plane (Please refer to the block diagram of the test setup and photographs).
2. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
3. Line conducted data is recorded for both Line and Neutral

Radiated Emission Procedure:

a) For below 30MHz

1. All measurements were made at a test distance of 3 m. The measured data was extrapolated from the test distance (3m) to the specification distance (300 m from 9-490 kHz and 30 m from 490 kHz- 30 MHz) to clearly show the relative levels of fundamental and spurious emissions and demonstrate compliance with the requirement that the level of any spurious emissions be below the level of the intentionally transmitted signal. The extrapolation factor for the limits were $40 \cdot \log(\text{test distance} / \text{specification distance})$.

2. Loop antenna use, investigation was done on the three antenna orientations (parallel, perpendicular, ground-parallel)
3. The RBW/VBW of receiver is set to 300Hz/1kHz for 9kHz to 150kHz range, to 10kHz/30kHz for 150kHz to 30MHz range for scan Peak emission, 200Hz/9kHz IF BW was used for final measurement in the Quasi-peak or average detection mode for frequency range 9~150kHz/150kHz~30MHz respectively.
4. If the Peak emission complies with the QP limit, then perform final measurement is optional.

b) For 30MHz-1GHz:

1. The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 3 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 3 m.
2. EUT works in each mode of operation that needs to be tested. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. The RBW/VBW of receiver is set to 100kHz/300kHz for scan Peak emission, 120kHz IF BW was used for final measurement in the Quasi-peak detection mode.
4. If the Peak emission complies with the QP limit, then perform final measurement is optional.

c) For above 1GHz:

1. The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m (1-18GHz) and 1.5 m (above 18GHz).
2. EUT works in each mode of operation that needs to be tested, and having the EUT continuously working. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.
3. The RBW/VBW of spectrum analyzer is set to 1MHz/3MHz for scan Peak emission, for measured average emission, reduce the VBW to 10Hz(for duty cycle≥98%), or ≥1/T(for duty cycle<98%). T is minimum transmission duration. (Note: a high VBW (for example 1kHz, not less than 1/T) may used to scan average emissions to avoid long sweep time.)
4. If the Peak emission complies with the Average limit, then perform average measurement is optional.
5. Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
6. Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

RF Conducted Test:

1. The antenna port of EUT was connected to the RF port of the test equipment (Power Meter or Spectrum analyzer) through Attenuator and RF cable.
2. The cable assembly insertion loss of 8.0dB (including 6.0 dB Attenuator and 2.0 dB cable) was entered as an offset in the power meter. Note: Actual cable loss was unavailable at the time of testing, therefore a loss of 2.0dB was assumed as worst case. This was later verified to be true by laboratory. (if the RF cable provided by client, the cable loss declared by client)
3. The EUT is keeping in continuous transmission mode and tested in all modulation modes.

2.7 Measurement Method

Description of Test	Measurement Method
AC Line Conducted Emissions	ANSI C63.10-2013 Section 6.2
Maximum Conducted Output Power	ANSI C63.10-2013 Section 11.9.1.2 PKPM1 Peak power meter method or ANSI C63.10-2013 Section 11.9.2.3.2 Method AVGPM-G
Power Spectral Density	ANSI C63.10-2013 Section 11.10.2 Method PKPSD (peak PSD)
6 dB Emission Bandwidth	ANSI C63.10-2013 Section 11.8.1
99% Occupied Bandwidth	ANSI C63.10-2013 Section 6.9.3
100kHz Bandwidth of Frequency Band Edge	ANSI C63.10-2013 Section 6.10
Radiated emission	ANSI C63.10-2013 Section 11.11&11.12
Duty Cycle	ANSI C63.10-2013 Section 11.6

2.8 Measurement Equipment

Manufacturer	Description	Model	Management No.	Calibration Date	Calibration Due Date
AC Line Conducted Emission Test					
ROHDE& SCHWARZ	EMI TEST RECEIVER	ESR	101817	2024/6/4	2025/6/3
R&S	LISN	ENV216	101748	2024/6/4	2025/6/3
N/A	Coaxial Cable	NO.12	N/A	2024/6/4	2025/6/3
Farad	Test Software	EZ-EMC	Ver. EMEC-3A1	/	/
Radiated Emission Test					
R&S	EMI test receiver	ESR3	102758	2024/6/4	2025/6/3
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40-N	101608	2024/6/4	2025/6/3
SONOMA INSTRUMENT	Low frequency amplifier	310	186014	2024/6/4	2025/6/3
A.H. Systems	PREAMPLIFIER	PAM-0118P	531	2024/6/4	2025/6/3
COM-POWER	Amplifier	PAM-840A	461306	2024/8/7	2025/8/6
BACL	Loop Antenna	1313-1A	4010611	2024/2/7	2027/2/6
SCHWARZBECK	Log - periodic wideband antenna	VULB 9163	9163-872	2023/7/7	2026/7/6

Astro Antenna Ltd	Horn antenna	AHA-118S	3015	2023/7/6	2026/7/5
Ducommun technologies	Horn Antenna	ARH-4223-02	1007726-03	2023/7/10	2026/7/9
Oulitong	Band Reject Filter	OBSF-2400-248 3.5-50N	OE02103119	2024/6/4	2025/6/3
N/A	Coaxial Cable	NO.9	N/A	2024/6/4	2025/6/3
N/A	Coaxial Cable	NO.13	N/A	2024/6/4	2025/6/3
N/A	Coaxial Cable	NO.15	N/A	2024/6/4	2025/6/3
N/A	Coaxial Cable	NO.16	N/A	2024/6/4	2025/6/3
N/A	Coaxial Cable	NO.17	N/A	2024/6/4	2025/6/3
Audix	Test Software	E3	191218 V9	/	/
RF Conducted Test					
ROHDE& SCHWARZ	SPECTRUM ANALYZER	FSV40	101419	2024/6/4	2025/6/3
ANRITSU	USB Power Sensor	MA24418A	12620	2024/6/4	2025/6/3
MEEA	6dB attenuator	603-06-1	N/A	2024/6/4	2025/6/3

Note: All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or International standards.

3 Test Results

3.1 Test Summary


FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
-	99% Occupied Bandwidth	Report only
§15.247(d)	100kHz Bandwidth of Frequency Band Edge	Compliance
§15.205, §15.209, §15.247(d)	Radiated emission	Compliance
-	Duty Cycle	Report only


3.2 Limit

Test items	Limit
AC Line Conducted Emissions	See details §15.207 (a)
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Spurious Emissions, 100kHz Bandwidth of Frequency Band Edge	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.3 AC Line Conducted Emissions Test Data

Test Date:	2024-12-10	Test By:	Lirou Li
Environment condition:	Temperature: 23.1°C; Relative Humidity:56%; ATM Pressure: 101kPa		





Remark:

Measurement (dBuV)= Reading Level (dBuV) + Correct Factor(dB)


Correct Factor (dB)= LISN Voltage Division Factor (dB)+ Cable loss(dB)

Over Limit = Measurement – Limit

3.4 Radiated emission Test Data

9 kHz-30MHz:

Test Date:	2025-01-13	Test By:	Luke Li
Environment condition:	Temperature: 21.9°C; Relative Humidity:31%; ATM Pressure: 101.5kPa		




Project No. : 2405A41406E
 Test Mode : Transmitting
 Test Voltage : AC 120V/60Hz
 Environment : 21.9°C/31%R.H./101.5kPa
 Tested by : Luke Li
 Polarization : PARALLEL
 Remark : /

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector

1	0.176	27.31	12.85	40.16	102.70	-62.54	Peak
2	0.454	28.13	6.45	34.58	94.46	-59.88	Peak
3	0.721	28.22	3.24	31.46	70.37	-38.91	Peak
4	5.349	30.65	-4.00	26.65	69.54	-42.89	Peak
5	9.892	38.79	-3.48	35.31	69.54	-34.23	Peak
6	17.596	34.05	-3.21	30.84	69.54	-38.70	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain
 Result = Reading + Factor
 Over Limit = Result - Limit

SA Setting: RBW/VBW: 300Hz/1kHz, DET: PK



Project No. : 2405A41406E
Test Mode : Transmitting
Test Voltage : AC 120V/60Hz
Environment : 21.9°C/31%R.H./101.5kPa
Tested by : Luke Li
Polarization : PARALLEL
Remark : /


--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	0.009	11.36	37.99	49.35	128.48	-79.13	Peak
2	0.018	12.86	32.24	45.10	122.58	-77.48	Peak
3	0.028	11.06	25.50	36.56	118.52	-81.96	Peak
4	0.042	10.88	22.07	32.95	115.15	-82.20	Peak
5	0.067	15.35	18.09	33.44	111.11	-77.67	Peak
6	0.091	13.29	15.60	28.89	108.47	-79.58	Peak


Remarks: Factor = Antenna factor + Cable loss - Preamp gain
Result = Reading + Factor
Over Limit = Result - Limit

SA Setting: RBW/VBW: 9kHz/30kHz, DET: PK

30MHz-1GHz:

Test Date:	2025-01-13	Test By:	Luke Li
Environment condition:	Temperature: 21.9°C; Relative Humidity:31%; ATM Pressure: 101.5kPa		





Project No. : 2405A41406E
 Test Mode : Transmitting
 Test Voltage : AC 120V/60Hz
 Environment : 21.9°C/31%R.H./101.5kPa
 Tested by : Luke Li
 Polarization : vertical
 Remark : 802.11g 2437

--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	47.784	34.72	-12.08	22.64	40.00	-17.36	Peak
2	97.200	39.20	-14.43	24.77	43.50	-18.73	Peak
3	130.493	46.91	-17.17	29.74	43.50	-13.76	Peak
4	188.992	45.32	-14.67	30.65	43.50	-12.85	Peak
5	216.024	39.79	-13.68	26.11	46.00	-19.89	Peak
6	629.477	36.51	-4.53	31.98	46.00	-14.02	Peak

Remarks: Factor = Antenna factor + Cable loss - Preamp gain
 Result = Reading + Factor
 Over Limit = Result - Limit

SA Setting: RBW/VBW: 100kHz/300kHz, DET: PK

Above 1GHz:

Test Date:	2025-01-14~2025-01-17	Test By:	Bard Huang
Environment condition:	Temperature: 22.1~22.9°C; Relative Humidity:36~42%; ATM Pressure: 101.2~101.5kPa		

Frequency (MHz)	Reading level (dBμV)	Polar (H/V)	Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark
802.11b							
Low Channel							
4824.000	51.48	horizontal	-2.29	49.19	74.00	-24.81	Peak
4824.000	53.89	vertical	-2.29	51.60	74.00	-22.40	Peak
Middle Channel							
4874.000	52.65	horizontal	-1.92	50.73	74.00	-23.27	Peak
4874.000	54.62	vertical	-1.92	52.70	74.00	-21.30	Peak
High Channel							
4924.000	51.88	horizontal	-1.70	50.18	74.00	-23.82	Peak
4924.000	52.40	vertical	-1.70	50.70	54.00	-3.30	Average
4924.000	55.68	vertical	-1.70	53.98	74.00	-20.02	Peak
802.11g							
Low Channel							
4824.000	51.36	horizontal	-2.29	49.07	74.00	-24.93	Peak
4824.000	52.42	vertical	-2.29	50.13	74.00	-23.87	Peak
Middle Channel							
4874.000	50.67	horizontal	-1.92	48.75	74.00	-25.25	Peak
4874.000	51.39	vertical	-1.92	49.47	74.00	-24.53	Peak
High Channel							
4924.000	48.02	horizontal	-1.70	46.32	74.00	-27.68	Peak
4924.000	52.68	vertical	-1.70	50.98	74.00	-23.02	Peak
802.11n20							
Low Channel							
4824.000	47.77	horizontal	-2.29	45.48	74.00	-28.52	Peak
4824.000	50.30	vertical	-2.29	48.01	74.00	-25.99	Peak
Middle Channel							
4874.000	47.70	horizontal	-1.92	45.78	74.00	-28.22	Peak
4874.000	51.47	vertical	-1.92	49.55	74.00	-24.45	Peak
High Channel							
4924.000	48.28	horizontal	-1.70	46.58	74.00	-27.42	Peak

4924.000	51.68	vertical	-1.70	49.98	74.00	-24.02	Peak
802.11n40							
Low Channel							
4844.000	48.07	horizontal	-2.17	45.90	74.00	-28.10	Peak
4844.000	49.82	vertical	-2.17	47.65	74.00	-26.35	Peak
Middle Channel							
4874.000	49.29	horizontal	-1.92	47.37	74.00	-26.63	Peak
4874.000	50.52	vertical	-1.92	48.60	74.00	-25.40	Peak
High Channel							
4904.000	47.66	horizontal	-1.71	45.95	74.00	-28.05	Peak
4904.000	51.14	vertical	-1.71	49.43	74.00	-24.57	Peak

Remark:

Corrected Amplitude= Reading level + corrected Factor

Corrected Factor = Antenna factor + Cable loss – Amplifier gain


Margin = Corrected Amplitude – Limit


For the test result of Peak below the Peak limit more than 20dB, which can compliance with the average limit, just the Peak level was recorded.


The emission levels of other frequencies that were lower than the limit 20dB not show in test report.


For emissions in 18GHz-25GHz range, all emissions were investigated and in the noise floor level.


Test plot for example as below:



















































Radiated Band edge:


Mode:	802.11b	Channel:	2412MHz
--------------	---------	-----------------	---------





Project No. : 2405A41406E-RF
Test Mode : Transmitting
Test Voltage : AC 120V/60Hz
Environment : 22.1°C/36%R.H./101.5kPa
Tested by : Bard Huang
Polarization : horizontal
Remark : 802.11b 2412


--No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Over Limit (dB)	Detector
1	2332.781	37.17	6.91	44.08	54.00	-9.92	Average
2	2332.781	50.14	6.91	57.05	74.00	-16.95	Peak
3	2390.000	36.61	7.00	43.61	54.00	-10.39	Average
4	2390.000	49.10	7.00	56.10	74.00	-17.90	Peak


Remarks: Factor = Antenna factor + Cable loss - Preamp gain
Result = Reading + Factor
Over Limit = Result - Limit
SA setting: Peak: RBW/VWB: 1MHz/3MHz, DET: PK
Average: RBW/VWB: 1MHz/10Hz , DET: PK









































3.5 RF Conducted Test Data

Test Date:	2025-01-18	Test By:	Ryan Zhang
Environment condition:	Temperature: 22.4°C; Relative Humidity:40%; ATM Pressure: 100.7kPa		

3.5.1 6dB Emission Bandwidth and 99% Occupied Bandwidth

Test Mode	Antenna	Channel	6dB BW [MHz]	99% OBW[MHz]	6dB BW Limit[MHz]	Verdict
802.11b	Chain 0	2412	9.089	13.560	0.5	pass
		2437	8.168	13.520	0.5	pass
		2462	8.128	13.480	0.5	pass
802.11g	Chain 0	2412	16.416	16.560	0.5	pass
		2437	16.416	16.560	0.5	pass
		2462	16.416	16.640	0.5	pass
802.11n20	Chain 0	2412	17.618	17.680	0.5	pass
		2437	17.658	17.680	0.5	pass
		2462	17.417	17.720	0.5	pass
802.11n40	Chain 0	2422	35.876	36.320	0.5	pass
		2437	36.196	36.320	0.5	pass
		2452	36.036	36.320	0.5	pass

3.5.2 Maximum Conducted Peak Output Power

Mode	Antenna	Test Frequency (MHz)	Peak Output Power(dBm)	Limit (dBm)	Verdict
802.11b	Chain 0	2412	14.01	30	Pass
		2437	14.72	30	Pass
		2462	14.64	30	Pass
802.11g	Chain 0	2412	22.62	30	Pass
		2437	22.74	30	Pass
		2462	21.26	30	Pass
802.11n20	Chain 0	2412	21.79	30	Pass
		2437	21.87	30	Pass
		2462	21.22	30	Pass
802.11n40	Chain 0	2422	22.60	30	Pass
		2437	22.74	30	Pass
		2452	22.33	30	Pass

3.5.3 Power Spectral Density

Mode	Antenna	Test Frequency (MHz)	Result (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	Chain 0	2412	-10.12	8	Pass
		2437	-9.83	8	Pass
		2462	-10.50	8	Pass
802.11g	Chain 0	2412	-13.67	8	Pass
		2437	-12.59	8	Pass
		2462	-14.72	8	Pass
802.11n20	Chain 0	2412	-13.87	8	Pass
		2437	-14.60	8	Pass
		2462	-13.31	8	Pass
802.11n40	Chain 0	2422	-15.55	8	Pass
		2437	-16.55	8	Pass
		2452	-16.53	8	Pass

3.5.4 100 kHz Bandwidth of Frequency Band Edge

Mode	Antenna	Test Frequency (MHz)	Result (dB)	Limit (dB)	Verdict
802.11b	Chain 0	2412	48.48	20	Pass
		2462	53.27	20	Pass
802.11g	Chain 0	2412	38.51	20	Pass
		2462	48.88	20	Pass
802.11n20	Chain 0	2412	37.08	20	Pass
		2462	49.22	20	Pass
802.11n40	Chain 0	2422	35.62	20	Pass
		2452	46.20	20	Pass

3.5.5 Duty Cycle

Mode	Antenna	Test Frequency (MHz)	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)	1/Ton (Hz)	VBW Setting (kHz)
802.11b	Chain 0	2437	12.416	12.535	99.05	/	/	0.010
802.11g	Chain 0	2437	2.062	2.127	96.94	0.13	485	0.5
802.11n20	Chain 0	2437	1.918	1.974	97.16	0.12	521	1.0
802.11n40	Chain 0	2437	0.944	1.079	87.49	0.58	1059	2.0


Duty Cycle = Ton/(Ton+Toff)*100%

Test Plots:

6 dB Emission Bandwidth:


2412~2462

802.11b_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:34:22

802.11b_2437MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:53:49

802.11b_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:57:04

802.11g_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:00:12

802.11g_2437MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:03:52

802.11g_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:06:57

802.11n20_2412MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:10:33

802.11n20_2437MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:14:03

802.11n20_2462MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:16:27

802.11n40_2422MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:19:46

802.11n40_2437MHz



ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:26:18

802.11n40_2452MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:30:46

99% Occupied Bandwidth:


2412~2462

802.11b_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:34:49

802.11b_2437MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:54:13

802.11b_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:57:28

802.11g_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:00:19

802.11g_2437MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:04:17

802.11g_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:07:23

802.11n20_2412MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:11:00

802.11n20_2437MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:14:26

802.11n20_2462MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:16:53

802.11n40_2422MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:20:00

802.11n40_2437MHz



ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:26:33

802.11n40_2452MHz




ProjectNo.:2405A41406B-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:31:00

Power Spectral Density:


2412~2462

802.11b_2412MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:47:42

802.11b_2437MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:54:45

802.11b_2462MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:58:36

802.11g_2412MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:01:58

802.11g_2437MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:05:07

802.11g_2462MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:08:59

802.11n20_2412MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:12:25

802.11n20_2437MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:15:20

802.11n20_2462MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:18:21

802.11n40_2422MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:22:10

802.11n40_2437MHz



ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:28:10

802.11n40_2452MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:33:21

100kHz Bandwidth of Frequency Band Edge:


2412~2462

802.11b_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:46:03

802.11b_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 13:58:04

802.11g_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:01:06

802.11g_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:08:07

802.11n20_2412MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:11:32

802.11n20_2462MHz




ProjectNo.:2405A41406EB-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:17:27

802.11n40_2422MHz



ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:20:33

802.11n40_2452MHz




ProjectNo.:2405A41406E-RF Tester:Ryan Zhang
Date: 18.JAN.2025 14:31:37


Duty Cycle:

2412~2462


802.11b_2437MHz




802.11g_2437MHz



802.11n20_2437MHz



802.11n40_2437MHz



4 Test Setup Photo

Please refer to the attachment 2405A41406E Test Setup photo.

5 E.U.T Photo

Please refer to the attachment 2405A41406E External photo and 2405A41406E Internal photo.

---End of Report---