

## FCC MPE calculation Report

Product name : "FullCloud" IoT Lock System  
Applicant : PinvAccess B.V.  
FCC ID : 2A225-FC0320

Test report No. : 210400900 002 Ver 1.00 FCC RF exposure

## Laboratory information

### Accreditation

*Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).*

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.  
The Industry Canada company number for Telefication is: 4173A.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

### Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

### Testing Location

<b>Test Site</b>	Kiwa Telefication BV
<b>Test Site location</b>	Wilmersdorf 50 7327 AC Apeldoorn The Netherlands  Tel. +31 88998 3393
<b>Test Site FCC</b>	NL0001
<b>CABID</b>	NL0001

**Revision History**

Version	Date	Remarks	By
v1.00	22-09-2021	Release version	KK

## Table of Contents

Revision History .....	2
<b>1 General Description .....</b>	<b>4</b>
1.1 Applicant .....	4
1.2 Manufacturer .....	4
1.3 Tested Equipment Under Test (EUT) .....	4
1.4 SAR Measurement Evaluation .....	5
1.4.1 Maximum Output Power .....	5
1.4.2 MPE Limits .....	5
1.4.3 MPE calculation .....	6
1.5 Summary .....	<b>Error! Bookmark not defined.</b>

## 1 General Description

### 1.1 Applicant

Client name:	PinvAccess B.V.
Address:	Laan van de Maagd 103, Apeldoorn
Zip code:	7324 BT
Telephone:	-
E-mail:	kai@pinvaccess.com
Contact name:	Kai Schöllkopf

### 1.2 Manufacturer

Manufacturer name:	PinvAccess B.V.
Address:	Laan van de Maagd 103, Apeldoorn
Zip code:	7324 BT
Telephone:	-
E-mail:	kai@pinvaccess.com
Contact name:	Kai Schöllkopf

### 1.3 Tested Equipment Under Test (EUT)

Product name:	"FullCloud" IoT Lock System
Brand name:	PinvAccess B.V.
Product type:	Lock System
FCC ID:	2A225-FC0320
Model(s):	-
Software version:	-
Hardware version:	-

## 1.4 SAR Measurement Evaluation

### 1.4.1 Maximum Output Power

The maximum radiated power including antenna gain is shown as below.

Technology	Output power (dBm)
BLE	-0.88
Proprietary	5.39

\* from Telefication test report no: 210400900 001 Ver 1.00

### 1.4.2 MPE Limits

Limits for occupational/controlled exposure

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 – 3.0	614	1.63	100 (see note 1)	≤6
3.0 – 30	1842/f	4.89/f	900/f <sup>2</sup> (see note 1)	≤6
30 – 300	61.4	0.163	1.0	≤6
300 – 1500	--	--	f/300	≤6
1500 – 100000	--	--	5	≤6

Limits for general population/uncontrolled exposure

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
0.3 – 1.34	614	1.63	100 (see note 1)	≤30
1.34 – 30	824/f	2.19/f	180/f <sup>2</sup> (see note 1)	≤30
30 – 300	27.5	0.073	0.2	≤30
300 – 1500	--	--	f/1500	≤30
1500 – 100000	--	--	1.0	≤30

Notes :

f = frequency in MHz

1: plane wave equivalent power density

### 1.4.3 MPE calculation

As declared by the Applicant, the EUT is a wireless device used in a fixed application, at least 20 cm from any body part of the user or nearby persons.

Calculation method of RF Safety Distance:

$$PD = \frac{P_{out} * G}{4\pi r^2} = \frac{P(eirp)}{4\pi r^2}$$

Where:

PD = Power Density in  $mW/cm^2$

Pout = Output power in mW

G = Gain of antenna

R = Distance between observation point and centre of the radiator in cm

#### Calculation results

Technology	Frequency (MHz)	Max radiated power (mW)	Distance (cm)	Power density ( $mW/cm^2$ )	Limit ( $mW/cm^2$ )	Pass/Fail
<b>BLE</b>	2440	0.81	20	0.00016	1.00	Pass
<b>Proprietary</b>	915	3.46	20	0.00068	0.61	Pass