

TEST REPORT

Reference No...... : WTD22D02019007W003
FCC ID : 2A4RQ-ESP32
Applicant..... : Shen Zhen Shi Ya Ying Technology Co., Ltd.
Address..... : Room 704, No.18, Huayuan New Village, Longyuan Community,
Longhua District Shenzhen 518109 China
Manufacturer : Shen Zhen Shi Ya Ying Technology Co., Ltd.
Address..... : Room 704, No.18, Huayuan New Village, Longyuan Community,
Longhua District Shenzhen 518109 China
Product..... : ESP32 WiFi & Bluetooth Development Board
Model(s) : ESP32
Standards..... : FCC 47CFR Part15 Subpart C §15.247
Date of Receipt sample : 2022-02-17
Date of Test : 2022-02-17 to 2022-02-24
Date of Issue..... : 2022-02-25
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Estel Qian

Estel Qian / Project Engineer

Approved by:



Daniel Liu

Daniel Liu / Designated Reviewer

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.	4
4.2 DETAILS OF E.U.T.	4
4.3 CHANNEL LIST.....	4
4.4 TEST FACILITY.....	5
4.5 SUBCONTRACTED.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.7 TEST MODE	6
5 TEST SUMMARY	7
6 EQUIPMENT USED DURING TEST	8
6.1 EQUIPMENTS LIST	8
6.2 DESCRIPTION OF SUPPORT UNITS	9
6.3 MEASUREMENT UNCERTAINTY	9
6.4 TEST EQUIPMENT CALIBRATION	9
7 DUTY CYCLE.....	10
8 RADIATED EMISSIONS.....	12
8.1 EUT OPERATION.....	12
8.2 TEST SETUP	13
8.3 SPECTRUM ANALYZER SETUP	14
8.4 TEST PROCEDURE	15
8.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	15
8.6 SUMMARY OF TEST RESULTS	16
9 BAND EDGE MEASUREMENT	19
9.1 TEST PRODUCE.....	19
9.2 TEST RESULT	20
10 6 DB BANDWIDTH AND 99% BANDWIDTH MEASUREMENT	22
10.1 TEST PROCEDURE:.....	22
10.2 TEST RESULT:	22
11 MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	29
11.1 TEST PROCEDURE:.....	29
11.2 TEST RESULT:	29
12 POWER SPECTRAL DENSITY	34
12.1 TEST PROCEDURE:.....	34
12.2 TEST RESULT:	34
13 ANTENNA REQUIREMENT	39
14 RF EXPOSURE.....	39
15 PHOTOGRAPHS OF TEST SETUP AND EUT.....	39

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD22D02019007 W003	2022-02-17	2022-02-17 to 2022-02-24	2022-02-25	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	ESP32 WiFi & Bluetooth Development Board
Model(s):	ESP32
Model Description:	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40
Hardware Version:	V2.0
Software Version:	V2.0

4.2 Details of E.U.T.

Operation Frequency:	802.11b/g/n HT20: 2412~2462MHz, 11CH 802.11n HT40: 2422~2452, 7CH
Max. RF output power:	17.29dBm
Modulation Technology:	CCK, OFDM
Antenna installation:	PCB printed antenna
Antenna Gain:	2.0dBi
Ratings:	DC 5V

4.3 Channel List

Wi-Fi

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462	12	-

4.4 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.5 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.6 Abnormalities from Standard Conditions

None.

4.7 Test Mode

Tests Carried Out Under FCC part 15.247

Test Items	Mode	Data Rate	Channel	TX/RX
Maximum Peak Output Power	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Power Spectral Density	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
6dB Bandwidth	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Band Edge	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX
Transmitter Spurious Emissions	802.11b	1 Mbps	1/6/11	TX
	802.11g	6 Mbps	1/6/11	TX
	802.11n HT20	MCS0	1/6/11	TX
	802.11n HT40	MCS0	3/6/9	TX

Note: Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product.

5 Test Summary

Test Items	Test Requirement	Result
Radiated Spurious Emissions	15.247(d) 15.205(a) 15.209(a)	PASS
Conducted Spurious Emissions	15.247(d)	N/A
Conducted Emissions	15.207(a)	N/A
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3),(4)	PASS
Power Spectral Density	15.247(e)	PASS
Band Edge	15.247(d)	PASS
Antenna Requirement	15.203	PASS
Note: Pass=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable.		

6 Equipment Used during Test

6.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date	Valid
1	EMI Test Receiver	R&S	ESCI	100947	2021-07-26	1Year
2	LISN	R&S	ENV216	101215	2021-07-26	1Year
3	Cable	Top	TYPE16(3.5M)	-	2021-07-26	1Year
Conducted Emissions Test Site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date	Valid
1	EMI Test Receiver	R&S	ESCI	101155	2021-07-26	1Year
2	LISN	SCHWARZBECK	NSLK 8128	8128-289	2021-07-26	1Year
3	Limiter	York	MTS-IMP-136	261115-001-0024	2021-07-26	1Year
4	Cable	LARGE	RF300	-	2021-07-26	1Year
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date	Valid
1	Spectrum Analyzer	R&S	FSP30	100091	2021-04-26	1Year
2	Amplifier	Agilent	8447D	2944A10178	2021-07-26	1Year
4	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2021-08-23	1Year
5	Coaxial Cable	Top	TYPE16(13M)	-	2021-04-26	1Year
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2021-04-30	1Year
7	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2021-07-30	1Year
8	Broadband Preamplifier	COMPLIANCE	PAP-1G18	2004	2021-07-26	1Year
9	Coaxial Cable	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2021-04-26	1Year
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date	Valid
1	Test Receiver	R&S	ESCI	101296	2021-04-26	1Year
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2021-10-30	1Year
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2021-04-29	1Year
4	Amplifier	ANRITSU	MH648A	M43381	2021-04-26	1Year
5	Cable	HUBER+SUHNER	CBL2	525178	2021-04-26	1Year
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date	Valid
1	Spectrum Analyzer	R&S	FSP30	100091	2021-04-26	1Year
2	Spectrum Analyzer	R&S	FSP40	100501	2021-07-26	1Year
3	Signal Analyzer	Agilent	N9010A	MY50520207	2021-04-19	1Year

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64dB (AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	± 1 x 10 ⁻⁷ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor: k=2	

6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R. China.

7 Duty Cycle

Type of Modulation	On time ms	Period ms	Duty Cycle linear	Duty Cycle %	Duty Cycle Factor(dB)	Average Factor(dB)
802.11b	100.0	100.0	1.00	100.00	0.00	0.00
802.11g	100.0	100.0	1.00	100.00	0.00	0.00
802.11n-HT20	100.0	100.0	1.00	100.00	0.00	0.00
802.11n-HT40	100.0	100.0	1.00	100.00	0.00	0.00


Remark:

Duty cycle=On Time/period;


Duty cycle factor= $10 \cdot \log(1/\text{Duty cycle})$;

Average factor= $20 \log_{10} \text{Duty cycle}$


Wi-Fi 802.11b




Wi-Fi 802.11g



Wi-Fi 802.11n-HT20



Wi-Fi 802.11n-HT40



8 Radiated Emissions

Test Requirement: FCC 47CFR Part 15 Section 15.209 & 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019;
ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

8.1 EUT Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation:

The test was performed in TX transmitting mode, the test data were shown in the report.


8.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



8.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth..... 10kHz
Video Bandwidth..... 10kHz
Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 100kHz
Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
Detector PK
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 3MHz
Detector Ave.
Resolution Bandwidth..... 1MHz
Video Bandwidth..... 10Hz

8.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

8.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

8.6 Summary of Test Results

Note:

1. Only the worst-case 802.11b mode were record in the report.
2. Lowest frequency generated in the device is 40MHz, frequency range of measurement should be above 30MHz.

Test Frequency: 30MHz ~ 8GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
11b: Low Channel 2412MHz									
223.45	38.14	QP	256	1.8	H	-11.62	26.52	46.00	-19.48
223.45	31.73	QP	4	1.4	V	-11.62	20.11	46.00	-25.89
4824.00	50.13	PK	325	1.3	V	-1.06	49.07	74.00	-24.93
4824.00	50.87	Ave	325	1.3	V	-1.06	49.81	54.00	-4.19
7236.00	45.58	PK	113	2.0	H	1.33	46.91	74.00	-27.09
7236.00	41.96	Ave	113	2.0	H	1.33	43.29	54.00	-10.71
2326.61	45.40	PK	242	1.5	V	-13.19	32.21	74.00	-41.79
2326.61	37.84	Ave	242	1.5	V	-13.19	24.65	54.00	-29.35
2353.40	44.64	PK	12	1.3	H	-13.14	31.50	74.00	-42.50
2353.40	37.13	Ave	12	1.3	H	-13.14	23.99	54.00	-30.01
2492.32	42.19	PK	206	1.0	V	-13.08	29.11	74.00	-44.89
2492.32	37.49	Ave	206	1.0	V	-13.08	24.41	54.00	-29.59

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: Middle Channel 2437MHz									
223.45	37.47	QP	24	1.6	H	-11.62	25.85	46.00	-20.15
223.45	31.49	QP	286	1.1	V	-11.62	19.87	46.00	-26.13
4874.00	48.90	PK	159	1.7	V	-0.62	48.28	74.00	-25.72
4874.00	51.40	Ave	159	1.7	V	-0.62	50.78	54.00	-3.22
7311.00	44.61	PK	282	1.5	H	2.21	46.82	74.00	-27.18
7311.00	42.64	Ave	282	1.5	H	2.21	44.85	54.00	-9.15
2348.88	45.57	PK	159	1.7	V	-13.19	32.38	74.00	-41.62
2348.88	37.77	Ave	159	1.7	V	-13.19	24.58	54.00	-29.42
2377.39	42.27	PK	315	1.5	H	-13.14	29.13	74.00	-44.87
2377.39	37.72	Ave	315	1.5	H	-13.14	24.58	54.00	-29.42
2484.01	44.80	PK	341	1.2	V	-13.08	31.72	74.00	-42.28
2484.01	38.90	Ave	341	1.2	V	-13.08	25.82	54.00	-28.18

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	Limit	Margin
				Height	Polar				
(MHz)	(dB μ V)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
11b: High Channel 2462MHz									
223.45	38.05	QP	151	1.8	H	-11.62	26.43	46.00	-19.57
223.45	31.38	QP	85	1.7	V	-11.62	19.76	46.00	-26.24
4924.00	47.95	PK	153	1.3	V	-0.24	47.71	74.00	-26.29
4924.00	51.39	Ave	153	1.3	V	-0.24	51.15	54.00	-2.85
7386.00	43.40	PK	13	1.2	H	2.84	46.24	74.00	-27.76
7386.00	41.15	Ave	13	1.2	H	2.84	43.99	54.00	-10.01
2324.96	46.76	PK	298	1.3	V	-13.19	33.57	74.00	-40.43
2324.96	37.91	Ave	298	1.3	V	-13.19	24.72	54.00	-29.28
2360.03	42.81	PK	182	1.5	H	-13.14	29.67	74.00	-44.33
2360.03	38.20	Ave	182	1.5	H	-13.14	25.06	54.00	-28.94
2484.19	44.41	PK	189	1.8	V	-13.08	31.33	74.00	-42.67
2484.19	37.87	Ave	189	1.8	V	-13.08	24.79	54.00	-29.21

Test Frequency: 8GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

9 Band Edge Measurement

Test Requirement: FCC 47CFR Part 15 Section 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019

Regulation 15.247 (d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Mode: Transmitting


9.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


9.2 Test Result

Test result plots shown as follows:


TX 11b: Band edge-left side




TX 11b: Band edge-right side




TX 11g: Band edge-left side




TX 11g: Band edge-right side




TX 11n HT20: Band edge-left side




TX 11n HT20: Band edge-right side



TX 11n HT40: Band edge-left side



TX 11n HT40: Band edge-right side



10 6 dB Bandwidth and 99% Bandwidth Measurement

Test Requirement: FCC 47CFR Part 15 Section 15.247
 Test Method: ANSI C63.10:2013
 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
 Test Limit: §15.247(a)(2)
 Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
 Test Mode: Transmitting

10.1 Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. 6dB Bandwidth Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz
 99% Bandwidth Set the spectrum analyzer: 1~5% of the OBW, VBW = 3 times the RBW

10.2 Test Result:



Operation mode	Test Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)
TX 11b	Channel 1	9.608	13.216
	Channel 6	9.568	13.184
	Channel 11	9.568	13.120
TX 11g	Channel 1	16.550	16.750
	Channel 6	16.550	16.650
	Channel 11	16.550	16.650
TX 11n HT20	Channel 1	17.604	17.496
	Channel 6	17.388	17.442
	Channel 11	17.388	17.442
TX 11n HT40	Channel 3	33.990	38.870
	Channel 6	33.950	34.870
	Channel 9	33.800	34.870

Test result plot:



6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 1





Mode: TX 11b channel 6





6 dB Bandwidth

99% Bandwidth

Mode: TX 11b channel 11





Mode: TX 11g channel 1





6 dB Bandwidth

99% Bandwidth

Mode: TX 11g channel 6





Mode: TX 11g channel 11





6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT20 channel 1





Mode: TX 11n HT20 channel 6





6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT20 channel 11





Mode: TX 11n HT40 channel 3





6 dB Bandwidth

99% Bandwidth

Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



11 Maximum Peak conducted Output Power

Test Requirement:	FCC 47CFR Part 15 Section 15.247
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Test Limit:	§15.247(b) The maximum peak conducted output power of the intentional radiator shall not exceed 1W.
Test Mode:	Transmitting

11.1 Test Procedure:

According to KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019

Section 8.3.1.1 RBW $\geq$ DTS bandwidth

Subclause 11.9.1.1 of ANSI C63.10 is applicable.

Section 8.3.1.2 Integrated band power method

For measuring the output power of a device transmitting a wide-band noise-like signal where the peak power amplitude is a statistical parameter, the preferred methodology is to use an integrated average power measurement, as described in 8.3.2. The peak integrated band power method of 11.9.1 in ANSI C63.10 is not applicable.


Subclause 11.9.2 of ANSI C63.10 is applicable.

11.2 Test Result:


Operation mode	Channel Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit
TX 11b	Low-2412	17.29	1W/30dBm
	Middle-2437	16.97	1W/30dBm
	High-2462	16.89	1W/30dBm
TX 11g	Low-2412	16.20	1W/30dBm
	Middle-2437	15.45	1W/30dBm
	High-2462	15.63	1W/30dBm
TX 11n HT20	Low-2412	16.25	1W/30dBm
	Middle-2437	15.59	1W/30dBm
	High-2462	15.65	1W/30dBm
TX 11n HT40	Low-2422	15.45	1W/30dBm
	Middle-2437	15.14	1W/30dBm
	High-2452	15.35	1W/30dBm

Test Plot:


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT20 channel 3



Mode: TX 11n HT20 channel 6



Mode: TX 11n HT20 channel 9



12 Power Spectral density

Test Requirement:	FCC 47CFR Part 15 Section 15.247
Test Method:	ANSI C63.10:2013 KDB 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019
Test Limit:	§15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Test Mode:	Transmitting

12.1 Test Procedure:

According to KDB 558074 D01 15.247 Meas Guidance v05r02 April 2, 2019 section 8.4

Subclause 11.10 of ANSI C63.10 is applicable.

Choose the test procedure according to the product type

Peak PSD

Subclause 11.10.2 of ANSI C63.10 is applicable.

AVG PSD


Subclause 11.10.3/4/5/6/7/8 of ANSI C63.10 is applicable.

12.2 Test Result:


Operation mode	Channel Frequency (MHz)	Power Spectral (dBm per 3kHz)	Limit
TX 11b	Low-2412	-15.47	8dBm per 3kHz
	Middle-2437	-16.13	8dBm per 3kHz
	High-2462	-15.91	8dBm per 3kHz
TX 11g	Low-2412	-19.87	8dBm per 3kHz
	Middle-2437	-20.40	8dBm per 3kHz
	High-2462	-20.46	8dBm per 3kHz
TX 11n HT20	Low-2412	-20.14	8dBm per 3kHz
	Middle-2437	-20.60	8dBm per 3kHz
	High-2462	-20.66	8dBm per 3kHz
TX 11n HT40	Low-2422	-23.27	8dBm per 3kHz
	Middle-2437	-23.71	8dBm per 3kHz
	High-2452	-23.53	8dBm per 3kHz

Test Plot:


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode: TX 11g channel 1




Mode: TX 11g channel 6




Mode: TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3



Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 9



13 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfil the requirement of this section.

Note: Please refer to EUT photos for more details.

14 RF Exposure

Note: Please refer to RF Exposure Report: WTD22D02019007W004

15 Photographs of test setup and EUT.

Note: Please refer to appendix: Appendix-ESP32-Photos.

=====End of Report=====