



RF MEASUREMENT REPORT

FCC ID: 2A5R6AASA-2B-2C
Applicant: AXEND, Inc.
Product: AeroSense Assure Home Care Assistant
Model No.: AASA-2B, AASA-2C, AASA-2B/N, AASA-2C/N
Brand Name: AERROSENSE
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (Section 15.247)
Test Date: February 10 ~ 26, 2022

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2201RSU057-U3	Rev. 01	Initial Report	03-23-2022	Valid

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information.....	6
1.5. Radio Specification	6
1.6. Working Frequencies	6
2. Test Configuration	7
2.1. Test Mode.....	7
2.2. Test System Connection Diagram	7
2.3. Test System Details	7
2.4. Test Software	7
2.5. Applied Standards.....	8
2.6. Test Environment Condition	8
3. Antenna Requirements	9
4. Measuring Instrument	10
5. Measurement Uncertainty.....	11
6. Test Result.....	12
6.1. Summary.....	12
6.2. 6dB Bandwidth Measurement.....	13
6.2.1. Test Limit.....	13
6.2.2. Test Procedure.....	13
6.2.3. Test Setting	13
6.2.4. Test Setup	13
6.2.5. Test Result	13
6.3. Output Power Measurement.....	14
6.3.1. Test Limit.....	14
6.3.2. Test Procedure.....	14
6.3.3. Test Setting	14
6.3.4. Test Setup	15
6.3.5. Test Result	15
6.4. Power Spectral Density Measurement	16
6.4.1. Test Limit.....	16
6.4.2. Test Procedure.....	16
6.4.3. Test Setting	16

6.4.4.	Test Setup	17
6.4.5.	Test Result	17
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement	18
6.5.1.	Test Limit	18
6.5.2.	Test Procedure	18
6.5.3.	Test Settling	18
6.5.4.	Test Setup	19
6.5.5.	Test Result	19
6.6.	Radiated Spurious Emission Measurement.....	20
6.6.1.	Test Limit	20
6.6.2.	Test Procedure	20
6.6.3.	Test Setting	20
6.6.4.	Test Setup	22
6.6.5.	Test Result	22
6.7.	Radiated Restricted Band Edge Measurement	23
6.7.1.	Test Limit	23
6.7.2.	Test Procedure	24
6.7.3.	Test Setting	24
6.7.4.	Test Setup	25
6.7.5.	Test Result	25
6.8.	AC Conducted Emissions Measurement.....	26
6.8.1.	Test Limit	26
6.8.2.	Test Setup	26
6.8.3.	Test Result	26
Appendix A – Test Result.....		27
A.1	Duty Cycle Test Result.....	27
A.2	6dB Bandwidth Test Result	28
A.3	Output Power Test Result	32
A.4	Power Spectral Density Test Result.....	34
A.5	Conducted Band Edge and Out-of-Band Emissions Test Result.....	38
A.6	Radiated Spurious Emission Test Result.....	45
A.7	Radiated Restricted Band Edge Test Result.....	50
A.8	AC Conducted Emissions Test Result	74
Appendix B – Test Setup Photograph		76
Appendix C – EUT Photograph		77

1. General Information

1.1. Applicant

AXEND, Inc.

12045 E. Waterfront Drive, Ste 450 Los Angeles CA 90094

1.2. Manufacturer

Time Date Varying Transmission Co. Ltd

No.9 Venture Road, High-tech District, Xiangtan, Hunan, 411102, China

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP) 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
	A2LA: 3628.01 FCC: CN1166 VCCI: ☐ R-20025 ☐ G-20034 ☐ C-20020 ☐ T-20020 ☐ R-20141 ☐ G-20134 ☐ C-20103 ☐ T-20104
	CNAS: L10551 ISED: CN0001
☐	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 FCC: CN1284
	CNAS: L10551 ISED: CN0105
☐	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725 FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	AeroSense Assure Home Care Assistant
Model No.	AASA-2B, AASA-2C, AASA-2B/N, AASA-2C/N
Serial No.	0860047219080007
Wi-Fi Specification	802.11b/g/n
Radar Specification	60-64G
Antenna Information	Refer to Clause 1.5
Accessories	
Adapter	MODEL: XSC-0502000SWCNU INPUT: 100-240V ~ 50/60Hz 0.4A OUTPUT: 5V = 2A
Remark:	
1. The models (AASA-2B and AASA-C) use the different software algorithms, but the same hardware. The difference between AASA-2B and AASA-2B/N only external packing. AASA-2B was selected to perform test.	
2. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

Note: For other features of this EUT, test report will be issued separately.

1.5. Radio Specification

Frequency Range	802.11b/g/n-HT20: 2412 ~ 2462MHz
Channel Number	802.11b/g/n-HT20: 11
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 72.2Mbps
Antenna Type	on-board ceramic antenna
Antenna Gain	2 dBi

1.6. Working Frequencies

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11b (1Mbps)
Mode 2: Transmit by 802.11g (6Mbps)
Mode 3: Transmit by 802.11n-HT20 (MCS0)

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.



2.3. Test System Details

Product	Manufacturer	Model No.
1	Notebook	Lenovo
		E495

2.4. Test Software

The test utility software used during testing was “UI_mptool.exe”, and the version was 1v15.

2.5. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- ANSI C63.10-2013

2.6. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2022/12/29	SIP-AC2
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06599	1 year	2022/10/20	SIP-AC2
Preamplifier	EMCI	EMC184045SE	MRTSUE06602	1 year	2022/10/11	SIP-AC2
EMI Test Receiver	R&S	ESR3	MRTSUE06613	1 year	2022/6/24	SIP-AC2
Thermohygrometer	testo	608-H1	MRTSUE06623	1 year	2022/11/28	SIP-AC2
Thermohygrometer	testo	608-H1	MRTSUE06624	1 year	2022/11/28	SIP-AC2
Preamplifier	EMCI	EMC001330	MRTSUE06643	1 year	2023/1/13	SIP-AC2
Preamplifier	EMCI	EMC051845SE	MRTSUE06644	1 year	2022/11/8	SIP-AC2
TRILOG Antenna	Schwarzbeck	VULB 9168	MRTSUE06647	1 year	2022/8/5	SIP-AC2
Anechoic Chamber	RIKEN	SIP-AC2	MRTSUE06781	1 year	2022/12/23	SIP-AC2
Signal Analyzer	Keysight	N9010B	MRTSUE07028	1 year	2022/12/9	SIP-AC2/SIP-TR1/SIP-TR2
Signal Analyzer	Keysight	N9030B	MRTSUE06395	1 year	2022/8/8	SIP-TR1/SIP-TR2
USB Power Sensor	Keysight	U2021XA	MRTSUE06595	1 year	2022/9/7	SIP-TR1/SIP-TR2
USB Power Sensor	Keysight	U2021XA	MRTSUE06596	1 year	2022/9/7	SIP-TR1/SIP-TR2
Signal Generator	Keysight	N5182B	MRTSUE06605	1 year	2022/10/31	SIP-TR1/SIP-TR2
Thermohygrometer	testo	622	MRTSUE06628	1 year	2023/1/6	SIP-TR2

Software	Version	Function
EMI Software	V3	EMI Test Software

5. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 9kHz~150kHz: 3.74dB 150kHz~30MHz: 3.44dB
Radiated Emission Measurement
Measurement Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): Horizontal: 30MHz~300MHz: 5.04dB 300MHz~1GHz: 4.95dB 1GHz~40GHz: 6.40dB Vertical: 30MHz~300MHz: 5.24dB 300MHz~1GHz: 6.03dB 1GHz~40GHz: 6.40dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.78dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 1.13dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 1.15dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2Uc(y)$): 0.28%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Remark:

1. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
2. For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting

Peak Power Measurement


The maximum peak conducted output power may be measured using a broadband peak RF power meter.

The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON Time Date of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


6.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 Time Dates the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
8. Sweep Time Date = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $10 \log (1/x)$, where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission Time Date. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 Time Dates the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep Time Date = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep Time Date = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep Time Date = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep Time Date = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.
If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.
4. Detector = Peak
5. Sweep Time Date = auto
6. Trace mode = max hold
7. Trace was allowed to stabilize

6.6.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3

ANSI C63.10-2013 Section 6.6

ANSI C63.10-2013 Section 11.13

6.7.3. Test Setting


Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep Time Date = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW $\geq 1/T$
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep Time Date = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 Time Dates (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement


6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBuV)	AV (dBuV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.8.2. Test Setup



6.8.3. Test Result


Refer to Appendix A.8.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	SIP-TR1	Test Engineer	Alisa Deng
Test Date	2022/02/10		

Test Mode	Duty Cycle
802.11b	100%
802.11g	100%
802.11n-HT20	100%

Duty Cycle (T = Transmission Duration)	
802.11b	802.11g
	
802.11n-HT20	
	


A.2 6dB Bandwidth Test Result

Test Site	SIP-TR1	Test Engineer	Alisa Deng
Test Date	2022/02/10		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	9.08	≥ 0.5
11b	1Mbps	06	2437	9.08	≥ 0.5
11b	1Mbps	11	2462	9.08	≥ 0.5
11g	6Mbps	01	2412	16.58	≥ 0.5
11g	6Mbps	06	2437	16.57	≥ 0.5
11g	6Mbps	11	2462	16.57	≥ 0.5
11n-HT20	MCS0	01	2412	17.75	≥ 0.5
11n-HT20	MCS0	06	2437	17.74	≥ 0.5
11n-HT20	MCS0	11	2462	17.74	≥ 0.5

802.11b 6dB Bandwidth


Channel 01 (2412MHz)




Channel 06 (2437MHz)




Channel 11 (2462MHz)






802.11n-HT20 6dB Bandwidth


Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



A.3 Output Power Test Result

Power output test was verified over all data rates of each mode shown as below, and then choose the worst data rate (gray marker) for final test of each channel.

Test Mode	Bandwidth (MHz)	Channel No.	Frequency (MHz)	Data Rate / MCS	Average Power (dBm)
802.11b	20	1	2412	1Mbps	18.65
				5.5Mbps	18.46
				11Mbps	18.23
802.11g	20	1	2412	6Mbps	17.82
				24Mbps	17.63
				54Mbps	17.41
802.11n	20	1	2412	MCS0	15.62
				MCS3	15.40
				MCS7	15.23

Test Site	SIP-TR1	Test Engineer	Alisa Deng
Test Date	2022/02/14		

Test Result of Peak Output Power

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Peak Power (dBm)	Limit (dBm)
11b	1Mbps	01	2412	21.48	≤ 30.00
11b	1Mbps	06	2437	21.35	≤ 30.00
11b	1Mbps	11	2462	21.37	≤ 30.00
11g	6Mbps	01	2412	24.63	≤ 30.00
11g	6Mbps	06	2437	24.98	≤ 30.00
11g	6Mbps	11	2462	25.22	≤ 30.00
11n-HT20	MCS0	01	2412	23.50	≤ 30.00
11n-HT20	MCS0	06	2437	23.88	≤ 30.00
11n-HT20	MCS0	11	2462	24.15	≤ 30.00

Test Result of Average Output Power (Reporting Only)

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)
11b	1Mbps	01	2412	18.65	≤ 30.00
11b	1Mbps	06	2437	18.61	≤ 30.00
11b	1Mbps	11	2462	18.64	≤ 30.00
11g	6Mbps	01	2412	17.82	≤ 30.00
11g	6Mbps	06	2437	17.58	≤ 30.00
11g	6Mbps	11	2462	17.83	≤ 30.00
11n-HT20	MCS0	01	2412	15.62	≤ 30.00
11n-HT20	MCS0	06	2437	15.70	≤ 30.00
11n-HT20	MCS0	11	2462	15.80	≤ 30.00

A.4 Power Spectral Density Test Result

Test Site	SIP-TR1	Test Engineer	Alisa Deng
Test Date	2022/02/14		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	PKPSD (dBm/ 3KHz)	Limit (dBm / 3kHz)	Result
11b	1Mbps	01	2412	-11.79	≤ 8.00	Pass
11b	1Mbps	06	2437	-11.76	≤ 8.00	Pass
11b	1Mbps	11	2462	-11.71	≤ 8.00	Pass
11g	6Mbps	01	2412	-11.39	≤ 8.00	Pass
11g	6Mbps	06	2437	-11.69	≤ 8.00	Pass
11g	6Mbps	11	2462	-11.61	≤ 8.00	Pass
11n-HT20	MCS0	01	2412	-13.01	≤ 8.00	Pass
11n-HT20	MCS0	06	2437	-12.77	≤ 8.00	Pass
11n-HT20	MCS0	11	2462	-12.65	≤ 8.00	Pass

802.11b - PKPSD

Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11g – PKPSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




802.11n-HT20 – PKPSD


Channel 01 (2412MHz)



Channel 06 (2437MHz)



Channel 11 (2462MHz)



A.5 Conducted Band Edge and Out-of-Band Emissions Test Result


Test Site	SIP-TR1	Test Engineer	Alisa Deng
Test Date	2022/02/15		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	Limit
11b	1Mbps	01	2412	20dBc
11b	1Mbps	06	2437	20dBc
11b	1Mbps	11	2462	20dBc
11g	6Mbps	01	2412	20dBc
11g	6Mbps	06	2437	20dBc
11g	6Mbps	11	2462	20dBc
11n-HT20	MCS0	01	2412	20dBc
11n-HT20	MCS0	06	2437	20dBc
11n-HT20	MCS0	11	2462	20dBc


802.11b Out-of-Band Emissions

Channel 01 (2412MHz)


Reference Level



Low Band Edge




Spurious Emission




Channel 06 (2437MHz)

Reference Level




Spurious Emission



802.11b Out-of-Band Emissions

Channel 11 (2462MHz)


Reference Level



High Band Edge



Spurious Emission



802.11g Out-of-Band Emissions

Channel 01 (2412MHz)


Reference Level



Low Band Edge



Spurious Emission




Channel 06 (2437MHz)

Reference Level



Spurious Emission



802.11g Out-of-Band Emissions

Channel 11 (2462MHz)


Reference Level



High Band Edge



Spurious Emission




802.11n-HT20 Out-of-Band Emissions

Channel 01 (2412MHz)


Reference Level



Low Band Edge



Spurious Emission




Channel 06 (2437MHz)

Reference Level



Spurious Emission



802.11n-HT20 Out-of-Band Emissions

Channel 11 (2462MHz)


Reference Level



High Band Edge



Spurious Emission



A.6 Radiated Spurious Emission Test Result

Test Site	SIP-AC2	Test Engineer	Allen Zou
Test Date	2022/02/15	Test Mode:	802.11b
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
01	4825.0	52.5	-5.9	46.6	74.0	-27.4	Peak	Horizontal
	10996.0	42.3	7.5	49.8	74.0	-24.2	Peak	Horizontal
	12177.5	41.9	7.9	49.8	74.0	-24.2	Peak	Horizontal
	4825.0	54.0	-5.9	48.1	74.0	-25.9	Peak	Vertical
	10919.5	42.3	7.3	49.6	74.0	-24.4	Peak	Vertical
	12092.5	41.3	8.2	49.5	74.0	-24.5	Peak	Vertical
06	4876.0	51.3	-5.6	45.7	74.0	-28.3	Peak	Horizontal
	7307.0	47.4	1.5	48.9	74.0	-25.1	Peak	Horizontal
	11599.5	41.9	8.2	50.1	74.0	-23.9	Peak	Horizontal
	4876.0	52.4	-5.6	46.8	74.0	-27.2	Peak	Vertical
	7315.5	49.8	1.7	51.5	74.0	-22.5	Peak	Vertical
	7315.5	46.6	1.7	48.3	54.0	-5.7	Average	Vertical
	12152.0	42.0	8.3	50.3	74.0	-23.7	Peak	Vertical
11	7383.5	47.1	1.9	49.0	74.0	-25.0	Peak	Horizontal
	11557.0	41.9	8.2	50.1	74.0	-23.9	Peak	Horizontal
	12101.0	41.5	8.4	49.9	74.0	-24.1	Peak	Horizontal
	7383.5	47.1	1.9	49.0	74.0	-25.0	Peak	Vertical
	11557.0	41.9	8.2	50.1	74.0	-23.9	Peak	Vertical
	12101.0	41.5	8.4	49.9	74.0	-24.1	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Site	SIP-AC2	Test Engineer	Allen Zou
Test Date	2022/02/15	Test Mode:	802.11g
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
01	8072.0	42.9	2.9	45.8	74.0	-28.2	Peak	Horizontal
	11455.0	41.3	8.4	49.7	74.0	-24.3	Peak	Horizontal
	12152.0	40.9	8.3	49.2	74.0	-24.8	Peak	Horizontal
	8182.5	42.5	2.8	45.3	74.0	-28.7	Peak	Vertical
	11004.5	42.2	7.4	49.6	74.0	-24.4	Peak	Vertical
	11489.0	42.5	8.7	51.2	74.0	-22.8	Peak	Vertical
	11489.0	31.7	8.7	40.4	54.0	-13.6	Average	Vertical
06	7307.0	47.8	1.5	49.3	74.0	-24.7	Peak	Horizontal
	10826.0	42.2	7.2	49.4	74.0	-24.6	Peak	Horizontal
	12101.0	41.1	8.4	49.5	74.0	-24.5	Peak	Horizontal
	7307.0	52.3	1.5	53.8	74.0	-20.2	Peak	Vertical
	7307.0	42.2	1.5	43.7	54.0	-10.3	Average	Vertical
	10877.0	42.0	7.6	49.6	74.0	-24.4	Peak	Vertical
	11582.5	41.8	8.5	50.3	74.0	-23.7	Peak	Vertical
11	7375.0	46.9	1.8	48.7	74.0	-25.3	Peak	Horizontal
	10826.0	42.3	7.2	49.5	74.0	-24.5	Peak	Horizontal
	11455.0	41.4	8.4	49.8	74.0	-24.2	Peak	Horizontal
	7383.5	52.2	1.9	54.1	74.0	-19.9	Peak	Vertical
	7383.5	42.8	1.9	44.7	54.0	-9.3	Average	Vertical
	10758.0	41.4	7.3	48.7	74.0	-25.3	Peak	Vertical
	11633.5	41.8	8.0	49.8	74.0	-24.2	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Site	SIP-AC2	Test Engineer	Allen Zou
Test Date	2022/02/15	Test Mode:	802.11n-HT20
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		


Test Channel	Frequency (MHz)	Reading Level (dBμV)	Factor (dB/m)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
01	8182.5	42.7	2.8	45.5	74.0	-28.5	Peak	Horizontal
	10953.5	42.5	7.6	50.1	74.0	-23.9	Peak	Horizontal
	11599.5	42.3	8.2	50.5	74.0	-23.5	Peak	Horizontal
	8131.5	42.2	3.0	45.2	74.0	-28.8	Peak	Vertical
	10860.0	42.4	7.6	50.0	74.0	-24.0	Peak	Vertical
	11480.5	41.7	8.7	50.4	74.0	-23.6	Peak	Vertical
06	7315.5	43.9	1.7	45.6	74.0	-28.4	Peak	Horizontal
	8182.5	42.5	2.8	45.3	74.0	-28.7	Peak	Horizontal
	11480.5	41.3	8.7	50.0	74.0	-24.0	Peak	Horizontal
	7315.5	47.7	1.7	49.4	74.0	-24.6	Peak	Vertical
	11489.0	41.4	8.7	50.1	74.0	-23.9	Peak	Vertical
	12118.0	41.0	8.5	49.5	74.0	-24.5	Peak	Vertical
11	7375.0	46.2	1.8	48.0	74.0	-26.0	Peak	Horizontal
	8446.0	42.5	2.7	45.2	74.0	-28.8	Peak	Horizontal
	11472.0	40.6	8.6	49.2	74.0	-24.8	Peak	Horizontal
	7375.0	47.6	1.8	49.4	74.0	-24.6	Peak	Vertical
	8106.0	42.2	3.0	45.2	74.0	-28.8	Peak	Vertical
	11480.5	40.7	8.7	49.4	74.0	-24.6	Peak	Vertical

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The Result of Radiated Emission below 1GHz:

Site: SIP-AC2	Time: 2022/02/26
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_VULB 9168_30-1000MHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Note: Transmit by 802.11n at channel 2412MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1			46.005	19.879	2.068	-20.121	40.000	17.810	PK
2			110.510	20.337	4.593	-23.163	43.500	15.744	PK
3			166.285	22.303	3.995	-21.197	43.500	18.308	PK
4			302.570	25.353	6.259	-20.647	46.000	19.094	PK
5			710.455	29.372	1.620	-16.628	46.000	27.752	PK
6		*	887.480	31.314	1.370	-14.686	46.000	29.944	PK

Note 1: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)


Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: QP measurement was not performed when peak measure level was lower than the QP limit.

Note 3: The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value.

Therefore, the data is not presented in the report.

Site: SIP-AC2	Time: 2022/02/26
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_VULB 9168_30-1000MHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Note: Transmit by 802.11n at channel 2412MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			36.790	31.074	13.436	-8.926	40.000	17.638	PK
2		*	46.975	32.446	14.577	-7.554	40.000	17.869	PK
3			89.170	22.828	9.834	-20.672	43.500	12.994	PK
4			110.995	23.210	7.397	-20.290	43.500	15.813	PK
5			286.565	24.948	6.098	-21.052	46.000	18.849	PK
6			889.420	30.541	0.660	-15.459	46.000	29.881	PK

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m)


Note 2: QP measurement was not performed when peak measure level was lower than the QP limit.

Note 3: The amplitude of radiated emissions (frequency range from 9kHz to 30MHz and 18GHz to 25GHz) is that proximity to ambient noise, which also are attenuated more than 20 dB below the permissible value.

Therefore, the data is not presented in the report.

A.7 Radiated Restricted Band Edge Test Result

Site: SIP-AC2	Test Data: 2022/02/15 - 16:25
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1			2382.464	58.655	26.201	-15.345	74.000	32.454	PK
2			2390.000	56.550	24.146	-17.450	74.000	32.404	PK
3		*	2412.200	104.499	72.147	N/A	N/A	32.352	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:30
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	44.823	12.419	-9.177	54.000	32.404	AV
2		*	2411.024	102.253	69.901	N/A	N/A	32.352	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:31
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1			2381.456	57.299	24.838	-16.701	74.000	32.461	PK
2			2390.000	55.900	23.496	-18.100	74.000	32.404	PK
3		*	2411.136	94.552	62.200	N/A	N/A	32.352	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:35
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	44.336	11.932	-9.664	54.000	32.404	AV
2		*	2410.968	91.965	59.613	N/A	N/A	32.352	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:36
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11b	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		*	2460.952	103.797	71.514	N/A	N/A	32.284	PK
2			2483.500	56.403	24.208	-17.597	74.000	32.195	PK
3			2494.528	58.121	25.896	-15.879	74.000	32.225	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		*	2461.096	101.610	69.327	N/A	N/A	32.283	AV
2			2483.500	44.956	12.761	-9.044	54.000	32.195	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:43
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11b	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1		*	2461.504	94.780	62.498	N/A	N/A	32.281	PK
2			2483.500	55.940	23.745	-18.060	74.000	32.195	PK
3			2484.856	57.584	25.385	-16.416	74.000	32.198	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:48
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11b	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		*	2461.072	92.618	60.335	N/A	N/A	32.283	AV
2			2483.500	44.515	12.320	-9.485	54.000	32.195	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 16:50
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2389.800	72.672	40.266	-1.328	74.000	32.406	PK
2			2390.000	72.304	39.900	-1.696	74.000	32.404	PK
3		*	2418.584	105.042	72.689	N/A	N/A	32.353	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:09
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	53.854	21.450	-0.146	54.000	32.404	AV
2		*	2410.632	95.703	63.350	N/A	N/A	32.353	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:18
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2389.520	60.445	28.037	-13.555	74.000	32.407	PK
2			2390.000	59.638	27.234	-14.362	74.000	32.404	PK
3		*	2405.592	94.458	62.098	N/A	N/A	32.361	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:25
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	46.948	14.544	-7.052	54.000	32.404	AV
2		*	2413.040	86.380	54.028	N/A	N/A	32.352	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:27
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1		*	2455.504	105.001	72.700	N/A	N/A	32.301	PK
2			2483.500	66.504	34.309	-7.496	74.000	32.195	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:32
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		*	2456.008	96.636	64.337	N/A	N/A	32.300	AV
2			2483.500	50.526	18.331	-3.474	54.000	32.195	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:33
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		*	2455.528	95.760	63.459	N/A	N/A	32.301	PK
2			2483.500	59.575	27.380	-14.425	74.000	32.195	PK
3			2483.776	60.576	28.380	-13.424	74.000	32.196	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11g	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1		*	2456.008	87.314	55.015	N/A	N/A	32.300	AV
2			2483.500	46.255	14.060	-7.745	54.000	32.195	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:42
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2389.912	68.540	36.135	-5.460	74.000	32.405	PK
2			2390.000	68.358	35.954	-5.642	74.000	32.404	PK
3		*	2408.896	102.696	70.341	N/A	N/A	32.356	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 17:51
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	48.501	16.097	-5.499	54.000	32.404	AV
2		*	2410.352	94.136	61.783	N/A	N/A	32.353	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 18:05
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	60.028	27.624	-13.972	74.000	32.404	PK
2		*	2408.840	92.454	60.099	N/A	N/A	32.356	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 18:09
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2412MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1			2390.000	45.007	12.603	-8.993	54.000	32.404	AV
2		*	2406.096	83.581	51.221	N/A	N/A	32.360	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 18:11
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1		*	2457.136	102.265	69.969	N/A	N/A	32.296	PK
2			2483.500	63.396	31.201	-10.604	74.000	32.195	PK
3			2485.048	64.183	31.984	-9.817	74.000	32.199	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 18:22
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1		*	2456.752	92.908	60.611	N/A	N/A	32.297	AV
2			2483.500	48.059	15.864	-5.941	54.000	32.195	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 18:24
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Margin (dB)	Limit (dBuV/m)	Factor (dB/m)	Type
1		*	2454.016	91.140	58.834	N/A	N/A	32.306	PK
2			2483.500	56.646	24.451	-17.354	74.000	32.195	PK
3			2483.776	58.071	25.875	-15.929	74.000	32.196	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

Site: SIP-AC2	Test Data: 2022/02/15 - 18:27
Limit: FCC_Part15.209_RE(3m)	Engineer: Allen Zou
Probe: SIP-AC2_BBHA9120D_1-18GHz	Polarity: Vertical
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit at channel 2462MHz by 802.11n-HT20	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV/m)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV/m)	Factor (dB/m)	Type
1		*	2456.752	82.358	50.061	N/A	N/A	32.297	AV
2			2483.500	45.050	12.855	-8.950	54.000	32.195	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m).

A.8 AC Conducted Emissions Test Result

Site: SIP-SR2	Test Data: 2022/02/11 - 10:31
Limit: FCC_Part15.207_CE_AC Power	Engineer: Augleo Wang
Probe: SIP-SR2-ENV216_101684_E	Polarity: Line
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at channel 2437MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV)	Factor (dB)	Type
1			0.174	50.453	40.718	-14.315	64.767	9.735	QP
2			0.174	33.252	23.517	-21.515	54.767	9.735	AV
3			0.218	46.986	37.205	-15.909	62.895	9.782	QP
4			0.218	30.618	20.836	-22.277	52.895	9.782	AV
5			0.470	32.429	22.604	-24.085	56.514	9.825	QP
6			0.470	20.530	10.705	-25.984	46.514	9.825	AV
7		*	0.606	43.506	33.672	-12.494	56.000	9.834	QP
8			0.606	33.414	23.580	-12.586	46.000	9.834	AV
9			0.890	31.805	21.960	-24.195	56.000	9.845	QP
10			0.890	21.969	12.124	-24.031	46.000	9.845	AV
11			1.222	32.951	23.075	-23.049	56.000	9.876	QP
12			1.222	22.618	12.742	-23.382	46.000	9.876	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Site: SIP-SR2	Test Data: 2022/02/11 - 10:37
Limit: FCC_Part15.207_CE_AC Power	Engineer: Augleo Wang
Probe: SIP-SR2-ENV216_101684_E	Polarity: Neutral
EUT: AeroSense Assure Home Care Assistant	Power: AC 120V/60Hz
Test Mode: Transmit by 802.11n-HT20 at channel 2437MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBμV)	Reading Level (dBμV)	Margin (dB)	Limit (dBμV)	Factor (dB)	Type
1			0.174	50.535	40.800	-14.232	64.767	9.735	QP
2			0.174	33.942	24.207	-20.826	54.767	9.735	AV
3			0.218	46.987	37.210	-15.908	62.895	9.777	QP
4			0.218	31.816	22.040	-21.078	52.895	9.777	AV
5			0.482	34.289	24.469	-22.016	56.305	9.820	QP
6			0.482	23.722	13.902	-22.582	46.305	9.820	AV
7			0.602	42.096	32.271	-13.904	56.000	9.825	QP
8		*	0.602	34.879	25.054	-11.121	46.000	9.825	AV
9			0.910	31.147	21.306	-24.853	56.000	9.841	QP
10			0.910	22.496	12.655	-23.504	46.000	9.841	AV
11			1.206	36.843	26.970	-19.157	56.000	9.873	QP
12			1.206	24.880	15.008	-21.120	46.000	9.873	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB)

Appendix B – Test Setup Photograph

Refer to “2201RSU057-UT” file.

Appendix C – EUT Photograph

Refer to “2201RSU057-UE” file.

————— The End —————