

## RF Exposure Evaluation

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

---

## Test Result of RF Exposure Evaluation

wifi 5G mode

Channel		Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Band 1	802.11a	13.16	20.7014	0.01034	1.0	PASS
	802.11n HT20	9.82	9.5940	0.00479	1.0	PASS
	802.11n HT40	10.91	12.3310	0.00616	1.0	PASS
	802.11ac HT20	9.47	8.8512	0.00442	1.0	PASS
	802.11ac HT40	10.78	11.9674	0.00598	1.0	PASS
	802.11ac HT80	7.54	5.6754	0.00284	1.0	PASS
Band 4	802.11a	10.28	10.6660	0.00533	1.0	PASS
	802.11n HT20	13.02	20.0447	0.01002	1.0	PASS
	802.11n HT40	13.32	21.4783	0.01073	1.0	PASS
	802.11ac HT20	13.12	20.5116	0.01025	1.0	PASS
	802.11ac HT40	12.59	18.1552	0.00907	1.0	PASS
	802.11ac HT80	11.32	13.5519	0.00677	1.0	PASS

Remark: antenna gain=4dBi