

6dB Bandwidth



Offset 11dB = Attenuator + Temporary antenna connector loss + Cable loss

Test Mode	Antenna	6dB Bandwidth (MHz)		
		5745MHz	5785MHz	5825MHz
802.11a	Chain0	16.31	16.42	16.09
802.11n HT20	Chain0	17.57	17.64	17.63
802.11ac VHT20	Chain0	17.60	17.62	17.06

Test Mode	Antenna	6dB Bandwidth (MHz)		
		5755MHz	---	5795MHz
802.11n HT40	Chain0	35.55	---	34.68
802.11ac VHT40	Chain0	36.36	---	36.40


Test Mode	Antenna	6dB Bandwidth (MHz)		
		5775MHz	---	---
802.11ac VHT80	Chain0	75.43	---	---

Test Mode: 802.11a




Mode:802.11a Frequency:5745MHz Ant:Chain0

Mode:802.11a Frequency:5785MHz Ant:Chain0




Mode:802.11a Frequency:5825MHz Ant:Chain0


Test Mode: 802.11n HT20




Test Mode: 802.11ac VHT20



Test Mode: 802.11n HT40




Mode:802.11n HT40 Frequency:5755MHz Ant:Chain0




Mode:802.11n HT40 Frequency:5795MHz Ant:Chain0

Test Mode: 802.11ac VHT40




Mode:802.11ac VHT40 Frequency:5755MHz
Ant:Chain0



Mode:802.11ac VHT40 Frequency:5795MHz
Ant:Chain0

Test Mode: 802.11ac VHT80



Mode:802.11ac VHT80 Frequency:5775MHz
Ant:Chain0

Transmitter Power Spectral Density

Offset 11dB = Attenuator + Temporary antenna connector loss + Cable loss

Test Mode	Antenna	Tones	5745MHz		5785MHz		5825MHz	
			Correction Factor (dB)	Power Density (dBm/500KHz)	Correction Factor (dB)	Power Density (dBm/500KHz)	Correction Factor (dB)	Power Density (dBm/500KHz)
802.11a	Chain0	NA	0	2.521	0	2.265	0	1.717
802.11n HT20	Chain0	NA	0	1.937	0	1.468	0	1.441
802.11ac VHT20	Chain0	NA	0	2.028	0	1.601	0	1.197

Note: As measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result.


Test Mode	Antenna	Tones	5755MHz		---		5795MHz	
			Correction Factor (dB)	Power Density (dBm/500KHz)	Correction Factor (dB)	Power Density (dBm/500KHz)	Correction Factor (dB)	Power Density (dBm/500KHz)
802.11n HT40	Chain0	NA	0	-1.143	---	---	0	-1.433
802.11ac VHT40	Chain0	NA	0	-0.946	---	---	0	-1.337

Note: As measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result.


Test Mode	Antenna	Tones	5775MHz		---		---	
			Correction Factor (dB)	Power Density (dBm/500KHz)	Correction Factor (dB)	Power Density (dBm/500KHz)	Correction Factor (dB)	Power Density (dBm/500KHz)
802.11ac VHT80	Chain0	NA	0.15	-3.220	---	---	---	---

Note: As measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result.


Test Mode: 802.11a




Test Mode: 802.11n HT20




Test Mode: 802.11ac VHT20



Test Mode: 802.11n HT40



Test Mode: 802.11ac VHT40



Test Mode: 802.11ac VHT80

