

FCC Test Report (Part 22)

Report No.: RFBEEKK-WTW-P20080111-1

FCC ID: 2AARN-DLWPH-8M

Test Model: DLWPH-8M

Series Model: DLWPH-8M-RW

Received Date: Aug. 06, 2020

Test Date: Sep. 02, 2020 ~ Oct. 20, 2020

Issued Date: Oct. 21, 2020

Applicant: PHIHONG TECHNOLOGY CO. LTD.

Address: No.568, Fu Xing 3rd Rd., Guishan, Tao Yuan Hsien, 333 Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Test Site and Instruments	7
3 General Information	9
3.1 General Description of EUT	9
3.2 Configuration of System under Test	11
3.2.1 Description of Support Units	11
3.3 Test Mode Applicability and Tested Channel Detail	12
3.4 EUT Operating Conditions	15
3.5 General Description of Applied Standards and References	15
4 Test Types and Results	16
4.1 Output Power Measurement	16
4.1.1 Limits of Output Power Measurement	16
4.1.2 Test Procedures	16
4.1.3 Test Setup	16
4.1.4 Test Results	17
4.2 Modulation Characteristics Measurement	23
4.2.1 Limits of Modulation Characteristics	23
4.2.2 Test Procedure	23
4.2.3 Test Setup	23
4.2.4 Test Results	24
4.3 Frequency Stability Measurement	25
4.3.1 Limits of Frequency Stability Measurement	25
4.3.2 Test Procedure	25
4.3.3 Test Setup	25
4.3.4 Test Results	26
4.4 Occupied Bandwidth Measurement	31
4.4.1 Test Procedure	31
4.4.2 Test Setup	31
4.4.3 Test Result	32
4.5 Band Edge Measurement	38
4.5.1 Limits of Band Edge Measurement	38
4.5.2 Test Setup	38
4.5.3 Test Procedures	38
4.5.4 Test Results	39
4.6 Peak to Average Ratio	44
4.6.1 Limits of Peak to Average Ratio Measurement	44
4.6.2 Test Setup	44
4.6.3 Test Procedures	44
4.6.4 Test Results	45
4.7 Conducted Spurious Emissions	48
4.7.1 Limits of Conducted Spurious Emissions Measurement	48
4.7.2 Test Setup	48
4.7.3 Test Procedure	48
4.7.4 Test Results	49
4.8 Radiated Emission Measurement	56
4.8.1 Limits of Radiated Emission Measurement	56
4.8.2 Test Procedure	56
4.8.3 Deviation from Test Standard	56
4.8.4 Test Setup	57
4.8.5 Test Results	58

5	Pictures of Test Arrangements	66
	Appendix – Information of the Testing Laboratories	67

Release Control Record

Issue No.	Description	Date Issued
RFBEKK-WTW-P20080111-1	Original Release	Oct. 21, 2020

1 Certificate of Conformity

Product: EV charging system module 4G with WI-FI

Brand: Pihong Technology Co., Ltd.

Test Model: DLWPH-8M

Series Model: DLWPH-8M-RW

Sample Status: Engineering Sample

Applicant: PHIHONG TECHNOLOGY CO. LTD.

Test Date: Sep. 02, 2020 ~ Oct. 20, 2020

Standards: FCC Part 22, Subpart H

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Lena Wang, **Date:** Oct. 21, 2020
Lena Wang / Specialist

Approved by : Dylan Chiou, **Date:** Oct. 21, 2020
Dylan Chiou / Senior Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 22 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 22.913 (a)	Effective radiated power	Pass	Meet the requirement of limit.
2.1047	Modulation Characteristics	Pass	Meet the requirement
22.913 (d)	Peak To Average Ratio	Pass	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
22.917	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -38.60 dB at 1652.80 MHz and 1693.20 MHz.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.04 dB
	30MHz ~ 200MHz	3.86 dB
	200MHz ~1000MHz	3.87 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver KEYSIGHT	N9038A	MY55420137	Apr. 16, 2020	Apr. 15, 2021
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Jun. 12, 2020	Jun. 11, 2021
Spectrum Analyzer KEYSIGHT	N9030B	MY57140953	Jul. 02, 2020	Jul. 01, 2021
MXG Vector signal generator Agilent	N5182B	MY53050162	Jan. 14, 2020	Jan. 13, 2021
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Nov. 08, 2019	Nov. 07, 2020
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Nov. 07, 2019	Nov. 06, 2020
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-1169	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 24, 2019	Nov. 23, 2020
Loop Antenna EMCI	EM-6879	269	Sep. 18, 2019 Sep. 17, 2020	Sep. 17, 2020 Sep. 16, 2021
Preamplifier Agilent (Below 1GHz)	8447D	2944A10638	Jun. 08, 2020	Jun. 07, 2021
Preamplifier Agilent (Above 1GHz)	8449B	3008A02367	Feb. 18, 2020	Feb. 17, 2021
RF signal cable HUBER+SUHNER&EMCI	SUCOFLEX 104 & EMC104-SM- SM8000	CABLE-CH9-02 (248780+171006)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9- (250795/4)	Jan. 18, 2020	Jan. 17, 2021
RF signal cable Woken	8D-FB	Cable-CH9-01	Jun. 08, 2020	Jun. 07, 2021
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn BV ADT	AT100	AT93021705	NA	NA
Turn Table BV ADT	TT100	TT93021705	NA	NA
Turn Table Controller BV ADT	SC100	SC93021705	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
JFW 20dB attenuation	50HF-020-SMA	NA	NA	NA
True RMS Clamp Meter Fluke	325	31130711WS	Jun. 06, 2020	Jun. 05, 2021
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Jul. 01, 2019	Jun. 30, 2021

Radio Communication Analyzer Anritsu	MT8821C	6201462755	Feb. 13, 2020	Feb. 12, 2021
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 18, 2019	Sep. 17, 2020
			Sep. 09, 2020	Sep. 08, 2021
DC Power Supply Topward	33010D	807748	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 9.

3 General Information

3.1 General Description of EUT

Product	EV charging system module 4G with WI-FI		
Brand	Phihong Technology Co., Ltd.		
Test Model	DLWPH-8M		
Series Model	DLWPH-8M-RW		
Model Difference	Refer to Note as below		
Sample Status	Engineering Sample		
Power Supply Rating	10Vdc~35Vdc (for DC power supply)		
Modulation Type	WCDMA: BPSK, QPSK HSDPA: BPSK HSUPA: QPSK LTE: QPSK, 16QAM		
Operating Frequency	WCDMA Band 5	826.4~846.6MHz	
	LTE Band 5 (Channel Bandwidth 1.4MHz)	824.7~848.3MHz	
	LTE Band 5 (Channel Bandwidth 3MHz)	825.5~847.5MHz	
	LTE Band 5 (Channel Bandwidth 5MHz)	826.5~846.5MHz	
	LTE Band 5 (Channel Bandwidth 10MHz)	829.0~844.0MHz	
Max. ERP Power	WCDMA Band 5	121.619mW (20.85dBm)	
		QPSK	16QAM
	LTE Band 5 (Channel Bandwidth 1.4MHz)	137.721mW (21.39dBm)	102.329mW (20.10dBm)
	LTE Band 5 (Channel Bandwidth 3MHz)	132.434mW (21.22dBm)	105.925mW (20.25dBm)
	LTE Band 5 (Channel Bandwidth 5MHz)	125.026mW (20.97dBm)	96.383mW (19.84dBm)
	LTE Band 5 (Channel Bandwidth 10MHz)	127.938mW (21.07dBm)	100.000mW (20.00dBm)
Emission Designator	WCDMA Band 5	4M17F9W	
		QPSK	16QAM
	LTE Band 5 (Channel Bandwidth 1.4MHz)	1M09G7D	1M09D7W
	LTE Band 5 (Channel Bandwidth 3MHz)	2M70G7D	2M70D7W
	LTE Band 5 (Channel Bandwidth 5MHz)	4M49G7D	4M49D7W
	LTE Band 5 (Channel Bandwidth 10MHz)	8M97G7D	8M96D7W
Antenna Type	Refer to Note as below		
Antenna Connector	Refer to Note as below		
Accessory Device	NA		
Cable Supplied	NA		

Note:

1. All models are listed as below.

Brand	Model	Difference of WLAN Antenna type
Phihong Technology Co., Ltd.	DLWPH-8M	internal antenna
	DLWPH-8M-RW	external antenna

2. The following antennas were provided to the EUT.


Brand	Model	Antenna Gain(dBi)	Antenna Type	Connector Type
Gortec	DR0727-4201BSM	-0.37	PCB	SMA Male

3. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test



Remote site



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	DC Power Supply	Topward	33010D	807748	NA	-
B.	Ext. Antenna	Gortec	DR0727-4201BSM	NA	NA	Provided by client
C.	Radio Communication Analyzer	Anritsu	MT8821C	6201462755	NA	-

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	Power cable	1	1	-	0	-

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Z-plane. Following channel(s) was (were) selected for the final test as listed below.

WCDMA Band 5

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	4132 to 4233	4132 (826.4MHz), 4182 (836.4MHz), 4233 (846.6MHz)	WCDMA, HSDPA, HSUPA
-	Modulation Characteristics	4132 to 4233	4182 (836.4MHz)	WCDMA, HSDPA, HSUPA
-	Frequency Stability	4132 to 4233	4132 (826.4MHz), 4233 (846.6MHz)	WCDMA
-	Occupied Bandwidth	4132 to 4233	4132 (826.4MHz), 4182 (836.4MHz), 4233 (846.6MHz)	WCDMA, HSDPA, HSUPA
-	Band Edge	4132 to 4233	4132 (826.4MHz), 4233 (846.6MHz)	WCDMA, HSDPA, HSUPA
-	Peak To Average Ratio	4132 to 4233	4132 (826.4MHz), 4182 (836.4MHz), 4233 (846.6MHz)	WCDMA, HSDPA, HSUPA
-	Conducted Emission	4132 to 4233	4132 (826.4MHz), 4182 (836.4MHz), 4233 (846.6MHz)	WCDMA, HSDPA, HSUPA
-	Radiated Emission Below 1GHz	4132 to 4233	4233 (846.6MHz)	WCDMA
-	Radiated Emission Above 1GHz	4132 to 4233	4132 (826.4MHz), 4182 (836.4MHz), 4233 (846.6MHz)	WCDMA

Note:

1. This device was tested under all modulations. The worst case of conducted output power was found in WCDMA modulation. Therefore, only ERP, modulation characteristics, occupied bandwidth, band edge, conducted Emission and peak to average ratio items had been tested under WCDMA, HSDPA and HSUPA mode, the other items were performed under WCDMA mode only.
2. For radiated emission below 1GHz, select the worst radiated emission (above 1GHz) channel for final testing.

LTE Band 5

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	ERP	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM	3 RB / 1 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM	1 RB / 7 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM	1 RB / 12 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM	1 RB / 0 RB Offset
-	Modulation characteristics	20450 to 20600	20525(836.5MHz)	10MHz	QPSK / 16QAM	50 RB / 0 RB Offset
-	Frequency Stability	20407 to 20643	20407(824.7MHz), 20643(848.3MHz)	1.4MHz	QPSK	6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20635(847.5MHz)	3MHz	QPSK	15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20625(846.5MHz)	5MHz	QPSK	25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20600(844.0MHz)	10MHz	QPSK	50 RB / 0 RB Offset
-	Occupied Bandwidth	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM	6 RB / 0RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM	15 RB / 0RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM	25RB / 0RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM	50RB / 0RB Offset
-	Band Edge	20407 to 20643	20407(824.7MHz), 20643(848.3MHz)	1.4MHz	QPSK	1 RB / 0 RB Offset 1 RB / 5 RB Offset 6 RB / 0 RB Offset
		20415 to 20635	20415(825.5MHz), 20635(847.5MHz)	3MHz	QPSK	1 RB / 0 RB Offset 1 RB / 14 RB Offset 15 RB / 0 RB Offset
		20425 to 20625	20425(826.5MHz), 20625(846.5MHz)	5MHz	QPSK	1 RB / 0 RB Offset 1 RB / 24 RB Offset 25 RB / 0 RB Offset
		20450 to 20600	20450(829.0MHz), 20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset 1 RB / 49 RB Offset 50 RB / 0 RB Offset

EUT Configure Mode	Test item	Available channel	Tested channel	Channel Bandwidth	Modulation	Mode
-	Peak to Average Ratio	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK / 16QAM	3 RB / 1 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK / 16QAM	1 RB / 7 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK / 16QAM	1 RB / 12 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK / 16QAM	1 RB / 0 RB Offset
-	Conducted Emission	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK	3 RB / 1 RB Offset
		20415 to 20635	20415(825.5MHz), 20525(836.5MHz), 20635(847.5MHz)	3MHz	QPSK	1 RB / 7 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset
-	Radiated Emission Below 1GHz	20407 to 20643	20643(848.3MHz)	1.4MHz	QPSK	3 RB / 1 RB Offset
-	Radiated Emission Above 1GHz	20407 to 20643	20407(824.7MHz), 20525(836.5MHz), 20643(848.3MHz)	1.4MHz	QPSK	3 RB / 1 RB Offset
		20425 to 20625	20425(826.5MHz), 20525(836.5MHz), 20625(846.5MHz)	5MHz	QPSK	1 RB / 12 RB Offset
		20450 to 20600	20450(829.0MHz), 20525(836.5MHz), 20600(844.0MHz)	10MHz	QPSK	1 RB / 0 RB Offset

Note:

1. For radiated emission below 1GHz, select the worst radiated emission (above 1GHz) channel for final testing.
2. For radiated emission above 1GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5MHz & highest channel bandwidth for final test.
3. The conducted output power for QPSK and 16QAM, measured value of QPSK is higher than 16QAM mode. Therefore, only ERP, Modulation characteristics, occupied bandwidth and Peak to average ratio items had been tested under QPSK and 16QAM modes, the other test items were performed under QPSK mode only.

Test Condition:

Test Item	Environmental Conditions	Input Power (system)	Tested By
ERP	25deg. C, 70%RH	120Vac, 60Hz	Tank Wu
Modulation Characteristics	24deg. C, 64%RH	120Vac, 60Hz	Tank Wu
Frequency Stability	24deg. C, 64%RH	120Vac, 60Hz	Tank Wu
Occupied Bandwidth	24deg. C, 64%RH	120Vac, 60Hz	Tank Wu
Band Edge	24deg. C, 64%RH	120Vac, 60Hz	Tank Wu
Peak To Average Ratio	24deg. C, 64%RH	120Vac, 60Hz	Tank Wu
Conducted Emission	24deg. C, 64%RH	120Vac, 60Hz	Tank Wu
Radiated Emission	22deg. C, 68%RH	120Vac, 60Hz	Noah Chang, Greg Lin, Titan Hsu

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and References:

Test Standard:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

ANSI 63.26-2015

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 Test Procedures

Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA, LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Maximum EIRP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , e.g., dBm or dBW)

P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)

4.1.3 Test Setup

Conducted Power Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

Conducted Output Power (dBm)

Band	WCDMA V		
TX Channel	4132	4182	4233
Rx Channel	4357	4407	4458
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.33	23.37	23.35
HSDPA Subtest-1	22.51	22.56	22.56
HSDPA Subtest-2	22.53	22.55	22.56
HSDPA Subtest-3	22.55	22.57	22.56
HSDPA Subtest-4	22.53	22.60	22.51
HSUPA Subtest-1	21.68	21.78	21.72
HSUPA Subtest-2	21.70	21.77	21.74
HSUPA Subtest-3	21.71	21.80	21.75
HSUPA Subtest-4	21.75	21.79	21.74
HSUPA Subtest-5	21.71	21.69	21.64

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20407	20525	20643
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	23.47	23.36	23.21
		1	2	23.60	23.50	23.45
		1	5	23.41	23.38	23.38
		3	0	23.59	23.66	23.59
		3	1	23.63	23.91	23.57
		3	3	23.67	23.63	23.55
		6	0	22.59	22.36	22.30
	16QAM	1	0	22.59	22.22	22.04
		1	2	22.62	22.24	22.11
		1	5	22.37	22.14	22.13
		3	0	22.52	22.48	22.29
		3	1	22.48	22.56	22.49
		3	3	22.48	22.47	22.60
		6	0	21.45	21.31	21.07

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20415	20525	20635
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	23.50	23.35	23.45
		1	7	23.46	23.69	23.74
		1	14	23.44	23.54	23.39
		8	0	22.66	22.57	22.55
		8	3	22.56	22.50	22.44
		8	7	22.62	22.47	22.50
		15	0	22.56	22.55	22.52
	16QAM	1	0	22.54	22.77	22.52
		1	7	22.52	22.44	22.25
		1	14	22.58	22.33	22.32
		8	0	21.34	21.47	21.55
		8	3	21.23	21.53	21.46
		8	7	21.23	21.19	21.52
		15	0	21.55	21.34	21.31

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20425	20525	20625
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	23.42	23.33	23.21
		1	12	23.36	23.24	23.49
		1	24	23.48	23.06	23.29
		12	0	22.68	22.54	22.50
		12	6	22.56	22.56	22.59
		12	13	22.61	22.52	22.41
		25	0	22.60	22.52	22.49
	16QAM	1	0	22.31	22.21	22.11
		1	12	22.30	22.26	22.29
		1	24	22.36	22.09	22.00
		12	0	21.28	21.54	21.43
		12	6	21.49	21.65	21.41
		12	13	21.59	21.59	21.43
		25	0	21.61	21.32	21.40

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20450	20525	20600
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	23.37	23.25	23.59
		1	24	23.58	23.48	23.37
		1	49	23.45	23.27	23.50
		25	0	22.60	22.49	22.52
		25	12	22.60	22.53	22.45
		25	25	22.58	22.50	22.51
		50	0	22.61	22.54	22.38
	16QAM	1	0	22.42	22.52	22.03
		1	24	21.96	22.10	22.12
		1	49	22.03	21.86	22.01
		25	0	21.76	21.50	21.46
		25	12	21.76	21.49	21.48
		25	25	21.45	21.51	21.44
		50	0	21.61	21.49	21.26

ERP Power (dBm)

Band	WCDMA V		
TX Channel	4132	4182	4233
Rx Channel	4357	4407	4458
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	20.81	20.85	20.83
HSDPA Subtest-1	19.99	20.04	20.04
HSDPA Subtest-2	20.01	20.03	20.04
HSDPA Subtest-3	20.03	20.05	20.04
HSDPA Subtest-4	20.01	20.08	19.99
HSUPA Subtest-1	19.16	19.26	19.20
HSUPA Subtest-2	19.18	19.25	19.22
HSUPA Subtest-3	19.19	19.28	19.23
HSUPA Subtest-4	19.23	19.27	19.22
HSUPA Subtest-5	19.19	19.17	19.12

*ERP = Conducted + antenna gain (-0.37dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20407	20525	20643
		Frequency (MHz)		824.7	836.5	848.3
1.4M	QPSK	1	0	20.95	20.84	20.69
		1	2	21.08	20.98	20.93
		1	5	20.89	20.86	20.86
		3	0	21.07	21.14	21.07
		3	1	21.11	21.39	21.05
		3	3	21.15	21.11	21.03
		6	0	20.07	19.84	19.78
	16QAM	1	0	20.07	19.70	19.52
		1	2	20.10	19.72	19.59
		1	5	19.85	19.62	19.61
		3	0	20.00	19.96	19.77
		3	1	19.96	20.04	19.97
		3	3	19.96	19.95	20.08
		6	0	18.93	18.79	18.55

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20415	20525	20635
		Frequency (MHz)		825.5	836.5	847.5
3M	QPSK	1	0	20.98	20.83	20.93
		1	7	20.94	21.17	21.22
		1	14	20.92	21.02	20.87
		8	0	20.14	20.05	20.03
		8	3	20.04	19.98	19.92
		8	7	20.10	19.95	19.98
		15	0	20.04	20.03	20.00
	16QAM	1	0	20.02	20.25	20.00
		1	7	20.00	19.92	19.73
		1	14	20.06	19.81	19.80
		8	0	18.82	18.95	19.03
		8	3	18.71	19.01	18.94
		8	7	18.71	18.67	19.00
		15	0	19.03	18.82	18.79

*ERP = Conducted + antenna gain (-0.37dBi)-2.15

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20425	20525	20625
		Frequency (MHz)		826.5	836.5	846.5
5M	QPSK	1	0	20.90	20.81	20.69
		1	12	20.84	20.72	20.97
		1	24	20.96	20.54	20.77
		12	0	20.16	20.02	19.98
		12	6	20.04	20.04	20.07
		12	13	20.09	20.00	19.89
		25	0	20.08	20.00	19.97
	16QAM	1	0	19.79	19.69	19.59
		1	12	19.78	19.74	19.77
		1	24	19.84	19.57	19.48
		12	0	18.76	19.02	18.91
		12	6	18.97	19.13	18.89
		12	13	19.07	19.07	18.91
		25	0	19.09	18.80	18.88

LTE Band 5						
BW	MCS Index	RB Size	RB Offset	Low	Mid	High
		Channel		20450	20525	20600
		Frequency (MHz)		829	836.5	844
10M	QPSK	1	0	20.85	20.73	21.07
		1	24	21.06	20.96	20.85
		1	49	20.93	20.75	20.98
		25	0	20.08	19.97	20.00
		25	12	20.08	20.01	19.93
		25	25	20.06	19.98	19.99
		50	0	20.09	20.02	19.86
	16QAM	1	0	19.90	20.00	19.51
		1	24	19.44	19.58	19.60
		1	49	19.51	19.34	19.49
		25	0	19.24	18.98	18.94
		25	12	19.24	18.97	18.96
		25	25	18.93	18.99	18.92
		50	0	19.09	18.97	18.74

*ERP = Conducted + antenna gain (-0.37dBi)-2.15

4.2 Modulation Characteristics Measurement

4.2.1 Limits of Modulation Characteristics

N/A



4.2.2 Test Procedure

Connect the EUT to Communication Simulator via the antenna connector, The frequency band is set as EUT supported Modulation and Channels, the EUT output is matched with 50 ohm load, the waveform quality and constellation of the EUT was tested.

4.2.3 Test Setup



4.2.4 Test Results



4.3 Frequency Stability Measurement

4.3.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.3.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

Note: The frequency error was recorded frequency error from the communication simulator.

4.3.3 Test Setup



4.3.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	WCDMA Band 5			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	826.400002	0.002	846.600002	0.002
10	826.400004	0.005	846.600004	0.004
35	826.400004	0.005	846.600003	0.003

Note: The applicant defined the normal working voltage is from 10Vdc to 35Vdc.

Frequency Error vs. Temperature

Temp. (°C)	WCDMA Band 5			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	826.400004	0.004	846.600002	0.002
-30	826.400003	0.004	846.600001	0.001
-20	826.400003	0.003	846.600003	0.003
-10	826.400004	0.005	846.600003	0.004
0	826.400003	0.004	846.600002	0.002
10	826.400002	0.003	846.600002	0.003
20	826.399996	-0.005	846.599997	-0.004
30	826.399996	-0.004	846.599996	-0.005
40	826.399999	-0.001	846.599999	-0.002
50	826.399997	-0.004	846.599999	-0.001
60	826.399999	-0.002	846.599998	-0.003
70	826.399997	-0.003	846.599998	-0.003
80	826.399997	-0.004	846.599998	-0.002
85	826.399997	-0.004	846.599997	-0.004

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	824.700001	0.002	848.300003	0.004
10	824.700002	0.002	848.300002	0.002
35	824.700002	0.002	848.300003	0.003

Note: The applicant defined the normal working voltage is from 10Vdc to 35Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 5			
	Channel Bandwidth: 1.4 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	824.700002	0.002	848.300002	0.003
-30	824.700001	0.001	848.300003	0.003
-20	824.700003	0.003	848.300004	0.005
-10	824.700004	0.005	848.300001	0.001
0	824.700003	0.003	848.300002	0.003
10	824.700003	0.004	848.300002	0.002
20	824.699996	-0.004	848.299998	-0.002
30	824.699998	-0.002	848.299997	-0.004
40	824.699997	-0.003	848.299997	-0.003
50	824.699997	-0.004	848.299997	-0.003
60	824.699998	-0.003	848.299998	-0.003
70	824.699999	-0.001	848.299997	-0.004
80	824.699998	-0.002	848.299999	-0.002
85	824.699999	-0.001	848.299997	-0.003

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	825.500003	0.004	847.500002	0.002
10	825.500004	0.004	847.500003	0.003
35	825.500002	0.003	847.500002	0.002

Note: The applicant defined the normal working voltage is from 10Vdc to 35Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 5			
	Channel Bandwidth: 3 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	825.500002	0.002	847.500002	0.002
-30	825.500003	0.004	847.500004	0.005
-20	825.500003	0.004	847.500004	0.005
-10	825.500004	0.005	847.500001	0.001
0	825.500002	0.003	847.500003	0.003
10	825.500003	0.004	847.500002	0.003
20	825.499996	-0.004	847.499996	-0.005
30	825.499996	-0.004	847.499997	-0.003
40	825.499998	-0.003	847.499998	-0.002
50	825.499997	-0.004	847.499997	-0.003
60	825.499999	-0.001	847.499998	-0.002
70	825.499998	-0.002	847.499996	-0.005
80	825.499997	-0.003	847.499997	-0.004
85	825.499997	-0.004	847.499997	-0.003

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	826.500004	0.004	846.500002	0.002
10	826.500001	0.001	846.500003	0.003
35	826.500004	0.004	846.500001	0.001

Note: The applicant defined the normal working voltage is from 10Vdc to 35Vdc.

Frequency Error vs. Temperature

Temp. (°C)	LTE Band 5			
	Channel Bandwidth: 5 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	826.500003	0.004	846.500002	0.002
-30	826.500002	0.003	846.500002	0.003
-20	826.500004	0.004	846.500004	0.004
-10	826.500002	0.003	846.500001	0.001
0	826.500001	0.001	846.500002	0.002
10	826.500003	0.004	846.500002	0.002
20	826.499998	-0.002	846.499996	-0.005
30	826.499999	-0.001	846.499997	-0.004
40	826.499998	-0.003	846.499996	-0.005
50	826.499997	-0.003	846.499997	-0.004
60	826.499998	-0.003	846.499998	-0.002
70	826.499997	-0.004	846.499996	-0.004
80	826.499998	-0.003	846.499999	-0.002
85	826.499999	-0.002	846.499996	-0.004

Frequency Error vs. Voltage

Voltage (Volts)	LTE Band 5			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
12	829.000004	0.004	844.000004	0.005
10	829.000003	0.004	844.000004	0.005
35	829.000003	0.003	844.000003	0.004

Note: The applicant defined the normal working voltage is from 10Vdc to 35Vdc.

Frequency Error vs. Temperature


Temp. (°C)	LTE Band 5			
	Channel Bandwidth: 10 MHz			
	Low Channel		High Channel	
	Frequency (MHz)	Frequency Error (ppm)	Frequency (MHz)	Frequency Error (ppm)
-40	829.000003	0.003	844.000002	0.002
-30	829.000004	0.004	844.000002	0.002
-20	829.000002	0.003	844.000003	0.003
-10	829.000003	0.003	844.000003	0.003
0	829.000003	0.004	844.000002	0.003
10	829.000004	0.005	844.000004	0.005
20	828.999996	-0.005	843.999996	-0.005
30	828.999998	-0.003	843.999996	-0.005
40	828.999999	-0.001	843.999999	-0.002
50	828.999997	-0.004	843.999996	-0.004
60	828.999996	-0.004	843.999997	-0.003
70	828.999996	-0.004	843.999999	-0.001
80	828.999998	-0.002	843.999997	-0.003
85	828.999999	-0.002	843.999998	-0.003

4.4 Occupied Bandwidth Measurement

4.4.1 Test Procedure

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.4.2 Test Setup



4.4.3 Test Result

Occupied Bandwidth

WCDMA Band 5

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)		
		WCDMA	HSDPA	HSUPA
4132	826.4	4.16	4.16	4.17
4182	836.4	4.15	4.15	4.16
4233	846.6	4.15	4.15	4.15

Spectrum Plot of Worst Value




LTE Band 5


LTE Band 5, Channel Bandwidth 1.4MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM
20407	824.7	1.09	1.09
20525	836.5	1.09	1.09
20643	848.3	1.09	1.09
LTE Band 5, Channel Bandwidth 3MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM
20415	825.5	2.70	2.69
20525	836.5	2.70	2.70
20635	847.5	2.70	2.70
LTE Band 5, Channel Bandwidth 5MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM
20425	826.5	4.49	4.49
20525	836.5	4.48	4.49
20625	846.5	4.49	4.49
LTE Band 5, Channel Bandwidth 10MHz			
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	
		QPSK	16QAM
20450	829.0	8.97	8.96
20525	836.5	8.94	8.94
20600	844.0	8.96	8.96

Spectrum Plot of Worst Value


1.4MHz / 16QAM




3MHz / QPSK



5MHz / 16QAM



10MHz / QPSK



26dB Bandwidth WCDMA Band 5

Channel	Frequency (MHz)	26dB Bandwidth (MHz)		
		WCDMA	HSDPA	HSUPA
4132	826.4	4.74	4.74	4.73
4182	836.4	4.73	4.73	4.72
4233	846.6	4.73	4.73	4.73


Spectrum Plot of Worst Value



LTE Band 5

LTE Band 5, Channel Bandwidth 1.4MHz			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	
		QPSK	16QAM
20407	824.7	1.25	1.25
20525	836.5	1.25	1.24
20643	848.3	1.25	1.25
LTE Band 5, Channel Bandwidth 3MHz			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	
		QPSK	16QAM
20415	825.5	2.93	2.92
20525	836.5	2.92	2.93
20635	847.5	2.92	2.92
LTE Band 5, Channel Bandwidth 5MHz			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	
		QPSK	16QAM
20425	826.5	4.80	4.82
20525	836.5	4.82	4.81
20625	846.5	4.80	4.82
LTE Band 5, Channel Bandwidth 10MHz			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	
		QPSK	16QAM
20450	829.0	9.52	9.51
20525	836.5	9.50	9.51
20600	844.0	9.53	9.51

Spectrum Plot of Worst Value




4.5 Band Edge Measurement

4.5.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


4.5.2 Test Setup



4.5.3 Test Procedures

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 2MHz. RB of the spectrum is 51kHz and VB of the spectrum is 160kHz (WCDMA / HSDPA / HSUPA).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 15kHz and VB of the spectrum is 51kHz (LTE Channel Bandwidth 1.4MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 30kHz and VB of the spectrum is 100kHz (LTE Channel Bandwidth 3MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 62kHz and VB of the spectrum is 200kHz (LTE Channel Bandwidth 5MHz).
- The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (LTE Channel Bandwidth 10MHz).
- Record the max trace plot into the test report.

4.5.4 Test Results



LTE Band 5, Channel Bandwidth 1.4MHz

Channel 20407
(824.7MHz)



QPSK

1 RB / 0 RB Offset

Channel 20643
(848.3MHz)

QPSK

1 RB / 5 RB Offset



Channel 20407
(824.7MHz)



QPSK

6 RB / 0 RB Offset

Channel 20643
(848.3MHz)



QPSK

6 RB / 0 RB Offset





LTE Band 5, Channel Bandwidth 3MHz


Channel 20415 (825.5MHz)	QPSK	1 RB / 0 RB Offset	Channel 20635 (847.5MHz)	QPSK	1 RB / 14 RB Offset
-----------------------------	------	--------------------	-----------------------------	------	---------------------




Channel 20415 (825.5MHz)	QPSK	15 RB / 0 RB Offset	Channel 20635 (847.5MHz)	QPSK	15 RB / 0 RB Offset
-----------------------------	------	---------------------	-----------------------------	------	---------------------



LTE Band 5, Channel Bandwidth 5MHz



LTE Band 5, Channel Bandwidth 10MHz




4.6 Peak to Average Ratio

4.6.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.6.2 Test Setup



4.6.3 Test Procedures


- Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
- Set the number of counts to a value that stabilizes the measured CCDF curve;
- Record the maximum PAPR level associated with a probability of 0.1%.

4.6.4 Test Results

WCDMA Band 5

Channel	Frequency (MHz)	Peak To Average Ratio (dB)		
		WCDMA	HSDPA	HSUPA
4132	826.4	2.83	2.82	2.84
4182	836.4	2.97	2.97	2.98
4233	846.6	2.92	2.92	2.92

Spectrum Plot of Worst Value




LTE Band 5


LTE Band 5, Channel Bandwidth 1.4MHz			
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	
		QPSK	16QAM
20407	824.7	4.01	4.90
20525	836.5	4.59	5.57
20643	848.3	4.53	5.36
LTE Band 5, Channel Bandwidth 3MHz			
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	
		QPSK	16QAM
20415	825.5	4.00	4.92
20525	836.5	4.70	5.52
20635	847.5	4.34	5.15
LTE Band 5, Channel Bandwidth 5MHz			
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	
		QPSK	16QAM
20425	826.5	4.02	4.93
20525	836.5	4.64	5.47
20625	846.5	3.92	4.77
LTE Band 5, Channel Bandwidth 10MHz			
Channel	Frequency (MHz)	Peak To Average Ratio (dB)	
		QPSK	16QAM
20450	829.0	3.92	4.90
20525	836.5	4.62	5.52
20600	844.0	3.97	4.94

Spectrum Plot of Worst Value


1.4MHz / 16QAM




3MHz / 16QAM



5MHz / 16QAM



10MHz / 16QAM




4.7 Conducted Spurious Emissions

4.7.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.7.2 Test Setup



4.7.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9kHz to 10GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.7.4 Test Results


WCDMA

Channel 4132 (826.4MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~10GHz




Channel 4407 (836.4MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~10GHz




Channel 4233 (846.6MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




*The 9kHz signal over the limit is from Spectrum.

HSDPA


HSDPA

Channel 4132 (826.4MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~10GHz




Channel 4407 (836.4MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~10GHz




Channel 4233 (846.6MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




*The 9kHz signal over the limit is from Spectrum.


HSUPA

Channel 4132 (826.4MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~10GHz




Channel 4407 (836.4MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~10GHz




Channel 4233 (846.6MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~10GHz




*The 9kHz signal over the limit is from Spectrum.


LTE Band 5, Channel Bandwidth 1.4MHz

Channel 20407 (824.7MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20525 (836.5MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20643 (848.3MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~9GHz




*The 9kHz signal over the limit is from Spectrum.


LTE Band 5, Channel Bandwidth 3MHz

Channel 20415 (825.5MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20525 (836.5MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20635 (847.5MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~9GHz




*The 9kHz signal over the limit is from Spectrum.


LTE Band 5, Channel Bandwidth 5MHz

Channel 20425 (826.5MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20525 (836.5MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20625 (846.5MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~9GHz




*The 9kHz signal over the limit is from Spectrum.


LTE Band 5, Channel Bandwidth 10MHz

Channel 20450 (829.0MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20525 (836.5MHz)

Frequency Range : 9kHz~1GHz




Frequency Range : 1GHz~9GHz




Channel 20600 (844.0MHz)

Frequency Range : 9kHz~1GHz



Frequency Range : 1GHz~9GHz



*The 9kHz signal over the limit is from Spectrum.

4.8 Radiated Emission Measurement

4.8.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.8.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- c. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.
2. The emission levels were against the limit of frequency range 9 kHz ~ 30 MHz:
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

4.8.3 Deviation from Test Standard


No deviation.

4.8.4 Test Setup

For radiated emission 30MHz to 1GHz



For radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).


4.8.5 Test Results

Below 1GHz

WCDMA Band 5


Mode	TX channel 4233 (846.6MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	25deg. C, 70%RH	Input Power	120Vac, 60Hz
Tested By	Noah Chang		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	76.56	-47.50	-52.90	-2.80	-55.70	-13.00	-42.70
2	159.98	-48.50	-56.40	0.40	-56.00	-13.00	-43.00
3	210.42	-51.50	-67.80	5.40	-62.40	-13.00	-49.40
4	379.20	-61.20	-69.80	5.30	-64.50	-13.00	-51.50
5	769.14	-68.70	-70.30	4.40	-65.90	-13.00	-52.90
6	935.98	-68.00	-67.10	3.90	-63.20	-13.00	-50.20



Mode	TX channel 4233 (846.6MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	25deg. C, 70%RH	Input Power	120Vac, 60Hz
Tested By	Noah Chang		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	64.92	-41.20	-44.10	-6.30	-50.40	-13.00	-37.40
2	159.98	-51.40	-54.40	0.40	-54.00	-13.00	-41.00
3	173.56	-50.10	-54.50	2.10	-52.40	-13.00	-39.40
4	210.42	-52.40	-61.30	5.40	-55.90	-13.00	-42.90
5	747.80	-64.20	-65.50	4.70	-60.80	-13.00	-47.80
6	988.36	-69.50	-65.30	3.90	-61.40	-13.00	-48.40




LTE Band 5, Channel Bandwidth: 1.4MHz

Mode	TX channel 20643 (848.3MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	25deg. C, 70%RH	Input Power	120Vac, 60Hz
Tested By	Noah Chang		


Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	113.42	-44.00	-54.10	0.30	-53.80	-13.00	-40.80
2	136.70	-45.50	-53.70	-0.30	-54.00	-13.00	-41.00
3	159.98	-48.50	-56.30	0.40	-55.90	-13.00	-42.90
4	542.16	-56.60	-64.20	4.70	-59.50	-13.00	-46.50
5	730.34	-58.90	-62.70	4.90	-57.80	-13.00	-44.80
6	918.52	-68.80	-68.00	4.00	-64.00	-13.00	-51.00



Mode	TX channel 20643 (848.3MHz)	Frequency Range	Below 1000 MHz
Environmental Conditions	25deg. C, 70%RH	Input Power	120Vac, 60Hz
Tested By	Noah Chang		

Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	37.76	-33.80	-33.20	-11.20	-44.40	-13.00	-31.40
2	66.86	-36.80	-39.60	-5.80	-45.40	-13.00	-32.40
3	111.48	-39.10	-48.30	0.40	-47.90	-13.00	-34.90
4	449.04	-52.40	-60.80	5.00	-55.80	-13.00	-42.80
5	612.00	-52.40	-54.50	4.60	-49.90	-13.00	-36.90
6	730.34	-59.20	-60.60	4.90	-55.70	-13.00	-42.70



Above 1GHz
WCDMA Band 5

Mode	TX channel 4132 (826.4MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1652.80	-61.40	-53.60	0.90	-52.70	-13.00	-39.70
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1652.80	-59.80	-52.50	0.90	-51.60	-13.00	-38.60

Mode	TX channel 4182 (836.4MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1672.80	-61.30	-53.70	0.80	-52.90	-13.00	-39.90
Antenna Polarity & Test Distance: Vertical at 3 m							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1672.80	-61.00	-53.70	0.80	-52.90	-13.00	-39.90

Mode	TX channel 4233 (846.6MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	22deg. C, 68%RH	Input Power	120Vac, 60Hz
Tested By	Greg Lin		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.20	-60.80	-53.20	0.70	-52.50	-13.00	-39.50
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.20	-59.60	-52.30	0.70	-51.60	-13.00	-38.60

LTE Band 5, Channel Bandwidth: 1.4MHz

Mode	TX channel 20407 (824.7MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1649.40	-60.20	-63.70	5.50	-58.20	-13.00	-45.20

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1649.40	-61.00	-63.30	5.50	-57.80	-13.00	-44.80

Mode	TX channel 20525 (836.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1673.00	-60.50	-63.80	5.50	-58.30	-13.00	-45.30

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1673.00	-60.10	-62.10	5.50	-56.60	-13.00	-43.60

Mode	TX channel 20643 (848.3MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1696.60	-58.20	-61.30	5.60	-55.70	-13.00	-42.70

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1696.60	-59.50	-61.40	5.60	-55.80	-13.00	-42.80

LTE Band 5, Channel Bandwidth: 5MHz

Mode	TX channel 20425 (826.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1653.00	-60.80	-64.20	5.50	-58.70	-13.00	-45.70
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1653.00	-61.00	-63.30	5.50	-57.80	-13.00	-44.80

Mode	TX channel 20525 (836.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1673.00	-61.60	-64.90	5.50	-59.40	-13.00	-46.40
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1673.00	-60.60	-62.60	5.50	-57.10	-13.00	-44.10

Mode	TX channel 20625 (846.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.00	-61.20	-64.40	5.60	-58.80	-13.00	-45.80
Antenna Polarity & Test Distance: Vertical at 3 M							
No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1693.00	-60.20	-62.20	5.60	-56.60	-13.00	-43.60

LTE Band 5, Channel Bandwidth: 10MHz

Mode	TX channel 20450 (829.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1658.00	-59.60	-63.00	5.50	-57.50	-13.00	-44.50

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1658.00	-60.80	-62.90	5.50	-57.40	-13.00	-44.40

Mode	TX channel 20525 (836.5MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1673.00	-60.90	-64.10	5.50	-58.60	-13.00	-45.60

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1673.00	-61.80	-63.80	5.50	-58.30	-13.00	-45.30

Mode	TX channel 20600 (844.0MHz)	Frequency Range	1GHz ~ 18GHz
Environmental Conditions	23deg. C, 66%RH	Input Power	120Vac, 60Hz
Tested By	Titan Hsu		

Antenna Polarity & Test Distance: Horizontal at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1688.00	-58.20	-61.30	5.50	-55.80	-13.00	-42.80

Antenna Polarity & Test Distance: Vertical at 3 M

No.	Freq. (MHz)	Reading (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)
1	1688.00	-59.40	-61.30	5.50	-55.80	-13.00	-42.80

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---