



No. I22Z61676-SEM01

For

TCL Communication Ltd.

GSM/UMTS/LTE Mobile phone

Modelname:T430W

With

Hardware Version: 03

Software Version: UGS4

FCC ID: 2ACCJH167

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504


Email:cttl_terminals@caict.ac.cn, website:www.caict.ac.cn




Picture 1: Constituents of the sample

Test positions for head:


The Head SAR is tested at the following 4 test positions:




Picture 2: Left Head Touch Cheek Position



Picture 3: Left Head Tilt 15° Position



Picture 4: Right Head Touch Cheek Position



Picture 5: Right Head Tilt 15° Position

Test positions for body:


The Body SAR is tested at the following 8 test positions all with the distance =10/15mm between the EUT and the phantom bottom:




Picture 6: Front10mm




Picture 7: Rear 10mm




Picture 8: Left 10mm



Picture 9: Right 10mm



Picture 10: Top10mm



Picture 11: Bottom 10mm



Picture 12: Front 15mm



Picture 13: Rear 15mm