

**RF Exposure Statement: JP23GWD8 001**Page 1 of 2  
Seite 1 von 2

**Client:** Nisshinbo Micro Devices Inc.  
1-1, Fukuoka 2-Chome, Fujimino-City, Saitama, 356-8510 Japan

**Test item:** K-Band Doppler Sensor Module (Movement Sensor)

**Identification:** NJR4267F3B1

**FCC Requirement**

According to FCC §2.1093 (d)(1), Portable Devices that transmit at frequencies above 6 GHz must comply with the following applicable limit for Maximum Permissible Exposure (MPE) specified in FCC §1.1310 (e)(1), Table 1:

| Equipment Use                              | Frequency Range [MHz] | Power Density Limit [mW/cm <sup>2</sup> ] | Average Time [min] |
|--|-----------------------|---|--------------------|
| General Population / Uncontrolled Exposure | 1,500 – 100,000       | 1.0                                       | <30                |

Note:

This evaluation was conducted at 2.0cm test separation distance (variable r in the statement). It was specified by the customer.

**Measurement Result**

The maximum measured E-field strength and estimated EIRP from the transmitter are given in the following table:

| Freq. [GHz] | Wave Length [cm] | Measured E-Field Strength E |       | Meas. Distance R [m] | Calculated EIRP |       | Test Distance r [cm] | Calculated Power Density S [mW/cm <sup>2</sup> ] |
|-------------|------------------|-----------------------------|-------|----------------------|-----------------|-------|----------------------|--|
|             |                  | [dBuV/m]                    | [V/m] |                      | [mW]            | [dBm] |                      |  |
| 24.091186   | 1.245268         | 105.63                      | 0.191 | 3.0                  | 10.944          | 10.39 | 2.0                  | 0.217724   |

Note:

The EIRP in mW is calculated in conjunction with the following formula:

$$\text{EIRP} = (E \times R)^2 / 30 = (0.191 \times 3.0)^2 / 30 = 0.010944 \text{ [W]} = 10.944 \text{ [mW]}$$

The power density S in mW/cm<sup>2</sup> is calculated in conjunction with the next formula:

$$S = \text{EIRP} / (4 \times \pi \times r^2) = 10.944 / (4 \times \pi \times 2.0^2) = 0.217724 \text{ [mW/cm}^2\text{]}$$

**RF Exposure Statement: JP23GWD8 001****Page 2 of 2**  
Seite 2 von 2

Since the shortest wave length  $\lambda$  of transmitter is 1.245cm, above mentioned calculations are considered in far field condition.

Normal mode is the worst case configuration of this transmitter, therefore above mentioned condition is considered as the most severe estimation. For details, refer to the relevant sections that is submitted test report, JP232TC8 001.

**Conclusion**

This transmitter module is classified as Portable Devices by the client.

SAR evaluation is not required since nominal frequency of the transmitter is higher than 6GHz, therefore, RF exposure evaluation (MPE) was conducted by the above-mentioned calculated method.

As a result, calculated Power Density S is below FCC limit at the separation distance of 2.0cm.