



RF EXPOSURE REPORT

Applicant	:	KREAFUNK APS
Address of Applicant	:	Klamsagervej 35 A, st.8230 Abyhoj,Denmark
Manufacturer	:	Shen Zhen Lighkeep Co., Ltd.
Address of Manufacturer	:	3&4 Floor, No.19 Plant, Baotong South Road, XikengCommunity, Yuanshan Street, Longgang DistrictShenzhen
Equipment under Test	:	Safe Audio Headphone
Model No.	:	Buzz junior
FCC ID	:	2ACVC-BUZZJUNIOR
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24010331-3E04
Issue Date	:	2024/03/19
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	General Test Information.....	5
1.1.	Description of EUT.....	5
1.2.	Accessories of EUT	5
1.3.	Test laboratory	5
2.	RF Exposure evaluation for FCC.....	6
2.1.	Assessment procedure.....	6
2.2.	Assess result.....	6
3.	Photos of the EUT	7

Test Report Declare

Applicant	:	KREAFUNK APS
Address of Applicant	:	Klamsagervej 35 A, st.8230 Abyhoj,Denmark
Equipment under Test	:	Safe Audio Headphone
Model No.	:	Buzz junior
Manufacturer	:	Shen Zhen Lighkeep Co., Ltd.
Address of Manufacturer	:	3&4 Floor, No.19 Plant, Baotong South Road, XikengCommunity, Yuanshan Street, Longgang DistrictShenzhen

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24010331-3E04		
Date of Receipt:	2024/01/26	Date of Test:	2024/01/26~2024/03/18

Prepared By:

Tiger Mo

Tiger Mo/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/03/19	

1. General Test Information

1.1. Description of EUT

EUT Name	: Safe Audio Headphone
Model Number	: Buzz junior
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 5V by external AC Adapter or 3.7V built-in lithium battery

Note: This EUT support Bluetooth BR/EDR,NFC, this report only for Bluetooth BR/EDR.

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.2. Assess result

Manufacturing Tolerance:

Mode	Antenna	Frequency [MHz]	Target (dBm)	Tolerance \pm (dB)
GFSK (Peak)	Ant1	2402	-3.90	2
		2441	-3.41	2
		2480	-3.65	2
$\pi/4$ DQPSK (Peak)	Ant1	2402	-3.30	2
		2441	-2.79	2
		2480	-3.12	2
8DPSK (Peak)	Ant1	2402	-2.79	2
		2441	-2.27	2
		2480	-2.66	2

Estimtion Result:

Worse case is as below: [2441 MHz, -0.27 dBm, (0.94 mW) output power]

$(0.94/5) \cdot [\sqrt{2.441(\text{GHz})}] = 0.332 < 0.29$ for 1-g SAR

Then SAR evaluation is not required.

3. Photos of the EUT

Please refer to DDT-Q24010331-2E appendix I

-----End Report-----