



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

TEST REPORT

For

C&A Makingting Inc.

114 Tived Lane East Edison New Jersey United States

FCC ID: 2AD2WHOOPPC01

Report Type: Original Report	Product Type: Hoop Pan Home Cam
Report Number: RBJ190528051-00B	
Report Date: 2019-08-05	
Reviewed By:	Jerry Zhang EMC Manager
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	9
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	9
SUPPORT CABLE LIST AND DETAILS	9
CONFIGURATION OF TEST SETUP	10
SUMMARY OF TEST RESULTS	11
FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	12
APPLICABLE STANDARD	12
FCC §15.203 - ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST DATA	16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	19
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST DATA	20
FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA	27
FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35

TEST DATA	35
FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA	38
FCC §15.247(e) - Power Spectral Density.....	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	43

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Hoop Pan Home Cam
EUT Model:		HOOPPC01
Operation Frequency:		2412-2462 MHz(802.11b/g/n ht20) 2422-2452 MHz(802.11n ht40)
Maximum Peak Output Power (Conducted):		13.17 dBm
Modulation Type:		DSSS, OFDM(802.11b/g/n)
Rated Input Voltage:		DC 5V,2A
Adapter Information	Model:	KA12C-0502000US
	Input:	100-240V~50/60Hz 0.35A Max
	Output:	5V, 2000mA
External Dimension:		113(mm)*65(mm)*65(mm)
Serial Number:		190528051
EUT Received Date:		2019-05-30

Objective

This report is prepared on behalf of *C&A Makingting Inc.* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s)

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11. For 802.11n ht40 mode was tested with channel 3, 6, 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

EUT Exercise Software


The software “SecureCRT” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer:

Mode	Channel	Frequency (MHz)	Data rate	Power level setting
802.11b	Low	2412	1 Mbps	Default
	Middle	2437	1 Mbps	Default
	High	2462	1 Mbps	Default
802.11g	Low	2412	6 Mbps	Default
	Middle	2437	6 Mbps	Default
	High	2462	6 Mbps	Default
802.11n ht20	Low	2412	MCS0	Default
	Middle	2437	MCS0	Default
	High	2462	MCS0	Default
802.11n ht40	Low	2422	MCS0	Default
	Middle	2437	MCS0	Default
	High	2452	MCS0	Default

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	2.120	2.180	97.25
802.11n ht20	1.976	2.024	97.63
802.11n ht40	0.970	1.040	93.27

802.11b




Date: 1.AUG.2019 20:28:05


802.11g



802.11n ht20



Configuration of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Frequency Range (MHz)	Antenna Gain		Max. Target Power including Tolerance		Evaluation Distance (cm)	Power Density (W/m ²)	MPE Limit (W/m ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	2	1.58	14	25	20.00	0.008	1.0

Note: the Max. Target Power including Tolerance was declared by manufacturer.

Result: Compliance, The device meets MPE requirement for Devices Used by the General Public (Uncontrolled Environment) at distance ≥ 20 cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal FPC antenna arrangement, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
FPC	50	2.0 dBi/2.4~2.5GHz


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2018-09-05	2019-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2018-12-10	2019-12-10
R&S	EMI Test Receiver	ESPI	100120	2019-05-09	2020-05-09


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	28.0℃
Relative Humidity:	62%
ATM Pressure:	100.6 kPa
Test Engineer:	Lily Xie
Test Date:	2019-06-13


Test Mode: Transmitting (Wi-Fi mode 802.11b middle channel was the worst)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.153015	41.0	9.000	L1	11.1	24.8	65.8
0.434989	30.6	9.000	L1	9.9	26.6	57.2
0.759409	32.2	9.000	L1	9.8	23.8	56.0
0.872921	29.0	9.000	L1	9.8	27.0	56.0
3.621856	23.0	9.000	L1	9.8	33.0	56.0
11.601974	18.5	9.000	L1	9.8	41.5	60.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.422196	24.1	9.000	L1	9.9	23.3	47.4
0.443733	25.0	9.000	L1	9.9	22.0	47.0
0.500009	35.5	9.000	L1	9.9	10.5	46.0
0.759409	27.2	9.000	L1	9.8	18.8	46.0
3.621856	13.3	9.000	L1	9.8	32.7	46.0
11.601974	9.4	9.000	L1	9.8	40.6	50.0

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.151500	44.6	9.000	N	11.1	21.3	65.9
0.430682	39.9	9.000	N	9.9	17.3	57.2
0.439339	39.9	9.000	N	9.9	17.2	57.1
0.899371	31.0	9.000	N	9.8	25.0	56.0
1.407345	29.0	9.000	N	9.8	27.0	56.0
2.880975	26.3	9.000	N	9.8	29.7	56.0

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.378425	29.3	9.000	N	10.0	19.0	48.3
0.397728	33.2	9.000	N	10.0	14.7	47.9
0.418016	35.0	9.000	N	9.9	12.5	47.5
0.439339	36.8	9.000	N	9.9	10.3	47.1
0.461750	31.1	9.000	N	9.9	15.6	46.7
0.500009	35.1	9.000	N	9.9	10.9	46.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 3 meters chamber test site A, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2019-06-26	2020-06-26
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2018-09-05	2019-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
HP	Amplifier	8447D	2727A05902	2018-09-05	2019-09-05
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2018-09-05	2019-09-05
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2018-09-05	2019-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5- S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	28 °C	26.1 °C
Relative Humidity:	48 %	60 %
ATM Pressure:	99.7kPa	100.1kPa
Test Engineer:	Vern Shen	Lucy Lu
Test Date:	2019-07-14	2019-08-02

Test Result: Compliance, please Refer to the following data


Test Mode: Transmitting

1) 30MHz-1GHz(802.11b middle channel was the worst):

Horizontal:



Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
262.8000	48.00	QP	-4.80	43.20	46.00	2.80
286.0800	46.50	QP	-4.03	42.47	46.00	3.53
357.8600	44.20	QP	-2.82	41.38	46.00	4.62
382.1100	44.24	QP	-2.48	41.76	46.00	4.24
406.3600	43.00	QP	-1.90	41.10	46.00	4.90
429.6400	41.80	QP	-1.29	40.51	46.00	5.49

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
262.8000	42.29	peak	-4.80	37.49	46.00	8.51
286.0800	43.80	QP	-4.03	39.77	46.00	6.23
399.5700	41.57	peak	-2.03	39.54	46.00	6.46
600.3600	40.10	QP	1.03	41.13	46.00	4.87
675.0500	36.79	peak	2.50	39.29	46.00	6.71
750.7100	37.70	QP	3.66	41.36	46.00	4.64

**2) 1-25GHz:
802.11b Mode**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2390.00	27.10	PK	H	28.08	1.80	0.00	56.98	74.00	17.02
2390.00	13.22	AV	H	28.08	1.80	0.00	43.10	54.00	10.90
4824.00	47.45	PK	H	32.95	3.19	37.20	46.39	74.00	27.61
4824.00	34.39	AV	H	32.95	3.19	37.20	33.33	54.00	20.67
7236.00	44.25	PK	H	35.81	4.77	37.27	47.56	74.00	26.44
7236.00	33.26	AV	H	35.81	4.77	37.27	36.57	54.00	17.43
Middle Channel: 2437 MHz									
4874.00	47.54	PK	0.00	33.05	3.26	37.21	46.64	74.00	27.36
4874.00	34.87	AV	0.00	33.05	3.26	37.21	33.97	54.00	20.03
7311.00	44.65	PK	0.00	36.01	4.64	37.36	47.94	74.00	26.06
7311.00	32.94	AV	0.00	36.01	4.64	37.36	36.23	54.00	17.77
High Channel: 2462 MHz									
2483.50	28.34	PK	0.00	28.27	1.84	0.00	58.45	74.00	15.55
2483.50	13.70	AV	0.00	28.27	1.84	0.00	43.81	54.00	10.19
4924.00	47.64	PK	0.00	33.15	3.27	37.22	46.84	74.00	27.16
4924.00	34.54	AV	0.00	33.15	3.27	37.22	33.74	54.00	20.26
7386.00	44.69	PK	0.00	36.20	4.51	37.46	47.94	74.00	26.06
7386.00	32.74	AV	0.00	36.20	4.51	37.46	35.99	54.00	18.01

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2390.00	26.73	PK	H	28.08	1.80	0.00	56.61	74.00	17.39
2390.00	12.81	AV	H	28.08	1.80	0.00	42.69	54.00	11.31
4824.00	47.15	PK	H	32.95	3.19	37.20	46.09	74.00	27.91
4824.00	34.15	AV	H	32.95	3.19	37.20	33.09	54.00	20.91
7236.00	45.15	PK	H	35.81	4.77	37.27	48.46	74.00	25.54
7236.00	32.87	AV	H	35.81	4.77	37.27	36.18	54.00	17.82
Middle Channel: 2437 MHz									
4874.00	47.50	PK	H	33.05	3.26	37.21	46.60	74.00	27.40
4874.00	34.15	AV	H	33.05	3.26	37.21	33.25	54.00	20.75
7311.00	45.18	PK	H	36.01	4.64	37.36	48.47	74.00	25.53
7311.00	32.78	AV	H	36.01	4.64	37.36	36.07	54.00	17.93
High Channel: 2462 MHz									
2483.50	26.75	PK	H	28.27	1.84	0.00	56.86	74.00	17.14
2483.50	13.26	AV	H	28.27	1.84	0.00	43.37	54.00	10.63
4924.00	47.21	PK	H	33.15	3.27	37.22	46.41	74.00	27.59
4924.00	34.54	AV	H	33.15	3.27	37.22	33.74	54.00	20.26
7386.00	45.29	PK	H	36.20	4.51	37.46	48.54	74.00	25.47
7386.00	32.49	AV	H	36.20	4.51	37.46	35.74	54.00	18.26

802.11n ht20 Mode




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2390.00	26.26	PK	H	28.08	1.80	0.00	56.14	74.00	17.86
2390.00	13.14	AV	H	28.08	1.80	0.00	43.02	54.00	10.98
4824.00	47.21	PK	H	32.95	3.19	37.20	46.15	74.00	27.85
4824.00	34.15	AV	H	32.95	3.19	37.20	33.09	54.00	20.91
7236.00	44.48	PK	H	35.81	4.77	37.27	47.79	74.00	26.21
7236.00	32.15	AV	H	35.81	4.77	37.27	35.46	54.00	18.54
Middle Channel: 2437 MHz									
4874.00	47.51	PK	H	33.05	3.26	37.21	46.61	74.00	27.39
4874.00	34.17	AV	H	33.05	3.26	37.21	33.27	54.00	20.73
7311.00	44.54	PK	H	36.01	4.64	37.36	47.83	74.00	26.17
7311.00	32.48	AV	H	36.01	4.64	37.36	35.77	54.00	18.23
High Channel: 2462 MHz									
2483.50	26.85	PK	H	28.27	1.84	0.00	56.96	74.00	17.04
2483.50	13.55	AV	H	28.27	1.84	0.00	43.66	54.00	10.34
4924.00	47.82	PK	H	33.15	3.27	37.22	47.02	74.00	26.98
4924.00	34.25	AV	H	33.15	3.27	37.22	33.45	54.00	20.55
7386.00	45.21	PK	H	36.20	4.51	37.46	48.46	74.00	25.54
7386.00	32.84	AV	H	36.20	4.51	37.46	36.09	54.00	17.91

802.11n ht40 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2422 MHz									
2390.00	30.17	PK	H	28.08	1.80	0.00	60.05	74.00	13.95
2390.00	14.60	AV	H	28.08	1.80	0.00	44.48	54.00	9.52
4844.00	47.68	PK	H	32.99	3.22	37.20	46.69	74.00	27.31
4844.00	35.77	AV	H	32.99	3.22	37.20	34.78	54.00	19.22
7266.00	45.58	PK	H	35.89	4.72	37.31	48.88	74.00	25.12
7266.00	32.84	AV	H	35.89	4.72	37.31	36.14	54.00	17.86
Middle Channel: 2437 MHz									
4874.00	47.35	PK	H	33.05	3.26	37.21	46.45	74.00	27.55
4874.00	35.03	AV	H	33.05	3.26	37.21	34.13	54.00	19.88
7311.00	45.11	PK	H	36.01	4.64	37.36	48.40	74.00	25.61
7311.00	32.78	AV	H	36.01	4.64	37.36	36.07	54.00	17.93
High Channel: 2452 MHz									
2483.50	26.94	PK	H	28.27	1.84	0.00	57.05	74.00	16.95
2483.50	14.90	AV	H	28.27	1.84	0.00	45.01	54.00	8.99
4904.00	47.55	PK	H	33.11	3.30	37.21	46.75	74.00	27.25
4904.00	35.73	AV	H	33.11	3.30	37.21	34.93	54.00	19.07
7356.00	45.25	PK	H	36.13	4.56	37.42	48.52	74.00	25.49
7356.00	32.94	AV	H	36.13	4.56	37.42	36.21	54.00	17.79




Test plots(802.11 b mode Low channel was the worst)
Horizontal:

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental
Test with Band
Rejection Filter




FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH**Applicable Standard**

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.4°C
Relative Humidity:	42 %
ATM Pressure:	100.5 kPa
Test Engineer:	Ven Shen
Test Date:	2019-08-01


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.220	≥ 0.5
	Middle	2437	10.201	≥ 0.5
	High	2462	10.220	≥ 0.5
802.11g	Low	2412	16.447	≥ 0.5
	Middle	2437	16.447	≥ 0.5
	High	2462	16.447	≥ 0.5
802.11n ht20	Low	2412	17.325	≥ 0.5
	Middle	2437	17.325	≥ 0.5
	High	2462	17.485	≥ 0.5
802.11n ht40	Low	2422	36.09	≥ 0.5
	Middle	2437	36.09	≥ 0.5
	High	2452	35.77	≥ 0.5

Please refer to following plots:


802.11 b_Low




802.11 b_Middle



802.11 b_High




802.11 g_Low




Date: 1.AUG.2019 20:37:51

802.11 g_Middle




Date: 1.AUG.2019 20:51:30

802.11 g_High




Date: 1.AUG.2019 21:03:02

802.11 n20_Low




Date: 1.AUG.2019 21:21:29


802.11 n20_Middle




802.11 n20_High




802.11 n40_Low



802.11 n40_Middle



802.11 n40_High



Date: 1.AUG.2019 22:24:53


FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2018-12-10	2019-12-10
Unknown	Coaxial Cable	C-SJ00-0010	C0010/04	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.4°C
Relative Humidity:	42 %
ATM Pressure:	100.5 kPa
Test Engineer:	Ven Shen
Test Date:	2019-08-01

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Mode	Frequency (MHz)	Maximum conducted Peak Output Power (dBm)	Limit (dBm)
802.11 b	2412	10.49	30
	2437	12.74	30
	2462	12.58	30
802.11 g	2412	10.40	30
	2437	12.78	30
	2462	12.05	30
802.11n ht20	2412	10.38	30
	2437	13.05	30
	2462	13.17	30
802.11n ht40	2422	11.21	30
	2437	11.43	30
	2452	11.52	30

FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	27.4°C
Relative Humidity:	42 %
ATM Pressure:	100.5 kPa
Test Engineer:	Ven Shen
Test Date:	2019-08-01


Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.

802.11 b_Low




802.11 b_High




Date: 1.AUG.2019 20:13:07

802.11 g_Low




Date: 1.AUG.2019 20:40:33

802.11 g_High




Date: 1.AUG.2019 22:49:55

802.11 n20_Low




Date: 1.AUG.2019 21:24:05

802.11 n20_High




Date: 1.AUG.2019 22:57:48

802.11 n40_Low



Date: 1.AUG.2019 22:15:56

802.11 n40_High



Date: 1.AUG.2019 22:26:52

FCC §15.247(e) - Power Spectral Density

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101474	2019-01-09	2020-01-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27~27.4°C
Relative Humidity:	42~45 %
ATM Pressure:	100.1~100.5 kPa
Test Engineer:	Ven Shen
Test Date:	2019-08-01~2019-08-02


Test Result: Compliance. Please refer to the following table and plots

Test Mode: Transmitting


Test mode	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-10.64	≤8
	2437	-9.64	≤8
	2462	-9.65	≤8
802.11g	2412	-13.92	≤8
	2437	-11.85	≤8
	2462	-13.22	≤8
802.11n ht20	2412	-23.88	≤8
	2437	-20.61	≤8
	2462	-20.17	≤8
802.11n ht40	2422	-16.93	≤8
	2437	-16.82	≤8
	2452	-16.61	≤8

Please refer to following plots:


802.11 b_Low




802.11 b Middle




802.11 b_High



802.11 g_Low




802.11 g_Middle




Date: 1.AUG.2019 20:52:45

802.11 g_High




Date: 1.AUG.2019 21:12:12


802.11 n20_Low




802.11 n20_Middle




802.11 n20_High




802.11 n40_Low



802.11 n40_Middle



802.11 n40_High



***** END OF REPORT *****