

FCC ID : 2AE59-MODCC32

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,³⁰ where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation³¹

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

For 2.4G WIFI

The test was performed with 802.11b

Frequency (MHz)	Ave output power (dBm)	Ave output power (mW)	Target power (dBm)	Calculation Value	Threshold Value
2412	5.20	3.311	5 ± 1	1.24	3.0
2437	5.14	3.266	5 ± 1	1.24	3.0
2462	5.26	3.357	5 ± 1	1.25	3.0

The test was performed with 802.11g

Frequency (MHz)	Ave output power (dBm)	Ave output power (mW)	Target power (dBm)	Calculation Value	Threshold Value
2412	4.23	2.649	4 ± 1	0.98	3.0
2437	4.12	2.582	4 ± 1	0.99	3.0
2462	4.46	2.793	4 ± 1	0.99	3.0

The test was performed with 802.11n (20MHz)

Frequency (MHz)	Ave output power (dBm)	Ave output power (mW)	Target power (dBm)	Calculation Value	Threshold Value
2412	4.26	2.667	4 ± 1	0.98	3.0
2437	4.92	3.105	4 ± 1	0.99	3.0
2462	4.63	2.904	4 ± 1	0.99	3.0

The test was performed with 802.11n (40MHz)

Frequency (MHz)	Ave output power (dBm)	Ave output power (mW)	Target power (dBm)	Calculation Value	Threshold Value
2422	3.88	2.443	4 ± 1	0.98	3.0
2437	3.82	2.410	4 ± 1	0.99	3.0
2452	3.83	2.415	4 ± 1	0.99	3.0

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion: No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A