FCC ID:2AI3QAI-IP019



RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)	
	(A) Limits	for Occupational/Controlled	Exposures		
0.3–3.0	614	1.63	*(100)	6	
3.0–30 1842/f		4.89/f	*(900/f ²)	6	
30–300	61.4	0.163 1.0			
300–1500			f/300	6	
1500–100,000			5	6	
I	(B) Limits for	General Population/Uncontro	olled Exposure		
0.3–1.34	614	1.63	*(100)	30	
1.34-30824/f30-30027.5		2.19/f	2.19/f *(180/f²) 0.073 0.2		
		0.073			
300–1500			f/1500	30	
1500–100,000			1.0	30	

f = frequency in MHz

Friis transmission formula: Pd = (Pout*G)/(4*pi*r²)

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

 ${\bf R}$ = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.









Test Result of RF Exposure Evaluation

2.4G WIFI mode

	Channel	Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum Tune-Up output power (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm ²)	Result
	802.11b Lowest	2.50	1.778	17.50	56.23	0.019894	1	PASS

BT mode

DTINOUC		1			1		
Channel	Antenna Gain (dBi)	Antenna Gain (numeric)	Maximum Tune-Up output power (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
π/4-DQPSK Lowest	-0.58	0.875	2.00	1.58	0.000276	1	PASS

Remark: antenna gain=-0.6dBi, antenna gain=-0.58dBi

BT and WIFI Simultaneous transmit, Max Power Density at R=20cm (mW/cm²)=0.019894mW/cm² +0.000276mW/cm² =0.02017mW/cm²

Shenzhen ZKT Technology Co., Ltd. 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China