



# TEST REPORT

**Reference No.**..... : WTU22F10202727W002  
**FCC ID** ..... : 2AJ2N-W902-DZB  
**Applicant**..... : EuControls Corporation  
**Address**..... : 19210 S. Vermont Ave Bldg C, Ste 310 Gardena, CA 90248 United States  
**Manufacturer** ..... : The same as above  
**Address**..... : The same as above  
**Product Name**..... : W902-DZB Zigbee  
**Model No.**..... : W902-DZB  
**Test specification**..... : FCC CFR47 Part 1 Subpart I(Section1.1307): 2020  
**Date of Receipt sample** .... : 2022-10-20  
**Date of Test** ..... : 2022-11-22  
**Date of Issue**..... : 2022-11-23  
**Test Report Form No.** ..... : WEW-MPE-01A  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Foshan) Co., Ltd.**

Address: No.13-19, 2/F., 2nd Building, Sunlink International Machinery City,  
Chencun, Shunde District, Foshan, Guangdong, China

Tel:+86-757-23811398 Fax:+86-757-23811381 E-mail:info@waltek.com.cn

Tested by:

Roy Hong

Approved by:

Danny Zhou



## 1 Revision History

Test Report No.	Date of Issue	Description	Status
WTU22F10202727W002	2022-11-23	Original	Valid

# WALTEK



## 2 Contents

	Page
1 REVISION HISTORY.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T.....	4
3.2 TECHNICAL CHARACTERISTICS OF EUT.....	4
3.3 DISCLAIMER.....	4
4 MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
4.1 STANDARD APPLICABLE.....	5
4.2 MPE CALCULATION METHOD.....	6
4.3 MPE CALCULATION RESULT.....	6

# WALTEK



### 3 General Information

#### 3.1 General Description of E.U.T

Product Name .....	: W902-DZB Zigbee
Model No. ....	: W902-DZB
Model Description .....	: ---
Rated Voltage.....	: 120-277Vac, 0.035A
Battery Capacity .....	: ---
Power Adapter .....	: ---

#### 3.2 Technical Characteristics of EUT

Support Standards .....	: IEEE 802.15.4
Frequency Range .....	: 2405-2475MHz
RF Output Power .....	: 15.86dBm (Conducted )
Modulation .....	: OQPSK
Quantity of Channels .....	: 15
Channel Separation.....	: 5MHz
Type of Antenna .....	: External IPEX Antenna
Antenna Gain .....	: 2.7dBi

#### 3.3 Disclaimer

The antenna gain information is provided by the customer. The laboratory is not responsible for the accuracy of the antenna gain information.



## 4 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 4.1 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

#### (a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

#### (b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz; \* = Plane-wave equivalent power density



## 4.2 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

## 4.3 MPE Calculation Result

Prediction distance (mm)	Prediction frequency (MHz)	Antenna Gain (dBi)	Numeric gain	Maximum Tune-up output power (dBm)	Maximum peak output power (mW)	PD (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
>200	2440	2.7	1.86	15.860	38.548	0.0143	1.0

Result: Pass

=====End of Report=====

# WALTEK