



August 10, 2017

TUV SUD BABT  
Octagon House, Concorde Way  
Segensworth Rd N, Fareham  
PO15 5RL

Attention: Director of Certification

**RE: Analysis of RF Exposure for Portable and Mobile use per KDB 447498 D01 Mobile Portable RF Exposure v06 and RSS-102 Issue 5 March 2015.**

FCC ID: 2AJZL-NW1000  
IC: 22101-NW1000

## 1. Limits

Limits for General Population/Uncontrolled Exposure (Title 47 Subpart J §2.1091 and KDB 447498 D01 referring to limits under §1.1310)

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Electric Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3 - 1.34	614	1.63	*(100)	30
1.34 - 30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f/1500	30
1500 - 100,000	-	-	1.0	30

*f = frequency in MHz*

*\*Plane-wave equivalent power density*



Limits for Devices Used by the General Public (Uncontrolled Environment (RSS-102 Issue 5 March 2015))

Frequency Range (MHz)	Electric Field Strength (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003 - 10 <sup>21</sup>	83	90	-	Instantaneous
0.1 - 10	-	0.73/f	-	6**
1.1 - 10	87/f <sup>0.5</sup>	-	-	6**
10 - 20	27.46	0.0728	2	6
20 - 48	-58.07/f <sup>0.25</sup>	0.1540/f <sup>0.25</sup>	8.944/f <sup>0.5</sup>	6
48 - 300	22.06	0.05852	1.291	6
300 - 6000	3.142 f <sup>0.3417</sup>	0.008335 f <sup>0.3417</sup>	0.02619 f <sup>0.6834</sup>	6
6000 - 15000	61.4	0.163	10	6
15000 - 150000	61.4	0.163	10	616000/f <sup>1.2</sup>
150000 - 300000	0.158f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>

*f* is frequency in MHz

\*Based on nerve stimulation (NS)

\*\* Based on specific absorption rate (SAR)

**2. Mobile MPE Calculation Summary using a 20cm separation distance:**

Mode	Output Power (dBm)*	Power Density (mW/cm <sup>2</sup> )	Power Density (W/m <sup>2</sup> )	FCC Limit (mW/cm <sup>2</sup> )	ISED Limit (W/m <sup>2</sup> )
WCDMA Band 2	22.54	0.0584427	0.584427	1	4.48
WCDMA Band 5	22.37	0.0561992	0.561992	0.551	2.581
2.4GHz WiFi	12.06	0.0080118	0.080118	1	5.351
UWB	-33.44	0.0000001	0.000001	1	10



**3. Co-Located Transmitters transmission table:**

Transmitter type	Transmitter type that can transmit at the same time
WCDMA	2.4G WiFi and UWB
2.4GHz WiFi	WCDMA and UWB
UWB	WCDMA and 2.4GHz WiFi

**4. Simultaneous Transmission MPE:**

Downlink and Uplink					
Transmitter type	MPE (mw/cm <sup>2</sup> )	FCC Limit (mW/cm <sup>2</sup> )	IC Limit (W/m <sup>2</sup> )	FCC MPE ratio (MPE/Limit)	ISED MPE ratio (MPE/Limit)
WCDMA Band 2	0.0584427	1	4.48	0.0584427	0.130452455
2.4GHz WiFi	0.0080118	1	5.351	0.0080118	0.014972528
UWB	0.0000001	1	10	0.0000001	0.0000001
Sum of the ratios (should be <1.0)				0.066	0.144



**5. Mobile MPE Calculation using a 20cm separation distance**

Using Power Density formula:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to isotropic

R = distance to the center of radiation of the antenna

**WCDMA Band 2:**

Maximum peak output power at antenna input terminal:	<b>22.54</b>	(dBm)
Maximum peak output power at antenna input terminal:	<b>179.47</b>	(mW)
Antenna gain(typical):	<b>2.14</b>	(dBi)
Maximum antenna gain:	<b>1.637</b>	(numeric)
Prediction distance:	<b>20</b>	(cm)
Source Based Time Average Duty Cycle:	<b>100</b>	(%)
Prediction frequency:	<b>1932.4</b>	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	<b>1.0</b>	(mW/cm <sup>2</sup> )
ISED MPE limit for uncontrolled exposure at prediction frequency:	<b>4.48</b>	(W/m <sup>2</sup> )
Power density at prediction frequency:	<b>0.0584427</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.584427</b>	(W/m <sup>2</sup> )
FCC Margin of Compliance:	<b>-12.33</b>	(dB)
IC Margin of Compliance:	<b>-8.85</b>	(dB)

**WCDMA Band 5:**

Maximum peak output power at antenna input terminal:	<b>22.37</b>	(dBm)
Maximum peak output power at antenna input terminal:	<b>172.58</b>	(mW)
Antenna gain(typical):	<b>2.14</b>	(dBi)
Maximum antenna gain:	<b>1.637</b>	(numeric)
Prediction distance:	<b>20</b>	(cm)
Source Based Time Average Duty Cycle:	<b>100</b>	(%)
Prediction frequency:	<b>826.4</b>	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	<b>0.551</b>	(mW/cm <sup>2</sup> )
ISED MPE limit for uncontrolled exposure at prediction frequency:	<b>2.581</b>	(W/m <sup>2</sup> )
Power density at prediction frequency:	<b>0.0561992</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.561992</b>	(W/m <sup>2</sup> )
FCC Margin of Compliance:	<b>-9.91</b>	(dB)
IC Margin of Compliance:	<b>-6.62</b>	(dB)



America

**2.4GHz WiFi:**

Maximum peak output power at antenna input terminal:	<b>12.06</b>	(dBm)
Maximum peak output power at antenna input terminal:	<b>16.07</b>	(mW)
Antenna gain(typical):	<b>3.99</b>	(dBi)
Maximum antenna gain:	<b>2.506</b>	(numeric)
Prediction distance:	<b>20</b>	(cm)
Source Based Time Average Duty Cycle:	<b>100</b>	(%)
Prediction frequency:	<b>2402</b>	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	<b>1</b>	(mW/cm <sup>2</sup> )
ISED MPE limit for uncontrolled exposure at prediction frequency:	<b>5.351</b>	(W/m <sup>2</sup> )
Power density at prediction frequency:	<b>0.0080118</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.080118</b>	(W/m <sup>2</sup> )
FCC Margin of Compliance:	<b>-20.96</b>	(dB)
IC Margin of Compliance:	<b>-18.25</b>	(dB)

**6.1GHz UWB:**

Maximum peak output power at antenna input terminal:	<b>-33.44</b>	(dBm)
Maximum peak output power at antenna input terminal:	<b>0</b>	(mW)
Antenna gain(typical):	<b>0</b>	(dBi)
Maximum antenna gain:	<b>1</b>	(numeric)
Prediction distance:	<b>20</b>	(cm)
Source Based Time Average Duty Cycle:	<b>100</b>	(%)
Prediction frequency:	<b>6058.8</b>	(MHz)
FCC MPE limit for uncontrolled exposure at prediction frequency:	<b>1</b>	(mW/cm <sup>2</sup> )
ISED MPE limit for uncontrolled exposure at prediction frequency:	<b>10</b>	(W/m <sup>2</sup> )
Power density at prediction frequency:	<b>0.000001</b>	(mW/cm <sup>2</sup> )
Power density at prediction frequency:	<b>0.000001</b>	(W/m <sup>2</sup> )
FCC Margin of Compliance:	<b>-70.45</b>	(dB)
IC Margin of Compliance:	<b>-70.45</b>	(dB)

Sincerely,

Xiaoying Zhang



America

Name

Authorized Signatory

Title: EMC/Wireless Test Engineer