


TEST REPORT

Application No.: KSEM2104000497CR
FCC ID: 2AL8S-0235C5DF
IC: 25987-0235C5DF
Applicant: Zhejiang Uniview Technologies Co., Ltd.
Address of Applicant: 88 Jiangling Road, Xixing Town, Binjiang District, Hangzhou City
Manufacturer: Zhejiang Uniview Technologies Co., Ltd.
Address of Manufacturer: 88 Jiangling Road, Xixing Town, Binjiang District, Hangzhou City
Equipment Under Test (EUT):
EUT Name: Access Control Terminal
Model No.: OET-C11H-M,OET-C11H-M-NB,OET-C11H-M-xxxxxxx-yyy-yyyy-zzz("x" "y" "z" can be 0-9,A-Z,a-z or blank denoting target regional; "-" may be blank)α
 α Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Standard(s): 47 CFR Part 15, Subpart C 15.225
 RSS-210 Issue 10 December 2019
 RSS-Gen Issue 5 Amendment 2 (February 2021)
Date of Receipt: 2021-04-14
Date of Test: 2021-05-15 to 2021-05-17
Date of Issue: 2021-05-18

| | |
|---------------------|--------------|
| Test Result: | Pass* |
|---------------------|--------------|

* In the configuration tested, the EUT complied with the standards specified above.



Eric Lin
EMC Lab Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.10, Weiye Road, Innovation Park, Kunshan, Jiangsu, China 215300
 中国·江苏·昆山市留学院创业园伟业路10号 邮编 215300

t(86-512)57355888 f(86-512)57370818 www.sgsgroup.com.cn
 t(86-512)57355888 f(86-512)57370818 sgs.china@sgs.com



**Compliance Certification Services
(Kunshan) Inc.**

Report No.: KSEM2210400049701
Page: 2 of 27

For IC Model: OET-C11H-M,OET-C11H-M-NB

| Revision Record | | | |
|-----------------|-------------|------------|--------|
| Version | Description | Date | Remark |
| 00 | Original | 2021-05-18 | / |
| | | | |
| | | | |

| | | | |
|--------------------------|--|-------------------------------|--|
| Authorized for issue by: | | | |
| | | Damon Zhou | |
| | | Damon Zhou / Project Engineer | |
| | | Eric Lin | |
| | | Eric Lin / Reviewer | |

2 Test Summary

| Radio Spectrum Technical Requirement | | | | |
|--------------------------------------|----------------------------------|----------------|--------------------------------|----------------------|
| Item | FCC Requirement | IC Requirement | Method | Result |
| Antenna Requirement | 47 CFR Part 15, Subpart C 15.225 | N/A | RSS-210 Issue 10 December 2019 | Customer Declaration |

| Radio Spectrum Matter Part | | | | |
|---|----------------------------------|--------------------------------|------------------------------------|--------|
| Item | FCC Requirement | IC Requirement | Method | Result |
| Conducted Emissions at AC Power Line (150kHz-30MHz) | 47 CFR Part 15, Subpart C 15.225 | RSS-210 Issue 10 December 2019 | ANSI C63.10 (2013) Section 6.2 | Pass |
| 20dB Bandwidth | 47 CFR Part 15, Subpart C 15.225 | RSS-210 Issue 10 December 2019 | ANSI C63.10 (2013) Section 6.9 | Pass |
| Emission Mask | 47 CFR Part 15, Subpart C 15.225 | RSS-210 Issue 10 December 2019 | ANSI C63.10 (2013) Section 6.4 | *Pass |
| Frequency tolerance | 47 CFR Part 15, Subpart C 15.225 | RSS-210 Issue 10 December 2019 | ANSI C63.10 (2013) Section 6.8 | Pass |
| Radiated Emissions(9kHz-30MHz) | 47 CFR Part 15, Subpart C 15.225 | RSS-210 Issue 10 December 2019 | ANSI C63.10 (2013) Section 6.4&6.5 | Pass |
| Radiated Emissions(30MHz-1GHz) | 47 CFR Part 15, Subpart C 15.225 | RSS-210 Issue 10 December 2019 | ANSI C63.10 (2013) Section 6.4&6.5 | Pass |
| 99% Bandwidth | - | RSS-210 Issue 10 December 2019 | RSS-Gen Section 6.7 | Pass |

Remark *: The test level of the fundamental signal is below the limit of general spurious emission, so the test item doesn't be performed.

Declaration of EUT Family Grouping:

Note 1: There are series models mentioned in this report, and they are the similar in electrical and electronic characters. Only the model OET-C11H-M was tested since their differences were the model number and appearance.

3 Contents

| | Page |
|---|------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 4 |
| 3 CONTENTS | 5 |
| 4 GENERAL INFORMATION | 6 |
| 4.1 DETAILS OF E.U.T. | 6 |
| 4.2 DESCRIPTION OF SUPPORT UNITS | 6 |
| 4.3 MEASUREMENT UNCERTAINTY | 6 |
| 4.4 TEST LOCATION | 7 |
| 4.5 TEST FACILITY | 7 |
| 4.6 ABNORMALITIES FROM STANDARD CONDITIONS | 7 |
| 5 EQUIPMENT LIST | 8 |
| 6 RADIO SPECTRUM TECHNICAL REQUIREMENT | 9 |
| 6.1 ANTENNA REQUIREMENT | 9 |
| 7 RADIO SPECTRUM MATTER TEST RESULTS | 10 |
| 7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150kHz-30MHz) | 10 |
| 7.2 20dB BANDWIDTH | 14 |
| 7.3 EMISSION MASK | 16 |
| 7.4 FREQUENCY TOLERANCE | 17 |
| 7.5 RADIATED EMISSIONS(9kHz-30MHz) | 19 |
| 7.6 RADIATED EMISSIONS(30MHz-1GHz) | 21 |
| 7.7 99% BANDWIDTH | 25 |
| 8 TEST SETUP PHOTOGRAPHS | 27 |
| 9 EUT CONSTRUCTIONAL DETAILS | 27 |

4 General Information

4.1 Details of E.U.T.

| | |
|-----------------------|------------------------|
| Power supply: | DC 12V by adapter |
| Serial Number: | A0210235C5DF3213000069 |
| Firmware Version: | QPTS-B2211.2.6.210428 |
| Test voltage: | AC 120V/60Hz |
| Operation Frequency | 13.56MHz |
| Modulation Technique: | ASK |
| Antenna Type: | Loop antenna |
| Number of Channel: | 1 |

4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|-------------|---|--------------|------------|
| AC Adapter | Sichuan Jiuzhou Electronic Technology Co.,Ltd | DYS05100CP-U | N/A |

4.3 Measurement Uncertainty

| No. | Item | Measurement Uncertainty |
|-----|---------------------------------|----------------------------------|
| 1 | Radio Frequency | $\pm 8.4 \times 10^{-8}$ |
| 2 | Occupied Bandwidth | $\pm 3\%$ |
| 3 | Radiated Spurious emission test | $\pm 4.2\text{dB}$ (Below 30MHz) |
| | | $\pm 4.4\text{dB}$ (30MHz-1GHz) |
| | | $\pm 4.8\text{dB}$ (1GHz-18GHz) |
| | | $\pm 5.2\text{dB}$ (Above 18GHz) |
| 4 | Temperature test | $\pm 1^\circ\text{C}$ |
| 5 | Humidity test | $\pm 3\%$ |
| 6 | Supply voltages | $\pm 1.5\%$ |
| 7 | Time | $\pm 3\%$ |

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

All measurement facilities used to collect the measurement data are located at
No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L4354)**

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 2541.01)**

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

- **FCC (Designation Number: CN1172)**

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory.
Designation Number: CN1172.

- **ISED (CAB Identifier: CN0072)**

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development (ISED) Canada as an accredited testing laboratory.
CAB Identifier: CN0072.

- **VCCI (Member No.: 1938)**

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.

None

4.6 Abnormalities from Standard Conditions

None

5 Equipment List

| Item | Equipment | Manufacturer | Model | Serial Number | Cal Date | Cal. Due Date |
|---|----------------------------|---------------|-----------|---------------|------------|---------------|
| Conducted Emission at Mains Terminals (150kHz-30MHz) | | | | | | |
| 1 | EMI Test Receive | R&S | ESCI | 100781 | 02/01/2021 | 01/31/2022 |
| 2 | LISN | R&S | ENV216 | 101604 | 10/19/2020 | 10/18/2021 |
| 3 | LISN | Schwarzbeck | NNLK 8129 | 8129-143 | 10/19/2020 | 10/18/2021 |
| 4 | Pulse Limiter | R&S | ESH3-Z2 | 100609 | 02/01/2021 | 01/31/2022 |
| 5 | CE test Cable | Thermax | / | 14 | 10/17/2020 | 10/16/2021 |
| 6 | Test Software | Farad | EZ-EMC | CCS-03A1 | N.C.R | N.C.R |
| RF Radiated Test | | | | | | |
| 1 | Spectrum Analyzer | R&S | FSV40 | 101493 | 10/19/2020 | 10/18/2021 |
| 2 | Signal Generator | Agilent | E8257C | MY43321570 | 10/19/2020 | 10/18/2021 |
| 3 | Loop Antenna | Schwarzbeck | HXYZ9170 | 9170-108 | 02/22/2021 | 02/21/2022 |
| 4 | Bilog Antenna | TESEQ | CBL 6112D | 35403 | 06/22/2019 | 06/21/2021 |
| 5 | Bilog Antenna | SCHWARZBECK | VULB9160 | 9160-3342 | 04/13/2021 | 04/12/2023 |
| 6 | Horn-antenna(1-18GHz) | Schwarzbeck | BBHA9120D | 267 | 10/26/2020 | 10/25/2022 |
| 7 | Horn-antenna(1-18GHz) | ETS-LINDGREN | 3117 | 00143290 | 02/22/2021 | 02/21/2023 |
| 8 | Pre-Amplifier(30MHz~18GHz) | LNA | / | / | 04/15/2021 | 04/14/2022 |
| 9 | Amplifier(18~40GHz) | COM-POWER | PAM-840A | 461332 | 10/23/2020 | 10/22/2021 |
| 10 | Low Pass Filter | MICRO-TRONICS | VLFX-950 | RV142900829 | N.C.R | N.C.R |
| 11 | High Pass Filter | Mini-Circuits | VHF-1200 | 15542 | N.C.R | N.C.R |
| 12 | RE test cable | / | RE01-RE04 | / | 04/15/2021 | 04/14/2022 |
| 13 | Software | Farad | EZ-EMC | CCS-03A1 | N/A | N/A |

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is loop antenna integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to Appendix (Internal Photos)

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

| Frequency range (MHz) | Limit (dBuV) | |
|-----------------------|--------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 45 % RH Atmospheric Pressure: 1001 mbar

Test mode: a:TX mode_Keep the EUT in transmitting with modulation mode.


7.1.2 Test Setup Diagram



7.1.3 Measurement Procedure and Data


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
 - 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
 - 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
 - 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
 - 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
1. LISN=Read Level+ Cable Loss+ LISN Factor

Mode:a; Line:Live Line



| No. | Frequency | QuasiPeak reading | Average reading | Correction factor | QuasiPeak result | Average result | QuasiPeak limit | Average limit | QuasiPeak margin | Average margin | Remark |
|-----|-----------|-------------------|-----------------|-------------------|------------------|----------------|-----------------|---------------|------------------|----------------|--------|
| | (MHz) | (dBuV) | (dBuV) | (dB) | (dBuV) | (dBuV) | (dBuV) | (dBuV) | (dB) | (dB) | |
| 1 | 0.1562 | 27.20 | 16.16 | 19.46 | 46.66 | 35.62 | 65.66 | 55.66 | -19.00 | -20.04 | Pass |
| 2 | 0.1974 | 25.17 | 15.40 | 19.46 | 44.63 | 34.86 | 63.71 | 53.72 | -19.08 | -18.86 | Pass |
| 3* | 0.4687 | 23.70 | 15.53 | 19.52 | 43.22 | 35.05 | 56.54 | 46.54 | -13.32 | -11.49 | Pass |
| 4 | 2.7314 | 16.92 | 8.93 | 19.63 | 36.55 | 28.56 | 56.00 | 46.00 | -19.45 | -17.44 | Pass |
| 5 | 3.0123 | 16.70 | 8.05 | 19.64 | 36.34 | 27.69 | 56.00 | 46.00 | -19.66 | -18.31 | Pass |
| 6 | 3.7491 | 14.82 | 6.73 | 19.68 | 34.50 | 26.41 | 56.00 | 46.00 | -21.50 | -19.59 | Pass |

Mode:a; Line:Neutral Line



| No. | Frequency | QuasiPeak reading | Average reading | Correction factor | QuasiPeak result | Average result | QuasiPeak limit | Average limit | QuasiPeak margin | Average margin | Remark |
|-----|-----------|-------------------|-----------------|-------------------|------------------|----------------|-----------------|---------------|------------------|----------------|--------|
| | (MHz) | (dBuV) | (dBuV) | (dB) | (dBuV) | (dBuV) | (dBuV) | (dBuV) | (dB) | (dB) | |
| 1 | 0.1652 | 25.18 | 17.57 | 19.42 | 44.60 | 36.99 | 65.19 | 55.20 | -20.59 | -18.21 | Pass |
| 2 | 0.1948 | 22.15 | 13.55 | 19.43 | 41.58 | 32.98 | 63.83 | 53.83 | -22.25 | -20.85 | Pass |
| 3* | 0.4642 | 21.68 | 13.76 | 19.50 | 41.18 | 33.26 | 56.62 | 46.62 | -15.44 | -13.36 | Pass |
| 4 | 1.1654 | 14.77 | 6.16 | 19.54 | 34.31 | 25.70 | 56.00 | 46.00 | -21.69 | -20.30 | Pass |
| 5 | 2.7170 | 16.65 | 8.74 | 19.61 | 36.26 | 28.35 | 56.00 | 46.00 | -19.74 | -17.65 | Pass |
| 6 | 2.9710 | 16.24 | 7.67 | 19.62 | 35.86 | 27.29 | 56.00 | 46.00 | -20.14 | -18.71 | Pass |

7.2 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.215
Test Method: ANSI C63.10 (2013) Section 6.9
Limit: N/A


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode_Keep the EUT in transmitting with modulation mode.


7.2.2 Test Setup Diagram



7.2.3 Measurement Procedure and Data

| 20dB bandwidth (kHz) | F _L (MHz) | F _H (MHz) | Limit(MHz) | Result |
|----------------------|----------------------|----------------------|-----------------|--------|
| 0.51 | 13.56014 | 13.56065 | 13.110 – 14.010 | Pass |

Test plot as follows:



7.3 Emission Mask

Test Requirement 47 CFR Part 15, Subpart C 15.225(a)&(b)&(C)

Test Method: ANSI C63.10 (2013) Section 6.4

Limit:

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15.848 microvolts/meter at 30 meters.

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode_Keep the EUT in transmitting with modulation mode.

7.3.2 Test Setup Diagram



7.3.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

Note: The test level of the fundamental signal is below the limit of general spurious emission, so the test item doesn't be performed.

7.4 Frequency tolerance

Test Requirement 47 CFR Part 15, Subpart C 15.225(e)

Test Method: ANSI C63.10 (2013) Section 6.8

Limit: 1.356kHz


7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode a:TX mode_Keep the EUT in transmitting with modulation mode.

7.4.2 Test Setup Diagram



7.4.3 Measurement Procedure and Data

Nominal Operation Frequency: 13.56MHz

| Test Conditions | | Test Result (MHz) | Deviation (kHz) | Limit (kHz) | Result |
|------------------------|------------------------|----------------------|--------------------|-----------------------|--------|
| Temp (°C) | Volt (V AC) | | | | |
| T _{nom} (-20) | V _{nom} (120) | 13.56041 | 0.41 | ±0.01% (1.3560kHz) | Pass |
| T _{nom} (-10) | V _{nom} (120) | 13.56041 | 0.41 | | Pass |
| T _{nom} (0) | V _{nom} (120) | 13.56040 | 0.40 | | Pass |
| T _{nom} (10) | V _{nom} (120) | 13.56041 | 0.41 | | Pass |
| T _{nom} (20) | V _{nom} (120) | 13.56041 | 0.41 | | Pass |
| T _{nom} (30) | V _{nom} (120) | 13.56041 | 0.41 | | Pass |
| T _{nom} (40) | V _{nom} (120) | 13.56041 | 0.41 | | Pass |
| T _{nom} (50) | V _{nom} (120) | 13.56040 | 0.40 | | Pass |
| T _{nom} (20) | V _{min} (102) | 13.56040 | 0.40 | | Pass |
| | V _{max} (138) | 13.56042 | 0.42 | | Pass |

Note: Deviation (kHz) = (Test Result-13.56MHz)*1000

7.5 Radiated Emissions(9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4&6.5

Limit:

| Frequency(MHz) | Field strength (microvolts/meter) | Limit (dBuV/m) | Detector | Measurement Distance (meters) |
|----------------|--------------------------------------|-------------------|----------|----------------------------------|
| 0.009-0.490 | 2400/F(kHz) | - | - | 300 |
| 0.490-1.705 | 24000/F(kHz) | - | - | 30 |
| 1.705-30 | 30 | - | - | 30 |
| 30-88 | 100 | 40.0 | QP | 3 |
| 88-216 | 150 | 43.5 | QP | 3 |
| 216-960 | 200 | 46.0 | QP | 3 |
| 960-1000 | 500 | 54.0 | QP | 3 |
| Above 1000 | 500 | 54.0 | AV | 3 |

NOTE:

- (1) For test distance other than what is specified, but fulfilling the requirements of section 15.31(f) (2) the field strength is calculated by adding additionally an extrapolation factor of 40dB/decade (inverse linear distance for field strength measurements).

So the Distance Extrapolation Factor in dB is $40 \cdot \log(D_{\text{TEST}} / D_{\text{SPEC}})$ where D_{TEST} = Test Distance and D_{SPEC} = Specified Distance.

Field strength limit (dBuV/m)@test distance= Field strength limit (dBuV/m)@specified distance +Distance Extrapolation Factor


- (2) The lower limit shall apply at the transition frequencies.

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar


Test mode: a:TX mode_Keep the EUT in transmitting with modulation mode.

7.5.2 Test Setup Diagram

7.5.3 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.

Mode a:



| Item | Freq. | Read Level | Correct Factor | Result Level@3m | Result Level@SP EC | Limit Line@SPEC | Over Limit | Detector |
|--------|---------|------------|----------------|-----------------|--------------------|-----------------|------------|----------|
| (Mark) | (MHz) | (dBμV) | (dB/m) | (dBuV/m) | (dBuV/m) | (dBuV/m) | (dB) | |
| 1 | 0.022 | 34.76 | 15.12 | 49.88 | -30.12 | 40.74 | -70.86 | QP |
| 2 | 0.0687 | 31.44 | 15.09 | 46.53 | -33.47 | 30.86 | -64.33 | QP |
| 3 | 0.2391 | 33.76 | 15.17 | 48.93 | -31.07 | 20.03 | -51.10 | QP |
| 4 | 0.604 | 29.98 | 15.25 | 45.23 | 5.23 | 31.99 | -26.76 | QP |
| 5 | 1.262 | 26.29 | 15.39 | 41.68 | 1.68 | 25.61 | -23.93 | QP |
| 6 | 2.5133 | 24.64 | 15.56 | 40.20 | 0.20 | 29.50 | -29.30 | QP |
| 7 | 13.6227 | 41.35 | 15.49 | 56.84 | 16.84 | 29.5 | -12.66 | Peak |

7.6 Radiated Emissions(30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4&6.5

Limit:

| Frequency | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
|---------------|-------------------------------------|----------------|------------|-----------------------------|
| 30MHz-88MHz | 100 | 40.0 | Quasi-peak | 3 |
| 88MHz-216MHz | 150 | 43.5 | Quasi-peak | 3 |
| 216MHz-960MHz | 200 | 46.0 | Quasi-peak | 3 |
| 960MHz-1GHz | 500 | 54.0 | Quasi-peak | 3 |


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Test mode: a:TX mode_Keep the EUT in transmitting with modulation mode.

7.6.2 Test Setup Diagram




7.6.3 Measurement Procedure and Data

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground for below 1GHz at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Mode:a; Polarization:Horizontal


100.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Correct Factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|--------|
| 1 | 147.3700 | 4.82 | 20.05 | 24.87 | 43.50 | -18.63 | QP |
| 2 | 369.5000 | 4.94 | 22.85 | 27.79 | 46.00 | -18.21 | QP |
| 3 | 465.5300 | 2.98 | 24.60 | 27.58 | 46.00 | -18.42 | QP |
| 4 | 614.9100 | 0.99 | 26.69 | 27.68 | 46.00 | -18.32 | QP |
| 5 | 777.8700 | 3.27 | 27.68 | 30.95 | 46.00 | -15.05 | QP |
| 6 | 933.0700 | 0.02 | 29.09 | 29.11 | 46.00 | -16.89 | QP |

Mode:a; Polarization:Vertical

100.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Correct Factor(dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|-------------------|-------------------------|--------------------|-------------------|----------------|--------|
| 1 | 100.8100 | 6.15 | 18.54 | 24.69 | 43.50 | -18.81 | QP |
| 2 | 247.2800 | 7.20 | 19.15 | 26.35 | 46.00 | -19.65 | QP |
| 3 | 443.2200 | 4.67 | 24.21 | 28.88 | 46.00 | -17.12 | QP |
| 4 | 517.9100 | 6.32 | 25.45 | 31.77 | 46.00 | -14.23 | QP |
| 5 | 650.8000 | 6.11 | 27.12 | 33.23 | 46.00 | -12.77 | QP |
| 6 | 912.7000 | 7.82 | 28.83 | 36.65 | 46.00 | -9.35 | QP |

7.7 99% Bandwidth

Test Requirement RSS-Gen section 6.7

Test Method: RSS-Gen Section 6.7


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar


Test mode: a:TX mode_Keep the EUT in transmitting with modulation mode.

7.7.2 Test Setup Diagram



7.7.3 Measurement Procedure and Data

| Frequency (MHz) | 99% bandwidth (kHz) |
|-----------------|---------------------|
| 13.56 | 1.281 |





8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

- End of the Report -