

### FCC Report (WIFI)

**Applicant:** SHENZHEN FLYPRO AEROSPACE TECH CO.,LTD

**Address of Applicant:** 1Floor,NO.15 Building,NO.1201 LiuXian Avenue, Nanshan District, Shenzhen,China

**Manufacturer/Factory:** SHENZHEN FLYPRO AEROSPACE TECH CO.,LTD

**Address of Manufacturer/Factory:** 1Floor,NO.15 Building,NO.1201 LiuXian Avenue, Nanshan District, Shenzhen,China

**Equipment Under Test (EUT)**

Product Name: FLYPRO-WUZEI

Model No.: FLYPRO-WUZEI

**FCC ID:** 2AM7EFLYPRO

**Applicable standards:** FCC CFR Title 47 Part 15.247:2017

**Date of sample receipt:** July 04, 2017

**Date of Test:** July 05-11, 2017

**Date of report issued:** July 12, 2017

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A circular blue stamp with the text "GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD." around the perimeter and "GTS" in the center. Overlaid on the stamp is a handwritten signature in black ink.

**Robinson Lo**  
**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date          | Description |
|-------------|---------------|-------------|
| 00          | July 12, 2017 | Original    |
|             |               |             |
|             |               |             |
|             |               |             |
|             |               |             |

**Prepared By:**

*Edward Pan*

**Date:**

*July 12, 2017*

**Project Engineer**

**Check By:**

*Andy Wu*

**Date:**

*July 12, 2017*

**Reviewer**

## 3 Contents

Page

|       |                                         |    |
|-------|-----------------------------------------|----|
| 1     | COVER PAGE .....                        | 1  |
| 2     | VERSION .....                           | 2  |
| 3     | CONTENTS .....                          | 3  |
| 4     | TEST SUMMARY .....                      | 4  |
| 5     | GENERAL INFORMATION .....               | 5  |
| 5.1   | GENERAL DESCRIPTION OF EUT .....        | 5  |
| 5.2   | TEST MODE .....                         | 6  |
| 5.3   | DESCRIPTION OF SUPPORT UNITS .....      | 6  |
| 5.4   | TEST FACILITY .....                     | 7  |
| 5.5   | TEST LOCATION .....                     | 7  |
| 6     | TEST INSTRUMENTS LIST .....             | 8  |
| 7     | TEST RESULTS AND MEASUREMENT DATA ..... | 9  |
| 7.1   | ANTENNA REQUIREMENT .....               | 9  |
| 7.2   | CONDUCTED PEAK OUTPUT POWER .....       | 10 |
| 7.3   | CHANNEL BANDWIDTH .....                 | 11 |
| 7.4   | POWER SPECTRAL DENSITY .....            | 16 |
| 7.5   | BAND EDGES .....                        | 21 |
| 7.5.1 | Conducted Emission Method .....         | 21 |
| 7.5.2 | Radiated Emission Method .....          | 24 |
| 7.6   | SPURIOUS EMISSION .....                 | 29 |
| 7.6.1 | Conducted Emission Method .....         | 29 |
| 7.6.2 | Radiated Emission Method .....          | 34 |
| 8     | TEST SETUP PHOTO .....                  | 49 |
| 9     | EUT CONSTRUCTIONAL DETAILS .....        | 50 |

## 4 Test Summary

| Test Item                        | Section in CFR 47 | Result |
|----------------------------------|-------------------|--------|
| Antenna requirement              | 15.203/15.247 (c) | Pass   |
| AC Power Line Conducted Emission | 15.207            | N/A    |
| Conducted Peak Output Power      | 15.247 (b)(3)     | Pass   |
| Channel Bandwidth                | 15.247 (a)(2)     | Pass   |
| Power Spectral Density           | 15.247 (e)        | Pass   |
| Band Edge                        | 15.247(d)         | Pass   |
| Spurious Emission                | 15.205/15.209     | Pass   |

*Pass: The EUT complies with the essential requirements in the standard.*

*N/A: Not applicable*

*Remark: Test according to ANSI C63.4:2014 and ANSI C63.10:2013.*

### Measurement Uncertainty

| Test Item                        | Frequency Range | Measurement Uncertainty | Notes |
|----------------------------------|-----------------|-------------------------|-------|
| Radiated Emission                | 9kHz ~ 30MHz    | ± 4.34dB                | (1)   |
| Radiated Emission                | 30MHz ~ 1000MHz | ± 4.24dB                | (1)   |
| Radiated Emission                | 1GHz ~ 26.5GHz  | ± 4.68dB                | (1)   |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | ± 3.45dB                | (1)   |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

|                        |                                                                                                                                            |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:          | FLYPRO-WUZEI                                                                                                                               |
| Model No.:             | FLYPRO-WUZEI                                                                                                                               |
| Operation Frequency:   | 802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz<br>802.11n(HT40): 2422MHz~2452MHz                                                           |
| Channel numbers:       | 802.11b/802.11g /802.11n(HT20): 11<br>802.11(HT40): 7                                                                                      |
| Channel separation:    | 5MHz                                                                                                                                       |
| Modulation technology: | 802.11b: Direct Sequence Spread Spectrum (DSSS)<br>802.11g/802.11n(H20)/802.11n(H40):<br>Orthogonal Frequency Division Multiplexing (OFDM) |
| Antenna Type:          | Integral antenna                                                                                                                           |
| Antenna gain:          | 2dBi                                                                                                                                       |
| Power supply:          | DC 7.4V 3.922Wh 530mAh Polymer Li-ion Battery                                                                                              |

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2                                   | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3                                   | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Test channel    | Frequency (MHz)               |               |
|-----------------|-------------------------------|---------------|
|                 | 802.11b/802.11g/802.11n(HT20) | 802.11n(HT40) |
| Lowest channel  | 2412MHz                       | 2422MHz       |
| Middle channel  | 2437MHz                       | 2437MHz       |
| Highest channel | 2462MHz                       | 2452MHz       |

## 5.2 Test mode

|                                                                                                                                                                                                                                                                     |                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                                                   | Keep the EUT in continuously transmitting mode |
| <i>Remark: During the test, the dutycycle &gt;98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i> |                                                |

|                                                                                                                                                                                                              |         |         |               |               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------|---------------|---------------|
| We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows: |         |         |               |               |
| Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.                                                                                                         |         |         |               |               |
| Mode                                                                                                                                                                                                         | 802.11b | 802.11g | 802.11n(HT20) | 802.11n(HT40) |
| Data rate                                                                                                                                                                                                    | 1Mbps   | 6Mbps   | 6.5Mbps       | 13Mbps        |

## 5.3 Description of Support Units

|      |
|------|
| None |
|------|

## 5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

## 5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960


## 6 Test Instruments list

| Radiated Emission: |                               |                                |                             |               |                     |                         |
|--------------------|-------------------------------|--------------------------------|-----------------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment                | Manufacturer                   | Model No.                   | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | 3m Semi- Anechoic Chamber     | ZhongYu Electron               | 9.2(L)*6.2(W)* 6.4(H)       | GTS250        | July 03 2015        | July 02 2020            |
| 2                  | Control Room                  | ZhongYu Electron               | 6.2(L)*2.5(W)* 2.4(H)       | GTS251        | N/A                 | N/A                     |
| 3                  | Spectrum Analyzer             | Agilent                        | E4440A                      | GTS533        | June 29 2017        | June 28 2018            |
| 4                  | EMI Test Receiver             | Rohde & Schwarz                | ESU26                       | GTS203        | June 29 2017        | June 28 2018            |
| 5                  | BiConiLog Antenna             | SCHWARZBECK<br>MESS-ELEKTRONIK | VULB9163                    | GTS214        | June 29 2017        | June 28 2018            |
| 6                  | Double -ridged waveguide horn | SCHWARZBECK<br>MESS-ELEKTRONIK | 9120D-829                   | GTS208        | June 29 2017        | June 28 2018            |
| 7                  | Horn Antenna                  | ETS-LINDGREN                   | 3160                        | GTS217        | June 29 2017        | June 28 2018            |
| 8                  | EMI Test Software             | AUDIX                          | E3                          | N/A           | N/A                 | N/A                     |
| 9                  | Coaxial Cable                 | GTS                            | N/A                         | GTS213        | June 29 2017        | June 28 2018            |
| 10                 | Coaxial Cable                 | GTS                            | N/A                         | GTS211        | June 29 2017        | June 28 2018            |
| 11                 | Coaxial cable                 | GTS                            | N/A                         | GTS210        | June 29 2017        | June 28 2018            |
| 12                 | Coaxial Cable                 | GTS                            | N/A                         | GTS212        | June 29 2017        | June 28 2018            |
| 13                 | Amplifier(100kHz-3GHz)        | HP                             | 8347A                       | GTS204        | June 29 2017        | June 28 2018            |
| 14                 | Amplifier(2GHz-20GHz)         | HP                             | 8349B                       | GTS206        | June 29 2017        | June 28 2018            |
| 15                 | Amplifier (18-26GHz)          | Rohde & Schwarz                | AFS33-18002<br>650-30-8P-44 | GTS218        | June 29 2017        | June 28 2018            |
| 16                 | Band filter                   | Amindeon                       | 82346                       | GTS219        | June 29 2017        | June 28 2018            |
| 17                 | Power Meter                   | Anritsu                        | ML2495A                     | GTS540        | June 29 2017        | June 28 2018            |
| 18                 | Power Sensor                  | Anritsu                        | MA2411B                     | GTS541        | June 29 2017        | June 28 2018            |


| General used equipment: |                |              |           |               |                     |                         |
|-------------------------|----------------|--------------|-----------|---------------|---------------------|-------------------------|
| Item                    | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                       | Barometer      | ChangChun    | DYM3      | GTS257        | June. 29 2017       | June. 28 2018           |

## 7 Test results and Measurement Data

### 7.1 Antenna requirement

| Standard requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | FCC Part15 C Section 15.203 /247(c) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <p><b>15.203 requirement:</b></p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p><b>15.247(c) (1)(i) requirement:</b></p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> |                                     |
| EUT Antenna:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                     |
| <p><i>The antenna is integral antenna, the best case gain of the antenna is 2dBi</i></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                     |


## 7.2 Conducted Peak Output Power

|                   |                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3)                                                                                                                                                                                                                                                                                                      |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04                                                                                                                                                                                                                                                                                |
| Limit:            | 30dBm                                                                                                                                                                                                                                                                                                                                   |
| Test setup:       |  <p>The diagram illustrates the test setup. A Power Meter is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Power Meter and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                        |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                        |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                    |

### Measurement Data

| Test CH | Peak Output Power (dBm) |         |               |               | Limit(dBm) | Result |
|---------|-------------------------|---------|---------------|---------------|------------|--------|
|         | 802.11b                 | 802.11g | 802.11n(HT20) | 802.11n(HT40) |            |        |
| Lowest  | 15.62                   | 12.89   | 12.29         | 11.72         | 30.00      | Pass   |
| Middle  | 15.33                   | 12.60   | 11.94         | 11.21         |            |        |
| Highest | 15.54                   | 12.54   | 11.92         | 11.08         |            |        |

## 7.3 Channel Bandwidth


|                   |                                                                                                                                                                                                                                                                                                                   |
|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2)                                                                                                                                                                                                                                                                                |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04                                                                                                                                                                                                                                                          |
| Limit:            | >500KHz                                                                                                                                                                                                                                                                                                           |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                  |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                  |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                              |

## Measurement Data


| Test CH | Channel Bandwidth (MHz) |         |               |               | Limit(KHz) | Result |
|---------|-------------------------|---------|---------------|---------------|------------|--------|
|         | 802.11b                 | 802.11g | 802.11n(HT20) | 802.11n(HT40) |            |        |
| Lowest  | 9.403                   | 15.346  | 17.651        | 39.957        | >500       | Pass   |
| Middle  | 9.314                   | 15.937  | 17.651        | 35.897        |            |        |
| Highest | 9.505                   | 16.029  | 17.602        | 36.088        |            |        |

Test plot as follows:


|            |         |
|------------|---------|
| Test mode: | 802.11b |
|------------|---------|



Lowest channel




Middle channel




Highest channel


|            |         |
|------------|---------|
| Test mode: | 802.11g |
|------------|---------|



Lowest channel




Middle channel




Highest channel


|            |               |
|------------|---------------|
| Test mode: | 802.11n(HT20) |
|------------|---------------|



Lowest channel




Middle channel




Highest channel


|            |               |
|------------|---------------|
| Test mode: | 802.11n(HT40) |
|------------|---------------|



Lowest channel




Middle channel



Highest channel

## 7.4 Power Spectral Density


|                   |                                                                                                                                                                                                                                                                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (e)                                                                                                                                                                                                                                                                                                                            |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04                                                                                                                                                                                                                                                                                                   |
| Limit:            | 8dBm/3KHz                                                                                                                                                                                                                                                                                                                                                  |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                           |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                           |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                       |

### Measurement Data


| Test CH | Power Spectral Density (dBm) |         |               |               | Limit<br>(dBm/3kHz) | Result |
|---------|------------------------------|---------|---------------|---------------|---------------------|--------|
|         | 802.11b                      | 802.11g | 802.11n(HT20) | 802.11n(HT40) |                     |        |
| Lowest  | 4.82                         | 2.02    | -0.16         | -5.03         | 8.00                | Pass   |
| Middle  | 4.34                         | 1.98    | -0.95         | -4.85         |                     |        |
| Highest | 4.37                         | 1.94    | -1.33         | -5.21         |                     |        |

Test plot as follows:


|            |         |
|------------|---------|
| Test mode: | 802.11b |
|------------|---------|



Lowest channel




Middle channel




Highest channel


|            |         |
|------------|---------|
| Test mode: | 802.11g |
|------------|---------|



Lowest channel




Middle channel




Highest channel


|            |               |
|------------|---------------|
| Test mode: | 802.11n(HT20) |
|------------|---------------|



Lowest channel




Middle channel




Highest channel


|            |               |
|------------|---------------|
| Test mode: | 802.11n(HT40) |
|------------|---------------|



Lowest channel




Middle channel




Highest channel



## 7.5 Band edges

### 7.5.1 Conducted Emission Method


|                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.                                                                                                        |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer, shown with a green trace on its screen, is connected to an E.U.T. (Equipment Under Test) box by a red cable. Both the Spectrum Analyzer and the E.U.T. are positioned on a table labeled 'Non-Conducted Table'. This table is supported by two vertical legs and sits on a thick grey horizontal bar labeled 'Ground Reference Plane'.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

Test plot as follows:





## 7.5.2 Radiated Emission Method

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |          |                    |      |         |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------------------|------|---------|
| Test Requirement:     | FCC Part15 C Section 15.209 and 15.205                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |          |                    |      |         |
| Test Method:          | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |                    |      |         |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |          |                    |      |         |
| Test site:            | Measurement Distance: 3m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |          |                    |      |         |
| Receiver setup:       | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Detector | RBW                | VBW  | Value   |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Peak     | 1MHz               | 3MHz | Peak    |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Average  | 1MHz               | 3MHz | Average |
| Limit:                | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |          | Limit (dBuV/m @3m) |      | Value   |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |          | 54.00              |      | Average |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |          | 74.00              |      | Peak    |
| Test setup:           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |          |                    |      |         |
| Test Procedure:       | <ol style="list-style-type: none"><li>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li><li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li><li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li><li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li><li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li><li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li><li>7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test</li></ol> |          |                    |      |         |

|                   |                                            |
|-------------------|--------------------------------------------|
|                   | worst case mode is recorded in the report. |
| Test Instruments: | Refer to section 6.0 for details           |
| Test mode:        | Refer to section 5.2 for details           |
| Test results:     | Pass                                       |

Measurement data:

*Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11b | Test channel: | Lowest |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 51.84             | 27.59                 | 5.38            | 34.01                    | 50.80          | 74.00               | -23.20          | Horizontal   |
| 2400.00         | 60.92             | 27.58                 | 5.39            | 34.01                    | 59.88          | 74.00               | -14.12          | Horizontal   |
| 2390.00         | 53.54             | 27.59                 | 5.38            | 34.01                    | 52.50          | 74.00               | -21.50          | Vertical     |
| 2400.00         | 62.77             | 27.58                 | 5.39            | 34.01                    | 61.73          | 74.00               | -12.27          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 38.55             | 27.59                 | 5.38            | 34.01                    | 37.51          | 54.00               | -16.49          | Horizontal   |
| 2400.00         | 46.86             | 27.58                 | 5.39            | 34.01                    | 45.82          | 54.00               | -8.18           | Horizontal   |
| 2390.00         | 40.38             | 27.59                 | 5.38            | 34.01                    | 39.34          | 54.00               | -14.66          | Vertical     |
| 2400.00         | 48.00             | 27.58                 | 5.39            | 34.01                    | 46.96          | 54.00               | -7.04           | Vertical     |

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11b | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 52.58             | 27.53                 | 5.47            | 33.92                    | 51.66          | 74.00               | -22.34          | Horizontal   |
| 2500.00         | 48.35             | 27.55                 | 5.49            | 29.93                    | 51.46          | 74.00               | -22.54          | Horizontal   |
| 2483.50         | 54.88             | 27.53                 | 5.47            | 33.92                    | 53.96          | 74.00               | -20.04          | Vertical     |
| 2500.00         | 50.89             | 27.55                 | 5.49            | 29.93                    | 54.00          | 74.00               | -20.00          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 38.94             | 27.53                 | 5.47            | 33.92                    | 38.02          | 54.00               | -15.98          | Horizontal   |
| 2500.00         | 35.01             | 27.55                 | 5.49            | 29.93                    | 38.12          | 54.00               | -15.88          | Horizontal   |
| 2483.50         | 40.91             | 27.53                 | 5.47            | 33.92                    | 39.99          | 54.00               | -14.01          | Vertical     |
| 2500.00         | 36.89             | 27.55                 | 5.49            | 29.93                    | 40.00          | 54.00               | -14.00          | Vertical     |

*Remark:*

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11g | Test channel: | Lowest |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 50.42             | 27.59                 | 5.38            | 34.01                    | 49.38          | 74.00               | -24.62          | Horizontal   |
| 2400.00         | 59.03             | 27.58                 | 5.39            | 34.01                    | 57.99          | 74.00               | -16.01          | Horizontal   |
| 2390.00         | 52.02             | 27.59                 | 5.38            | 34.01                    | 50.98          | 74.00               | -23.02          | Vertical     |
| 2400.00         | 60.49             | 27.58                 | 5.39            | 34.01                    | 59.45          | 74.00               | -14.55          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 37.54             | 27.59                 | 5.38            | 34.01                    | 36.50          | 54.00               | -17.50          | Horizontal   |
| 2400.00         | 45.70             | 27.58                 | 5.39            | 34.01                    | 44.66          | 54.00               | -9.34           | Horizontal   |
| 2390.00         | 39.26             | 27.59                 | 5.38            | 34.01                    | 38.22          | 54.00               | -15.78          | Vertical     |
| 2400.00         | 46.73             | 27.58                 | 5.39            | 34.01                    | 45.69          | 54.00               | -8.31           | Vertical     |

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11g | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 50.55             | 27.53                 | 5.47            | 33.92                    | 49.63          | 74.00               | -24.37          | Horizontal   |
| 2500.00         | 46.77             | 27.55                 | 5.49            | 29.93                    | 49.88          | 74.00               | -24.12          | Horizontal   |
| 2483.50         | 52.56             | 27.53                 | 5.47            | 33.92                    | 51.64          | 74.00               | -22.36          | Vertical     |
| 2500.00         | 49.05             | 27.55                 | 5.49            | 29.93                    | 52.16          | 74.00               | -21.84          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 37.72             | 27.53                 | 5.47            | 33.92                    | 36.80          | 54.00               | -17.20          | Horizontal   |
| 2500.00         | 34.05             | 27.55                 | 5.49            | 29.93                    | 37.16          | 54.00               | -16.84          | Horizontal   |
| 2483.50         | 39.55             | 27.53                 | 5.47            | 33.92                    | 38.63          | 54.00               | -15.37          | Vertical     |
| 2500.00         | 35.89             | 27.55                 | 5.49            | 29.93                    | 39.00          | 54.00               | -15.00          | Vertical     |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT20) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 50.64             | 27.59                 | 5.38            | 34.01                    | 49.60          | 74.00               | -24.40          | Horizontal   |
| 2400.00         | 59.31             | 27.58                 | 5.39            | 34.01                    | 58.27          | 74.00               | -15.73          | Horizontal   |
| 2390.00         | 52.25             | 27.59                 | 5.38            | 34.01                    | 51.21          | 74.00               | -22.79          | Vertical     |
| 2400.00         | 60.84             | 27.58                 | 5.39            | 34.01                    | 59.80          | 74.00               | -14.20          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 37.69             | 27.59                 | 5.38            | 34.01                    | 36.65          | 54.00               | -17.35          | Horizontal   |
| 2400.00         | 45.88             | 27.58                 | 5.39            | 34.01                    | 44.84          | 54.00               | -9.16           | Horizontal   |
| 2390.00         | 39.43             | 27.59                 | 5.38            | 34.01                    | 38.39          | 54.00               | -15.61          | Vertical     |
| 2400.00         | 46.92             | 27.58                 | 5.39            | 34.01                    | 45.88          | 54.00               | -8.12           | Vertical     |

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT20) | Test channel: | Highest |
|------------|---------------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 50.86             | 27.53                 | 5.47            | 33.92                    | 49.94          | 74.00               | -24.06          | Horizontal   |
| 2500.00         | 47.01             | 27.55                 | 5.49            | 29.93                    | 50.12          | 74.00               | -23.88          | Horizontal   |
| 2483.50         | 52.91             | 27.53                 | 5.47            | 33.92                    | 51.99          | 74.00               | -22.01          | Vertical     |
| 2500.00         | 49.33             | 27.55                 | 5.49            | 29.93                    | 52.44          | 74.00               | -21.56          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 37.90             | 27.53                 | 5.47            | 33.92                    | 36.98          | 54.00               | -17.02          | Horizontal   |
| 2500.00         | 34.20             | 27.55                 | 5.49            | 29.93                    | 37.31          | 54.00               | -16.69          | Horizontal   |
| 2483.50         | 39.76             | 27.53                 | 5.47            | 33.92                    | 38.84          | 54.00               | -15.16          | Vertical     |
| 2500.00         | 36.04             | 27.55                 | 5.49            | 29.93                    | 39.15          | 54.00               | -14.85          | Vertical     |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT40) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 49.72             | 27.59                 | 5.38            | 34.01                    | 48.68          | 74.00               | -25.32          | Horizontal   |
| 2400.00         | 58.08             | 27.58                 | 5.39            | 34.01                    | 57.04          | 74.00               | -16.96          | Horizontal   |
| 2390.00         | 51.26             | 27.59                 | 5.38            | 34.01                    | 50.22          | 74.00               | -23.78          | Vertical     |
| 2400.00         | 59.36             | 27.58                 | 5.39            | 34.01                    | 58.32          | 74.00               | -15.68          | Vertical     |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2390.00         | 37.03             | 27.59                 | 5.38            | 34.01                    | 35.99          | 54.00               | -18.01          | Horizontal   |
| 2400.00         | 45.12             | 27.58                 | 5.39            | 34.01                    | 44.08          | 54.00               | -9.92           | Horizontal   |
| 2390.00         | 38.70             | 27.59                 | 5.38            | 34.01                    | 37.66          | 54.00               | -16.34          | Vertical     |
| 2400.00         | 46.10             | 27.58                 | 5.39            | 34.01                    | 45.06          | 54.00               | -8.94           | Vertical     |

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT40) | Test channel: | Highest |
|------------|---------------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 49.54             | 27.53                 | 5.47            | 33.92                    | 48.62          | 74.00               | -25.38          | Horizontal   |
| 2500.00         | 45.99             | 27.55                 | 5.49            | 29.93                    | 49.10          | 74.00               | -24.90          | Horizontal   |
| 2483.50         | 51.41             | 27.53                 | 5.47            | 33.92                    | 50.49          | 74.00               | -23.51          | Vertical     |
| 2500.00         | 48.14             | 27.55                 | 5.49            | 29.93                    | 51.25          | 74.00               | -22.75          | Vertical     |

**Average value:**


| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 2483.50         | 37.11             | 27.53                 | 5.47            | 33.92                    | 36.19          | 54.00               | -17.81          | Horizontal   |
| 2500.00         | 33.58             | 27.55                 | 5.49            | 29.93                    | 36.69          | 54.00               | -17.31          | Horizontal   |
| 2483.50         | 38.88             | 27.53                 | 5.47            | 33.92                    | 37.96          | 54.00               | -16.04          | Vertical     |
| 2500.00         | 35.38             | 27.55                 | 5.49            | 29.93                    | 38.49          | 54.00               | -15.51          | Vertical     |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.6 Spurious Emission


### 7.6.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04                                                                                                                                                                                                                                                                                                                                                                     |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.                                      |
| Test setup:       |  <p>The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by two vertical legs. Below the table is a Ground Reference Plane, represented by a thick grey bar.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                             |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                             |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                                                         |

Test plot as follows:


|            |         |
|------------|---------|
| Test mode: | 802.11b |
|------------|---------|

Lowest channel




30MHz~25GHz

Middle channel



30MHz~25GHz


Highest channel



30MHz~25GHz


|            |         |
|------------|---------|
| Test mode: | 802.11g |
|------------|---------|

Lowest channel




30MHz~25GHz

Middle channel



30MHz~25GHz


Highest channel



30MHz~25GHz


|            |               |
|------------|---------------|
| Test mode: | 802.11n(HT20) |
|------------|---------------|

Lowest channel




30MHz~25GHz

Middle channel



30MHz~25GHz


Highest channel



30MHz~25GHz


|            |               |
|------------|---------------|
| Test mode: | 802.11n(HT40) |
|------------|---------------|

Lowest channel




30MHz~25GHz

Middle channel




30MHz~25GHz


Highest channel



30MHz~25GHz

## 7.6.2 Radiated Emission Method

|                       |                                                                                                 |            |                    |        |            |
|-----------------------|-------------------------------------------------------------------------------------------------|------------|--------------------|--------|------------|
| Test Requirement:     | FCC Part15 C Section 15.209                                                                     |            |                    |        |            |
| Test Method:          | ANSI C63.10:2013                                                                                |            |                    |        |            |
| Test Frequency Range: | 30MHz to 25GHz                                                                                  |            |                    |        |            |
| Test site:            | Measurement Distance: 3m                                                                        |            |                    |        |            |
| Receiver setup:       | Frequency                                                                                       | Detector   | RBW                | VBW    | Value      |
|                       | 30MHz-1GHz                                                                                      | Quasi-peak | 120KHz             | 300KHz | Quasi-peak |
|                       | Above 1GHz                                                                                      | Peak       | 1MHz               | 3MHz   | Peak       |
|                       |                                                                                                 | Average    | 1MHz               | 3MHz   | Average    |
| Limit:                | Frequency                                                                                       |            | Limit (dBuV/m @3m) |        | Value      |
|                       | 30MHz-88MHz                                                                                     |            | 40.00              |        | Quasi-peak |
|                       | 88MHz-216MHz                                                                                    |            | 43.50              |        | Quasi-peak |
|                       | 216MHz-960MHz                                                                                   |            | 46.00              |        | Quasi-peak |
|                       | 960MHz-1GHz                                                                                     |            | 54.00              |        | Quasi-peak |
|                       | Above 1GHz                                                                                      |            | 54.00              |        | Average    |
|                       |                                                                                                 |            | 74.00              |        | Peak       |
| Test setup:           | Below 1GHz                                                                                      |            |                    |        |            |
|                       | <div></div> |            |                    |        |            |
| Test setup:           | Above 1GHz                                                                                      |            |                    |        |            |
|                       |                                                                                                 |            |                    |        |            |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <p>Test Procedure:</p>   | <ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table(0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.</li> </ol> |
| <p>Test Instruments:</p> | <p>Refer to section 6.0 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <p>Test mode:</p>        | <p>Refer to section 5.2 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <p>Test results:</p>     | <p>Pass</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

**Remark:**

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

## Measurement Data

### ■ Below 1GHz

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 262.90          | 41.28             | 12.24                 | 2.19            | 29.74              | 25.97          | 46.00               | -20.03          | Vertical     |
| 287.99          | 38.67             | 13.11                 | 2.31            | 29.92              | 24.17          | 46.00               | -21.83          | Vertical     |
| 336.04          | 39.64             | 14.21                 | 2.55            | 29.80              | 26.60          | 46.00               | -19.40          | Vertical     |
| 672.85          | 41.27             | 19.65                 | 3.99            | 29.23              | 35.68          | 46.00               | -10.32          | Vertical     |
| 721.73          | 39.87             | 20.12                 | 4.17            | 29.20              | 34.96          | 46.00               | -11.04          | Vertical     |
| 768.75          | 37.64             | 20.85                 | 4.35            | 29.20              | 33.64          | 46.00               | -12.36          | Vertical     |
| 162.04          | 36.60             | 8.20                  | 1.64            | 29.35              | 17.09          | 43.50               | -26.41          | Horizontal   |
| 262.90          | 35.14             | 12.24                 | 2.19            | 29.74              | 19.83          | 46.00               | -26.17          | Horizontal   |
| 576.64          | 35.48             | 18.88                 | 3.63            | 29.30              | 28.69          | 46.00               | -17.31          | Horizontal   |
| 721.73          | 35.21             | 20.12                 | 4.17            | 29.20              | 30.30          | 46.00               | -15.70          | Horizontal   |
| 815.97          | 43.65             | 21.46                 | 4.52            | 29.18              | 40.45          | 46.00               | -5.55           | Horizontal   |
| 912.86          | 37.37             | 22.27                 | 4.90            | 29.10              | 35.44          | 46.00               | -10.56          | Horizontal   |

## ■ Above 1GHz

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11b | Test channel: | Lowest |
|------------|---------|---------------|--------|

### Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 40.99             | 31.79                 | 8.62            | 32.10              | 49.30          | 74.00               | -24.70          | Vertical     |
| 7236.00         | 34.66             | 36.19                 | 11.68           | 31.97              | 50.56          | 74.00               | -23.44          | Vertical     |
| 9648.00         | 33.03             | 38.07                 | 14.16           | 31.56              | 53.70          | 74.00               | -20.30          | Vertical     |
| 12060.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4824.00         | 39.55             | 31.79                 | 8.62            | 32.10              | 47.86          | 74.00               | -26.14          | Horizontal   |
| 7236.00         | 34.35             | 36.19                 | 11.68           | 31.97              | 50.25          | 74.00               | -23.75          | Horizontal   |
| 9648.00         | 32.58             | 38.07                 | 14.16           | 31.56              | 53.25          | 74.00               | -20.75          | Horizontal   |
| 12060.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

### Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 30.02             | 31.79                 | 8.62            | 32.10              | 38.33          | 54.00               | -15.67          | Vertical     |
| 7236.00         | 23.51             | 36.19                 | 11.68           | 31.97              | 39.41          | 54.00               | -14.59          | Vertical     |
| 9648.00         | 23.36             | 38.07                 | 14.16           | 31.56              | 44.03          | 54.00               | -9.97           | Vertical     |
| 12060.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4824.00         | 29.06             | 31.79                 | 8.62            | 32.10              | 37.37          | 54.00               | -16.63          | Horizontal   |
| 7236.00         | 22.93             | 36.19                 | 11.68           | 31.97              | 38.83          | 54.00               | -15.17          | Horizontal   |
| 9648.00         | 22.32             | 38.07                 | 14.16           | 31.56              | 42.99          | 54.00               | -11.01          | Horizontal   |
| 12060.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

### Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “\*”, means this data is too weak instrument of signal is unable to test.

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11b | Test channel: | Middle |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 39.93             | 31.85                 | 8.66            | 32.12              | 48.32          | 74.00               | -25.68          | Vertical     |
| 7311.00         | 34.66             | 36.37                 | 11.71           | 31.91              | 50.83          | 74.00               | -23.17          | Vertical     |
| 9748.00         | 33.99             | 38.27                 | 14.25           | 31.56              | 54.95          | 74.00               | -19.05          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4874.00         | 40.32             | 31.85                 | 8.66            | 32.12              | 48.71          | 74.00               | -25.29          | Horizontal   |
| 7311.00         | 33.25             | 36.37                 | 11.71           | 31.91              | 49.42          | 74.00               | -24.58          | Horizontal   |
| 9748.00         | 33.86             | 38.27                 | 14.25           | 31.56              | 54.82          | 74.00               | -19.18          | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 30.74             | 31.85                 | 8.66            | 32.12              | 39.13          | 54.00               | -14.87          | Vertical     |
| 7311.00         | 22.96             | 36.37                 | 11.71           | 31.91              | 39.13          | 54.00               | -14.87          | Vertical     |
| 9748.00         | 23.24             | 38.27                 | 14.25           | 31.56              | 44.20          | 54.00               | -9.80           | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4874.00         | 30.40             | 31.85                 | 8.66            | 32.12              | 38.79          | 54.00               | -15.21          | Horizontal   |
| 7311.00         | 22.33             | 36.37                 | 11.71           | 31.91              | 38.50          | 54.00               | -15.50          | Horizontal   |
| 9748.00         | 23.57             | 38.27                 | 14.25           | 31.56              | 44.53          | 54.00               | -9.47           | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11b | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 45.88             | 31.90                 | 8.70            | 32.15              | 54.33          | 74.00               | -19.67          | Vertical     |
| 7386.00         | 35.60             | 36.49                 | 11.76           | 31.83              | 52.02          | 74.00               | -21.98          | Vertical     |
| 9848.00         | 37.48             | 38.62                 | 14.31           | 31.77              | 58.64          | 74.00               | -15.36          | Vertical     |
| 12310.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4924.00         | 45.03             | 31.90                 | 8.70            | 32.15              | 53.48          | 74.00               | -20.52          | Horizontal   |
| 7386.00         | 34.42             | 36.49                 | 11.76           | 31.83              | 50.84          | 74.00               | -23.16          | Horizontal   |
| 9848.00         | 33.62             | 38.62                 | 14.31           | 31.77              | 54.78          | 74.00               | -19.22          | Horizontal   |
| 12310.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 36.71             | 31.90                 | 8.70            | 32.15              | 45.16          | 54.00               | -8.84           | Vertical     |
| 7386.00         | 25.49             | 36.49                 | 11.76           | 31.83              | 41.91          | 54.00               | -12.09          | Vertical     |
| 9848.00         | 25.96             | 38.62                 | 14.31           | 31.77              | 47.12          | 54.00               | -6.88           | Vertical     |
| 12310.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4924.00         | 35.34             | 31.90                 | 8.70            | 32.15              | 43.79          | 54.00               | -10.21          | Horizontal   |
| 7386.00         | 23.79             | 36.49                 | 11.76           | 31.83              | 40.21          | 54.00               | -13.79          | Horizontal   |
| 9848.00         | 22.86             | 38.62                 | 14.31           | 31.77              | 44.02          | 54.00               | -9.98           | Horizontal   |
| 12310.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11g | Test channel: | lowest |
|------------|---------|---------------|--------|

## Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 39.82             | 31.79                 | 8.62            | 32.10              | 48.13          | 74.00               | -25.87          | Vertical     |
| 7236.00         | 33.92             | 36.19                 | 11.68           | 31.97              | 49.82          | 74.00               | -24.18          | Vertical     |
| 9648.00         | 32.50             | 38.07                 | 14.16           | 31.56              | 53.17          | 74.00               | -20.83          | Vertical     |
| 12060.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4824.00         | 38.56             | 31.79                 | 8.62            | 32.10              | 46.87          | 74.00               | -27.13          | Horizontal   |
| 7236.00         | 33.70             | 36.19                 | 11.68           | 31.97              | 49.60          | 74.00               | -24.40          | Horizontal   |
| 9648.00         | 32.09             | 38.07                 | 14.16           | 31.56              | 52.76          | 74.00               | -21.24          | Horizontal   |
| 12060.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

## Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 28.94             | 31.79                 | 8.62            | 32.10              | 37.25          | 54.00               | -16.75          | Vertical     |
| 7236.00         | 22.80             | 36.19                 | 11.68           | 31.97              | 38.70          | 54.00               | -15.30          | Vertical     |
| 9648.00         | 22.85             | 38.07                 | 14.16           | 31.56              | 43.52          | 54.00               | -10.48          | Vertical     |
| 12060.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4824.00         | 28.12             | 31.79                 | 8.62            | 32.10              | 36.43          | 54.00               | -17.57          | Horizontal   |
| 7236.00         | 22.30             | 36.19                 | 11.68           | 31.97              | 38.20          | 54.00               | -15.80          | Horizontal   |
| 9648.00         | 21.85             | 38.07                 | 14.16           | 31.56              | 42.52          | 54.00               | -11.48          | Horizontal   |
| 12060.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |         |               |        |
|------------|---------|---------------|--------|
| Test mode: | 802.11g | Test channel: | Middle |
|------------|---------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 38.96             | 31.85                 | 8.66            | 32.12              | 47.35          | 74.00               | -26.65          | Vertical     |
| 7311.00         | 34.04             | 36.37                 | 11.71           | 31.91              | 50.21          | 74.00               | -23.79          | Vertical     |
| 9748.00         | 33.56             | 38.27                 | 14.25           | 31.56              | 54.52          | 74.00               | -19.48          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4874.00         | 39.50             | 31.85                 | 8.66            | 32.12              | 47.89          | 74.00               | -26.11          | Horizontal   |
| 7311.00         | 32.71             | 36.37                 | 11.71           | 31.91              | 48.88          | 74.00               | -25.12          | Horizontal   |
| 9748.00         | 33.46             | 38.27                 | 14.25           | 31.56              | 54.42          | 74.00               | -19.58          | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 29.84             | 31.85                 | 8.66            | 32.12              | 38.23          | 54.00               | -15.77          | Vertical     |
| 7311.00         | 22.37             | 36.37                 | 11.71           | 31.91              | 38.54          | 54.00               | -15.46          | Vertical     |
| 9748.00         | 22.82             | 38.27                 | 14.25           | 31.56              | 43.78          | 54.00               | -10.22          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4874.00         | 29.63             | 31.85                 | 8.66            | 32.12              | 38.02          | 54.00               | -15.98          | Horizontal   |
| 7311.00         | 21.81             | 36.37                 | 11.71           | 31.91              | 37.98          | 54.00               | -16.02          | Horizontal   |
| 9748.00         | 23.18             | 38.27                 | 14.25           | 31.56              | 44.14          | 54.00               | -9.86           | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |         |               |         |
|------------|---------|---------------|---------|
| Test mode: | 802.11g | Test channel: | Highest |
|------------|---------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 44.20             | 31.90                 | 8.70            | 32.15                    | 52.65          | 74.00               | -21.35          | Vertical     |
| 7386.00         | 34.54             | 36.49                 | 11.76           | 31.83                    | 50.96          | 74.00               | -23.04          | Vertical     |
| 9848.00         | 36.72             | 38.62                 | 14.31           | 31.77                    | 57.88          | 74.00               | -16.12          | Vertical     |
| 12310.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4924.00         | 43.61             | 31.90                 | 8.70            | 32.15                    | 52.06          | 74.00               | -21.94          | Horizontal   |
| 7386.00         | 33.49             | 36.49                 | 11.76           | 31.83                    | 49.91          | 74.00               | -24.09          | Horizontal   |
| 9848.00         | 32.92             | 38.62                 | 14.31           | 31.77                    | 54.08          | 74.00               | -19.92          | Horizontal   |
| 12310.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 35.17             | 31.90                 | 8.70            | 32.15                    | 43.62          | 54.00               | -10.38          | Vertical     |
| 7386.00         | 24.47             | 36.49                 | 11.76           | 31.83                    | 40.89          | 54.00               | -13.11          | Vertical     |
| 9848.00         | 25.24             | 38.62                 | 14.31           | 31.77                    | 46.40          | 54.00               | -7.60           | Vertical     |
| 12310.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4924.00         | 34.01             | 31.90                 | 8.70            | 32.15                    | 42.46          | 54.00               | -11.54          | Horizontal   |
| 7386.00         | 22.89             | 36.49                 | 11.76           | 31.83                    | 39.31          | 54.00               | -14.69          | Horizontal   |
| 9848.00         | 22.19             | 38.62                 | 14.31           | 31.77                    | 43.35          | 54.00               | -10.65          | Horizontal   |
| 12310.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is too weak instrument of signal is unable to test.

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT20) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 40.44             | 31.79                 | 8.62            | 32.10              | 48.75          | 74.00               | -25.25          | Vertical     |
| 7236.00         | 34.31             | 36.19                 | 11.68           | 31.97              | 50.21          | 74.00               | -23.79          | Vertical     |
| 9648.00         | 32.78             | 38.07                 | 14.16           | 31.56              | 53.45          | 74.00               | -20.55          | Vertical     |
| 12060.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4824.00         | 39.08             | 31.79                 | 8.62            | 32.10              | 47.39          | 74.00               | -26.61          | Horizontal   |
| 7236.00         | 34.05             | 36.19                 | 11.68           | 31.97              | 49.95          | 74.00               | -24.05          | Horizontal   |
| 9648.00         | 32.35             | 38.07                 | 14.16           | 31.56              | 53.02          | 74.00               | -20.98          | Horizontal   |
| 12060.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4824.00         | 29.51             | 31.79                 | 8.62            | 32.10              | 37.82          | 54.00               | -16.18          | Vertical     |
| 7236.00         | 23.17             | 36.19                 | 11.68           | 31.97              | 39.07          | 54.00               | -14.93          | Vertical     |
| 9648.00         | 23.12             | 38.07                 | 14.16           | 31.56              | 43.79          | 54.00               | -10.21          | Vertical     |
| 12060.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4824.00         | 28.62             | 31.79                 | 8.62            | 32.10              | 36.93          | 54.00               | -17.07          | Horizontal   |
| 7236.00         | 22.63             | 36.19                 | 11.68           | 31.97              | 38.53          | 54.00               | -15.47          | Horizontal   |
| 9648.00         | 22.10             | 38.07                 | 14.16           | 31.56              | 42.77          | 54.00               | -11.23          | Horizontal   |
| 12060.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT20) | Test channel: | Middle |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 39.47             | 31.85                 | 8.66            | 32.12              | 47.86          | 74.00               | -26.14          | Vertical     |
| 7311.00         | 34.37             | 36.37                 | 11.71           | 31.91              | 50.54          | 74.00               | -23.46          | Vertical     |
| 9748.00         | 33.79             | 38.27                 | 14.25           | 31.56              | 54.75          | 74.00               | -19.25          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4874.00         | 39.93             | 31.85                 | 8.66            | 32.12              | 48.32          | 74.00               | -25.68          | Horizontal   |
| 7311.00         | 33.00             | 36.37                 | 11.71           | 31.91              | 49.17          | 74.00               | -24.83          | Horizontal   |
| 9748.00         | 33.67             | 38.27                 | 14.25           | 31.56              | 54.63          | 74.00               | -19.37          | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 30.31             | 31.85                 | 8.66            | 32.12              | 38.70          | 54.00               | -15.30          | Vertical     |
| 7311.00         | 22.68             | 36.37                 | 11.71           | 31.91              | 38.85          | 54.00               | -15.15          | Vertical     |
| 9748.00         | 23.04             | 38.27                 | 14.25           | 31.56              | 44.00          | 54.00               | -10.00          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4874.00         | 30.04             | 31.85                 | 8.66            | 32.12              | 38.43          | 54.00               | -15.57          | Horizontal   |
| 7311.00         | 22.08             | 36.37                 | 11.71           | 31.91              | 38.25          | 54.00               | -15.75          | Horizontal   |
| 9748.00         | 23.38             | 38.27                 | 14.25           | 31.56              | 44.34          | 54.00               | -9.66           | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT20) | Test channel: | Highest |
|------------|---------------|---------------|---------|

## Peak value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 45.09             | 31.90                 | 8.70            | 32.15              | 53.54          | 74.00               | -20.46          | 4924.00      |
| 7386.00         | 35.10             | 36.49                 | 11.76           | 31.83              | 51.52          | 74.00               | -22.48          | 7386.00      |
| 9848.00         | 37.12             | 38.62                 | 14.31           | 31.77              | 58.28          | 74.00               | -15.72          | 9848.00      |
| 12310.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4924.00         | 44.36             | 31.90                 | 8.70            | 32.15              | 52.81          | 74.00               | -21.19          | Horizontal   |
| 7386.00         | 33.98             | 36.49                 | 11.76           | 31.83              | 50.40          | 74.00               | -23.60          | Horizontal   |
| 9848.00         | 33.28             | 38.62                 | 14.31           | 31.77              | 54.44          | 74.00               | -19.56          | Horizontal   |
| 12310.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

## Average value:

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4924.00         | 35.98             | 31.90                 | 8.70            | 32.15              | 44.43          | 54.00               | -9.57           | Vertical     |
| 7386.00         | 25.01             | 36.49                 | 11.76           | 31.83              | 41.43          | 54.00               | -12.57          | Vertical     |
| 9848.00         | 25.62             | 38.62                 | 14.31           | 31.77              | 46.78          | 54.00               | -7.22           | Vertical     |
| 12310.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4924.00         | 34.71             | 31.90                 | 8.70            | 32.15              | 43.16          | 54.00               | -10.84          | Horizontal   |
| 7386.00         | 23.37             | 36.49                 | 11.76           | 31.83              | 39.79          | 54.00               | -14.21          | Horizontal   |
| 9848.00         | 22.54             | 38.62                 | 14.31           | 31.77              | 43.70          | 54.00               | -10.30          | Horizontal   |
| 12310.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

## Remark:

- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “\*”, means this data is the too weak instrument of signal is unable to test.

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT40) | Test channel: | Lowest |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4844.00         | 39.32             | 31.81                 | 8.63            | 32.11                    | 47.65          | 74.00               | -26.35          | Vertical     |
| 7266.00         | 33.60             | 36.28                 | 11.69           | 31.94                    | 49.63          | 74.00               | -24.37          | Vertical     |
| 9688.00         | 32.27             | 38.13                 | 14.21           | 31.52                    | 53.09          | 74.00               | -20.91          | Vertical     |
| 12060.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                          |                | 74.00               |                 | Vertical     |
| 4844.00         | 38.14             | 31.81                 | 8.63            | 32.11                    | 46.47          | 74.00               | -27.53          | Horizontal   |
| 7266.00         | 33.43             | 36.28                 | 11.69           | 31.94                    | 49.46          | 74.00               | -24.54          | Horizontal   |
| 9688.00         | 31.89             | 38.13                 | 14.21           | 31.52                    | 52.71          | 74.00               | -21.29          | Horizontal   |
| 12060.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                          |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamplifier Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------------|----------------|---------------------|-----------------|--------------|
| 4844.00         | 28.48             | 31.81                 | 8.63            | 32.11                    | 36.81          | 54.00               | -17.19          | Vertical     |
| 7266.00         | 22.49             | 36.28                 | 11.69           | 31.94                    | 38.52          | 54.00               | -15.48          | Vertical     |
| 9688.00         | 22.64             | 38.13                 | 14.21           | 31.52                    | 43.46          | 54.00               | -10.54          | Vertical     |
| 12060.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 14472.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 16884.00        | *                 |                       |                 |                          |                | 54.00               |                 | Vertical     |
| 4844.00         | 27.73             | 31.81                 | 8.63            | 32.11                    | 36.06          | 54.00               | -17.94          | Horizontal   |
| 7266.00         | 22.03             | 36.28                 | 11.69           | 31.94                    | 38.06          | 54.00               | -15.94          | Horizontal   |
| 9688.00         | 21.65             | 38.13                 | 14.21           | 31.52                    | 42.47          | 54.00               | -11.53          | Horizontal   |
| 12060.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 14472.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |
| 16884.00        | *                 |                       |                 |                          |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |               |               |        |
|------------|---------------|---------------|--------|
| Test mode: | 802.11n(HT40) | Test channel: | Middle |
|------------|---------------|---------------|--------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 38.54             | 31.85                 | 8.66            | 32.12              | 46.93          | 74.00               | -27.07          | Vertical     |
| 7311.00         | 33.78             | 36.37                 | 11.71           | 31.91              | 49.95          | 74.00               | -24.05          | Vertical     |
| 9748.00         | 33.37             | 38.27                 | 14.25           | 31.56              | 54.33          | 74.00               | -19.67          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4874.00         | 39.15             | 31.85                 | 8.66            | 32.12              | 47.54          | 74.00               | -26.46          | Horizontal   |
| 7311.00         | 32.48             | 36.37                 | 11.71           | 31.91              | 48.65          | 74.00               | -25.35          | Horizontal   |
| 9748.00         | 33.29             | 38.27                 | 14.25           | 31.56              | 54.25          | 74.00               | -19.75          | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4874.00         | 29.46             | 31.85                 | 8.66            | 32.12              | 37.85          | 54.00               | -16.15          | Vertical     |
| 7311.00         | 22.11             | 36.37                 | 11.71           | 31.91              | 38.28          | 54.00               | -15.72          | Vertical     |
| 9748.00         | 22.64             | 38.27                 | 14.25           | 31.56              | 43.60          | 54.00               | -10.40          | Vertical     |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4874.00         | 29.30             | 31.85                 | 8.66            | 32.12              | 37.69          | 54.00               | -16.31          | Horizontal   |
| 7311.00         | 21.59             | 36.37                 | 11.71           | 31.91              | 37.76          | 54.00               | -16.24          | Horizontal   |
| 9748.00         | 23.01             | 38.27                 | 14.25           | 31.56              | 43.97          | 54.00               | -10.03          | Horizontal   |
| 12185.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14622.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17059.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “\*”, means this data is the too weak instrument of signal is unable to test.

|            |               |               |         |
|------------|---------------|---------------|---------|
| Test mode: | 802.11n(HT40) | Test channel: | Highest |
|------------|---------------|---------------|---------|

**Peak value:**

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4904.00         | 43.49             | 31.88                 | 8.68            | 32.13              | 51.92          | 74.00               | -22.08          | Vertical     |
| 7356.00         | 34.09             | 36.45                 | 11.75           | 31.86              | 50.43          | 74.00               | -23.57          | Vertical     |
| 9808.00         | 36.40             | 38.43                 | 14.29           | 31.68              | 57.44          | 74.00               | -16.56          | Vertical     |
| 12310.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                    |                | 74.00               |                 | Vertical     |
| 4904.00         | 43.01             | 31.88                 | 8.68            | 32.13              | 51.44          | 74.00               | -22.56          | Horizontal   |
| 7356.00         | 33.10             | 36.45                 | 11.75           | 31.86              | 49.44          | 74.00               | -24.56          | Horizontal   |
| 9808.00         | 32.62             | 38.43                 | 14.29           | 31.68              | 53.66          | 74.00               | -20.34          | Horizontal   |
| 12310.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                    |                | 74.00               |                 | Horizontal   |

**Average value:**



| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | polarization |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------------|
| 4904.00         | 34.51             | 31.88                 | 8.68            | 32.13              | 42.94          | 54.00               | -11.06          | Vertical     |
| 7356.00         | 24.03             | 36.45                 | 11.75           | 31.86              | 40.37          | 54.00               | -13.63          | Vertical     |
| 9808.00         | 24.93             | 38.43                 | 14.29           | 31.68              | 45.97          | 54.00               | -8.03           | Vertical     |
| 12310.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 14772.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 17234.00        | *                 |                       |                 |                    |                | 54.00               |                 | Vertical     |
| 4904.00         | 33.45             | 31.88                 | 8.68            | 32.13              | 41.88          | 54.00               | -12.12          | Horizontal   |
| 7356.00         | 22.51             | 36.45                 | 11.75           | 31.86              | 38.85          | 54.00               | -15.15          | Horizontal   |
| 9808.00         | 21.90             | 38.43                 | 14.29           | 31.68              | 42.94          | 54.00               | -11.06          | Horizontal   |
| 12310.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 14772.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |
| 17234.00        | *                 |                       |                 |                    |                | 54.00               |                 | Horizontal   |

**Remark:**


- 1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “\*”, means this data is the too weak instrument of signal is unable to test.


## 8 Test Setup Photo



Radiated Emission






## 9 EUT Constructional Details


























-----End-----