



Shenzhen CTL Testing Technology Co., Ltd.  
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

# DFS TEST REPORT

Report Reference No. .... : CTL2206207031-WF05

Compiled by:  
( position+printed name+signature)

Happy Guo  
(File administrators)

Tested by:  
( position+printed name+signature)

Gary Gao  
(Test Engineer)

Approved by:  
( position+printed name+signature)

Ivan Xie  
(Manager)



Product Name ..... : Laser Projector

Model/Type reference ..... : PJ90

List Model(s)..... : PJ91, PJ92, PJ93, PJ94, PJ95, PJ96, PJ97, PJ98, PJ99

Trade Mark..... : NexiGo

FCC ID..... : 2AWDN-PJ90

Applicant's name ..... : Nexight INC

Address of applicant ..... : 11075 SW 11th St, Beaverton, OR 97005, United States

Test Firm..... : Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm ..... : Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,  
Nanshan District, Shenzhen, China 518055

Test specification..... :

Standard ..... : 47 CFR FCC Part 15 Subpart E 15.407&  
RSS 247 Issue 2, February 2017

TRF Originator ..... : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF..... : Dated 2011-01

Date of receipt of test item ..... : June.22, 2022

Date of Test Date..... : June.22, 2022- July.20, 2022

Date of Issue ..... : July.21, 2022

Result..... : Pass

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

# TEST REPORT

|   |   |
|---|---|
| <b>Test Report No. :</b> CTL2206207031-WF05 | July.21, 2022<br>-----<br>Date of issue |
|---|---|

Equipment under Test : Laser Projector

Sample No : CTL220620703-1-S001

Model /Type : PJ90

Listed Models : PJ91, PJ92, PJ93, PJ94, PJ95, PJ96, PJ97, PJ98, PJ99

**Applicant** : **Nexight INC**

Address : 11075 SW 11th St, Beaverton, OR 97005, United States

**Manufacturer** : **Nexight INC**

Address : 11075 SW 11th St, Beaverton, OR 97005, United States

|                    |               |
|--------------------|---------------|
| <b>Test result</b> | <b>Pass *</b> |
|--------------------|---------------|

\* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

[illegible]

## Table of Contents

## Page

|  |           |
|--|-----------|
| <b>1. SUMMARY .....</b>                                | <b>5</b>  |
| 1.1. TEST STANDARDS .....                              | 5         |
| 1.2. TEST DESCRIPTION .....                            | 5         |
| 1.3. TEST FACILITY .....                               | 6         |
| 1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY .....    | 6         |
| 1.5. EUT CONFIGURATION .....                           | 7         |
| <b>2. GENERAL INFORMATION .....</b>                    | <b>8</b>  |
| 2.1. ENVIRONMENTAL CONDITIONS .....                    | 8         |
| 2.2. GENERAL DESCRIPTION OF EUT .....                  | 8         |
| 2.3. DESCRIPTION OF TEST MODES .....                   | 9         |
| 2.4. MEASUREMENT EQUIPMENTS USED DURING THE TEST ..... | 9         |
| 2.5. RELATED SUBMITTAL(S) / GRANT (S) .....            | 9         |
| 2.6. MODIFICATIONS .....                               | 9         |
| <b>3. TEST CONDITIONS AND RESULTS .....</b>            | <b>10</b> |
| 3.1. APPLICABILITY .....                               | 10        |
| 3.2. REQUIREMENTS .....                                | 10        |
| 3.3. DFS DETECTION THRESHOLD VALUES .....              | 11        |
| 3.4. PARAMETERS OF DFS TEST SIGNALS .....              | 11        |
| 3.5. TEST AND MEASUREMENT SYSTEM .....                 | 13        |
| 3.6. RADAR WAVEFORM VERIFICATION .....                 | 14        |
| 3.7. TEST RESULT .....                                 | 16        |
| <b>4. EUT TEST PHOTOS .....</b>                        | <b>18</b> |
| <b>5. PHOTOS OF THE EUT .....</b>                      | <b>19</b> |

## 1. SUMMARY

### 1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[KDB 905462 D02](#) UNII DFS Compliance Procedures New Rules v02

[KDB 905462 D03](#) UNII Clients Without Radar Detection New Rules v01r02

[KDB 905462 D04](#) Operational Modes for DFS Testing New Rules v01

[RSS-Gen Issue 5](#): General Requirements for Compliance of Radio Apparatus

### 1.2. Test Description

| Test Description                  | Section of FCC CFR 47                  | Limit  | Test Result |
|-----------------------------------|--|--|-------------|
| In-Service Monitoring             | 15.407(h)(2)(iv)<br>RSS-247 6.3.2(a)   | Monitor Co-channel Radar                               | N/A*        |
| Channel Availability Check        | 15.407 (h)(2)(ii)<br>RSS-247 6.3.2(b)  | 60s Detection  | N/A*        |
| Channel Move Time                 | 15.407 (h)(2)(iii)<br>RSS-247 6.3.2(c) | 10s  | Pass        |
| Channel Closing Transmission Time | 15.407 (h)(2)(iii)<br>RSS-247 6.3.2(d) | 200ms + Aggregate<br>60ms over remaining<br>10s period | Pass        |
| Non-Occupancy Period              | 15.407 (h)(2)(iv)<br>RSS-247 6.3.2(e)  | 30 minutes   | N/A*        |

\*Note: The EUT is a Client device without radar detection.

### 1.3. Test Facility

#### 1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

#### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

##### CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

##### A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

##### IC Registration No.: 9618B

##### CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

##### FCC-Registration No.: 399832

##### Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

### 1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

| Test                                    | Measurement Uncertainty | Notes |
|---|-------------------------|-------|
| Transmitter power conducted             | $\pm 0.57$ dB           | (1)   |
| Transmitter power Radiated              | $\pm 2.20$ dB           | (1)   |
| Conducted spurious emission 9KHz-40 GHz | $\pm 2.20$ dB           | (1)   |
| Occupied Bandwidth                      | $\pm 0.01$ ppm          | (1)   |
| Radiated Emission 9KHz~30MHz            | $\pm 3.66$ dB           | (1)   |
| Radiated Emission 30~1000MHz            | $\pm 4.10$ dB           | (1)   |
| Radiated Emission Above 1GHz            | $\pm 4.32$ dB           | (1)   |

|                                 |                     |     |
|---------------------------------|---------------------|-----|
| Conducted Disturbance0.15~30MHz | $\pm 3.20\text{dB}$ | (1) |
|---------------------------------|---------------------|-----|

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 1.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

|   |        |                |                  |
|---|--------|----------------|------------------|
| ○ | Router | Manufacturer : | Cambium Networks |
|   |        | Model No. :    | PJ90             |

## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

|                     |         |
|---------------------|---------|
| Normal Temperature: | 25°C    |
| Relative Humidity:  | 55 %    |
| Air Pressure:       | 101 kPa |

### 2.2. General Description of EUT

|                       |  |   |  |               |
|-----------------------|--|---|--|---------------|
| Product Name:         | Laser Projector  |   |  |               |
| Model/Type reference: | PJ90   |   |  |               |
| Power supply:         | Input: 100-240V~, 50/60Hz, 2.5A                              |   |  |               |
| Hardware Version:     | E.1  |   |  |               |
| Software Version:     | V1.0   |   |  |               |
| 5G WIFI :             |  |   |  |               |
| Supported type:       | 20MHz system   | 40MHz system  | 80MHz system                             | 160MHz system |
|                       | 802.11a<br>802.11n<br>802.11ac                               | 802.11n<br>802.11ac   | 802.11ac                                 | N/A           |
| Operation frequency:  | 5180-5240MHz<br>5260-5320MHz<br>5500-5700MHz<br>5745-5825MHz | 5190 - 5795MHz<br>5270 - 5310MHz<br>5510 - 5670MHz<br>5755MHz,5795MHz | 5210MHz<br>5290MHz<br>5530MHz<br>5775MHz | N/A           |
| Modulation:           | OFDM   | OFDM  | OFDM                                     | N/A           |
| Channel number:       | 24   | 11  | 4  | N/A           |
| Channel separation:   | 20MHz  | 40MHz   | 80MHz                                    | N/A           |
| Antenna type:         | PIFA Antenna   |   |  |               |
| Antenna gain:         | 3.48dBi  |   |  |               |

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

Note3: This report is for DFS only.



## 2.3. Description of Test Modes

The EUT operates over the 5260 MHz - 5320 MHz and 5500 MHz - 5700 MHz ranges.

The EUT is a slave device without radar detection.

The EUT one transmitter/receiver chain connected to a coaxial cable to perform conducted tests.

TPC is not required since the maximum EIRP is less than 500mW.

The EUT utilizes the 802.11a/n/ac architecture.

The nominal channel bandwidth is implemented: 20, 40, 80 MHz

## 2.4. Measurement Equipments Used during the Test

| Test Equipment          | Manufacturer | Model No. | Serial No.  | Calibration Date | Calibration Due Date |
|-------------------------|--------------|-----------|-------------|------------------|----------------------|
| Spectrum Analyzer       | Agilent      | N9020     | US46220290  | 2022/05/07       | 2023/05/06           |
| Vector Signal Generator | Agilent      | N5182A    | MY50142850  | 2022/05/07       | 2023/05/06           |
| DFS test box            | Tonscend     | JS0806-2  | JS00001     | 2022/05/07       | 2023/05/06           |
| Test Software           |              |           |             |                  |                      |
| Name of Software        |              |           | Version     |                  |                      |
| JS1120-3                |              |           | 2.6.77.0518 |                  |                      |

The calibration interval was one year

## 2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

## 2.6. Modifications

No modifications were implemented to meet testing criteria.

### 3. TEST CONDITIONS AND RESULTS

#### 3.1. APPLICABILITY

The following table from KDB905462 D02 v02 lists the applicable requirements for the DFS testing. The device evaluated in this report is considered a client device without radar detection capability.

Table 3-1. DFS Applicability

| Requirement                     | Operation Mode |                                |                             |
|---------------------------------|----------------|--------------------------------|-----------------------------|
|                                 | Master         | Client Without Radar Detection | Client With Radar Detection |
| Non-Occupancy Period            | Yes            | Not required                   | Yes                         |
| DFS Detection Threshold         | Yes            | Not required                   | Yes                         |
| Channel Availability Check Time | Yes            | Not required                   | Not required                |
| Uniform Spreading               | Yes            | Not required                   | Not required                |
| U-NII Detection Bandwidth       | Yes            | Not required                   | Yes                         |

Table 3-2. DFS Applicability during Normal Operation

| Requirement                       | Operation Mode |                                |                             |
|-----------------------------------|----------------|--------------------------------|-----------------------------|
|                                   | Master         | Client Without Radar Detection | Client With Radar Detection |
| DFS Detection Threshold           | Yes            | Not required                   | Yes                         |
| Channel Closing Transmission Time | Yes            | Yes                            | Yes                         |
| Channel Move Time                 | Yes            | Yes                            | Yes                         |
| U-NII Detection Bandwidth         | Yes            | Not required                   | Yes                         |

#### 3.2. REQUIREMENTS

Per KDB905462 D02 v02 (04/08/2016) the following are the requirements for Client Devices:

- a) A Client Device will not transmit before having received appropriate control signals from a Master Device.
- b) A Client Device will stop all its transmissions whenever instructed by a Master Device to which it is associated and will meet the Channel Move Time and Channel Closing Transmission Time requirements.  
The Client Device will not resume any transmissions until it has again received control signals from a Master Device.
- c) If a Client Device is performing In-Service Monitoring and detects a Radar Waveform above the DFS Detection Threshold, it will inform the Master Device. This is equivalent to the Master Device detecting the Radar Waveform and d) through f) of section 5.1.1 apply.
- d) Irrespective of Client Device or Master Device detection the Channel Move Time and Channel Closing Transmission Time requirements remain the same.

Channel Move Time and Channel Closing Transmission Time requirements are listed following table.

Table 3-3: DFS Response requirements

| Parameter   | Value  |
|---|--|
| Non-occupancy period  | Minimum 30 minutes   |
| Channel Availability Check Time   | 60 seconds   |
| Channel Move Time   | 10 seconds <sup>Note 1</sup>   |
| Channel Closing Transmission Time   | 200 milliseconds + an Aggregate of 60 milliseconds over Remaining 10 second period <sup>Notes1 and 2</sup> |
| U-NII Detection Bandwidth   | Minimum 100 % of the U-NII99 % transmission Power bandwidth <sup>Note 3</sup>                              |
| <p>Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.</p> <p>Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of The Channel Move Time plus any additional intermittent control signals required to facilitate a Channell move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.</p> <p>Note3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed With no data traffic.</p> |  |

### 3.3. DFS DETECTION THRESHOLD VALUES

The DFS detection thresholds are defined for Master devices and Client Devices with In-service monitoring. These detection thresholds are listed in the following table.

Table 3-4: Detection Thresholds for Master Devices and Client Devices with Radar Detection

| Maximum Transmit Power   | Value<br>(See Notes 1 and 2) |
|--|------------------------------|
| $\geq 200$ milliwatt   | -64 dBm                      |
| EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz   | -62 dBm                      |
| EIRP < 200 milliwatt that do not meet the power spectral density requirement   | -64 dBm                      |
| <p>Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.</p> <p>Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.</p> <p>Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.</p> |                              |

### 3.4. PARAMETERS OF DFS TEST SIGNALS

As the EUT is a Client Device with no Radar Detection only one type radar pulse is required for the testing. Radar Pulse type 0 was used in the evaluation of the Client device for the purpose of measuring the Channel Move Time and the Channel Closing Transmission Time. Table 3-5 lists the parameters for the Short Pulse Radar Waveforms. A plot of the Radar pulse Type 0 used for testing is included in Section 3.6 of this report.

Table 3-5: Parameters for Short Pulse Radar Waveforms

| Radar Type | Pulse Width (μsec) | PRI (μsec)  | Number Of Pulses  | Minimum Percentage of Successful Detection | Minimum Number of Trials |
|------------|--------------------|---|---|--|--------------------------|
| 0          | 1                  | 1428  | 18  | See Note 1                                 | See Note 1               |
| 1          | 1                  | Test A: 15 unique PRI values Randomly selected From the list of 23 PRI values in Table 5a   | Roundup $\left\{ \frac{1}{360} \right\}$<br>$\left\{ \frac{19 \cdot 10^6}{PRI \text{ } \mu\text{sec}} \right\}$ | 60%  | 30                       |
|            |                    | Test B: 15 unique PRI values Randomly selected within the range of 518-3066 μ sec, with a minimum increment of 1 μ sec, excluding PRI values selected in Test A |   |  |                          |
| 2          | 1-5                | 150-230   | 23-29   | 60%  | 30                       |
| 3          | 6-10               | 200-500   | 16-18   | 60%  | 30                       |
| 4          | 11-20              | 200-500   | 12-16   | 60%  | 30                       |
|            |                    |   |   | 80%  | 120                      |

Note1: Short pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.

### 3.5. TEST AND MEASUREMENT SYSTEM

#### General Test Setup Procedure:

1. The EUT was operating 802.11a, 802.11n\_HT20, 802.11ac\_VHT20 during the test.
2. Connect FCC approved Master AP to a network, via wired Ethernet, that allows connection to an FTP server.
3. Associate the EUT with the Master AP.
4. Launch the FTP application on the EUT.
5. Connect to the FTP server application to the FTP server hosting the file
6. Initiate an FTP download of the file from the host.
7. Monitor the channel loading during transfer.
8. Reduce the maximum allowed data rate for the Master AP, using the AP's GUI interface.
9. Repeat steps 5-7 until the channel loading is as close to 20 % as possible.
10. Record the data rate setting on the Master AP and the channel loading.
11. While the system is performing an FTP transfer using the settings from item 9 above, perform the Channel Closing Transmission Time and Channel Move Time Measurements as required by KDB905462 D02 v02 using a conducted test.

#### PROCEDURE

The KDB905462 D02 v02 describes a radiated test setup and a conducted test setup. A conducted test setup was used for this testing. Figure 3-1 shows the typical test setup. Each one channel selected between 5260 and 5320 MHz, 5500 and 5700 is chosen for the testing.




Figure 3-1. Conducted Test Setup for DFS

1. The radar pulse generator is setup to provide a pulse at the frequency that the Master and Client are operating. A Type 0 radar pulse with a 1  $\mu$ s pulse width and a 1428  $\mu$ s PRI is used for the testing.
2. The vector signal generator is adjusted to provide the radar burst (18 pulses) at a level of approximately -62 dBm at the antenna of the Master device.
3. The Client Device (EUT) is set up per the diagram in Figure 3-1 and communications between the Master device and the Client is established.
4. The MPEG file specified by the FCC (" $6\frac{1}{2}$  Magic Hours") is streamed from the "file computer" through the Master to the Slave Device and played in full motion video using Media Player Classic Ver.6.4.8.6 in order to properly load the network.

5. The spectrum analyzer is set to record about 15 sec window to any transmissions occurring up to and after 10 sec.
6. The system is again setup and the monitoring time is shortened in order to capture the Channel Closing Transmission Time. This time is measured to insure that the Client ceases transmission within 200 ms and the aggregate of emissions occurring after 200 ms up to 10 sec do not exceed 60 ms.

(Note: the channel may be different since the Master and Client have changed channels due to the detection of the initial radar pulse.)

7. After the initial radar burst the channel is monitored for 30 minutes to insure no transmissions or beacons occur. A second monitoring setup is used to verify that the Master and Client have both moved to different channels.

### 3.6. Radar Waveform Verification

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a coaxial cable. The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of - 62 dBm as measured on the spectrum analyzer.





Figure 3-2 Test Setup for Conducted Measurement Radar Verification

| Test Mode | Channel | Radar Type | Result  | Limit[dBm] | Verdict |
|-----------|---------|------------|---------|------------|---------|
| 11A20SISO | 5320    | Type0      | -62.595 | -62.00     | PASS    |




### 3.7. TEST RESULT





According to 905462 D02V02, Channel Move Time and Channel Closing Transmission Time Test using the widest BW mode for each WIFI operation modes.

**Channel Move Time and Channel Closing Transmission Time**

| Test Mode  | Channel | CCT[ms] | Limit[ms] | CMT[ms] | Limit[ms] | Verdict |
|------------|---------|---------|-----------|---------|-----------|---------|
| 11A        | 5320    | 35.1    | 200+60    | 624     | 10000     | PASS    |
|            | 5500    | 35.1    | 200+60    | 607.1   | 10000     | PASS    |
| 11N40SISO  | 5310    | 50.7    | 200+60    | 746.2   | 10000     | PASS    |
|            | 5510    | 26      | 200+60    | 640.9   | 10000     | PASS    |
| 11AC80SISO | 5290    | 41.6    | 200+60    | 624     | PASS      | PASS    |
|            | 5530    | 28.6    | 200+60    | 607.1   | PASS      | PASS    |







#### 4. EUT TEST PHOTOS



## 5. Photos of the EUT

Reference to the test report No. CTL2206207031-WF01

\*\*\*\*\* End of Report \*\*\*\*\*