



# H.B. Compliance Solutions

## Intentional Radiator Test Report

For the

**Aira, Inc.**

**PV**

Tested under

The FCC Rules contained in Title 47 of the CFR, Part 15.209

22 March 2024

**Prepared for:**

Aira, Inc.

2048 N 44th St.

Phoenix, AZ 85008

**Prepared By:**

H.B. Compliance Solutions

5005 S. Ash Avenue, Suite # A-10

Tempe, Arizona 85282

**Reviewed By:**

Hoosamuddin Bandukwala



Cert # ATL-0062-E

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedure indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurement made, the equipment tested is capable of operation in accordance with the requirements of Part 15 of the FCC Rules under normal use and maintenance. All results contained herein relate only to the sample tested.



## Report Status Sheet

Revision #	Report Date	Reason for Revision
∅	March 22, 2024	Initial Issue

## Table of Contents

EXECUTIVE SUMMARY .....	4
1. Testing Summary .....	4
EQUIPMENT CONFIGURATION .....	5
1. Overview .....	5
2. Test Facility .....	6
3. Description of Test Sample .....	7
4. Equipment Configuration .....	7
5. Support Equipment .....	7
6. Ports and Cabling Information .....	7
7. Method of Monitoring EUT Operation .....	8
8. Mode of Operation .....	8
9. Modifications .....	8
10. Disposition of EUT .....	8
Criteria for Intentional Radiators .....	9
1. Radiated Emissions .....	9
Emissions Tests Calculations .....	10
2. Conducted Emissions .....	13
2. Occupied Bandwidth .....	19
5. Radiated Spurious Emissions .....	21
Test Equipment .....	24
6. Measurement Uncertainty .....	25

## EXECUTIVE SUMMARY

### 1. Testing Summary

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15.209. All tests were conducted using measurement procedure from ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9kHz to 40GHz and ANSI C63.10-2013 Procedures for Compliance Testing of Unlicensed Wireless Devices as appropriate.

Test Name	Test Method/Standard	Result	Comments
Unintentional Radiated Emissions	15.109	Pass	
A/C Power Line Conducted Emissions	15.207(a)	Pass	
Occupied Bandwidth	15.215	Pass	
Radiated Fundamental Emissions	15.209(a)	Pass	
Radiated Spurious Emissions	15.209(a), 15.205, 15.35(C)	Pass	



## EQUIPMENT CONFIGURATION

### 1. Overview

H.B Compliance Solutions was contracted by Aira, Inc. to perform testing on the PV under the purchase order number 1368.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Aira, Inc. PV.

The tests were based on FCC Part 15 Rules. The tests described in this document were formal tests as described with the objective of the testing was to evaluate compliance of the Equipment Under Test (EUT) to the requirements of the aforementioned specifications. Aira, Inc. is to retain a copy of this document and it should be kept on file for at least five years after the manufacturing of the EUT has been permanently discontinued. The results obtained relate only to the item(s) tested.

<b>Product Name:</b>	PV
<b>Model(s) Tested:</b>	T0009-B
<b>FCC ID:</b>	2AWGG-CT-T09
<b>Supply Voltage Input:</b>	Primary Power: 120VAC
<b>Frequency Range:</b>	126 kHz to 225 kHz
<b>No. of Channels:</b>	1
<b>Type(s) of Modulation:</b>	Sinewave
<b>Range of Operation Power:</b>	0.2mW (Radiated)
<b>Emission Designator:</b>	N/A
<b>Channel Spacing(s)</b>	None
<b>Test Item:</b>	Pre-Production
<b>Type of Equipment:</b>	Fixed
<b>Antenna Requirement (§15.203):</b>	Type of Antenna: Integral Loop Gain of Antenna: 0dBi
<b>Environmental Test Conditions:</b>	Temperature: 15-35°C Humidity: 30-60% Barometric Pressure: 860-1060 mbar
<b>Modification to the EUT:</b>	None
<b>Evaluated By:</b>	Staff at H.B Compliance Solutions
<b>Test Date(s):</b>	02/23/2024 till 03/15/2024
<b>Firmware Number</b>	-
<b>PCBA Version</b>	-

## 2. Test Facility

All testing was performed at H.B. Compliance Solutions. This facility is located at 5005 S. Ash Avenue, Suite # A-10, Tempe AZ-85282. All equipment used in making physical determination is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a GTEM chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at H.B. Compliance Solutions.

Test facility H.B. Compliance Solutions is an ANAB accredited test site. The ANAB certificate number is L2458. The scope of accreditation can be found on ANAB website [www.anab.org](http://www.anab.org)



### 3. Description of Test Sample

The Aira Wireless, FreePower Wireless charging technology operates as 126kHz to 225kHz inductive coupling wireless charging radio. The wireless charger allows for upto to 3 devices to charge anywhere while resting on the top of the charging surface of the product.

### 4. Equipment Configuration

Ref. ID	Name / Description	Model Number	Serial Number
# 1	PV	T0009-B	0021
# 2	AC/DC Power Adaptor	DCT65W150433ZZ-A2	-

Table 1. Equipment Configuration

### 5. Support Equipment

All support equipment supplied is listed in the following Support Equipment List.

Ref ID	Name / Description	Manufacturer	Model #	Serial #
# 2	15W Loads (3 ea.)	Aira, Inc.	None	None

Table 2. Support Equipment

### 6. Ports and Cabling Information

Ref ID	Port name on the EUT	Cable Description	Qty.	Length (m)	Shielded? (Y/N)	Termination Box ID & Port ID
# 4	Power	DC	1	1	N	AC Outlet

Table 3. Ports and Cabling Information

## **7. Method of Monitoring EUT Operation**

A test receiver will be used to monitor the RF transmission from the EUT.

## **8. Mode of Operation**

The EUT will be configured to transmit at maximum power level. It was set to continuous transmit. Emissions were checked in both full Wireless Power Transfer (WPT) mode and the Idle pinging mode. For Radiated Spurious testing the WIFI and Bluetooth transmitters were controlled through a testing firmware to set the frequency and enable continuous transmission. This was enabled for testing purposes only.

## **9. Modifications**

### **9.1 Modifications to EUT**

Fair-Rite product number 0431164951 was added to the DC barrel jack end of the power supply cable for Radiated Emissions testing purposes.

### **9.2 Modifications to Test Standard**

No Modifications were made to the test standard.

## **10. Disposition of EUT**

The test sample including all support equipment submitted to H.B Compliance Solutions for testing will be returned to Aira, Inc. upon completion of testing & certification.

## Criteria for Intentional Radiators

### 1. Radiated Emissions

<b>Test Requirement(s):</b>	§15.109	<b>Test Engineer(s):</b>	Evan L.
<b>Test Results:</b>	Pass	<b>Test Date(s):</b>	02/22/2024

#### Test Procedures:

The final radiated emissions test was performed using the parameters described above as worst case. That final test was conducted at a facility that meets the ANSI C63.4 TEM waveguides requirements. The frequency range noted in the data sheets was scanned/tested at that facility. Emissions were maximized as specified, by varying table azimuth, and manipulating cables.

Using the mode of operation and configuration noted within this report, a final radiated emissions test was performed. The frequency range investigated (scanned), is also noted in this report. Radiated emissions measurements were made at the EUT azimuth such that the maximum radiated emissions level will be detected. This requires the use of a turntable.

Tests were made with the EUT rotated on X,Y,Z planes to obtain the maximum signal strength. Though specified in the report, the measurement distance shall be 3 meters.

#### Test Limits:

Frequency Range (MHz)	Distance (Meters)	Field Strength	
		uV/m	dBuV/m
0.009 – 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 – 1.705	30	2400/F(kHz)	87.6-20log(F)
1.705 – 30.0	30	30	29.54
30 – 88	3	100	40.0
88 – 216	3	150	43.5
216 – 960	3	200	46.0
960 – 1000	3	500	54.0

Note: Emissions limits are based on measurements employing CISPR QP detector except for bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector

**Table 4. Radiated Emissions Limit – FCC Limits from Section 15.209**

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
30 MHz to 1 GHz	120 kHz	120 kHz	N/A
1 GHz to 11 GHz	1MHz	N/A	1MHz

Measurements were made using the bandwidths and detectors specified. The video filter was at least as wide as the IF bandwidth of the measuring receiver.

**Table 5. Radiated Emissions – Measurement Bandwidth**

## Emissions Tests Calculations

In the case of indoor measurements, radiated emissions measurements are made by the manipulation of correction factors using TILE4 software. This is done automatically by the software during the final measurement process.

In both cases, the level of the Field Strength of the interfering signal is calculated by adding the Antenna Factor, Cable Factor and by subtracting the Amplifier Gain from the measured reading. The basic equation is as follows:

$$FS = RA + AF + (CF - AG)$$

Where: FS = Field Strength

RA = Receiver (indicated) Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

This laboratory uses an approach of combining the CF and AG using an end-to-end measurement of the entire cabling system, including the test cable, any in-line amplifiers, attenuators, or transient protection networks, all measured in-situ.

For a sample calculation, assume a receiver reading of 52.5 dBuV is obtained. With an antenna factor of 7.4 and a combined cable factor (CF + AG) of -27.9:


$$FS = 52.5 + 7.4 + (-27.9) = 32 \text{ dBuV/m}$$

$$FS = 32 \text{ dBuV/m}$$


If desired, this can be converted into its corresponding level in uV/m:

$$FS = 10^{((32 \text{ dBuV/m})/20)} = 39.8 \text{ uV/m}$$

**Test Setup:**



**Figure 1. Radiated Emissions Test Setup (30MHz – 1GHz)**



**Plot 1 – Radiated Emissions – 30MHz to 1GHz**

Frequency (MHz)	Measured Level (dBuV/m)	Measurement Detector	Limit (dBuV)	Margin (dB)
50.37	27.77	Peak	40	-12.23
171.23	40.91	Peak	43.52	-2.61
624.47	35.84	Peak	46.02	-10.18

**Table 6. Final Measurement Results for Radiated Emissions Above 30MHz**

**Note:** Fair-Rite product number 0431164951 was added to the DC barrel jack end of the power supply cable for Radiated Emissions testing purposes.

## 2. Conducted Emissions

<b>Test Requirement(s):</b>	§15.207	<b>Test Engineer(s):</b>	Evan L.
<b>Test Results:</b>	Pass	<b>Test Date(s):</b>	02/24/2024

**Test Procedures:** The EUT was placed on a non-metallic table, 80cm above the ground plane inside a shielded enclosure. The EUT was powered through a 50Ω/50μH LISN. The conducted emissions tests were performed using the mode of operation and configuration noted within this report. The frequency range investigated (scanned), is also noted in this report. Conducted power line measurements are made, unless otherwise specified, over the frequency range from 150 kHz to 30 MHz to determine the line-to-ground radio-noise voltage that is conducted from the EUT power-input terminals that are directly (or indirectly via separate transformer or power supplies) connected to a public power network. Equipment is tested with power cords that are the same as those cords normally used or that have electrical or shielding characteristics that are the same as those cords normally used. Typically, those measurements are made using a LISN (Line Impedance Stabilization Network). All 50 Ohm measuring ports of the LISN are terminated by 50 Ohms, either by the 50 Ohm EMI receiver or a 50 Ohm resistive load.

Refer to the Emissions Tests Calculations section in the Radiated Emissions section for sample calculations. For the purposes of the conducted emissions test, the Antenna Factor (AF) is replaced by the LISN correction factor.

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
0.150 - 30	9.0	9.0	9.0
Measurements were made using the bandwidths and detectors specified. No video filter was used.			

Table 7. Conducted Emissions – Measurement Bandwidth

Frequency Range (MHz)	15.107(b), Class A Limits (dBuV)		15.107(a), Class B Limits (dBuV)	
	Quasi-Peak	Average	Quasi Peak	Average
0.15 – 0.5	79	66	66 - 56	56 - 46
0.5 – 5.0	73	60	56	46
5.0 – 30	73	60	60	50

Note 1 – The lower limit shall apply at the transition frequencies.

Table 8. Conducted Emissions Limits – FCC Limits from Section 15.207

### Test Setup:






Figure 2. Conducted Emissions Test Setup



Plot 2 – Conducted Emission – Line Side

Frequency (Hz)	Detector	Measured Level (dBuV)	Limit (dBuV)	Margin (dB)
150k	Peak	58.44	--	--
	QPeak	43.66	66	-22.34
	Avg	18.49	56	-37.51
186.09k	Peak	53.761	--	--
	QPeak	43.991	64.209	-20.218
	Avg	22.041	54.209	-32.168
16.16M	Peak	41.125	--	--
	QPeak	33.345	60	-26.655
	Avg	23.805	50	-26.195
29.694M	Peak	34.302	--	--
	QPeak	19.952	60	-40.048
	Avg	14.062	50	-35.938

Table 9. Measurement Results Summary



**Plot 3 – Conducted Emissions – Neutral Side**

Frequency (Hz)	Detector	Measured Level (dBuV)	Limit (dBuV)	Margin (dB)
150k	Peak	57.53	--	--
	QPeak	42.15	66	-23.85
	Avg	18.51	56	-37.49
163.534k	Peak	54.719	--	--
	QPeak	41.369	65.283	-23.913
	Avg	17.989	55.283	-37.293
16.341M	Peak	38.68	--	--
	QPeak	32.03	60	-27.97
	Avg	22.29	50	-27.71
29.683M	Peak	35.102	--	--
	QPeak	31.872	60	-28.128
	Avg	28.802	50	-21.198

Table 10. Measurement Results Summary

## 2. Occupied Bandwidth

<b>Test Requirement(s):</b>	15.215(c)	<b>Test Engineer(s):</b>	Sean E.
<b>Test Results:</b>	Pass	<b>Test Date(s):</b>	03/13/2024 – 03/14/2024

**Test Procedure:** As required by 47 CFR 15.215(c): The bandwidth of the emission shall be determined at the points 20dB down from the modulated carrier.

Customer provided a test mode internal to the EUT to control the RF modulation. The EUT antenna was attached and the waveform was received by the test antenna which was connected to the spectrum analyzer. The measured highest peak power was set relative to zero dB reference. The RBW of the Spectrum Analyzer was set to 300Hz and VBW>RBW.

Frequency (kHz)	20dB Bandwidth (Hz)	99% Bandwidth (kHz)
126	105.37	91.96


Table 11. Occupied Bandwidth Summary, Test Results

**Test Setup:**




Figure 3. Occupied Bandwidth Test Setup

The following pages show measurements of Occupied Bandwidth plot:



Plot 4 – 20dB BW



Plot 5 – Frequency of Fundamental WPT and Analog Pings

## 5. Radiated Spurious Emissions

<b>Test Requirement(s):</b>	§15.209	<b>Test Engineer(s):</b>	Sean E.
<b>Test Results:</b>	Pass	<b>Test Date(s):</b>	03/15/2024

**Test Procedures:** As required by 47 CFR 15.209, Radiated emission measurements were made in accordance with the procedures of the ANSI C63.10 - 2013.


The EUT was placed on a non-reflective table inside 3 meter open area test site. The EUT was set on continuous transmit.

The measurement distance was set at 3 meters from the EUT. During the tests, EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The frequency range up to the 10<sup>th</sup> harmonic was investigated.


Frequency Range	Detector Setting	Resolution Bandwidth	Video Bandwidth	Span
9kHz-150kHz	As Specified in §15.209	200Hz	As Specified in §15.35(c)	As necessary
150kHz-30MHz	As Specified in §15.209	9kHz	As Specified in §15.35(c)	As necessary
30MHz – 1000 MHz	Quasi Peak	120kHz	As Specified in §15.35(c)	Zero
1000 MHz – 5GHz	Peak	1MHz	1MHz	As necessary
1000 MHz – 5GHz	Average	1MHz	As Specified in §15.35(c)	As necessary

**Table 12 - Analyzer Settings**

**Test Setup:**



**Figure 4. Radiated Emissions Test Setup (9kHz - 30MHz)**



**Figure 5. Radiated Emission Above 1GHz Test Setup**

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical

Frequency (MHz)	Peak Measurement @ 3m (dBuV/m)	Final Measurement @ 3m (dBuV/m)	FCC Limit (dBuV/m)	FCC Peak Limit (dBuV/m)	Final Measurement Margin (dB)	Peak Margin (dB)	Detector for Final Measurement	Comment
0.126	99.97	78.29	105.59	125.59	-27.31	-25.63	Average	Fundamental

**Table 13 – Fundamental Field Strength**

Frequency (MHz)	Final Measurement @ 3m (dBuV/m)	FCC Limit (dBuV/m)	Final Measurement Margin (dB)	Detector for Final Measurement	Comment
0.128	54.16	105.46	-51.30	Average	WPT Mode
0.3795	27.95	96.02	-68.07	Average	WPT Mode
0.883	62.61	68.69	-6.08	Quasi Peak	WPT Mode
4.998	48.05	69.54	-21.49	Quasi Peak	WPT Mode
0.048	79.69	113.92	-34.23	Average	Idle Mode
0.084	66.65	109.10	-42.45	Average	Idle Mode
0.091	65.24	108.41	-43.17	Quasi Peak	Idle Mode
0.127	52.80	105.53	-52.73	Average	Idle Mode
0.219	63.15	100.77	-37.62	Average	Idle Mode
0.227	66.5	100.48	-33.98	Average	Idle Mode
4844	39.82	54.00	-14.18	Quasi Peak	WIFI
4880	34.17	54.00	-19.83	Quasi Peak	Bluetooth

**Table 14 - Radiated Spurious Emission Data**

Remark:

To get a maximum emission level from the EUT, the EUT was moved throughout the X-axis, Y-axis and Z-axis. Worst case is X-axis.

**Note: No spurious emissions above the second harmonic were found from the WIFI/Bluetooth Module.**

## Test Equipment

Equipment	Manufacturer	Model	Serial #	Last Cal Date	Cal Due Date
Two Line V-Network - LISN	Teseq	NNB 51	43198	Jan-12-23	Jan-12-25
Spectrum Analyzer (PSA)	Agilent	E4443A	US41420164	Jun-01-23	Jun-01-24
Spectrum Analyzer	Hewlett Packard	8595EM	3801A00177	May-02-23	May-02-24
EMI Test Receiver	Rohde & Schwarz	ESMI26	840607/005	Nov-15-23	Nov-15-24
EMI Receiver	Hewlett Packard	8566B	2747A05264	Feb-01-24	Feb-01-25
Amplifier	Amplifier Research	LN10000A	27023	Verified	
Loop Antenna	A.H. Systems	SAS-565H	150	Sep-15-22	Sep-15-24
Antenna	EMCO	GTEM 5417	1063	Verified	
Horn Antenna	Com Power	AHA-118	711150	Jan-09-23	Jan-09-25

**Table 15 – Test Equipment List**

**\*Statement of Traceability:** Test equipment is maintained and calibrated on a regular basis. All calibrations have been performed by a 17025 accredited test facility, traceable to National Institute of Standards and Technology (NIST)

## 6. Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. These measurements figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2. Instrumentation measurement uncertainty has **not** been taken into account to determine compliance.

The following measurement uncertainty values have been calculated as show in the table below:

Measured Parameter	Measurement Unit	Frequency Range	Expanded Uncertainty
Conducted Emissions (AC Power)	dBuV or dBuA	150kHz – 30MHz	± 4.3dB
Radiated Emission below 30MHz	dBuV/m	9kHz-30MHz	± 2.96dB
Radiated Emissions below 1GHz	dBuV/m	30 – 1000MHz	± 5.6dB
Radiated Emissions above 1GHz	dBuV/m	1 – 26.5GHz	± 4.1dB

The reported expanded uncertainty has been estimated at a 95% confidence level (k=2)

**END OF TEST REPORT**