

RF Exposure Evaluation

LIMIT

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	-	-	f/300	6
1500–100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	-	-	f/1500	30
1500–100,000	-	-	1.0	30

Note: f = frequency in MHz

EVALUATION METHOD

Transmission formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW, **G** = gain of antenna in linear scale;

Pi = 3.1416, **R** = distance between observation point and center of the radiator in cm

TEST RESULT

☒ Passed ☐ Not Applicable

Type	Maximum Tune-up (dBm) Conducted Average Power
802.11b	13.00~15.00
802.11g	12.00~14.00
802.11n(H20)	10.00~12.00
802.11n(H40)	10.00~12.00
Band I	12.00~14.00
Band II	12.00~14.00
Band IV	12.00~14.00

Type	Conducted Average Power (dBm)	Maximum Tune-up (dBm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	14.81	15.00	0.01284	1.0000	Pass
802.11g	12.10	14.00	0.00569	1.0000	Pass
802.11n(H20)	11.41	12.00	0.00644	1.0000	Pass
802.11n(H40)	10.82	12.00	0.00644	1.0000	Pass
Band I	13.82	14.00	0.01020	1.0000	Pass
Band II	13.69	14.00	0.01020	1.0000	Pass
Band IV	13.85	14.00	0.01020	1.0000	Pass

Note:

- 1) The maximum antenna gain is 3.1dBi
- 2) The exposure evaluation safety distance is 20cm.