

Page: 1 of 21

TEST REPORT

Application No.: HKEM2212001095AT
Applicant: Wittra Networks AB

Address of Applicant: Vastra Jarnvagsgatan 3,11164 Stockholm, Sweden

Equipment Under Test (EUT):

EUT Name: Wittra Unified Gateway

Model No.: UNIFIED-GATEWAY-1.0-US

FCC ID: 2AYHX00515 **IC:** 26847-00515

HVIN: UNIFIED GATEWAY-1.0-US

Standard(s): 47 CFR Part 1.1307; 47 CFR Part 2.1091

KDB447498 D04 Interim General RF Exposure Guidance v01

RSS102 Issue 5 March 2015

Date of Receipt: 2022-12-15

Date of Test: 2022-12-20 to 2023-02-16

Date of Issue: 2023-02-17

Test Result: The submitted sample was found to comply with the test requirement



Law Man Kit EMC Manager

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request and accessible at http://www.sgs.com/en/Terms-and-conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-conditions.aspx. Attention is drawn to the limitation of liability, indemnification industrial industrial information contained hereon reflects the Company's findings at the time of its intervention only adwithin the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. The document cannot be reproduced except in full without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: HKEM221200109503 Page: 2 of 21

Revision Record												
Revision No.	Date	Report superseded	Remark									

Authorized for issue by:		
	Panner	
	Panny Leung /Project Engineer	Date: 2023-02-17
	Law	
	Law Man Kit	-
	/Reviewer	Date: 2023-02-17



Page: 3 of 21

2 Test Summary

Radio Spectrum Technical Requirement												
Item	Standard	Method	Requirement	Result								
RF Exposure	47 CFR Part 1.1307, 47 CFR Part 2.1091, KDB 447498 D01	KDB447498D01	KDB447498D01	PASS								
RF Exposure	RSS102 Issue 5	RSS-102 Section 2.5.1	RSS102 Issue 5	PASS								

Declaration of EUT Family Grouping:

N/A

Abbreviation:

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application.



Report No.: HKEM221200109503 Page: 4 of 21

Contents

			Page
1	COV	/ER PAGE	1
2	TES	T SUMMARY	3
3	CON	NTENTS	4
4	GEN	NERAL INFORMATION	5
	4.1	DETAILS OF E.U.T.	
	4.2	DESCRIPTION OF SUPPORT UNITS	
	4.3	TEST LOCATION	
	4.4	TEST FACILITY	15
	4.5 4.6	DEVIATION FROM STANDARDS	
5	RAD	DIO SPECTRUM TECHNICAL REQUIREMENT	
	5.1	RF EXPOSURE	16
	5.1.1	1 Test Requirement:	16
	5.1.1	1 IC Radiofrequncy radiation	17
		2 EUT RF Exposure Evaluation	
6	PHO	DTOGRAPHS	21
-			



Page: 5 of 21

4 General Information

4.1 Details of E.U.T.

 Details of L.O.T.								
Power supply:	Adaptor Model: KSA-36W-120300D5							
	Input: AC 100-240V, 50/60Hz, 1.0A							
	Output: DC 12.0V, 3.0A, 36.0W							
	and							
	DC 3V ('CR2032' size battery x 1)							
Test voltage:	AC 120V							
	DC 3V							
Cable:	Power Cable: 143cm unshielded 2 wires DC cable							
Antenna Gain:	SubGhz: 2dBi							
	Mioty: 2dBi							
	BLE: 3.5dBi							
Antenna Type:	SubGhz: Dipole Antenna							
	Mioty: Integral Antenna							
	BLE: PIFA							
Modulation Type:	SubGhz: GFSK							
	Mioty: MSK/GMSK							
	BLE: GFSK							
Number of Channels:	SubGhz: 51							
	Mioty: 50							
	BLE: 40							
Operation Frequency:	SubGhz: 902.60MHz to 927.40MHz							
	Mioty: 915.25MHz to 916.75MHz							
	BLE: 2402MHz to 2480MHz							
Spectrum Spread	SubGhz: Frequency Hopping Spread Spectrum (FHSS)							
Technology:	Mioty: Frequency Hopping Spread Spectrum (FHSS)							
	BLE: Digital modulation							
Series number:	A1							
Hardware Version:	UNIFIED GATEWAY-1.0-US							
Software Version:	Radio FW v1.							
	Remark: Power level setting was not adjustable and fixed default through SW Version.							



Report No.: HKEM221200109503 Page: 6 of 21

Frequency List

SubGhz:

Ch Number	Frequency	Min frequency	Max frequency	Used by 802.15.4
0	902.2	902.1	902.3	
1	902.4	902.3	902.5	
2	902.6	902.5	902.7	X
3	902.8	902.7	902.9	X
4				X
	903	902.9	903.1	
5	903.2	903.1	903.3	
6	903.4	903.3	903.5	X
7	903.6	903.5	903.7	X
8	903.8	903.7	903.9	
9	904	903.9	904.1	
10	904.2	904.1	904.3	
11	904.4	904.3	904.5	
12	904.6	904.5	904.7	
13	904.8	904.7	904.9	
14 15	905 905.2	904.9	905.1	
16	905.4	905.1 905.3	905.3 905.5	
17	905.6	905.5	905.7	
18	905.8	905.7	905.9	
19	906	905.9	906.1	
20	906.2	906.1	906.3	X
21	906.4	906.3	906.5	X
22	906.6	906.5	906.7	X
23	906.8	906.7	906.9	V
24	907	906.9	907.1	X
25 26	907.2 907.4	907.1 907.3	907.3 907.5	
27	907.6	907.5	907.7	Χ
28	907.8	907.7	907.9	X
29	908	907.9	908.1	
30	908.2	908.1	908.3	Χ
31	908.4	908.3	908.5	
32	908.6	908.5	908.7	
33	908.8	908.7	908.9	X
34	909	908.9	909.1	X
35 36	909.2 909.4	909.1 909.3	909.3 909.5	Χ
37	909.6	909.5	909.7	X
38	909.8	909.7	909.9	~
39	910	909.9	910.1	Χ
40	910.2	910.1	910.3	
41	910.4	910.3	910.5	Χ
42	910.6	910.5	910.7	X
43	910.8	910.7	910.9	X
44	911	910.9	911.1	



Report No.: HKEM221200109503 Page: 7 of 21

45	911.2	911.1	911.3	Χ
46	911.4	911.3	911.5	Χ
				^
47	911.6	911.5	911.7	
48	911.8	911.7	911.9	Χ
49	912	911.9	912.1	Χ
50	912.2	912.1	912.3	,,
				.,
51	912.4	912.3	912.5	Χ
52	912.6	912.5	912.7	Χ
53	912.8	912.7	912.9	
54	913	912.9	913.1	Χ
55	913.2	913.1	913.3	Χ
56	913.4	913.3	913.5	
57	913.6	913.5	913.7	Χ
58	913.8	913.7	913.9	
59	914	913.9	914.1	
60	914.2	914.1	914.3	
61	914.4	914.3	914.5	
62	914.6	914.5	914.7	
63	914.8	914.7	914.9	
64	915	914.9	915.1	
65	915.2	915.1	915.3	
66	915.4	915.3	915.5	
67	915.6	915.5	915.7	
	915.8	915.7	915.9	
68				
69	916	915.9	916.1	
70	916.2	916.1	916.3	
71	916.4	916.3	916.5	
72	916.6	916.5	916.7	
73	916.8	916.7	916.9	
74	917	916.9	917.1	
75	917.2	917.1	917.3	
76	917.4	917.3	917.5	
77	917.6	917.5	917.7	
78	917.8	917.7	917.9	
				V
79	918	917.9	918.1	X
80	918.2	918.1	918.3	
81	918.4	918.3	918.5	Χ
82	918.6	918.5	918.7	Χ
83	918.8	918.7	918.9	
84			919.1	V
	919	918.9		Х
85	919.2	919.1	919.3	Χ
86	919.4	919.3	919.5	
87	919.6	919.5	919.7	Χ
88	919.8	919.7	919.9	
89	920	919.9	920.1	
90	920.2	920.1	920.3	Χ
91	920.4	920.3	920.5	Χ
92	920.6	920.5	920.7	
93	920.8	920.7	920.9	Χ
94	921			X
		920.9	921.1	^
95	921.2	921.1	921.3	
96	921.4	921.3	921.5	Χ
97	921.6	921.5	921.7	Χ
98	921.8	921.7	921.9	



Page: 8 of 21

922	921.9	922.1	Χ
922.2	922.1	922.3	Χ
922.4	922.3	922.5	
922.6	922.5	922.7	Χ
922.8	922.7	922.9	
923	922.9	923.1	Χ
923.2	923.1	923.3	Χ
923.4	923.3	923.5	
923.6	923.5	923.7	Χ
923.8	923.7	923.9	Χ
924	923.9	924.1	
924.2	924.1	924.3	
924.4	924.3	924.5	
924.6	924.5	924.7	
924.8	924.7	924.9	
925	924.9	925.1	
925.2	925.1	925.3	
925.4	925.3	925.5	
925.6	925.5	925.7	
925.8	925.7	925.9	
926	925.9	926.1	
926.2	926.1	926.3	Χ
926.4	926.3	926.5	
926.6	926.5	926.7	
926.8	926.7	926.9	Χ
927	926.9	927.1	
927.2	927.1	927.3	Χ
927.4	927.3	927.5	Χ
927.6	927.5	927.7	
927.8	927.7	927.9	
	922.2 922.4 922.6 922.8 923 923.2 923.4 923.6 923.8 924.2 924.4 924.6 924.8 925 925.2 925.4 925.6 925.8 926 926.2 926.4 926.6 926.8 927 927.2 927.4 927.6	922.2 922.1 922.4 922.3 922.6 922.5 922.8 922.7 923 922.9 923.2 923.1 923.4 923.3 923.6 923.5 923.8 923.7 924 923.9 924.2 924.1 924.4 924.3 924.5 924.5 924.8 924.7 925 924.9 925.2 925.1 925.4 925.3 925.5 925.5 925.8 925.7 926 925.9 926.2 926.1 926.4 926.3 926.5 926.5 926.8 926.7 927 926.9 927.2 927.1 927.4 927.3 927.6 927.5	922.2 922.1 922.5 922.6 922.5 922.7 922.8 922.7 922.9 923 922.9 923.1 923.2 923.1 923.3 923.4 923.3 923.5 923.6 923.5 923.7 923.8 923.7 923.9 924 923.9 924.1 924.2 924.1 924.3 924.4 924.3 924.5 924.6 924.5 924.7 924.8 924.7 924.9 925.2 925.1 925.3 925.2 925.1 925.3 925.2 925.1 925.3 925.3 925.5 925.7 925.8 925.7 925.9 925.8 925.7 925.9 926.1 926.3 926.1 926.2 926.1 926.3 926.3 926.5 926.5 926.4 926.3 926.5 926.5 926.7 926.9 927 926.9 927.1

Remark: 1. Test frequencies are the lowest channel: 902.06 MHz, the middle channel: 913.60 MHz and highest channel: 927.40 MHz



Report No.: HKEM221200109503 Page: 9 of 21

Mioty:

Channel A carrier frequency:

c	C_{RF}	f_{TX} in Hz	c	C_{RF}	f_{TX} in Hz	c	C_{RF}	f_{TX} in Hz
24	5	916754675.3	15	5	916497595.2	6	5	916240515.1
24	4	916752294.9	15	4	916495214.8	6	4	916238134.8
24	3	916749914.6	15	3	916492834.5	6	3	916235754.4
24	2	916747534.2	15	2	916490454.1	6	2	916233374.0
24	1	916745153.8	15	1	916488073.7	6	1	916230993.7
24	0	916742773.4	15	0	916485693.4	6	0	916228613.3
24	-1	916740393.1	15	-1	916483313.0	6	-1	916226232.9
24	-2	916738012.7	15	-2	916480932.6	6	-2	916223852.5
24	-3	916735632.3	15	-3	916478552.2	6	-3	916221472.2
24	-4	916733252.0	15	-4	916476171.9	6	-4	916219091.8
24	-5	916730871.6	15	-5	916473791.5	6	-5	916216711.4
		916728491.2			916471411.1			916214331.1
23	5	916726110.8	14	5	916469030.8	5	5	916211950.7
23	4	916723730.5	14	4	916466650.4	5	4	916209570.3
23	3	916721350.1	14	3	916464270.0	5	3	916207189.9
23	2	916718969.7	14	2	916461889.6	5	2	916204809.6
23	1	916716589.4	14	1	916459509.3	5	1	916202429.2
23	0	916714209.0	14	0	916457128.9	5	0	916200048.8
23	-1	916711828.6	14	-1	916454748.5	5	-1	916197668.5
23	-2	916709448.2	14	-2	916452368.2	5	-2	916195288.1
23	-3	916707067.9	14	-3	916449987.8	5	-3	916192907.7
23	-4	916704687.5	14	-4	916447607.4	5	-4	916190527.3
23	-5	916702307.1	14	-5	916445227.1	5	-5	916188147.0
		916699926.8			916442846.7			916185766.6
22	5	916697546.4	13	5	916440466.3	4	5	916183386.2
22	4	916695166.0	13	4	916438085.9	4	4	916181005.9
22	3	916692785.6	13	3	916435705.6	4	3	916178625.5
22	2	916690405.3	13	2	916433325.2	4	2	916176245.1
22	1	916688024.9	13	1	916430944.8	4	1	916173864.7
22	0	916685644.5	13	0	916428564.5	4	0	916171484.4
22	-1	916683264.2	13	-1	916426184.1	4	-1	916169104.0



Report No.: HKEM221200109503 Page: 10 of 21

22	-2	916680883.8		13	-2	916423803.7		4	-2	916166723.6
22	-3	916678503.4		13	-3	916421423.3		4	-3	916164343.3
22	-4	916676123.0		13	-4	916419043.0		4	-4	916161962.9
22	-5	916673742.7		13	-5	916416662.6		4	-5	916159582.5
		916671362.3				916414282.2				916157202.1
21	5	916668981.9		12	5	916411901.9		3	5	916154821.8
21	4	916666601.6		12	4	916409521.5		3	4	916152441.4
21	3	916664221.2		12	3	916407141.1		3	3	916150061.0
21	2	916661840.8		12	2	916404760.7		3	2	916147680.7
21	1	916659460.4		12	1	916402380.4		3	1	916145300.3
21	0	916657080.1		12	0	916400000.0		3	0	916142919.9
21	-1	916654699.7		12	-1	916397619.6		3	-1	916140539.6
21	-2	916652319.3		12	-2	916395239.3		3	-2	916138159.2
21	-3	916649939.0		12	-3	916392858.9		3	-3	916135778.8
21	-4	916647558.6		12	-4	916390478.5		3	-4	916133398.4
21	-5	916645178.2		12	-5	916388098.1		3	-5	916131018.1
		916642797.9				916385717.8				916128637.7
20	5	916640417.5		11	5	916383337.4		2	5	916126257.3
20	4	916638037.1		11	4	916380957.0		2	4	916123877.0
20	3	916635656.7		11	3	916378576.7		2	3	916121496.6
20	2	916633276.4		11	2	916376196.3		2	2	916119116.2
20	1	916630896.0		11	1	916373815.9		2	1	916116735.8
20	0	916628515.6		11	0	916371435.5		2	0	916114355.5
20	-1	916626135.3		11	-1	916369055.2		2	-1	916111975.1
20	-2	916623754.9		11	-2	916366674.8		2	-2	916109594.7
20	-3	916621374.5		11	-3	916364294.4		2	-3	916107214.4
20	-4	916618994.1		11	-4	916361914.1		2	-4	916104834.0
20	-5	916616613.8		11	-5	916359533.7		2	-5	916102453.6
		916614233.4				916357153.3				916100073.2
19	5	916611853.0		10	5	916354772.9	1	1	5	916097692.9
19	4	916609472.7		10	4	916352392.6		1	4	916095312.5
19	3	916607092.3		10	3	916350012.2		1	3	916092932.1
19	2	916604711.9	1	10	2	916347631.8	1	1	2	916090551.8
19	1	916602331.5	1	10	1	916345251.5	1	1	1	916088171.4
19	0	916599951.2	1	10	0	916342871.1	1	1	0	916085791.0
19	-1	916597570.8	1	10	-1	916340490.7	1	1	-1	916083410.6
19	-2	916595190.4	1	10	-2	916338110.4	1	1	-2	916081030.3
19	-3	916592810.1	1	10	-3	916335730.0	1	1	-3	916078649.9
19	-4	916590429.7	1	10	-4	916333349.6	1	1	-4	916076269.5
19	-5	916588049.3	1	10	-5	916330969.2	1	1	-5	916073889.2
	Ť	916585668.9				916328588.9	1	Ī		916071508.8
18	5	916583288.6	1	9	5	916326208.5	1	0	5	916069128.4
18	4	916580908.2		9	4	916323828.1	1	0	4	916066748.0
18	3	916578527.8	1	9	3	916321447.8	1	0	3	916064367.7
								-		



Report No.: HKEM221200109503 Page: 11 of 21

18	2	916576147.5	9	2	916319067.4	0	2	916061987.3
18	1	916573767.1	9	1	916316687.0	0	1	916059606.9
18	0	916571386.7	9	0	916314306.6	0	0	916057226.6
18	-1	916569006.3	9	-1	916311926.3	0	-1	916054846.2
18	-2	916566626.0	9	-2	916309545.9	0	-2	916052465.8
18	-3	916564245.6	9	-3	916307165.5	0	-3	916050085.4
18	-4	916561865.2	9	-4	916304785.2	0	-4	916047705.1
18	-5	916559484.9	9	-5	916302404.8	0	-5	916045324.7
		916557104.5			916300024.4			
17	5	916554724.1	8	5	916297644.0			
17	4	916552343.8	8	4	916295263.7			
17	3	916549963.4	8	3	916292883.3			
17	2	916547583.0	8	2	916290502.9			
17	1	916545202.6	8	1	916288122.6			
17	0	916542822.3	8	0	916285742.2			
17	-1	916540441.9	8	-1	916283361.8			
17	-2	916538061.5	8	-2	916280981.4			
17	-3	916535681.2	8	-3	916278601.1			
17	-4	916533300.8	8	-4	916276220.7			
17	-5	916530920.4	8	-5	916273840.3			
		916528540.0			916271460.0			
16	5	916526159.7	7	5	916269079.6			
16	4	916523779.3	7	4	916266699.2			
16	3	916521398.9	7	3	916264318.8			
16	2	916519018.6	7	2	916261938.5			
16	1	916516638.2	7	1	916259558.1			
16	0	916514257.8	7	0	916257177.7			
16	-1	916511877.4	7	-1	916254797.4			
16	-2	916509497.1	7	-2	916252417.0			
16	-3	916507116.7	7	-3	916250036.6			
16	-4	916504736.3	7	-4	916247656.3			
16	-5	916502356.0	7	-5	916245275.9			
		916499975.6			916242895.5			

Channel B carrier frequency:

C_{RF}	f_{TX} in Hz		c	C_{RF}	f_{TX} in Hz
5	915954870.6		15	5	915697790.5
4	915952490.2		15	4	915695410.2
3	915950109.9		15	3	915693029.8
2	915947729.5		15	2	915690649.4
1	915945349.1		15	1	915688269.0
	5 4 3	5 915954870.6 4 915952490.2 3 915950109.9 2 915947729.5	5 915954870.6 4 915952490.2 3 915950109.9 2 915947729.5	5 915954870.6 15 4 915952490.2 15 3 915950109.9 15 2 915947729.5 15	5 915954870.6 15 5 4 915952490.2 15 4 3 915950109.9 15 3 2 915947729.5 15 2

łz		с	C_{RF}	f_{TX} in Hz
.5		6	5	915440710.4
.2	П	6	4	915438330.1
.8		6	3	915435949.7
.4		6	2	915433569.3
.0	П	6	1	915431189.0



Report No.: HKEM221200109503 Page: 12 of 21

24	0	915942968.8		15	0	915685888.7		6	0	915428808.6
24	-1	915940588.4		15	-1	915683508.3		6	-1	915426428.2
24	-2	915938208.0		15	-2	915681127.9	П	6	-2	915424047.9
24	-3	915935827.6		15	-3	915678747.6	Ш	6	-3	915421667.5
24	-4	915933447.3		15	-4	915676367.2		6	-4	915419287.1
24	-5	915931066.9		15	-5	915673986.8	Ш	6	-5	915416906.7
		915928686.5				915671606.4				915414526.4
23	5	915926306.2		14	5	915669226.1		5	5	915412146.0
23	4	915923925.8		14	4	915666845.7		5	4	915409765.6
23	3	915921545.4		14	3	915664465.3		5	3	915407385.3
23	2	915919165.0		14	2	915662085.0	П	5	2	915405004.9
23	1	915916784.7		14	1	915659704.6		5	1	915402624.5
23	0	915914404.3		14	0	915657324.2		5	0	915400244.1
23	-1	915912023.9		14	-1	915654943.8		5	-1	915397863.8
23	-2	915909643.6		14	-2	915652563.5		5	-2	915395483.4
23	-3	915907263.2		14	-3	915650183.1	1	5	-3	915393103.0
23	-4	915904882.8		14	-4	915647802.7	1	5	-4	915390722.7
23	-5	915902502.4		14	-5	915645422.4	1	5	-5	915388342.3
		915900122.1				915643042.0	1			915385961.9
22	5	915897741.7		13	5	915640661.6	l	4	5	915383581.5
22	4	915895361.3		13	4	915638281.3	1	4	4	915381201.2
22	3	915892981.0		13	3	915635900.9	1	4	3	915378820.8
22	2	915890600.6		13	2	915633520.5	1	4	2	915376440.4
22	1	915888220.2		13	1	915631140.1	ı	4	1	915374060.1
22	0	915885839.8		13	0	915628759.8	ii	4	0	915371679.7
22	-1	915883459.5		13	-1	915626379.4	1	4	-1	915369299.3
22	-2	915881079.1		13	-2	915623999.0	ii	4	-2	915366918.9
22	-3	915878698.7		13	-3	915621618.7	ı	4	-3	915364538.6
22	-4	915876318.4		13	-4	915619238.3	i	4	-4	915362158.2
22	-5	915873938.0		13	-5	915616857.9	1	4	-5	915359777.8
	-	915871557.6			-	915614477.5	H	•	-	915357397.5
21	5	915869177.2		12	5	915612097.2	1	3	5	915355017.1
21	4	915866796.9		12	4	915609716.8	ı	3	4	915352636.7
21	3	915864416.5		12	3	915607336.4	H	3	3	915350256.3
21	2	915862036.1		12	2	915604956.1	H	3	2	915347876.0
21	1	915859655.8		12	1	915602575.7		3	1	915345495.6
21	0	915857275.4		12	0	915600195.3	H	3	0	915343475.0
21	-1	915854895.0		12	-1	915597814.9		3	-1	915343115.2
21								3		
	-2	915852514.6		12	-2	915595434.6		3	-2	915338354.5
21	-3	915850134.3		12	-3	915593054.2			-3	915335974.1
21	-4	915847753.9		12	-4	915590673.8		3	-4	915333593.8
21	-5	915845373.5		12	-5	915588293.5		3	-5	915331213.4
	_	915842993.2		- -		915585913.1		\exists	_	915328833.0
20	5	915840612.8	ı	11	5	915583532.7	1	2	5	915326452.6



Report No.: HKEM221200109503 Page: 13 of 21

			_	_					
20	4	915838232.4	11	4	915581152.3		2	4	915324072.3
20	3	915835852.1	11	3	915578772.0		2	3	915321691.9
20	2	915833471.7	11	2	915576391.6		2	2	915319311.5
20	1	915831091.3	11	1	915574011.2		2	1	915316931.2
20	0	915828710.9	11	0	915571630.9		2	0	915314550.8
20	-1	915826330.6	11	-1	915569250.5		2	-1	915312170.4
20	-2	915823950.2	11	-2	915566870.1		2	-2	915309790.0
20	-3	915821569.8	11	-3	915564489.7		2	-3	915307409.7
20	-4	915819189.5	11	-4	915562109.4		2	-4	915305029.3
20	-5	915816809.1	11	-5	915559729.0		2	-5	915302648.9
		915814428.7			915557348.6				915300268.6
19	5	915812048.3	10	5	915554968.3		1	5	915297888.2
19	4	915809668.0	10	4	915552587.9		1	4	915295507.8
19	3	915807287.6	10	3	915550207.5		1	3	915293127.4
19	2	915804907.2	10	2	915547827.1		1	2	915290747.1
19	1	915802526.9	10	1	915545446.8		1	1	915288366.7
19	0	915800146.5	10	0	915543066.4		1	0	915285986.3
19	-1	915797766.1	10	-1	915540686.0		1	-1	915283606.0
19	-2	915795385.7	10	-2	915538305.7		1	-2	915281225.6
19	-3	915793005.4	10	-3	915535925.3		1	-3	915278845.2
19	-4	915790625.0	10	-4	915533544.9		1	-4	915276464.8
19	-5	915788244.6	10	-5	915531164.6		1	-5	915274084.5
		915785864.3			915528784.2				915271704.1
18	5	915783483.9	9	5	915526403.8		0	5	915269323.7
18	4	915781103.5	9	4	915524023.4		0	4	915266943.4
18	3	915778723.1	9	3	915521643.1		0	3	915264563.0
18	2	915776342.8	9	2	915519262.7		0	2	915262182.6
18	1	915773962.4	9	1	915516882.3		0	1	915259802.2
18	0	915771582.0	9	0	915514502.0		0	0	915257421.9
18	-1	915769201.7	9	-1	915512121.6		0	-1	915255041.5
18	-2	915766821.3	9	-2	915509741.2		0	-2	915252661.1
18	-3	915764440.9	9	-3	915507360.8		0	-3	915250280.8
18	-4	915762060.5	9	-4	915504980.5		0	-4	915247900.4
18	-5	915759680.2	9	-5	915502600.1		0	-5	915245520.0
		915757299.8			915500219.7				
17	5	915754919.4	8	5	915497839.4				
17	4	915752539.1	8	4	915495459.0				
17	3	915750158.7	8	3	915493078.6				
17	2	915747778.3	8	2	915490698.2				
17	1	915745397.9	8	1	915488317.9				
17	0	915743017.6	8	0	915485937.5		П		
17	-1	915740637.2	8	-1	915483557.1				
17	-2	915738256.8	8	-2	915481176.8				
17	-3	915735876.5	8	-3	915478796.4				
1/	-0	/20/000/00		-0	22047077014	1			

17	-4	915733496.1	8	-4	9
17	-5	915731115.7	8	-5	9
		915728735.4			9
16	5	915726355.0	7	5	9
16	4	915723974.6	7	4	9
16	3	915721594.2	7	3	9
16	2	915719213.9	7	2	9
16	1	915716833.5	7	1	9
16	0	915714453.1	7	0	9
16	-1	915712072.8	7	-1	9
16	-2	915709692.4	7	-2	9
16	-3	915707312.0	7	-3	9
16	-4	915704931.6	7	-4	9
16	-5	915702551.3	7	-5	9
		915700170.9			9

8	-4	915476416.0	
8	-5	915474035.6	
		915471655.3	
7	5	915469274.9	
7	4	915466894.5	
7	3	915464514.2	
7	2	915462133.8	
7	1	915459753.4	
7	0	915457373.0	
7	-1	915454992.7	
7	-2	915452612.3	
7	-3	915450231.9	
7	-4	915447851.6	
7	-5	915445471.2	
		915443090.8	



Page: 14 of 21

BLE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2402	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2480
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

4.2 Description of Support Units

The EUT has been with corresponding accessories as below: Supplied by SGS:

Description	Manufacturer	Model No.	Serial No.
Notebook	Dell	Inspiron 15	4RZCWN2



Page: 15 of 21

4.3 Test Location

All tests were performed at:

SGS Hong Kong Limited

Unit 2 and 3, G/F, Block A, Po Lung Centre,

11 Wang Chiu Road, Kowloon Bay, Kowloon, Hong Kong

Tel: +852 2305 2570 Fax: +852 2756 4480

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• IAS Accreditation (Lab Code: TL-817)

SGS Hong Kong Limited has met the requirements of AC89, IAS Accreditation Criteria for Testing Laboratories, and has demonstrated compliance with ISO/IEC Standard 17025:2017, General requirements for the competence of testing and calibration laboratories. This organization is accredited to provide the services specified in the scope of accreditation maintained on the IAS website (www.iasonline.org).

The report must not be used by the client to claim product certification, approval, or endorsement by IAS, NIST, or any agency of the Federal Government.

• FCC Recognized Accredited Test Firm (CAB Registration No.: 514599)

SGS Hong Kong Limited has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: HK0015, Test Firm Registration Number: 514599.

• Industry Canada (Site Registration No.: 26103; CAB Identifier No.: HK0015)

SGS Hong Kong Limited has been recognized by Department of Innovation, Science and Economic Development (ISED) Canada as a wireless testing laboratory. The acceptance letter from the ISED is maintained in our files. CAB Identifier No: HK0015, Site Registration Number: 26103.

4.5 Deviation from Standards

None

4.6 Abnormalities from Standard Conditions

None



Page: 16 of 21

5 Radio Spectrum Technical Requirement

5.1 RF Exposure

5.1.1 Test Requirement:

CFR 47 Part 1.1310

Limit:

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in Part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
	(A) Limits for O	ccupational/Controlled Ex	posure	
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
	(B) Limits for Generation	al Population/Uncontrolle	d Exposure	
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

According to IEEE C95.3:2002 section 5.5.1.1, The power density S at a point on the axis at a distance d from a transmitting antenna is given by the Friis free-space transmission formula

$$S = \frac{PG}{4\pi d^2}$$

 $S = power density (mW/cm^2)$

P = the net power delivered to the antenna (mW)

G = gain of the antenna in linear scale

d = distance between observation point and center of the radiator (cm)

^{* =} Plane-wave equivalent power density



Page: 17 of 21

5.1.1 IC Radiofrequncy radiation

According to RSS-102 Issue 5, section 2.5.2 Exemption.

RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 22.48/f0.5W (adjusted for tune-up tolerance), where f is in MHz;

at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);

at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 \times 10-2 f0.6834 W (adjusted for tune-up tolerance), where f is in MHz;

at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).



Page: 18 of 21

5.1.2 EUT RF Exposure Evaluation

SubGhz:

Antenna Gain: 2dBi

The maximum Gain measured in fully anechoic chamber is 1.585 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

FHSS:

Channel	Frequency (MHz)	Conduct power (including Tune- up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Weighted MPE Ratios	Result
Low	902.60	9.46	8.831	0.0035	0.6017	0.0058	PASS
Middle	913.60	9.00	7.943	0.0032	0.6091	0.0052	PASS
High	927.40	9.37	8.650	0.0034	0.6183	0.0056	PASS

For IC:

FHSS:

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (dBm)	E.I.R.P (W)	Limit (W)	Weighted Power Ratios	Result
Low	902.60	9.46	11.46	0.014	1.371	0.010	PASS
Middle	913.60	9.00	11.00	0.013	1.382	0.009	PASS
High	927.40	9.37	11.37	0.014	1.397	0.010	PASS

Note:

1. Refer to report No. HKEM221200109502 for EUT test conducted power value.



Page: 19 of 21

Mioty:

Antenna Gain: 2dBi

The maximum Gain measured in fully anechoic chamber is 1.585 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

FHSS:

Channel	Frequency (MHz)	Conduct power (including Tune- up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Weighted MPE Ratios	Result
Low	915.25	13.08	20.324	0.0064	0.6102	0.0105	PASS
High	916.75	13.52	22.491	0.0071	0.6112	0.0116	PASS

For IC:

FHSS:

Channel	Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (dBm)	E.I.R.P (W)	Limit (W)	Weighted Power Ratios	Result
Low	915.25	13.08	15.08	0.0322	1.3842	0.0233	PASS
High	916.75	13.52	15.5	0.0356	1.3857	0.0257	PASS

Note:

1. Refer to report No. HKEM221200109502 for EUT test conducted power value.



Page: 20 of 21

BLE:

Antenna Gain: 3.5dBi according to the test report UL-RPT-RP13337971-1216A V2.0.

The maximum Gain measured in fully anechoic chamber is 2.24 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For FCC;

Conduct power data taken from the test report UL-RPT-RP13337971-1216A V2.0 (FCC ID:2ABCB-RPICM4, original FCC ID:2ABCB-RPIRM0), the worst-case conduct power is 4.7dBm.

Frequency (MHz)	Conduct power (including Tune- up tolerance) (dBm)	Conduct power (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Weighted MPE Ratios	Result
2402	4.6	2.884	0.0013	1	0.0013	PASS
2440	4.7	2.951	0.0013	1	0.0013	PASS
2480	4.2	2.630	0.0012	1	0.0012	PASS

For IC:

Conduct power data taken from the test report UL-RPT-RP13337971-1216A V2.0 (IC: 20953-RPICM4, original IC:20953-RPIRM0), the worst-case conduct power is 4.7dBm.

Frequency (MHz)	Conduct power (including Tune-up tolerance) (dBm)	E.I.R.P (dBm)	E.I.R.P (W)	Limit (W)	Weighted Power	Result
	tolerance) (abiii)				Ratios	
2402	4.6	8.1	0.006	2.68	0.0024	PASS
2440	4.7	8.2	0.007	2.71	0.0024	PASS
2480	4.2	7.7	0.006	2.74	0.0022	PASS

For simultaneous transmission of SubGhz, Mioty and BLE:

For FCC:

SubGhz	Mioty	BLE	Total	Limit	Result
Maximum	Maximum	Maximum	Weighted		
MPE	MPE	MPE	MPE		
Ratios	Ratios	Ratios	Ratios		
0.0058	0.0116	0.0013	0.0187	1	PASS

For IC:

SubGhz Maximum	Mioty Maximum	BLE Maximum	Total Weighted	Limit	Result
MPE	MPE	MPE	Power		
Ratios	Ratios	Ratios	Ratios		
0.01	0.0257	0.0024	0.0381	1	PASS



Page: 21 of 21

6 Photographs

Remark: Photos refer to Appendix: External Photo, Internal Photo, and Setup Photo

- End of the Report -