

Maximum Permissible Exposure

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Calculation

$$\text{Given } E = \sqrt{\frac{30 \times P \times G}{d}} \quad \& \quad S = \frac{E^2}{3770}$$

Where *E* = Field Strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts / square centimeter

For 2.4G WIFI

1) The maximum output power is 3.31 dBm 2.14mW) at 2402MHz, (with 1.5 dBi antenna gain (1.41 numeric antenna gain))

4) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Maximum Permissible Exposure

output power=2.14mW

Numeric Antenna gain=1.41 Substituting the MPE safe distance using d=20cm into above equation.

Yields: $S=0.000199 \times P \times G$

Where P=Power in mW

G=Numeric antenna gain

S=Power density in mW/cm²

Total Power density=0.0006 mW/cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm even if the calculation indicates that the power density would be larger.)