



FCC Test Report

Report No: FCS202212004W02

Issued for

Applicant:	E-Link Technology Co., Ltd
Address:	4-5 Floor,BL.B Tongwei Factory Area,No.8,Gongye 2nd Road,Shilong,Shiyan Street ,Bao an district,Shenzhen
Product Name:	EL-ATV-01,Hyperquad
Brand Name:	N/A
Model Name:	EL-ATV-01
Series Model:	HYPER QUAD,JATV,JATV-BLK
FCC ID:	2BAIH-ATV-01
Issued By: Flux Compliance Service Laboratory Add: Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan Tel: 769-27280901 Fax:769-27280901 http://www.FCS-lab.com	

TEST RESULT CERTIFICATION

Applicant's Name.....: E-Link Technology Co., Ltd
 Address.....: 4-5 Floor,BL.B Tongwei Optoelectronics Factory Area,No.8,
 Gongye 2nd Road,Shilong,Shiyan Street 518108,Bao'an dist
 rict,Shenzhen
 Manufacture's Name.....: E-Link Technology Co., Ltd
 Address.....: 4-5 Floor,BL.B Tongwei Optoelectronics Factory Area,No.8,
 Gongye 2nd Road,Shilong,Shiyan Street 518108,Bao'an dist
 rict,Shenzhen

Product Description

Product Name.....: EL-ATV-01,Hyperquad
 Brand Name.....: N/A
 Model Name.....: EL-ATV-01
 Series Model.....: HYPER QUAD,JATV,JATV-BLK
 Test Standards.....: FCC Rules and Regulations Part 15 Subpart C, Section 247
 Test Procedure.....: ANSI C63.10:2013

This device described above has been tested by Flux Compliance Service Laboratory, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Flux Compliance Service Laboratory, this document may be altered or revised by Flux Compliance Service Laboratory, personal only, and shall be noted in the revision of the document..

Date of Test.....:

Date (s) of performance of tests.: 01 Dec, 2022 ~ 7 Jan, 2023

Date of Issue.....: 7 Jan, 2023

Test Result.....: Pass

Tested by : Scott shen
 (Scott Shen)
 Reviewed by : Duke Qian
 (Duke Qian)
 Approved by : Jack Wang
 (Jack Wang)



Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.4 EQUIPMENTS LIST	12
3 CONDUCTED EMISSION MEASUREMENT	13
4. 20 DB BANDWIDTH	17
4.1 Limit	17
4.2 Test Procedure	17
4.3 Test setup	17
4.4 Test results	17
4.5 Original Test Data	18
5. CONDUCTED OUTPUT POWER	20
5.1 LIMIT	20
5.3 TEST SETUP	20
5.5 TEST RESULTS	20
6 NUMBER OF HOPPING CHANNEL	21
6.1 LIMIT	21
6.2 TEST PROCEDURE	21
5.3 TEST SETUP	21
6.4 EUT OPERATION CONDITIONS	21
6.5 TEST RESULTS	22
7. BAND EDGE AND SPURIOUS(CONDUCTED)	23
7.1 LIMIT	23
7.2 TEST PROCEDURE	23
7.3 TEST SETUP	23
7.4 TEST RESULTS	24
7.5 Original test data	24

Table of Contents	Page
7.6 For Hopping Band edge	27
8. RADIATED EMISSION MEASUREMENT	28
8.1 RADIATED EMISSION LIMITS	28
8.2 TEST PROCEDURE	29
8.3 TESTSETUP	30
8.4. TEST RESULTS	32
8.5 (30MHZ-1000MHZ)	33
■ 8.6 ABOVE 1GHZ	35
8.7 RADIATED BAND EDGE DATA	38
9. AVERAGE TIME OF OCCUPANCY	39
9.1 LIMIT	39
9.2 TEST PROCEDURE	39
9.3 TEST SETUP	39
9.4 TEST RESULTS	40
9.5 ORIGINAL TEST DATA	40
10. HOPPING CHANNEL SEPARATION MEASUREMEN	42
10.1 LIMIT	42
10.2 TEST PROCEDURE	42
10.3 TEST SETUP	42
10.4 EUT OPERATION CONDITIONS	43
10.5 TEST RESULTS	43
11. ANTENNA REQUIREMENT	45
11.1 STANDARD REQUIREMENT	45
11.2 RESULT	45

Revision History

Rev.	Issue Date	Effect Page	Contents
00	7 Jan, 2023	N/A	N/A

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247(a)(1)	Hopping Channel Separation	PASS	--
15.247 (b)(2)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247(a)(1)(i)	Number of Hopping Frequency	PASS	--
15.247(a)(1)(i)	Dwell Time	PASS	--
15.247(a)(1)	20dB Bandwidth 99% Bandwidth	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) "N/A" denotes test is not applicable in this Test Report
- (2) All tests are according to ANSI C63.10-2013

1.1 TEST FACTORY

Company Name:	Flux Compliance Service Laboratory
Address:	Room 105 Floor Bao hao Technology Building 1 NO.15 Gong ye West Road Hi-Tech Industrial, Song shan lake Dongguan
Telephone:	+86-769-27280901
Fax:	+86-769-27280901
Laboray Accreditations	
FCC Test Firm Registration Number: 514908 CNAS Number: L15566 Designation number: CN0127 A2LA accreditation number: 5545.01 ISED Number: 25801	

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.71\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.988\text{ dB}$
3	Conducted Emission (9KHz-150KHz)	$\pm 4.13\text{ dB}$
4	All emissions radiated (9KHz -30MHz)	$\pm 3.1\text{ dB}$
5	Conducted Emission (150KHz-30MHz)	$\pm 4.74\text{ dB}$
6	All emissions,radiated(<1G) 30MHz-1000MHz	$\pm 5.2\text{ dB}$
7	All emissions,radiated 1GHz -18GHz	$\pm 4.66\text{ dB}$
8	All emissions,radiated 18GHz -40GHz	$\pm 4.31\text{ dB}$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	EL-ATV-01,Hyperquad
Trade Name	N/A
Model Name	EL-ATV-01
Series Model	HYPER QUAD,JATV,JATV-BLK
Model Difference	The above product with same circuit, PCB layout, electrical parts, materials and wiring structures, the materials of decorative accessories is same, For the product appearance difference, the size is the same, but the color of the product is different
Channel List	Please refer to the Note 2.
Operation frequency	2402MHz-2480MHz
Modulation:	GFSK
Bluetooth version	5.0
Channel number	79 CH
Transmitter rate:	1MHz
Power Supply	Input:100-240V 50/60Hz 3A Output:42V 15A
Battery	DC 36V
Hardware version number	V1.0
Software version number	V1.0
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	NA	N/A	PCB Antenna	N/A	1.6	Antenna

2.2 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Block diagram of EUT configuration for test



Test software: the BT_Tool.exe

The test software was used to control EUT work in continuous TX mode, and select test channel, Wireless mode as below table

No.	Test model descrtion
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Hopping GFSK

Note:

1. All the test modes can be supply by battery, only the result of the worst case recorded in the report. GFSK mode is worst mode.
2. For radiated emission, 3 axis were chosen for testing for each applicable mode.
3. The EUT used fully charge battery when tested.
4. During the test, the dutycycle>98%, the test voltage was tuned from 85% to 115% of the Nominal rate supply votage, and found that the worst case was the nominal rated supply condition, So the report just shows that condition's data

2.3 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
1	Adapter	COMING DATA	CP4215	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.4 EQUIPMENTS LIST

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESRP 3	FCS-E001	2022.08.30	2023.08.29
Signal Analyzer	R&S	FSV40-N	FCS-E012	2022.08.30	2023.08.29
Active loop Antenna	ZHINAN	ZN30900C	FCS-E013	2022.08.30	2023.08.29
Bilog Antenna	SCHWARZBECK	VULB 9168	FCS-E002	2022.08.30	2023.08.29
Horn Antenna	SCHWARZBECK	BBHA 9120D	FCS-E003	2022.08.30	2023.08.29
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	FCS-E018	2022.08.30	2023.08.29
Pre-Amplifier(0.1M-3G Hz)	EMCI	EM330N	FCS-E004	2022.08.30	2023.08.29
Pre-Amplifier (1G-18GHz)	N/A	TSAMP-0518SE	FCS-E014	2022.08.30	2023.08.29
Pre-Amplifier (18G-40GHz)	TERA-MW	TRLA-0400	FCS-E019	2022.08.30	2023.08.29
Temperature & Humidity	HTC-1	victor	FCS-E005	2022.08.30	2023.08.29
Testing Software	EZ-EMC(Ver.STSLAB 03A1 RE)				

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	FCS-E020	2022.08.30	2023.08.29
LISN	R&S	ENV216	FCS-E007	2022.08.30	2023.08.29
LISN	ETS	3810/2NM	FCS-E009	2022.08.30	2023.08.29
Temperature & Humidity	HTC-1	victor	FCS-E008	2022.08.30	2023.08.29
Testing Software	EZ-EMC(Ver.EMC-CON 3A1.1)				

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Company No.	Last calibration	Calibrated until
MXA SIGNAL Analyzer	Keysight	N9020A	FCS-E015	2022.08.30	2023.08.29
Spectrum Analyzer	Agilent	E4447A	MY50180039	2022.08.30	2023.08.29
Spectrum Analyzer	R&S	FSV-40	101499	2022.08.30	2023.08.29
Power Sensor	Agilent	UX2021XA	FCS-E021	2022.08.30	2023.08.29
Testing Software	EZ-EMC(Ver.STSLAB 03A1 RE)				

3 CONDUCTED EMISSION MEASUREMENT

3.1 LIMIT

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


3.2 TEST PROCEDURE

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- a. The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP




3.4 TEST RESULTS

Temperature:	25℃	Relative Humidity:	50%
Test Mode:	GFSK(worst mode)	Test Voltage:	DC 42V by adapter
Result:	L	Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1725	35.90	9.52	45.42	64.84	19.42	QP
2	0.1725	12.08	9.52	21.60	54.84	33.24	AVG
3	0.5639	27.87	9.56	37.43	56.00	18.57	QP
4	0.5639	3.62	9.56	13.18	46.00	32.82	AVG
5	1.3425	23.63	9.57	33.20	56.00	22.80	QP
6	1.3425	11.71	9.57	21.28	46.00	24.72	AVG
7	2.2290	21.87	9.58	31.45	56.00	24.55	QP
8	2.2290	14.05	9.58	23.63	46.00	22.37	AVG
9	4.0065	22.09	9.59	31.68	56.00	24.32	QP
10	4.0065	10.72	9.59	20.31	46.00	25.69	AVG
11	7.7955	19.19	9.62	28.81	60.00	31.19	QP
12	7.7955	7.16	9.62	16.78	50.00	33.22	AVG

Temperature:	25°C	Relative Humidity:	50%
Test Mode:	GFSK(worst mode)	Test Voltage:	DC 42V by adapter
Result:	N	Result:	Pass



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.2085	34.06	9.53	43.59	63.26	19.67	QP
2	0.2085	9.14	9.53	18.67	53.26	34.59	AVG
3	0.2714	36.26	9.54	45.80	61.07	15.27	QP
4	0.2714	7.87	9.54	17.41	51.07	33.66	AVG
5	1.1085	24.64	9.57	34.21	56.00	21.79	QP
6	1.1085	17.69	9.57	27.26	46.00	18.74	AVG
7	2.6925	24.82	9.60	34.42	56.00	21.58	QP
8	2.6925	8.89	9.60	18.49	46.00	27.51	AVG
9	7.8495	19.81	9.76	29.57	60.00	30.43	QP
10	7.8495	8.61	9.76	18.37	50.00	31.63	AVG
11	22.9155	16.55	9.84	26.39	60.00	33.61	QP
12	22.9155	5.90	9.84	15.74	50.00	34.26	AVG

Remark:

1. All readings are Quasi-Peak and Average values

4. 20 DB BANDWIDTH

4.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247a(1)	20dB bandwidth	N/A	2400-2483.5

4.2 Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows

RBW: 30kHz

VBW: 100kHz

Detector Mode: AVG

Sweep time: auto

Trace mode Max hold

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3 Test setup




4.4 Test results


TestMode	Channel (MHz)	20dB Bandwidth (KHz)	Verdict
Lowest	2402MHz	948.4	Pass
Middle	2441MHz	968.1	Pass
Highest	2480MHz	973.5	Pass

4.5 Original Test Data


Low



Middle



High



5. CONDUCTED OUTPUT POWER

5.1 LIMIT

FCC Part 15 Subpart C			
Section	Test Item	Limit	Frequency Range
15.247(b)(3)	Peak output power	Power <1W(30dBm)	2400-2483.5

- 1.Connect each EUT's antenna output to power sensor by RF cable and attenuator
- 2.Measure the PK output power of each antenna port by power sensor.

5.3 TEST SETUP



5.5 TEST RESULTS

TestMode	Channel (MHz)	Result (dBm)	Limit (dBm)	Verdict
Lowest	2402MHz	3.66	30	Pass
Middle	2441MHz	2.84	30	Pass
Highest	2480MHz	3.55	30	Pass

6 NUMBER OF HOPPING CHANNEL

6.1 LIMIT


FCC Part 15.247, Subpart C RSS-247 Issue 2				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii) RSS-247	Number of Hopping Channel	>15	2400-2483.5	PASS

6.2 TEST PROCEDURE

a The EUT was directly connected to the spectrum analyzer and antenna output port as shown in the block diagram below.

b Spectrum Setting: RBW= 100KHz, VBW=300KHz, Sweep time = Auto

5.3 TEST SETUP




6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Mode:	Hopping Mode -GFSK Mode	Test Voltage:	DC 3.7V



7. BAND EDGE AND SPURIOUS(CONDUCTED)

7.1 LIMIT

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.2 TEST PROCEDURE

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Establish Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.3 TEST SETUP




7.4 TEST RESULTS


Eut set mode	CH or Frequency	Result
GFSK	CH1	Pass
	CH79	Pass

7.5 Original test data

CH1 2402MHZ



CH79 2480MHZ




Spurious emissions


Low Channel 30MHz-25GHz





Middle Channel 30MHz-25GHz



High Channel 30MHz-25GHz



7.6 For Hopping Band edge



8. RADIATED EMISSION MEASUREMENT

8.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2300 to 2403 MHz Upper Band Edge: 2479 to 2500 MHz
RB / VB (emission in restricted band)	PK=1MHz / 1MHz, AV=1 MHz / 10 Hz

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

8.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

8.3 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



8.4. TEST RESULTS

(9KHz-30MHz)

Temperature:	22.7℃	Relative Humidity:	61%
Test Voltage:	DC 36V	Test Mode:	GFSK(worst mode)

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

8.5 (30MHZ-1000MHZ)

Temperature:	24.7°C	Relative Humidity:	61%
Test Voltage:	DC 36V	Phase:	Horizontal
Test Mode:	GFSK(worst mode)		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	35.0048	36.93	- 10.60	26.33	40.00	- 13.67	QP
2	70.8315	56.54	-32.24	24.30	40.00	- 15.70	QP
3	162.6105	61.90	-32.24	29.66	43.50	- 13.84	QP
4	329.0390	62.29	-32.07	30.22	46.00	- 15.78	QP
5	597.2232	61.41	-31.77	29.64	46.00	- 16.36	QP
6	766.0570	69.30	-31.55	37.75	46.00	-8.25	QP

Note: 1. Margin = Result (Result = Reading + Factor) - Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Temperature:	22.7°C	Relative Humidity:	61%
Test Voltage:	DC 36V	Phase:	Vertical
Test Mode:	GFSK(worst mode)		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.6376	42.69	-7.75	34.94	40.00	-5.06	QP
2	68.1512	38.38	- 19.98	18.40	40.00	-21.60	QP
3	124.1330	65.44	-32.28	33.16	43.50	- 10.34	QP
4	236.6447	61.13	-32. 16	28.97	46.00	- 17.03	QP
5	495.9343	56.64	-31.90	24.74	46.00	-21.26	QP
6	766.0570	70.77	-31.55	39.22	46.00	-6.78	QP

Note: 1. Margin = Result (Result =Reading + Factor)–Limit

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

■ 8.6 ABOVE 1GHZ

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.84	31.78	8.60	32.09	44.13	74.00	-29.87	Vertical
7206.00	31.01	36.15	11.65	32.00	46.81	74.00	-27.19	Vertical
9608.00	31.15	37.95	14.14	31.62	51.62	74.00	-22.38	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	39.56	31.78	8.60	32.09	47.85	74.00	-26.15	Horizontal
7206.00	32.90	36.15	11.65	32.00	48.70	74.00	-25.30	Horizontal
9608.00	29.65	37.95	14.14	31.62	50.12	74.00	-23.88	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	25.11	31.78	8.60	32.09	33.40	54.00	-20.60	Vertical
7206.00	19.97	36.15	11.65	32.00	35.77	54.00	-18.23	Vertical
9608.00	19.52	37.95	14.14	31.62	39.99	54.00	-14.01	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	28.99	31.78	8.60	32.09	37.28	54.00	-16.72	Horizontal
7206.00	22.33	36.15	11.65	32.00	38.13	54.00	-15.87	Horizontal
9608.00	18.36	37.95	14.14	31.62	38.83	54.00	-15.17	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.86	31.85	8.67	32.12	44.26	74.00	-29.74	Vertical
7323.00	31.03	36.37	11.72	31.89	47.23	74.00	-26.77	Vertical
9764.00	31.16	38.35	14.25	31.62	52.14	74.00	-21.86	Vertical
12205.00	*					74.00		Vertical
14646.00	*					74.00		Vertical
4882.00	39.59	31.85	8.67	32.12	47.99	74.00	-26.01	Horizontal
7323.00	32.91	36.37	11.72	31.89	49.11	74.00	-24.89	Horizontal
9764.00	29.67	38.35	14.25	31.62	50.65	74.00	-23.35	Horizontal
12205.00	*					74.00		Horizontal
14646.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	25.13	31.85	8.67	32.12	33.53	54.00	-20.47	Vertical
7323.00	19.98	36.37	11.72	31.89	36.18	54.00	-17.82	Vertical
9764.00	19.53	38.35	14.25	31.62	40.51	54.00	-13.49	Vertical
12205.00	*					54.00		Vertical
14646.00	*					54.00		Vertical
4882.00	29.01	31.85	8.67	32.12	37.41	54.00	-16.59	Horizontal
7323.00	22.34	36.37	11.72	31.89	38.54	54.00	-15.46	Horizontal
9764.00	18.37	38.35	14.25	31.62	39.35	54.00	-14.65	Horizontal
12205.00	*					54.00		Horizontal
14646.00	*					54.00		Horizontal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.69	31.93	8.73	32.16	44.19	74.00	-29.81	Vertical
7440.00	30.91	36.59	11.79	31.78	47.51	74.00	-26.49	Vertical
9920.00	31.06	38.81	14.38	31.88	52.37	74.00	-21.63	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	39.38	31.93	8.73	32.16	47.88	74.00	-26.12	Horizontal
7440.00	32.78	36.59	11.79	31.78	49.38	74.00	-24.62	Horizontal
9920.00	29.55	38.81	14.38	31.88	50.86	74.00	-23.14	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.99	31.93	8.73	32.16	33.49	54.00	-20.51	Vertical
7440.00	19.89	36.59	11.79	31.78	36.49	54.00	-17.51	Vertical
9920.00	19.45	38.81	14.38	31.88	40.76	54.00	-13.24	Vertical
12400.00						54.00		Vertical
14880.00						54.00		Vertical
4960.00	28.86	31.93	8.73	32.16	37.36	54.00	-16.64	Horizontal
7440.00	22.24	36.59	11.79	31.78	38.84	54.00	-15.16	Horizontal
9920.00	18.28	38.81	14.38	31.88	39.59	54.00	-14.41	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. The test data shows only the worst case 8DPSK mode

8.7 RADIATED BAND EDGE DATA

Remark: All restriction band have been tested, and only the worst case is shown in report

Low CH (GFSK)

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	44.14	27.91	5.30	24.64	52.71	74.00	-21.29	Horizontal
2390.00	48.33	27.59	5.38	24.71	56.59	74.00	-17.41	Horizontal
2310.00	45.10	27.91	5.30	24.64	53.67	74.00	-20.33	Vertical
2390.00	48.57	27.59	5.38	24.71	56.83	74.00	-17.17	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.65	27.91	5.30	24.64	43.22	54.00	-10.78	Horizontal
2390.00	36.06	27.59	5.38	24.71	44.32	54.00	-9.68	Horizontal
2310.00	34.63	27.91	5.30	24.64	43.20	54.00	-10.80	Vertical
2390.00	36.58	27.59	5.38	24.71	44.84	54.00	-9.16	Vertical

High CH(GFSK)

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.36	27.53	5.47	24.80	54.56	74.00	-19.44	Horizontal
2500.00	45.61	27.55	5.49	24.86	53.79	74.00	-20.21	Horizontal
2483.50	47.36	27.53	5.47	24.80	55.56	74.00	-18.44	Vertical
2500.00	46.76	27.55	5.49	24.86	54.94	74.00	-19.06	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.49	27.53	5.47	24.80	43.69	54.00	-10.31	Horizontal
2500.00	35.47	27.55	5.49	24.86	43.65	54.00	-10.35	Horizontal
2483.50	36.18	27.53	5.47	24.80	44.38	54.00	-9.62	Vertical
2500.00	35.32	27.55	5.49	24.86	43.50	54.00	-10.50	Vertical

9. AVERAGE TIME OF OCCUPANCY

9.1 LIMIT

FCC Part 5 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(1)	Average Time of Occupancy	0.4 sec	2400-2483.5

9.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set RBW =1MHz/VBW =1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So the number of pulses in the observation period of 31.6 seconds is $3.37 \times 31.6 = 106.6$.
- DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So the number of pulses in the observation period of 31.6 seconds is $5.06 \times 31.6 = 160$.
- DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So the number of pulses in the observation period of 31.6 seconds is $10.12 \times 31.6 = 320$.


9.3 TEST SETUP




9.4 TEST RESULTS

AVERAGE TIME OF OCCUPANCY							
CONDITIO N	MOD E	FREQUENCY(M HZ)	PULSE TIME(M S)	AVERAGE TIME OF OCCUPANCY(MS)	LIMIT(M S)	BURST NUMBE R	RESULT S
NVNT	1DH1	2402	0.411	131.237	400	319	PASS
NVNT	1DH3	2402	1.676	261.503	400	156	PASS
NVNT	1DH5	2402	2.908	311.156	400	107	PASS

9.5 ORIGINAL TEST DATA





10. HOPPING CHANNEL SEPARATION MEASUREMENT

10.1 LIMIT


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> 20 dB Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

10.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement

10.3 TEST SETUP




10.4 EUT OPERATION CONDITIONS



The EUT was programmed to be in continuously transmitting mode.

10.5 TEST RESULTS

Temperature:	25 °C	Relative Humidity:	60%
Test Mode:	GFSK Mode	Test Voltage:	DC 36V

Modulation	Frequency (MHz)	Mark1 Frequency (MHz)	Mark2 Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
GFSK	2402	2401.872	2402.870	0.998	0.63	Pass
	2441	2440.870	2441.872	1.002	0.63	Pass
	2480	2478.872	2479.872	1.000	0.65	Pass





11. ANTENNA REQUIREMENT

11.1 STANDARD REQUIREMENT

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2 RESULT

The antennas used for this product are PCB antenna and no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 1.6dBi.

*****END OF THE REPORT*****