



SAR Test Report


For


Applicant Name: Zhejiang Lianyong Intelligent Technology Co., Ltd.
Address: No. 1, First Street, Eastern New Area, Wenling, Taizhou, Zhejiang, China
EUT Name: Mobile phone
Brand Name: MAZE SPEED, SOHO STYLE
Model Number: MS5614G
Series Model Number: Refer to section 2

Issued By

Company Name: BTF Testing Lab (Shenzhen) Co., Ltd.
Address: F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Report Number: BTF230613R00301
Test Standards: FCC 47 CFR§2.1093 IEEE1528-2013 IEEE C95.1-2019
KDB447498 D01 v06 KDB447498 D04 v01
KDB865664 D01 v01r04 KDB865664 D02 v01r02
KDB941225 D01 v03r01 KDB941225 D05 v02r05
KDB248227 D01 v02r02 KDB941225 D06 v02r01
KDB648474 D04 v01r03 KDB690783 D01 v01r03
FCC ID: 2BBW3-MS5614G
Test Conclusion: Pass
Test Date: 2023-06-27 to 2023-06-29
Date of Issue: 2023-06-30

Prepared By: 
Monica Zhou / Project Engineer
Date: 2023-06-30
Approved By: 
Ryan.CJ / EMC Manager
Date: 2023-06-30



Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2023-06-30	Original
Note:	Once the revision has been made, then previous versions reports are invalid.	

Table of Contents

1. Introduction.....	4
1.1 Identification of Testing Laboratory	4
1.2 Identification of the Responsible Testing Location	4
1.3 Laboratory Condition	4
1.4 Announcement.....	4
2. Product Information.....	5
2.1 Application Information	5
2.2 Manufacturer Information.....	5
2.3 Factory Information.....	5
2.4 General Description of Equipment under Test (EUT)	5
2.5 Equipment under Test Ancillary Equipment	5
2.6 Technical Information.....	5
3. Summary of Test Results	7
3.1 Test Standards	7
3.2 Device Category and SAR Limit.....	7
3.3 Test Result Summary	8
3.4 Test Uncertainty	9
4. Measurement System.....	11
4.1 Specific Absorption Rate (SAR) Definition	11
4.2 MVG SAR System	11
5. System Verification.....	15
5.1 Purpose of System Check	15
5.2 System Check Setup.....	16
6. TEST POSITION CONFIGURATIONS	16
6.1 Head Exposure Conditions.....	16
6.2 Body-worn Position Conditions	18
6.3 Hotspot Mode Exposure Position Conditions	19
6.4 Product Specific 10g Exposure Consideration	19
7. Measurement Procedure	20
7.1 Measurement Process Diagram.....	20
7.2 SAR Scan General Requirement.....	21
7.3 Measurement Procedure	22
7.4 Area & Zoom Scan Procedure.....	22
8. Conducted RF Output Power	23
8.1 GSM	23
8.2 WCDMA.....	24
8.3 LTE	25
8.4 Wi-Fi.....	36
8.5 Bluetooth	37
9. Test Exclusion Consideration	38
9.1 SAR Test Exclusion Consideration Table.....	39
10. Test Result	39
11. SAR Measurement Variability	45
12. Simultaneous Transmission	46
12.1 Simultaneous Transmission Mode Considerations.....	46
12.2 Sum SAR of Simultaneous Transmission	46
13. Test Equipment List.....	50
ANNEX A Simulating Liquid Verification Result	51
ANNEX B System Check Result	51
ANNEX C Test Data	70
ANNEX D SAR Test Setup Photos	140
ANNEX E EUT External and Internal Photos.....	142
ANNEX F Calibration Information	142

1. Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
Description:	All measurement facilities used to collect the measurement data are located at F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China
FCC Registration Number	518915
Designation Number	CN1330

1.3 Laboratory Condition

Ambient Temperature:	21°C to 25°C
Ambient Relative Humidity:	48% to 59%
Ambient Pressure:	100 kPa to 102 kPa

1.4 Announcement

- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Product Information

2.1 Application Information

Company Name:	Zhejiang Lianyong Intelligent Technology Co., Ltd.
Address:	No. 1, First Street, Eastern New Area, Wenling, Taizhou, Zhejiang, China

2.2 Manufacturer Information

Company Name:	Zhejiang Lianyong Intelligent Technology Co., Ltd.
Address:	No. 1, First Street, Eastern New Area, Wenling, Taizhou, Zhejiang, China

2.3 Factory Information

Company Name:	Zhejiang Lianyong Intelligent Technology Co., Ltd.
Address:	No. 1, First Street, Eastern New Area, Wenling, Taizhou, Zhejiang, China

2.4 General Description of Equipment under Test (EUT)

EUT Name	Mobile phone
Under Test Model Name	MS5614G
Series Model Name	SS5614G
Description of Model name differentiation	Only the model name and brand name are different, others are the same.
Sample No.	BTFSN230612E007-1/5

2.5 Equipment under Test Ancillary Equipment

Ancillary Equipment 1	Rechargeable Battery	
	Capacity	2100mAh
	Rated Voltage	3.7V

2.6 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EGPRS 850/1900 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network FDD LTE Band 2/4/5/12/17/30/66/71 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/HT40) 5G WIFI 802.11a, 802.11n(HT20/HT40) BT (EDR+BLE)
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	GSM, WCDMA, LTE, WLAN, Bluetooth		
Frequency Range	GSM 850	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	GSM 1900	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	WCDMA Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	WCDMA Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 2	TX: 1850 ~ 1910 MHz	RX: 1930 ~ 1990 MHz
	LTE Band 4	TX: 1710 ~ 1755 MHz	RX: 2110 ~ 2155 MHz
	LTE Band 5	TX: 824 ~ 849 MHz	RX: 869 ~ 894 MHz
	LTE Band 12	TX: 698 ~ 716 MHz	RX: 728 ~ 746 MHz
	LTE Band 17	TX: 704 ~ 716 MHz	RX: 734 ~ 746 MHz
	LTE Band 30	TX: 2305 ~ 2315 MHz	RX: 2350 ~ 2360 MHz
	LTE Band 66	TX: 1710 ~ 1780 MHz	RX: 2110 ~ 2200 MHz
	LTE Band 71	TX: 663 ~ 698 MHz	RX: 617 ~ 652 MHz
	802.11b/g/n(HT20)	2412 ~ 2462 MHz	
	802.11n(HT40)	2422 ~ 2452 MHz	
	802.11a /802.11n(HT20/HT40)	5150 ~ 5250 MHz	
		5250 ~ 5350 MHz	
		5725 ~ 5850 MHz	
	Bluetooth	2402 ~ 2480 MHz	
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna BT: PIFA Antenna		
Hotspot Function	Support		
Power Reduction	Not Support		
Exposure Category	General Population/Uncontrolled exposure		
EUT Stage	Portable Device		
Product	Type		
	☐ Production unit	☒ Identical prototype	

3. Summary of Test Results

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEEE1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate in the Human Head from Wireless Communications Devices: Measurement Techniques
3	IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
4	KDB447498 D01	General RF Exposure Guidance v06
5	KDB447498 D04	Interim General RF Exposure Guidance v01
6	KDB865664 D01	SAR measurement 100MHz to 6GHz v01r04
7	KDB865664 D02	RF Exposure Reporting v01r02
8	KDB941225 D01	3G SAR Procedures v03r01
9	KDB941225 D05	SAR for LTE Devices v02r05
10	KDB248227 D01	802.11 Wi-Fi SAR v02r02
11	KDB941225 D06	Hotspot Mode v02r01
12	KDB648474 D04	Handset SAR v01r03
13	KDB690783 D01	SAR Listings on Grant v01r03

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment- related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as bellows:

<Highest Reported standalone SAR Summary>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Head 1-g SAR (0 mm Gap)	GSM 850	0.326	PCE	0.378
	GSM 1900	0.168		
	WCDMA Band II	0.256		
	WCDMA Band IV	0.317		
	WCDMA Band V	0.199		
	LTE Band 2	0.288		
	LTE Band 4	0.281		
	LTE Band 5	0.325		
	LTE Band 12	0.109		
	LTE Band 17	0.116		
	LTE Band 30	0.125		
	LTE Band 66	0.378		
	LTE Band 71	0.098		
	WLAN 2.4 GHz	0.146	DTS	
	WLAN 5.2 GHz	0.219	NII	
	WLAN 5.4 GHz	0.289		
	WLAN 5.8 GHz	0.203		
Bluetooth	0.080	DSS		
Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Hotspot(Body) 1-g SAR (10 mm Gap)	GSM 850	0.534	PCB	0.567
	GSM 1900	0.549		
	WCDMA Band II	0.242		
	WCDMA Band IV	0.342		
	WCDMA Band V	0.160		
	LTE Band 2	0.341		
	LTE Band 4	0.479		
	LTE Band 5	0.209		
	LTE Band 12	0.208		
	LTE Band 17	0.185		
	LTE Band 30	0.085		
	LTE Band 66	0.567		
	LTE Band 71	0.151		
	WLAN 2.4 GHz	0.062	DTS	
	WLAN 5.2 GHz	0.166	NII	
	WLAN 5.4 GHz	0.103		
	WLAN 5.8 GHz	0.156		
Bluetooth	0.118	DSS		

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.

<Highest Reported Simultaneous SAR>

Exposure Position	Simultaneous Configuration	Highest Reported Simultaneous Transmission SAR (W/kg)	Limit (W/kg)	Verdict
Head 1-g SAR (0 mm Gap)	LTE Band 66 + 5G WIFI	0.667	1.6	Pass
Hotspot(Body) 1-g SAR (10 mm Gap)	LTE Band 66 + 5G WIFI	0.727	1.6	Pass

3.4 Test Uncertainty

3.4.1 Measurement uncertainty evaluation for SAR test

Measurement uncertainty evaluation for SAR test (300MHz to 6GHz)

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+- %)	10 g Ui (+-%)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	√3	√0.5	√0.5	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	√3	√0.5	√0.5	2.41	2.41	∞
Boundary effect	1.0	R	√3	1	1	0.58	0.58	∞
Linearity	4.7	R	√3	1	1	2.71	2.71	∞
System detection limits	1.0	R	√3	1	1	0.58	0.58	∞
Modulation response	3.0	R	√3	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	√3	1	1	0.00	0.00	∞
Integration Time	1.4	R	√3	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	√3	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	√3	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	√3	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	√3	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	√3	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device Holder Uncertainty	3.0	N	1	1	1	3.00	3.00	7
Output power Variation - SAR drift measurement	5.0	R	√3	1	1	2.89	2.89	∞
SAR scaling	2.0	R	√3	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	√3	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4.0	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	√3	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	√3	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		k				20.95	20.69	

* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.4.2 Measurement uncertainty evaluation for system check

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10 g)	1g Ui (+-%)	10 g Ui (+-%)	Vi veff
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient Conditions - Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR drift measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Dist.	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Shell Uncertainty - Shape, Thickness and Permittivity	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation in permittivity and conductivity	2.0	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity measurement	4	N	1	0.78	0.71	3.12	2.84	5
Liquid permittivity measurement	5.0	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid permittivity - Temperature Uncertainty	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		k				20.32	20.06	

4. Measurement System

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 MVG SAR System

4.2.1 SAR system diagram



4.2.2 Robot



A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System

- It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

4.2.3 E-Field Probe

For the measurements, the Specific Dosimetric SSE2 E-Field Probe with following specifications is used:

- Dynamic range: 0.01-100 W/kg
- Tip diameter: 2mm for SSE2
- Distance between probe tip and sensor centre: 1mm for SSE2
- Distance between sensor centre and the inner phantom surface: 2mm for $f \geq 4\text{GHz}$.
- Probe linearity: $<0.25\text{dB}$.
- Axial Isotropy: $<0.25\text{dB}$.
- Spherical Isotropy: $<0.50\text{dB}$.
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Angle between probe axis (evaluation axis) and surface normal line: less than 20° .



4.2.4 Phantoms

SAM Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The probe scanning of the E-Field is done in the 2 halves of the normalized head. The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size. It enables the dosimetric evaluation of left and right-hand phone usage and includes an additional flat phantom part for the simplified body performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



SAM Phantom

The thickness of the phantom amounts to $2\text{ mm} \pm 0.2\text{ mm}$. The materials for the phantom do not affect the radiation of the device under test (DUT) : $\epsilon_r' < 5$
The head is filled with tissue simulating liquid. The hand do not have to be modeled.

TWIN SAM phantom

	Mechanical	Electrical	
Overall thickness	$2 \pm 0.2\text{ mm}$ (except ear area)	Relative permittivity	3.4
Dimensions	1000 mm(L) x 500 mm(W) x 200 mm(H)	Loss tangent	0.02
Maximum volume	27 L		
Material	Fiberglass based		

ELLIPTICAL Phantom

The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.




ELLI Phantom

The shape of the phantom is an ellipse with length $600\text{ mm} \pm 5\text{ mm}$ and width $400\text{ mm} \pm 5\text{ mm}$.
The phantom shell is made of low-loss and low-permittivity material, having loss tangent $\tan \delta \leq 0.05$ and relative permittivity:
 $\epsilon_r' \leq 5$ for $f \leq 3\text{ GHz}$
 $3 \leq \epsilon_r' \leq 5$ for $f > 3\text{ GHz}$
The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of $\pm 0.2\text{ mm}$.

Technical & mechanical characteristics

Shell thickness	$2\text{ mm} \pm 0.2\text{ mm}$
Filling volume	25 L
Dimensions	600 mm x 400 mm x 200mm
Permittivity	4.4
Loss tangent	0.017

4.2.5 Device Holder



System Material	Permittivity	Loss tangent
Delrin	3.7	0.005


(The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.)

System Material	Permittivity	Loss tangent
PMMA	2.9	0.028


4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth



Body Liquid Depth



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.


Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

5. System Verification

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup



6. TEST POSITION CONFIGURATIONS


According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

6.1.1 Two Imaginary Lines on the Handset

- The vertical center line passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- The horizontal line is perpendicular to the vertical center line and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical center line is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




6.1.2 Two Imaginary Lines on the Handset

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.



6.1.3 Titled Position

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.




6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.


Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance ≤ 5 mm to support compliance.



6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



6.4 Product Specific 10g Exposure Consideration


According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

7. Measurement Procedure

7.1 Measurement Process Diagram

Body SAR



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
				5–6 GHz: ≤ 2 mm
	Δz Zoom (n>1): between subsequent points	≤ 1.5 · Δz Zoom (n-1)		
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm
Note:				
1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528- 2011 for details.				
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB				
447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8. Conducted RF Output Power

8.1 GSM

Mode: GSM850		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH128	CH190	CH251		CH128	CH190	CH251
			824.2MHz	836.6MHz	848.8MHz		824.2MHz	836.6MHz	848.8MHz
GSM		32.50	32.18	32.26	32.14	-9.03	23.15	23.23	23.11
GPRS (GMSK)	1Tx slot	32.50	32.15	32.24	32.11	-9.03	23.12	23.21	23.08
	2Tx slots	31.50	31.35	31.45	31.34	-6.02	25.33	25.43	25.32
	3Tx slots	30.00	29.66	29.76	29.64	-4.26	25.40	25.50	25.38
	4Tx slots	29.00	28.64	28.75	28.63	-3.01	25.63	25.74	25.62
EGPRS (8PSK)	1Tx slot	28.50	26.60	26.44	28.27	-9.03	17.57	17.41	19.24
	2Tx slots	26.00	25.52	25.58	25.44	-6.02	19.50	19.56	19.42
	3Tx slots	24.00	23.35	23.58	23.46	-4.26	19.09	19.32	19.20
	4Tx slots	27.00	22.17	26.67	26.60	-3.01	19.16	23.66	23.59
Mode: GSM1900		Maximum Tune-up(dBm)	Burst Average Power (dBm)			Division Factors	Frame-Average Power (dBm)		
			CH512	CH661	CH810		CH512	CH661	CH810
			1850.2MHz	1880.0MHz	1909.8MHz		1850.2MHz	1880.0MHz	1909.8MHz
GSM		28.00	26.73	27.52	27.76	-9.03	17.70	18.49	18.73
GPRS (GMSK)	1Tx slot	28.00	26.73	27.50	27.73	-9.03	17.70	18.47	18.70
	2Tx slots	27.50	26.13	27.00	27.23	-6.02	20.11	20.98	21.21
	3Tx slots	26.00	24.59	25.59	25.81	-4.26	20.33	21.33	21.55
	4Tx slots	25.00	23.58	24.59	24.87	-3.01	20.57	21.58	21.86
EGPRS (8PSK)	1Tx slot	25.50	23.62	24.91	25.41	-9.03	14.59	15.88	16.38
	2Tx slots	25.00	23.63	24.17	24.87	-6.02	17.61	18.15	18.85
	3Tx slots	23.00	20.74	22.14	22.65	-4.26	16.48	17.88	18.39
	4Tx slots	21.50	19.69	21.08	21.35	-3.01	16.68	18.07	18.34
Note: 1) Division Factors To average the power, the division factor is as follows: 1Tx-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB 2Tx-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB 3Tx-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB 4Tx-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB									

8.2 WCDMA

Mode		Maximum Tune-up(dBm)	WCDMA Band II		
			Conducted Power (dBm)		
			CH9262	CH9400	CH9538
RMC 12.2K		20.00	1852.4	1880.0	1907.6
HSDPA	Subtest-1	18.00	19.39	19.88	19.71
	Subtest-2	18.00	17.09	17.57	17.44
	Subtest-3	18.00	17.06	17.57	17.47
	Subtest-4	18.00	17.05	17.56	17.47
HSUPA	Subtest-1	15.50	17.10	17.59	17.46
	Subtest-2	15.50	14.82	15.02	14.87
	Subtest-3	16.00	15.04	15.54	14.92
	Subtest-4	15.50	15.03	15.03	15.38
	Subtest-5	16.00	14.80	15.53	14.93
RMC 12.2K		17.00	14.84	15.09	15.39
Mode		Maximum Tune-up(dBm)	WCDMA Band IV		
			Conducted Power (dBm)		
			CH1312	CH1413	CH1513
RMC 12.2K		17.00	1712.4	1732.6	1752.6
HSDPA	Subtest-1	14.50	16.69	13.56	10.65
	Subtest-2	14.50	14.38	11.26	8.32
	Subtest-3	14.50	14.35	11.25	8.36
	Subtest-4	14.50	14.36	11.24	8.35
HSUPA	Subtest-1	12.50	14.36	11.25	8.32
	Subtest-2	12.50	12.18	9.02	5.84
	Subtest-3	12.50	12.23	9.25	6.34
	Subtest-4	12.50	12.21	9.25	6.18
	Subtest-5	12.50	12.43	9.23	6.11
RMC 12.2K		22.00	12.18	9.04	6.12
Mode		Maximum Tune-up(dBm)	WCDMA Band V		
			Conducted Power (dBm)		
			CH4132	CH4183	CH4233
RMC 12.2K		22.00	826.4	836.6	846.6
HSDPA	Subtest-1	19.50	21.80	21.80	21.74
	Subtest-2	20.00	19.47	19.46	19.46
	Subtest-3	20.00	19.51	19.44	19.45
	Subtest-4	20.00	19.52	19.49	19.44
HSUPA	Subtest-1	17.50	19.52	19.46	19.44
	Subtest-2	17.50	17.30	16.99	16.94
	Subtest-3	17.50	17.01	17.33	17.47
	Subtest-4	17.50	17.47	16.99	16.98
	Subtest-5	17.50	17.31	17.31	17.26
RMC 12.2K		22.00	17.29	17.01	17.22
Per KDB 941225 D01, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is ≤1/2dB higher than the primary mode (RMC12.2kbps) or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.					

8.3 LTE

Band 2

LTE-FDD Band 2				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		18607	18900	19193
					1850.7MHz	1880.0MHz	1909.3MHz
1.4MHz	QPSK	1	0	20.50	19.78	20.28	20.12
			3	20.50	19.89	20.41	20.23
			5	20.50	19.78	20.32	20.16
		3	0	20.50	19.88	20.34	20.19
			2	20.50	19.91	20.41	20.25
			3	20.50	19.91	20.39	20.19
		6	0	19.50	18.85	19.35	19.23
	16QAM	1	0	19.50	18.74	19.24	19.26
			3	19.50	18.89	19.38	19.37
			5	19.50	18.79	19.33	19.31
		3	0	19.50	19.14	19.44	19.18
			2	20.00	19.10	19.50	19.23
			3	19.50	19.10	19.44	19.24
		6	0	18.50	17.84	18.25	18.20
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18615	18900	19185
					1851.5MHz	1880.0MHz	1908.5MHz
3MHz	QPSK	1	0	20.50	19.74	20.22	20.14
			7	20.50	19.96	20.43	20.34
			14	20.50	19.85	20.28	20.18
		8	0	19.50	18.83	19.28	19.14
			4	19.50	18.87	19.32	19.20
			7	19.50	18.81	19.31	19.19
		15	0	19.50	18.83	19.29	19.14
	16QAM	1	0	20.00	18.94	19.79	19.15
			7	20.50	19.12	20.01	19.33
			14	20.00	18.99	19.86	19.14
		8	0	18.50	17.79	18.41	18.21
			4	18.50	17.84	18.49	18.22
			7	18.50	17.81	18.45	18.21
		15	0	18.50	17.79	18.34	18.18
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18625	18900	19175
					1852.5MHz	1880.0MHz	1907.5MHz
5MHz	QPSK	1	0	20.50	19.69	20.13	20.04
			12	20.50	19.89	20.32	20.19
			24	20.50	19.76	20.29	20.07
		12	0	19.50	18.74	19.22	19.04
			6	19.50	18.85	19.33	19.14
			13	19.50	18.86	19.33	19.18
		25	0	19.50	18.82	19.29	19.14
	16QAM	1	0	19.50	18.78	19.34	18.88
			12	20.00	18.97	19.61	19.03
			24	20.00	18.86	19.55	18.93
		12	0	18.50	17.77	18.27	18.08
			6	18.50	17.87	18.39	18.19
			13	18.50	17.88	18.37	18.20
		25	0	18.50	17.81	18.29	18.16

LTE-FDD Band 2				Maximum Tune-up(dBm)	18650	18900	19150
Bandwidth	Modulation	RB allocation	RB offset		1855.0MHz	1880.0MHz	1905.0MHz
10MHz	QPSK	1	0	20.50	19.84	20.02	20.14
			24	20.50	19.97	20.41	20.27
			49	20.50	19.81	20.41	20.16
		25	0	19.50	18.84	19.23	19.20
			12	19.50	18.88	19.33	19.14
			25	19.50	19.00	19.47	19.33
		50	0	19.50	18.94	19.37	19.28
	16QAM	1	0	20.00	18.89	19.61	19.09
			24	20.50	19.15	20.01	19.29
			49	20.00	18.94	19.97	19.16
		25	0	18.50	17.88	18.27	18.27
			12	18.50	17.89	18.40	18.20
			25	19.00	18.03	18.52	18.40
		50	0	18.50	17.94	18.35	18.26
		50	0	18.50	17.94	18.35	18.26
			0	18.50	17.94	18.35	18.26
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18675	18900	19125
					1857.5MHz	1880.0MHz	1902.5MHz
15MHz	QPSK	1	0	20.50	19.69	19.88	20.17
			37	20.50	19.85	20.30	20.12
			74	20.50	19.70	20.34	20.04
		37	0	19.50	18.83	19.14	19.30
			18	19.50	18.89	19.31	19.17
			38	20.00	18.89	19.50	19.24
		75	0	19.50	18.88	19.33	19.28
	16QAM	1	0	20.00	18.88	19.46	19.58
			37	20.00	19.01	19.89	19.48
			74	20.00	18.84	19.92	19.43
		37	0	18.50	17.85	18.18	18.28
			18	18.50	17.90	18.33	18.18
			38	19.00	17.86	18.56	18.23
		75	0	18.50	17.84	18.33	18.23
		75	0	18.50	17.84	18.33	18.23
			0	18.50	17.84	18.33	18.23
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	18700	18900	19100
					1860.0MHz	1880.0MHz	1900.0MHz
20MHz	QPSK	1	0	20.50	19.50	19.67	20.18
			49	21.00	19.96	20.50	20.32
			99	20.50	19.61	20.22	19.93
		50	0	19.50	18.73	19.13	19.42
			25	19.50	18.84	19.31	19.22
			50	19.50	18.74	19.48	19.21
		100	0	19.50	18.75	19.36	19.33
	16QAM	1	0	19.50	19.05	18.83	19.45
			49	20.00	19.47	19.70	19.56
			99	19.50	19.13	19.41	19.19
		50	0	18.50	17.72	18.13	18.38
			25	18.50	17.83	18.29	18.19
			50	19.00	17.74	18.51	18.20
		100	0	18.50	17.78	18.33	18.30
		100	0	18.50	17.78	18.33	18.30
			0	18.50	17.78	18.33	18.30

Band 4

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		19957	20175	20393
					1710.7MHz	1732.5MHz	1754.3MHz
1.4MHz	QPSK	1	0	18.00	17.71	14.33	11.41
			3	18.00	17.76	14.46	11.47
			5	18.00	17.59	14.22	11.39
		3	0	18.00	17.76	14.39	11.47
			2	18.00	17.72	14.29	11.49
			3	18.00	17.66	14.37	11.43
		6	0	17.00	16.74	13.33	10.50
	16QAM	1	0	17.00	16.64	13.34	10.33
			3	17.00	16.68	13.39	10.42
			5	17.00	16.51	13.23	10.12
		3	0	17.00	16.87	13.40	10.20
			2	17.00	16.89	13.40	10.18
			3	17.00	16.86	13.37	10.13
		6	0	16.00	15.67	12.34	8.92
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19965	20175	20385
					1711.5MHz	1732.5MHz	1753.5MHz
3MHz	QPSK	1	0	18.00	17.81	14.01	11.10
			7	18.00	17.76	13.94	11.14
			14	17.50	17.44	13.55	10.97
		8	0	17.00	16.68	12.91	10.02
			4	17.00	16.62	12.83	10.01
			7	17.00	16.51	12.73	9.94
		15	0	17.00	16.56	12.81	9.97
	16QAM	1	0	17.00	16.69	13.19	10.06
			7	17.00	16.68	13.10	10.08
			14	16.50	16.39	12.77	9.92
		8	0	16.00	15.69	12.07	9.05
			4	16.00	15.61	11.99	9.06
			7	15.50	15.44	11.86	8.99
		15	0	15.50	15.30	11.87	9.00
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	19976	20175	20375
					1712.5MHz	1732.5MHz	1752.5MHz
5MHz	QPSK	1	0	17.50	17.29	14.06	11.12
			12	17.00	16.94	13.80	11.02
			24	17.00	16.58	13.38	10.84
		12	0	16.50	16.06	12.94	10.07
			6	16.00	15.94	12.85	10.03
			13	16.00	15.71	12.60	9.93
		25	0	16.00	15.92	12.83	10.01
	16QAM	1	0	16.50	16.19	13.35	9.93
			12	16.00	15.96	13.08	9.85
			24	16.00	15.64	12.71	9.71
		12	0	15.50	15.05	12.03	9.08
			6	15.00	14.98	11.93	9.05
			13	15.00	14.73	11.72	8.96
		25	0	15.00	14.93	11.84	9.03

LTE-FDD Band 4				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20000	20175	20350
					1715.0MHz	1732.5MHz	1750.0MHz
10MHz	QPSK	1	0	17.50	17.22	14.46	11.77
			24	17.00	16.75	13.91	11.35
			49	16.00	15.89	13.12	10.91
		25	0	16.00	15.98	13.18	10.47
			12	16.00	15.61	12.86	10.24
			25	15.50	15.30	12.56	10.03
		50	0	16.00	15.67	12.89	10.25
	16QAM	1	0	16.50	16.18	13.65	11.20
			24	16.00	15.72	13.15	10.76
			49	15.00	14.90	12.29	10.40
		25	0	15.50	15.04	12.20	9.51
			12	15.00	14.69	11.88	9.25
			25	14.50	14.40	11.57	9.08
		50	0	15.00	14.70	11.91	9.26
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20025	20175	20325
					1717.5MHz	1732.5MHz	1747.5MHz
15MHz	QPSK	1	0	17.50	17.09	14.73	12.43
			37	16.50	16.21	13.79	11.55
			74	15.00	14.97	12.70	10.86
		37	0	16.00	15.81	13.36	11.35
			18	15.50	15.32	12.92	11.79
			38	15.00	14.66	12.35	10.40
		75	0	15.50	15.33	12.89	10.72
	16QAM	1	0	16.50	16.34	13.96	12.55
			37	16.00	15.60	12.99	11.53
			74	14.50	14.44	11.86	10.89
		37	0	15.00	14.84	12.40	10.67
			18	14.50	14.33	11.95	10.26
			38	14.00	13.68	11.37	9.81
		75	0	14.50	14.29	11.90	10.24
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20050	20175	20300
					1720.0MHz	1732.5MHz	1745.0MHz
20MHz	QPSK	1	0	17.50	17.42	15.05	13.05
			49	16.50	16.01	14.06	12.09
			99	15.00	14.70	12.31	10.77
		50	0	16.00	15.72	13.56	11.61
			25	15.00	14.99	12.92	10.97
			50	14.50	14.26	12.27	10.40
		100	0	15.50	15.09	12.92	11.03
	16QAM	1	0	16.50	16.43	14.28	12.35
			49	16.00	15.53	13.20	11.26
			99	14.00	13.76	11.44	9.99
		50	0	15.00	14.70	12.53	10.62
			25	14.00	13.98	11.93	9.96
			50	13.50	13.22	11.25	9.38
		100	0	14.50	14.06	11.93	10.03

Band 5

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20407	20525	20643
					824.7MHz	836.5MHz	848.3MHz
1.4MHz	QPSK	1	0	22.50	22.46	21.92	21.82
			3	22.50	22.20	21.98	21.98
			5	22.50	22.02	21.91	21.85
		3	0	22.50	22.06	22.04	21.90
			2	22.50	22.13	22.01	21.92
			3	22.50	22.08	21.96	21.90
		6	0	21.50	21.11	21.06	20.93
	16QAM	1	0	21.50	21.16	20.86	20.79
			3	21.50	21.26	20.97	20.94
			5	21.50	21.17	20.88	20.89
		3	0	21.50	21.06	21.14	20.98
			2	21.50	21.10	21.19	20.98
			3	21.50	21.09	21.15	20.95
		6	0	20.50	20.10	20.00	19.85
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20405	20525	20635
					824.5MHz	836.5MHz	847.5MHz
3MHz	QPSK	1	0	22.50	22.09	21.96	21.84
			7	22.50	22.24	22.09	21.97
			14	22.50	22.08	21.91	21.87
		8	0	21.50	21.09	21.00	20.91
			4	21.50	21.15	21.05	20.95
			7	21.50	21.10	20.96	20.91
		15	0	21.50	21.06	20.95	20.93
	16QAM	1	0	21.50	21.09	21.11	21.38
			7	22.00	21.26	21.24	21.50
			14	21.50	21.02	21.08	21.34
		8	0	20.50	20.12	19.94	20.04
			4	20.50	20.17	19.98	20.08
			7	20.50	20.15	19.90	20.04
		15	0	20.50	20.09	19.91	19.95

LTE-FDD Band 5				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		20425	20525	20625
					826.5MHz	836.5MHz	846.5MHz
5MHz	QPSK	1	0	22.00	21.90	21.82	21.78
			12	22.50	22.03	21.89	21.82
			24	22.00	21.93	21.76	21.72
		12	0	21.00	20.96	20.89	20.85
			6	21.50	21.06	20.92	20.87
			13	21.50	21.01	20.86	20.80
		25	0	21.50	21.02	20.88	20.83
	16QAM	1	0	21.50	21.00	21.08	20.63
			12	21.50	21.12	21.15	20.68
			24	21.50	21.04	20.99	20.61
		12	0	20.00	19.91	19.96	19.87
			6	20.50	20.04	19.96	19.90
			13	20.50	20.04	19.94	19.83
		25	0	20.50	20.01	19.88	19.84

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	20450	20525	20600
					829.0MHz	836.5MHz	844.0MHz
10MHz	QPSK	1	0	22.50	22.03	21.91	21.85
			24	22.50	22.24	22.01	21.94
			49	22.00	21.96	21.83	21.82
		25	0	21.50	21.07	21.00	20.97
			12	21.50	21.04	20.95	20.95
			25	21.50	21.06	20.94	20.90
		50	0	21.50	21.06	20.98	20.94
	16QAM	1	0	21.50	21.01	21.08	21.36
			24	22.00	21.22	21.15	21.51
			49	21.50	20.95	21.01	21.31
		25	0	20.50	20.13	20.00	20.01
			12	20.50	20.10	19.95	19.95
			25	20.50	20.12	19.96	19.94
		50	0	20.50	20.04	19.96	19.94

Band 12

LTE-FDD Band 12				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23017	23095	23173
					699.7MHz	707.5MHz	715.3MHz
1.4MHz	QPSK	1	0	22.50	22.08	22.10	22.27
			3	22.50	22.21	21.85	22.40
			5	22.50	22.15	21.75	22.14
		3	0	22.50	22.11	21.83	22.04
			2	22.50	22.14	21.84	21.93
			3	22.50	22.17	21.81	21.87
		6	0	21.50	21.14	20.80	20.88
	16QAM	1	0	21.50	21.04	20.84	20.90
			3	21.50	21.13	20.96	21.01
			5	21.50	21.08	21.28	20.92
		3	0	21.50	21.16	21.36	20.82
			2	21.50	21.17	21.38	20.84
			3	21.50	21.16	21.38	20.86
		6	0	20.50	20.03	20.25	19.91
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23025	23095	23165
					700.5MHz	707.5MHz	714.5MHz
3MHz	QPSK	1	0	22.00	21.60	21.70	21.79
			7	22.00	21.78	21.86	21.97
			14	22.00	21.65	21.74	21.85
		8	0	21.00	20.58	20.70	20.83
			4	21.00	20.62	20.79	20.87
			7	21.00	20.57	20.75	20.81
		15	0	21.00	20.55	20.73	20.80
	16QAM	1	0	21.50	20.56	21.25	20.78
			7	21.50	20.74	21.39	20.93
			14	21.50	21.20	21.28	20.80
		8	0	20.00	19.81	19.84	19.86
			4	20.00	19.75	19.92	19.92
			7	20.00	19.55	19.89	19.86
		15	0	20.00	19.53	19.76	19.82

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23035	23095	23155
					701.5MHz	707.5MHz	713.5MHz
5MHz	QPSK	1	0	22.00	21.45	21.58	21.62
			12	22.00	21.62	21.79	21.78
			24	22.00	21.60	21.69	21.70
		12	0	21.00	20.61	20.65	20.71
			6	21.00	20.60	20.74	20.76
			13	21.00	20.57	20.83	20.67
		25	0	21.00	20.60	20.74	20.74
			0	21.00	20.62	20.39	20.72
			12	21.00	20.80	20.59	20.87
	16QAM	1	24	21.00	20.80	20.52	20.77
			0	20.00	19.71	19.66	19.77
			6	20.00	19.65	19.77	19.78
		12	13	20.00	19.62	19.79	19.69
			0	20.00	19.59	19.76	19.75
			0	20.00	19.59	19.76	19.75
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23060	23095	23130
					704.0MHz	707.5MHz	711.0MHz
10MHz	QPSK	1	0	22.00	21.53	21.55	21.72
			24	22.00	21.83	21.81	21.91
			49	22.00	21.80	21.70	21.84
		25	0	21.00	20.75	20.66	20.67
			12	21.00	20.64	20.74	20.83
			25	21.00	20.78	20.84	20.79
		50	0	21.00	20.76	20.78	20.71
			0	21.00	20.50	20.68	20.85
			24	21.50	20.77	20.96	21.01
	16QAM	1	49	21.00	20.73	20.85	20.97
			0	20.00	19.82	19.68	19.68
			12	20.00	19.74	19.79	19.83
		25	25	20.00	19.85	19.88	19.79
			0	20.00	19.78	19.85	19.73
			0	20.00	19.78	19.85	19.73

Band 17

LTE-FDD Band 17				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		23755	23790	23825
5MHz	QPSK	1	0	22.00	21.68	21.75	21.75
			12	22.00	21.88	21.88	21.90
			24	22.00	21.79	21.77	21.80
		12	0	21.00	20.70	20.72	20.86
			6	21.00	20.83	20.85	20.87
			13	21.00	20.87	20.83	20.75
		25	0	21.00	20.86	20.81	20.82
			0	21.00	20.91	20.60	20.82
			12	21.50	21.12	20.74	20.94
	16QAM	1	24	21.50	21.05	20.63	20.84
			0	20.00	19.80	19.78	19.81
			6	20.00	19.87	19.88	19.90
		12	13	20.00	19.90	19.87	19.76
			0	20.00	19.81	19.84	19.86
			0	20.00	19.81	19.84	19.86

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	23780	23790	23800
					709.0MHz	710.0MHz	711.0MHz
10MHz	QPSK	1	0	22.00	21.75	21.71	21.79
			24	22.50	22.03	21.97	21.96
			49	22.00	21.91	21.87	21.94
		25	0	21.00	20.80	20.73	20.78
			12	21.00	20.94	20.89	20.91
			25	21.50	21.02	20.89	20.85
		50	0	21.00	20.90	20.85	20.81
	16QAM	1	0	21.50	20.84	21.21	20.75
			24	22.00	21.16	21.57	20.99
			49	21.50	21.06	21.37	20.87
		25	0	20.00	19.81	19.79	19.82
			12	20.00	19.95	19.94	19.99
			25	20.50	20.01	19.94	19.93
		50	0	20.00	19.93	19.85	19.85

Band 30

LTE-FDD Band 30				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		27685	27710	27735
5MHz	QPSK	1	0	21.50	21.26	20.87	20.99
			12	21.50	21.05	21.03	20.99
			24	21.00	20.92	20.91	20.90
		12	0	20.00	19.93	19.95	19.97
			6	20.50	20.05	20.01	19.97
			11	20.00	19.96	19.90	19.85
		25	0	20.00	19.95	19.93	19.91
	16QAM	1	0	20.50	19.79	19.98	20.13
			12	20.50	19.86	20.05	20.17
			24	20.50	19.69	19.98	20.10
		12	0	19.00	18.95	18.91	18.96
			6	19.50	19.02	18.97	19.02
			11	19.00	18.94	18.88	18.90
		25	0	19.00	18.97	18.92	18.87

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	27710
10MHz	QPSK	1	0	22.00	21.56
			24	21.50	21.22
			49	21.50	21.00
		25	0	20.50	20.00
			12	20.00	19.97
			25	20.00	19.88
		50	0	20.00	19.97
	16QAM	1	0	20.00	19.94
			24	20.50	20.10
			49	20.00	19.92
		25	0	19.50	19.03
			12	19.50	19.05
			25	19.00	18.95
		50	0	19.00	18.96

Band 66

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		131979	132322	132665
					1710.7MHz	1745.0MHz	1779.3MHz
1.4MHz	QPSK	1	0	23.00	22.78	22.39	22.12
			2	23.00	22.76	22.52	22.22
			5	23.00	22.63	22.44	22.11
		3	0	23.00	22.69	22.46	22.18
			2	23.00	22.75	22.46	22.22
			3	23.00	22.72	22.43	22.16
		6	0	22.00	21.67	21.47	21.19
	16QAM	1	0	22.00	21.57	21.36	21.22
			2	22.00	21.74	21.48	21.35
			5	22.00	21.62	21.41	21.21
		3	0	22.00	21.79	21.52	21.14
			2	22.00	21.77	21.53	21.17
			3	22.00	21.73	21.49	21.16
		6	0	21.00	20.60	20.39	20.16
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131987	132322	132657
					1711.5MHz	1745.0MHz	1778.5MHz
3MHz	QPSK	1	0	23.00	22.62	22.43	22.16
			7	23.00	22.77	22.53	22.30
			14	23.00	22.62	22.35	22.16
		8	0	22.00	21.68	21.42	21.13
			4	22.00	21.66	21.44	21.16
			7	22.00	21.66	21.39	21.14
		15	0	22.00	21.65	21.37	21.12
	16QAM	1	0	22.00	21.79	21.87	21.15
			7	22.00	21.94	21.98	21.26
			14	22.00	21.81	21.80	21.10
		8	0	21.00	20.64	20.53	20.19
			4	21.00	20.66	20.54	20.22
			7	21.00	20.62	20.50	20.20
		15	0	21.00	20.60	20.42	20.17

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	131997	132322	132647
					1712.5MHz	1745.0MHz	1777.5MHz
5MHz	QPSK	1	0	23.00	22.57	22.34	22.06
			13	23.00	22.69	22.42	22.17
			24	23.00	22.58	22.29	22.05
		12	0	22.00	21.64	21.33	21.08
			6	22.00	21.67	21.38	21.14
			13	22.00	21.63	21.35	21.14
		25	0	22.00	21.65	21.36	21.14
	16QAM	1	0	22.00	21.83	21.14	21.15
			13	22.00	21.97	21.23	21.26
			24	22.00	21.84	21.11	21.14
		12	0	21.00	20.69	20.36	20.12
			6	21.00	20.75	20.40	20.16
			13	21.00	20.69	20.39	20.11
		25	0	21.00	20.60	20.38	20.13

LTE-FDD Band 66				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		132022	132322	132622
					1715.0MHz	1745.0MHz	1775.0MHz
10MHz	QPSK	1	0	23.00	22.69	22.44	22.13
			25	23.00	22.80	22.51	22.26
			49	23.00	22.69	22.33	22.11
		25	0	22.00	21.72	21.42	21.18
			13	22.00	21.69	21.43	21.20
			25	22.00	21.65	21.43	21.26
		50	0	22.00	21.73	21.44	21.23
			25	22.00	21.80	21.63	21.79
			49	22.00	21.67	21.48	21.61
	25	0	21.00	20.81	20.43	20.21	
		13	21.00	20.79	20.43	20.25	
		25	21.00	20.75	20.47	20.30	
	50	0	21.00	20.75	20.43	20.24	
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132047	132322
1717.5MHz						1745.0MHz	1772.5MHz
15MHz	QPSK	1	0	23.00	22.59	22.38	22.05
			38	23.00	22.65	22.40	22.15
			74	22.50	22.49	22.23	22.05
		36	0	22.00	21.68	21.50	21.18
			18	22.00	21.68	21.48	21.18
			39	22.00	21.67	21.46	21.26
		75	0	22.00	21.74	21.50	21.26
			38	22.50	22.07	21.53	21.71
			74	22.00	21.89	21.36	21.57
	36	0	21.00	20.68	20.46	20.24	
		18	21.00	20.70	20.48	20.25	
		39	21.00	20.68	20.46	20.29	
	75	0	21.00	20.68	20.46	20.24	
	Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	132072	132322
1720.0MHz						1745.0MHz	1770.0MHz
20MHz	QPSK	1	0	22.50	22.41	22.24	21.91
			50	23.00	22.77	22.53	22.27
			99	22.50	22.34	22.04	21.84
		50	0	22.00	21.74	21.40	21.22
			25	22.00	21.64	21.43	21.20
			50	22.00	21.61	21.34	21.17
		100	0	22.00	21.67	21.39	21.19
			50	22.00	21.98	21.74	21.76
			99	22.00	21.52	21.34	21.38
	50	0	21.00	20.75	20.39	20.20	
		25	21.00	20.69	20.44	20.19	
		50	21.00	20.65	20.33	20.19	
	100	0	21.00	20.69	20.37	20.18	

Band 71

LTE-FDD Band 71				Maximum Tune-up(dBm)	Conducted Power(dBm)		
Bandwidth	Modulation	RB allocation	RB offset		133147	133297	133447
					665.5MHz	680.5MHz	695.5MHz
5MHz	QPSK	1	0	22.00	21.56	21.33	21.33
			13	22.00	21.74	21.48	21.53
			24	22.00	21.53	21.32	21.46
		12	0	20.50	20.49	20.38	20.39
			6	21.00	20.65	20.44	20.49
			13	21.00	20.57	20.39	20.46
		25	0	21.00	20.53	20.42	20.43
	16QAM	1	0	21.00	20.71	20.20	20.41
			13	21.00	20.96	20.32	20.59
			24	21.00	20.75	20.21	20.51
		12	0	19.50	19.48	19.38	19.48
			6	20.00	19.66	19.43	19.50
			13	20.00	19.59	19.37	19.45
		25	0	19.50	19.47	19.39	19.46
Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	133172	133297	133422
					668.0MHz	680.5MHz	693.0MHz
10MHz	QPSK	1	0	22.00	21.64	21.48	21.40
			25	22.00	21.72	21.57	21.53
			49	22.00	21.62	21.46	21.52
		25	0	21.00	20.61	20.47	20.49
			13	21.00	20.63	20.53	20.51
			25	21.00	20.62	20.46	20.51
		50	0	21.00	20.59	20.45	20.52
	16QAM	1	0	21.00	20.63	20.66	20.90
			25	21.50	20.70	20.75	21.15
			49	21.50	20.59	20.60	21.06
		25	0	20.00	19.65	19.46	19.54
			13	20.00	19.68	19.52	19.53
			25	20.00	19.65	19.46	19.57
		50	0	20.00	19.56	19.44	19.48

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	133197	133297	133397
					670.5MHz	680.5MHz	690.5MHz
15MHz	QPSK	1	0	22.00	21.53	21.46	21.32
			38	22.00	21.57	21.50	21.49
			74	22.00	21.49	21.35	21.51
		36	0	21.00	20.67	20.48	20.49
			18	21.00	20.63	20.52	20.50
			39	21.00	20.72	20.43	20.58
		75	0	21.00	20.72	20.46	20.53
	16QAM	1	0	21.00	20.84	20.59	20.87
			38	21.50	20.94	20.65	21.02
			74	21.50	20.88	20.48	21.03
		36	0	20.00	19.62	19.52	19.53
			18	20.00	19.62	19.50	19.52
			39	20.00	19.67	19.45	19.65
		75	0	20.00	19.63	19.48	19.52

Bandwidth	Modulation	RB allocation	RB offset	Maximum Tune-up(dBm)	133222	133322	133372
					673.0MHz	683.0MHz	688.0MHz
20MHz	QPSK	1	0	21.50	21.39	21.27	21.26
			50	22.00	21.70	21.55	21.57
			99	21.50	21.29	21.27	21.36
		50	0	21.00	20.70	20.41	20.55
			25	21.00	20.59	20.47	20.47
			50	21.00	20.72	20.44	20.51
		100	0	21.00	20.73	20.44	20.49
	16QAM	1	0	21.00	20.60	20.84	20.41
			50	21.50	20.99	21.10	20.74
			99	21.00	20.54	20.81	20.55
		50	0	20.00	19.65	19.40	19.53
			25	20.00	19.54	19.47	19.47
			50	20.00	19.65	19.45	19.48
		100	0	20.00	19.67	19.45	19.53

8.4 Wi-Fi 2.4G

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	17.61	18.00	Yes
		6	2437	17.57	18.00	No
		11	2462	17.17	17.50	No
	802.11g	1	2412	21.61	22.00	No
		6	2437	21.19	21.50	No
		11	2462	21.74	22.00	No
	802.11n(HT20)	1	2412	20.78	21.00	No
		6	2437	21.21	21.50	No
		11	2462	17.36	17.50	No
	802.11n(HT40)	3	2422	14.09	14.50	No
		6	2437	14.73	15.00	No
		9	2452	14.73	15.00	No

Note: SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2\text{W/kg}$.

5G

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-1 (5.150~5.250)	802.11a	36	5180	11.32	11.50	No
		40	5200	11.41	11.50	No
		48	5240	11.39	11.50	No
	802.11n(HT20)	36	5180	11.10	11.50	No
		40	5200	11.54	12.00	No
		48	5240	11.66	12.00	No
	802.11n(HT40)	38	5190	11.81	12.00	No
		46	5230	12.12	12.50	Yes

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2a (5.250~5.350)	802.11a	52	5260	11.43	11.50	No
		60	5300	11.83	12.00	Yes
		64	5320	11.65	12.00	No
	802.11n(HT20)	52	5260	11.38	11.50	No
		60	5300	11.28	11.50	No
		64	5320	11.22	11.50	No
	802.11n(HT40)	54	5270	11.40	11.50	No
		62	5310	11.72	12.00	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-3 (5.725~5.850)	802.11a	149	5745	11.79	12.00	No
		157	5785	11.41	11.50	No
		165	5825	10.61	11.00	No
	802.11n(HT20)	149	5745	11.74	12.00	No
		157	5785	11.39	11.50	No
		165	5825	10.52	11.00	No
	802.11n(HT40)	151	5755	12.66	13.00	Yes
		159	5795	11.84	12.00	No

8.5 Bluetooth

EDR	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	39	78
			2402MHz	2441MHz	2480MHz
			6.56	6.94	7.06
BLE	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	20	39
			2402MHz	2440MHz	2480MHz
			1Mbps	-1.56	-1.43
BLE	Mode	Maximum Tune-up(dBm)	Average Conducted Output Power (dBm)		
			0	20	39
			2402MHz	2440MHz	2480MHz
			2Mbps	-1.57	-1.42

Channel	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Power thresholds (mW)	RF exposure evaluation required
78	2.480	7.50	5.62	0	2.72	Yes
78	2.480	7.50	5.62	10	10.17	No

Note

- Per KDB 447498 D04 Interim General RF Exposure Guidance v01, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at test separation distances ≤ 40 cm are determined by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \leq 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \leq 40\text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$P_{th} \text{ (mW)} = ERP_{20\text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases} \quad (\text{B. 1})$$


and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{ cm}}$ is per Formula (B.1).

*When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR.

- Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
- The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

9. Test Exclusion Consideration

Antenna information :



WWAN Main Antenna	GSM/WCDMA/LTE TX/RX
WLAN/BT Antenna	WLAN/BT TX/RX
Note: 1. KDB 447498 D01v06, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm. 2. Per KDB648474 D04, 10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR<1.2W/Kg.	

Distance of The Antenna to the EUT surface and edge (mm)						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	<25	<25	<25	57	141	<25
BT/Wifi	<25	<25	62	<25	<25	140

Positions for SAR tests: Hotspot mode						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
WWAN	Yes	Yes	Yes	No	No	Yes
BT/Wifi	Yes	Yes	No	Yes	Yes	No

9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

$$(\text{max.power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$$

W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

0.4 W/Kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

Mode	Position	Channel	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Estimated SAR (W/kg)
Bluetooth	Body	78	2.480	7.50	5.62	10	0.118

10. Test Result

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GSM 850 voice	Left Cheek	190	836.6	-1.258	0.291	100.00	1.000	32.26	32.50	1.057	0.308	/
	Left Tilt	190	836.6	3.512	0.143	100.00	1.000	32.26	32.50	1.057	0.151	/
	Right Cheek	190	836.6	2.980	0.308	100.00	1.000	32.26	32.50	1.057	0.326	1#
	Right Tilt	190	836.6	1.350	0.165	100.00	1.000	32.26	32.50	1.057	0.174	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GPRS 850+4slots	Front	190	836.6	-2.140	0.369	100.00	1.000	28.75	29.00	1.059	0.391	/
	Back	190	836.6	1.950	0.504	100.00	1.000	28.75	29.00	1.059	0.534	2#
	Left	190	836.6	-3.880	0.271	100.00	1.000	28.75	29.00	1.059	0.287	/
	Bottom	190	836.6	-4.170	0.165	100.00	1.000	28.75	29.00	1.059	0.175	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GSM 1900 voice	Left Cheek	810	1909.8	-2.158	0.152	100.00	1.000	27.76	28.00	1.057	0.161	/
	Left Tilt	810	1909.8	3.125	0.074	100.00	1.000	27.76	28.00	1.057	0.078	/
	Right Cheek	810	1909.8	1.800	0.159	100.00	1.000	27.76	28.00	1.057	0.168	3#
	Right Tilt	810	1909.8	2.190	0.081	100.00	1.000	27.76	28.00	1.057	0.086	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
GPRS 1900+4slots	Front	810	1909.8	1.930	0.533	100.00	1.000	24.87	25.00	1.030	0.549	4#
	Back	810	1909.8	4.580	0.506	100.00	1.000	24.87	25.00	1.030	0.521	/
	Left	810	1909.8	2.920	0.525	100.00	1.000	24.87	25.00	1.030	0.541	/
	Bottom	810	1909.8	-0.340	0.369	100.00	1.000	24.87	25.00	1.030	0.380	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 2 (RMC*)	Left Cheek	9400	1880.0	2.458	0.242	100.00	1.000	19.88	20.00	1.028	0.249	/
	Left Tilt	9400	1880.0	-2.145	0.146	100.00	1.000	19.88	20.00	1.028	0.150	/
	Right Cheek	9400	1880.0	3.380	0.249	100.00	1.000	19.88	20.00	1.028	0.256	5#
	Right Tilt	9400	1880.0	1.254	0.151	100.00	1.000	19.88	20.00	1.028	0.155	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 2 (RMC*)	Front	9400	1880.0	1.780	0.235	100.00	1.000	19.88	20.00	1.028	0.242	6#
	Back	9400	1880.0	2.140	0.201	100.00	1.000	19.88	20.00	1.028	0.207	/
	Left	9400	1880.0	-3.691	0.231	100.00	1.000	19.88	20.00	1.028	0.237	/
	Bottom	9400	1880.0	-1.257	0.159	100.00	1.000	19.88	20.00	1.028	0.163	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 4 (RMC*)	Left Cheek	1312	1712.4	2.540	0.284	100.00	1.000	16.69	17.00	1.074	0.305	/
	Left Tilt	1312	1712.4	-3.154	0.158	100.00	1.000	16.69	17.00	1.074	0.170	/
	Right Cheek	1312	1712.4	-2.120	0.295	100.00	1.000	16.69	17.00	1.074	0.317	7#
	Right Tilt	1312	1712.4	1.261	0.162	100.00	1.000	16.69	17.00	1.074	0.174	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 4 (RMC*)	Front	1312	1712.4	1.360	0.318	100.00	1.000	16.69	17.00	1.074	0.342	8#
	Back	1312	1712.4	3.251	0.283	100.00	1.000	16.69	17.00	1.074	0.304	/
	Left	1312	1712.4	-2.125	0.312	100.00	1.000	16.69	17.00	1.074	0.335	/
	Bottom	1312	1712.4	0.364	0.241	100.00	1.000	16.69	17.00	1.074	0.259	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 5 (RMC*)	Left Cheek	4132	826.4	-1.365	0.185	100.00	1.000	21.80	22.00	1.047	0.194	/
	Left Tilt	4132	826.4	3.584	0.099	100.00	1.000	21.80	22.00	1.047	0.104	/
	Right Cheek	4132	826.4	-2.350	0.190	100.00	1.000	21.80	22.00	1.047	0.199	9#
	Right Tilt	4132	826.4	1.451	0.102	100.00	1.000	21.80	22.00	1.047	0.107	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
WCDMA Band 5 (RMC*)	Front	4132	826.4	0.354	0.145	100.00	1.000	21.80	22.00	1.047	0.152	/
	Back	4132	826.4	-3.390	0.153	100.00	1.000	21.80	22.00	1.047	0.160	10#
	Left	4132	826.4	2.510	0.143	100.00	1.000	21.80	22.00	1.047	0.150	/
	Bottom	4132	826.4	3.961	0.124	100.00	1.000	21.80	22.00	1.047	0.130	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 2 (BW: 20MHz)	1RB	Left Cheek	18900	1880.0	-2.310	0.252	100.00	1.000	20.50	21.00	1.122	0.283	/
		Left Tilt	18900	1880.0	2.124	0.135	100.00	1.000	20.50	21.00	1.122	0.151	/
		Right Cheek	18900	1880.0	-1.510	0.257	100.00	1.000	20.50	21.00	1.122	0.288	11#
		Right Tilt	18900	1880.0	2.369	0.138	100.00	1.000	20.50	21.00	1.122	0.155	/
	50%RB	Left Cheek	18900	1880.0	4.210	0.241	100.00	1.000	19.48	19.50	1.005	0.242	/
		Left Tilt	18900	1880.0	3.102	0.126	100.00	1.000	19.48	19.50	1.005	0.127	/
		Right Cheek	18900	1880.0	1.021	0.245	100.00	1.000	19.48	19.50	1.005	0.246	/
		Right Tilt	18900	1880.0	2.210	0.131	100.00	1.000	19.48	19.50	1.005	0.132	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas. SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 2 (BW: 20MHz)	1RB	Front	18900	1880.0	0.650	0.304	100.00	1.000	20.50	21.00	1.122	0.341	12#
		Back	18900	1880.0	0.962	0.298	100.00	1.000	20.50	21.00	1.122	0.334	/
		Left	18900	1880.0	1.025	0.212	100.00	1.000	20.50	21.00	1.122	0.238	/
		Bottom	18900	1880.0	3.210	0.231	100.00	1.000	20.50	21.00	1.122	0.259	/
	50%RB	Front	18900	1880.0	-3.025	0.301	100.00	1.000	19.48	19.50	1.005	0.303	/
		Back	18900	1880.0	1.698	0.291	100.00	1.000	19.48	19.50	1.005	0.292	/
		Left	18900	1880.0	3.021	0.205	100.00	1.000	19.48	19.50	1.005	0.206	/
		Bottom	18900	1880.0	2.047	0.228	100.00	1.000	19.48	19.50	1.005	0.229	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 4 (BW: 20MHz)	1RB	Left Cheek	20070	1722.0	3.021	0.271	100.00	1.000	17.42	17.50	1.019	0.276	/
		Left Tilt	20070	1722.0	1.251	0.148	100.00	1.000	17.42	17.50	1.019	0.151	/
		Right Cheek	20070	1722.0	0.630	0.276	100.00	1.000	17.42	17.50	1.019	0.281	13#
		Right Tilt	20070	1722.0	-3.012	0.150	100.00	1.000	17.42	17.50	1.019	0.153	/
	50%RB	Left Cheek	20070	1722.0	2.015	0.273	100.00	1.000	15.72	16.00	1.067	0.291	/
		Left Tilt	20070	1722.0	0.256	0.147	100.00	1.000	15.72	16.00	1.067	0.157	/
		Right Cheek	20070	1722.0	1.250	0.269	100.00	1.000	15.72	16.00	1.067	0.287	/
		Right Tilt	20070	1722.0	4.011	0.143	100.00	1.000	15.72	16.00	1.067	0.153	/
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 4 (BW: 20MHz)	1RB	Front	20070	1722.0	-0.580	0.470	100.00	1.000	17.42	17.50	1.019	0.479	14#
		Back	20070	1722.0	0.521	0.465	100.00	1.000	17.42	17.50	1.019	0.474	/
		Left	20070	1722.0	1.310	0.398	100.00	1.000	17.42	17.50	1.019	0.406	/
		Bottom	20070	1722.0	2.240	0.245	100.00	1.000	17.42	17.50	1.019	0.250	/
	50%RB	Front	20070	1722.0	-2.513	0.463	100.00	1.000	15.72	16.00	1.067	0.494	/
		Back	20070	1722.0	0.620	0.452	100.00	1.000	15.72	16.00	1.067	0.482	/
		Left	20070	1722.0	3.521	0.385	100.00	1.000	15.72	16.00	1.067	0.411	/
		Bottom	20070	1722.0	-2.154	0.241	100.00	1.000	15.72	16.00	1.067	0.257	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 5 (BW: 10MHz)	1RB	Left Cheek	20450	829.0	1.021	0.189	100.00	1.000	22.24	24.50	1.683	0.318	/
		Left Tilt	20450	829.0	2.025	0.097	100.00	1.000	22.24	24.50	1.683	0.163	/
		Right Cheek	20450	829.0	-1.230	0.193	100.00	1.000	22.24	24.50	1.683	0.325	15#
		Right Tilt	20450	829.0	3.021	0.102	100.00	1.000	22.24	24.50	1.683	0.172	/
	50%RB	Left Cheek	20450	829.0	0.213	0.184	100.00	1.000	21.07	21.50	1.104	0.203	/
		Left Tilt	20450	829.0	-3.201	0.095	100.00	1.000	21.07	21.50	1.104	0.105	/
		Right Cheek	20450	829.0	2.102	0.190	100.00	1.000	21.07	21.50	1.104	0.210	/
		Right Tilt	20450	829.0	1.635	0.096	100.00	1.000	21.07	21.50	1.104	0.106	/
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 5 (BW: 10MHz)	1RB	Front	20450	829.0	1.552	0.120	100.00	1.000	22.24	24.50	1.683	0.202	/
		Back	20450	829.0	-2.060	0.124	100.00	1.000	22.24	24.50	1.683	0.209	16#
		Left	20450	829.0	0.221	0.118	100.00	1.000	22.24	24.50	1.683	0.199	/
		Bottom	20450	829.0	3.011	0.103	100.00	1.000	22.24	24.50	1.683	0.173	/
	50%RB	Front	20450	829.0	0.269	0.119	100.00	1.000	21.07	21.50	1.104	0.131	/
		Back	20450	829.0	2.025	0.122	100.00	1.000	21.07	21.50	1.104	0.135	/
		Left	20450	829.0	-2.025	0.115	100.00	1.000	21.07	21.50	1.104	0.127	/
		Bottom	20450	829.0	-1.021	0.101	100.00	1.000	21.07	21.50	1.104	0.112	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 12 (BW: 10MHz)	1RB	Left Cheek	23130	711.0	0.219	0.101	100.00	1.000	21.91	22.00	1.021	0.103	/
		Left Tilt	23130	711.0	-2.301	0.059	100.00	1.000	21.91	22.00	1.021	0.060	/
		Right Cheek	23130	711.0	-3.700	0.107	100.00	1.000	21.91	22.00	1.021	0.109	17#
		Right Tilt	23130	711.0	3.202	0.063	100.00	1.000	21.91	22.00	1.021	0.064	/
	50%RB	Left Cheek	23130	711.0	4.012	0.096	100.00	1.000	20.83	21.00	1.040	0.100	/
		Left Tilt	23130	711.0	0.951	0.051	100.00	1.000	20.83	21.00	1.040	0.053	/
		Right Cheek	23130	711.0	1.230	0.104	100.00	1.000	20.83	21.00	1.040	0.108	/
		Right Tilt	23130	711.0	3.021	0.061	100.00	1.000	20.83	21.00	1.040	0.063	/
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 12 (BW: 10MHz)	1RB	Front	23130	711.0	3.620	0.200	100.00	1.000	21.91	22.00	1.021	0.204	/
		Back	23130	711.0	-2.200	0.204	100.00	1.000	21.91	22.00	1.021	0.208	18#
		Left	23130	711.0	2.209	0.195	100.00	1.000	21.91	22.00	1.021	0.199	/
		Bottom	23130	711.0	1.254	0.165	100.00	1.000	21.91	22.00	1.021	0.168	/
	50%RB	Front	23130	711.0	-3.021	0.198	100.00	1.000	20.83	21.00	1.040	0.206	/
		Back	23130	711.0	-0.961	0.201	100.00	1.000	20.83	21.00	1.040	0.209	/
		Left	23130	711.0	2.018	0.184	100.00	1.000	20.83	21.00	1.040	0.191	/
		Bottom	23130	711.0	1.129	0.159	100.00	1.000	20.83	21.00	1.040	0.165	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g SAR Meas (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 17 (BW: 10MHz)	1RB	Left Cheek	23780	709.0	3.951	0.092	100.00	1.000	22.03	22.50	1.114	0.102	/
		Left Tilt	23780	709.0	2.051	0.057	100.00	1.000	22.03	22.50	1.114	0.063	/
		Right Cheek	23780	709.0	-1.860	0.104	100.00	1.000	22.03	22.50	1.114	0.116	19#
		Right Tilt	23780	709.0	-2.031	0.061	100.00	1.000	22.03	22.50	1.114	0.068	/
	50%RB	Left Cheek	23780	709.0	2.018	0.089	100.00	1.000	21.02	21.50	1.117	0.099	/
		Left Tilt	23780	709.0	3.954	0.053	100.00	1.000	21.02	21.50	1.117	0.059	/
		Right Cheek	23780	709.0	2.329	0.103	100.00	1.000	21.02	21.50	1.117	0.115	/
		Right Tilt	23780	709.0	3.241	0.063	100.00	1.000	21.02	21.50	1.117	0.070	/
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 17 (BW: 10MHz)	1RB	Front	23780	709.0	3.021	0.161	100.00	1.000	22.03	22.50	1.114	0.179	/
		Back	23780	709.0	-2.260	0.166	100.00	1.000	22.03	22.50	1.114	0.185	20#
		Left	23780	709.0	2.954	0.143	100.00	1.000	22.03	22.50	1.114	0.159	/
		Bottom	23780	709.0	1.230	0.119	100.00	1.000	22.03	22.50	1.114	0.133	/
	50%RB	Front	23780	709.0	3.018	0.159	100.00	1.000	21.02	21.50	1.117	0.178	/
		Back	23780	709.0	-2.010	0.162	100.00	1.000	21.02	21.50	1.117	0.181	/
		Left	23780	709.0	1.962	0.141	100.00	1.000	21.02	21.50	1.117	0.157	/
		Bottom	23780	709.0	2.201	0.114	100.00	1.000	21.02	21.50	1.117	0.127	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 30 (BW: 10MHz)	1RB	Left Cheek	27710	2310	2.095	0.109	100.00	1.000	21.56	22.00	1.107	0.121	/
		Left Tilt	27710	2310	0.297	0.068	100.00	1.000	21.56	22.00	1.107	0.075	/
		Right Cheek	27710	2310	-1.900	0.113	100.00	1.000	21.56	22.00	1.107	0.125	21#
		Right Tilt	27710	2310	3.021	0.072	100.00	1.000	21.56	22.00	1.107	0.080	/
	50%RB	Left Cheek	27710	2310	1.239	0.105	100.00	1.000	20.00	20.50	1.122	0.118	/
		Left Tilt	27710	2310	4.120	0.064	100.00	1.000	20.00	20.50	1.122	0.072	/
		Right Cheek	27710	2310	3.055	0.110	100.00	1.000	20.00	20.50	1.122	0.123	/
		Right Tilt	27710	2310	0.362	0.071	100.00	1.000	20.00	20.50	1.122	0.080	/
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 30 (BW: 10MHz)	1RB	Front	27710	2310	-1.940	0.077	100.00	1.000	21.56	22.00	1.107	0.085	22#
		Back	27710	2310	2.567	0.071	100.00	1.000	21.56	22.00	1.107	0.079	/
		Left	27710	2310	2.013	0.063	100.00	1.000	21.56	22.00	1.107	0.070	/
		Bottom	27710	2310	3.201	0.051	100.00	1.000	21.56	22.00	1.107	0.056	/
	50%RB	Front	27710	2310	2.019	0.074	100.00	1.000	20.00	20.50	1.122	0.083	/
		Back	27710	2310	3.210	0.069	100.00	1.000	20.00	20.50	1.122	0.077	/
		Left	27710	2310	0.024	0.060	100.00	1.000	20.00	20.50	1.122	0.067	/
		Bottom	27710	2310	1.025	0.059	100.00	1.000	20.00	20.50	1.122	0.066	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g SAR Meas (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 66 (BW: 20MHz)	1RB	Left Cheek	132072	1720.0	2.390	0.353	100.00	1.000	22.77	23.00	1.054	0.372	/
		Left Tilt	132072	1720.0	3.268	0.179	100.00	1.000	22.77	23.00	1.054	0.189	/
		Right Cheek	132072	1720.0	-4.780	0.359	100.00	1.000	22.77	23.00	1.054	0.378	23#
	50%RB	Right Tilt	132072	1720.0	1.950	0.186	100.00	1.000	22.77	23.00	1.054	0.196	/
		Left Cheek	132072	1720.0	2.029	0.351	100.00	1.000	21.74	22.00	1.062	0.373	/
		Left Tilt	132072	1720.0	-2.368	0.175	100.00	1.000	21.74	22.00	1.062	0.186	/
		Right Cheek	132072	1720.0	0.395	0.353	100.00	1.000	21.74	22.00	1.062	0.375	/
		Right Tilt	132072	1720.0	2.953	0.181	100.00	1.000	21.74	22.00	1.062	0.192	/
Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 66 (BW: 20MHz)	1RB	Front	132072	1720.0	-0.520	0.538	100.00	1.000	22.77	23.00	1.054	0.567	24#
		Back	132072	1720.0	2.064	0.529	100.00	1.000	22.77	23.00	1.054	0.558	/
		Left	132072	1720.0	1.362	0.469	100.00	1.000	22.77	23.00	1.054	0.494	/
		Bottom	132072	1720.0	0.563	0.443	100.00	1.000	22.77	23.00	1.054	0.467	/
	50%RB	Front	132072	1720.0	2.265	0.531	100.00	1.000	21.74	22.00	1.062	0.564	/
		Back	132072	1720.0	0.128	0.521	100.00	1.000	21.74	22.00	1.062	0.553	/
		Left	132072	1720.0	-2.058	0.459	100.00	1.000	21.74	22.00	1.062	0.487	/
		Bottom	132072	1720.0	0.652	0.435	100.00	1.000	21.74	22.00	1.062	0.462	/

Head(0mm gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 71 (BW: 20MHz)	1RB	Left Cheek	133222	673.0	2.105	0.086	100.00	1.000	21.70	22.00	1.072	0.092	/
		Left Tilt	133222	673.0	2.854	0.047	100.00	1.000	21.70	22.00	1.072	0.050	/
		Right Cheek	133222	673.0	-1.050	0.091	100.00	1.000	21.70	22.00	1.072	0.098	25#
		Right Tilt	133222	673.0	1.026	0.051	100.00	1.000	21.70	22.00	1.072	0.055	/
	50%RB	Left Cheek	133222	673.0	-3.201	0.085	100.00	1.000	20.72	21.00	1.067	0.091	/
		Left Tilt	133222	673.0	4.210	0.043	100.00	1.000	20.72	21.00	1.067	0.046	/
		Right Cheek	133222	673.0	1.395	0.088	100.00	1.000	20.72	21.00	1.067	0.094	/
		Right Tilt	133222	673.0	0.248	0.050	100.00	1.000	20.72	21.00	1.067	0.053	/

Body(hotspot open, 10mm Gap)													
Mode	Channel Type	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Band 71 (BW: 20MHz)	1RB	Front	133222	673.0	0.369	0.139	100.00	1.000	21.70	22.00	1.072	0.149	/
		Back	133222	673.0	-4.540	0.141	100.00	1.000	21.70	22.00	1.072	0.151	26#
		Left	133222	673.0	2.031	0.125	100.00	1.000	21.70	22.00	1.072	0.134	/
		Bottom	133222	673.0	3.125	0.122	100.00	1.000	21.70	22.00	1.072	0.131	/
	50%RB	Front	133222	673.0	1.284	0.137	100.00	1.000	20.72	21.00	1.067	0.146	/
		Back	133222	673.0	2.321	0.140	100.00	1.000	20.72	21.00	1.067	0.149	/
		Left	133222	673.0	1.254	0.121	100.00	1.000	20.72	21.00	1.067	0.129	/
		Bottom	133222	673.0	2.648	0.135	100.00	1.000	20.72	21.00	1.067	0.144	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835)	Left Cheek	1	2412	2.115	0.130	100.00	1.000	17.61	18.00	1.094	0.142	/
	Left Tilt	1	2412	1.365	0.100	100.00	1.000	17.61	18.00	1.094	0.109	/
	Right Cheek	1	2412	-1.090	0.133	100.00	1.000	17.61	18.00	1.094	0.146	27#
	Right Tilt	1	2412	-0.630	0.101	100.00	1.000	17.61	18.00	1.094	0.110	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835) 802.11b	Front	1	2412	2.210	0.036	100.00	1.000	17.61	18.00	1.094	0.039	/
	Back	1	2412	-1.330	0.057	100.00	1.000	17.61	18.00	1.094	0.062	28#
	Right	1	2412	1.480	0.045	100.00	1.000	17.61	18.00	1.094	0.049	/
	Top	1	2412	-1.180	0.033	100.00	1.000	17.61	18.00	1.094	0.036	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11n(HT40)	Left Cheek	46	5230	2.361	0.199	100.00	1.000	12.12	12.50	1.091	0.217	/
	Left Tilt	46	5230	0.361	0.174	100.00	1.000	12.12	12.50	1.091	0.190	/
	Right Cheek	46	5230	-1.350	0.201	100.00	1.000	12.12	12.50	1.091	0.219	29#
	Right Tilt	46	5230	0.784	0.178	100.00	1.000	12.12	12.50	1.091	0.194	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11n(HT40)	Front	46	5230	2.651	0.147	100.00	1.000	12.12	12.50	1.091	0.160	/
	Back	46	5230	-1.870	0.152	100.00	1.000	12.12	12.50	1.091	0.166	30#
	Right	46	5230	2.301	0.135	100.00	1.000	12.12	12.50	1.091	0.147	/
	Top	46	5230	1.621	0.149	100.00	1.000	12.12	12.50	1.091	0.163	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2a (5.250~5.350) 802.11a	Left Cheek	60	5300	-2.510	0.264	100.00	1.000	11.83	12.00	1.040	0.275	/
	Left Tilt	60	5300	2.651	0.241	100.00	1.000	11.83	12.00	1.040	0.251	/
	Right Cheek	60	5300	-3.030	0.278	100.00	1.000	11.83	12.00	1.040	0.289	31#
	Right Tilt	60	5300	1.951	0.245	100.00	1.000	11.83	12.00	1.040	0.255	/

Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2a (5.250~5.350) 802.11a	Front	60	5300	2.653	0.094	100.00	1.000	11.83	12.00	1.040	0.098	/
	Back	60	5300	3.920	0.099	100.00	1.000	11.83	12.00	1.040	0.103	32#
	Right	60	5300	-0.987	0.082	100.00	1.000	11.83	12.00	1.040	0.085	/
	Top	60	5300	1.265	0.076	100.00	1.000	11.83	12.00	1.040	0.079	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11n(HT40)	Left Cheek	151	5755	2.301	0.182	100.00	1.000	12.66	13.00	1.081	0.197	/
	Left Tilt	151	5755	2.054	0.148	100.00	1.000	12.66	13.00	1.081	0.160	/
	Right Cheek	151	5755	-2.160	0.188	100.00	1.000	12.66	13.00	1.081	0.203	33#
	Right Tilt	151	5755	1.694	0.150	100.00	1.000	12.66	13.00	1.081	0.162	/
Body(hotspot open, 10mm Gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11n(HT40)	Front	151	5755	2.941	0.132	100.00	1.000	12.66	13.00	1.081	0.143	/
	Back	151	5755	3.540	0.144	100.00	1.000	12.66	13.00	1.081	0.156	34#
	Right	151	5755	1.025	0.125	100.00	1.000	12.66	13.00	1.081	0.135	/
	Top	151	5755	-2.651	0.123	100.00	1.000	12.66	13.00	1.081	0.133	/

Head(0mm gap)												
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Duty cycle (%)	Duty cycle Factor	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
Bluetooth	Left Cheek	78	2.480	2.621	0.068	100.00	1.000	7.06	7.50	1.107	0.075	/
	Left Tilt	78	2.480	3.201	0.040	100.00	1.000	7.06	7.50	1.107	0.044	/
	Right Cheek	78	2.480	-1.650	0.072	100.00	1.000	7.06	7.50	1.107	0.080	35#
	Right Tilt	78	2.480	1.350	0.043	100.00	1.000	7.06	7.50	1.107	0.048	/

Note:

- Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8W/kg$, other channels SAR testing is not necessary.
- Per KDB 447498 D01 v06, head/body-worn use is evaluated with the device positioned at 0mm/10 mm from a head/flat phantom respectively filled with head tissue-equivalent medium.
- Per KDB Publication 941225 D06 where SAR test considerations for handsets (L x W ≥ 9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.
- Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor= $10^{[(\text{tune-up limit power(dBm)} - \text{Ave.power power (dBm)})/10]}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

11. SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.538 < 0.80$ W/kg, repeated measurement is not required.

12. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 2 Tx antennas, WWAN main antenna, Wifi/BT antenna supports 2.4G/5G Wi-Fi and BT. The 2 antennas can always transmit simultaneously. The work mode combination is showed as below table.

Application Simultaneous Transmission information:

NO.	Configuration	Body-worn
1	WWAN+WIFI(2.4g)	Yes
2	WWAN+WIFI(5g)	Yes
3	WWAN+BT	Yes

12.2 Sum SAR of Simultaneous Transmission

Head

Band	Test Position	Scaled SAR				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
		WWAN	WIFI 2.4G	WIFI 5G	BT					
GSM850 (voice)	Left Cheek	0.308	0.142	0.275	0.075	0.450	0.583	0.383	N/A	N/A
	Left Tilt	0.151	0.109	0.251	0.044	0.260	0.402	0.195	N/A	N/A
	Right Cheek	0.326	0.146	0.289	0.080	0.472	0.615	0.406	N/A	N/A
	Right Tilt	0.174	0.110	0.255	0.048	0.284	0.429	0.222	N/A	N/A
GSM1900 (voice)	Left Cheek	0.161	0.142	0.275	0.075	0.303	0.436	0.236	N/A	N/A
	Left Tilt	0.078	0.109	0.251	0.044	0.187	0.329	0.122	N/A	N/A
	Right Cheek	0.168	0.146	0.289	0.080	0.314	0.457	0.248	N/A	N/A
	Right Tilt	0.086	0.110	0.255	0.048	0.196	0.341	0.134	N/A	N/A
WCDMA Band II	Left Cheek	0.249	0.142	0.275	0.075	0.391	0.524	0.324	N/A	N/A
	Left Tilt	0.150	0.109	0.251	0.044	0.259	0.401	0.194	N/A	N/A
	Right Cheek	0.256	0.146	0.289	0.080	0.402	0.545	0.336	N/A	N/A
	Right Tilt	0.155	0.110	0.255	0.048	0.265	0.410	0.203	N/A	N/A
WCDMA Band IV	Left Cheek	0.305	0.142	0.275	0.075	0.447	0.580	0.380	N/A	N/A
	Left Tilt	0.170	0.109	0.251	0.044	0.279	0.421	0.214	N/A	N/A
	Right Cheek	0.317	0.146	0.289	0.080	0.463	0.606	0.397	N/A	N/A
	Right Tilt	0.174	0.110	0.255	0.048	0.284	0.429	0.222	N/A	N/A
WCDMA Band V	Left Cheek	0.194	0.142	0.275	0.075	0.336	0.469	0.269	N/A	N/A
	Left Tilt	0.104	0.109	0.251	0.044	0.213	0.355	0.148	N/A	N/A
	Right Cheek	0.199	0.146	0.289	0.080	0.345	0.488	0.279	N/A	N/A
	Right Tilt	0.107	0.110	0.255	0.048	0.217	0.362	0.155	N/A	N/A

Band	Test Position	RB allocation	Scaled				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
			WWAN	WIFI 2.4G	WIFI 5G	Bluetooth					
LTE Band 2 QPSK (20MHz)	Left Cheek	1RB	0.283	0.142	0.275	0.075	0.425	0.558	0.358	N/A	N/A
	Left Tilt		0.151	0.109	0.251	0.044	0.260	0.402	0.195	N/A	N/A
	Right Cheek		0.288	0.146	0.289	0.080	0.434	0.577	0.368	N/A	N/A
	Right Tilt		0.155	0.110	0.255	0.048	0.265	0.410	0.203	N/A	N/A
	Left Cheek	50%RB	0.242	0.142	0.275	0.075	0.384	0.517	0.317	N/A	N/A
	Left Tilt		0.127	0.109	0.251	0.044	0.236	0.378	0.171	N/A	N/A
	Right Cheek		0.246	0.146	0.289	0.080	0.392	0.535	0.326	N/A	N/A
	Right Tilt		0.132	0.110	0.255	0.048	0.242	0.387	0.180	N/A	N/A
LTE Band 4 QPSK (20MHz)	Left Cheek	1RB	0.276	0.142	0.275	0.075	0.418	0.551	0.351	N/A	N/A
	Left Tilt		0.151	0.109	0.251	0.044	0.260	0.402	0.195	N/A	N/A
	Right Cheek		0.281	0.146	0.289	0.080	0.427	0.570	0.361	N/A	N/A
	Right Tilt		0.153	0.110	0.255	0.048	0.263	0.408	0.201	N/A	N/A
	Left Cheek	50%RB	0.291	0.142	0.275	0.075	0.433	0.566	0.366	N/A	N/A
	Left Tilt		0.157	0.109	0.251	0.044	0.266	0.408	0.201	N/A	N/A
	Right Cheek		0.287	0.146	0.289	0.080	0.433	0.576	0.367	N/A	N/A
	Right Tilt		0.153	0.110	0.255	0.048	0.263	0.408	0.201	N/A	N/A
LTE Band 5 QPSK (10MHz)	Left Cheek	1RB	0.318	0.142	0.275	0.075	0.460	0.593	0.393	N/A	N/A
	Left Tilt		0.163	0.109	0.251	0.044	0.272	0.414	0.207	N/A	N/A
	Right Cheek		0.325	0.146	0.289	0.080	0.471	0.614	0.405	N/A	N/A
	Right Tilt		0.172	0.110	0.255	0.048	0.282	0.427	0.220	N/A	N/A
	Left Cheek	50%RB	0.203	0.142	0.275	0.075	0.345	0.478	0.278	N/A	N/A
	Left Tilt		0.105	0.109	0.251	0.044	0.214	0.356	0.149	N/A	N/A
	Right Cheek		0.210	0.146	0.289	0.080	0.356	0.499	0.290	N/A	N/A
	Right Tilt		0.106	0.110	0.255	0.048	0.216	0.361	0.154	N/A	N/A
LTE Band 12 QPSK (10MHz)	Left Cheek	1RB	0.103	0.142	0.275	0.075	0.245	0.378	0.178	N/A	N/A
	Left Tilt		0.060	0.109	0.251	0.044	0.169	0.311	0.104	N/A	N/A
	Right Cheek		0.109	0.146	0.289	0.080	0.255	0.398	0.189	N/A	N/A
	Right Tilt		0.064	0.110	0.255	0.048	0.174	0.319	0.112	N/A	N/A
	Left Cheek	50%RB	0.100	0.142	0.275	0.075	0.242	0.375	0.175	N/A	N/A
	Left Tilt		0.053	0.109	0.251	0.044	0.162	0.304	0.097	N/A	N/A
	Right Cheek		0.108	0.146	0.289	0.080	0.254	0.397	0.188	N/A	N/A
	Right Tilt		0.063	0.110	0.255	0.048	0.173	0.318	0.111	N/A	N/A
LTE Band 17 QPSK (10MHz)	Left Cheek	1RB	0.102	0.142	0.275	0.075	0.244	0.377	0.177	N/A	N/A
	Left Tilt		0.063	0.109	0.251	0.044	0.172	0.314	0.107	N/A	N/A
	Right Cheek		0.116	0.146	0.289	0.080	0.262	0.405	0.196	N/A	N/A
	Right Tilt		0.068	0.110	0.255	0.048	0.178	0.323	0.116	N/A	N/A
	Left Cheek	50%RB	0.099	0.142	0.275	0.075	0.241	0.374	0.174	N/A	N/A
	Left Tilt		0.059	0.109	0.251	0.044	0.168	0.310	0.103	N/A	N/A
	Right Cheek		0.115	0.146	0.289	0.080	0.261	0.404	0.195	N/A	N/A
	Right Tilt		0.070	0.110	0.255	0.048	0.180	0.325	0.118	N/A	N/A
LTE Band 30 QPSK (10MHz)	Left Cheek	1RB	0.121	0.142	0.275	0.075	0.263	0.396	0.196	N/A	N/A
	Left Tilt		0.075	0.109	0.251	0.044	0.184	0.326	0.119	N/A	N/A
	Right Cheek		0.125	0.146	0.289	0.080	0.271	0.414	0.205	N/A	N/A
	Right Tilt		0.080	0.110	0.255	0.048	0.190	0.335	0.128	N/A	N/A
	Left Cheek	50%RB	0.118	0.142	0.275	0.075	0.260	0.393	0.193	N/A	N/A
	Left Tilt		0.072	0.109	0.251	0.044	0.181	0.323	0.116	N/A	N/A
	Right Cheek		0.123	0.146	0.289	0.080	0.269	0.412	0.203	N/A	N/A
	Right Tilt		0.080	0.110	0.255	0.048	0.190	0.335	0.128	N/A	N/A
LTE Band 66 QPSK (20MHz)	Left Cheek	1RB	0.372	0.142	0.275	0.075	0.514	0.647	0.447	N/A	N/A
	Left Tilt		0.189	0.109	0.251	0.044	0.298	0.440	0.233	N/A	N/A
	Right Cheek		0.378	0.146	0.289	0.080	0.524	0.667	0.458	N/A	N/A
	Right Tilt		0.196	0.110	0.255	0.048	0.306	0.451	0.244	N/A	N/A
	Left Cheek	50%RB	0.373	0.142	0.275	0.075	0.515	0.648	0.448	N/A	N/A
	Left Tilt		0.186	0.109	0.251	0.044	0.295	0.437	0.230	N/A	N/A
	Right Cheek		0.375	0.146	0.289	0.080	0.521	0.664	0.455	N/A	N/A
	Right Tilt		0.192	0.110	0.255	0.048	0.302	0.447	0.240	N/A	N/A
LTE Band 71 QPSK (20MHz)	Left Cheek	1RB	0.092	0.142	0.275	0.075	0.234	0.367	0.167	N/A	N/A
	Left Tilt		0.050	0.109	0.251	0.044	0.159	0.301	0.094	N/A	N/A
	Right Cheek		0.098	0.146	0.289	0.080	0.244	0.387	0.178	N/A	N/A
	Right Tilt		0.055	0.110	0.255	0.048	0.165	0.310	0.103	N/A	N/A
	Left Cheek	50%RB	0.091	0.142	0.275	0.075	0.233	0.366	0.166	N/A	N/A
	Left Tilt		0.046	0.109	0.251	0.044	0.155	0.297	0.090	N/A	N/A
	Right Cheek		0.094	0.146	0.289	0.080	0.240	0.383	0.174	N/A	N/A
	Right Tilt		0.053	0.110	0.255	0.048	0.163	0.308	0.101	N/A	N/A

Hotspot(body-worn)

Band	Test Position	Scaled SAR				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
		WWAN	WIFI 2.4G	WIFI 5G	Bluetooth					
GSM850 (GPRS 4slots)	Front	0.391	0.039	0.160	0.118	0.430	0.551	0.509	N/A	N/A
	Back	0.534	0.062	0.166	0.118	0.596	0.700	0.652	N/A	N/A
	Left	0.287	/	/	/	0.287	0.287	0.287	N/A	N/A
	Right	/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top	/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom	0.175	/	/	/	0.175	0.175	0.175	N/A	N/A
GSM1900 (GPRS 4slots)	Front	0.549	0.039	0.160	0.118	0.588	0.709	0.667	N/A	N/A
	Back	0.521	0.062	0.166	0.118	0.583	0.687	0.639	N/A	N/A
	Left	0.541	/	/	/	0.541	0.541	0.541	N/A	N/A
	Right	/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top	/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom	0.380	/	/	/	0.380	0.380	0.380	N/A	N/A
WCDMA Band II	Front	0.242	0.039	0.160	0.118	0.281	0.402	0.360	N/A	N/A
	Back	0.207	0.062	0.166	0.118	0.269	0.373	0.325	N/A	N/A
	Left	0.237	/	/	/	0.237	0.237	0.237	N/A	N/A
	Right	/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top	/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom	0.163	/	/	/	0.163	0.163	0.163	N/A	N/A
WCDMA Band IV	Front	0.342	0.039	0.160	0.118	0.381	0.502	0.460	N/A	N/A
	Back	0.304	0.062	0.166	0.118	0.366	0.470	0.422	N/A	N/A
	Left	0.335	/	/	/	0.335	0.335	0.335	N/A	N/A
	Right	/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top	/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom	0.259	/	/	/	0.259	0.259	0.259	N/A	N/A
WCDMA Band V	Front	0.152	0.039	0.160	0.118	0.191	0.312	0.270	N/A	N/A
	Back	0.160	0.062	0.166	0.118	0.222	0.326	0.278	N/A	N/A
	Left	0.150	/	/	/	0.150	0.150	0.150	N/A	N/A
	Right	/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top	/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom	0.130	/	/	/	0.130	0.130	0.130	N/A	N/A

Band	Test Position	RB allocation	Scaled				Σ SAR (W/kg) WWAN + WIFI 2.4G	Σ SAR (W/kg) WWAN + WIFI 5G	Σ SAR (W/kg) WWAN + BT	SPLSR	Remark
			WWAN	WIFI 2.4G	WIFI 5G	Bluetooth					
LTE Band 2 QPSK (20MHz)	Front	1RB	0.341	0.039	0.160	0.118	0.380	0.501	0.459	N/A	N/A
	Back		0.334	0.062	0.166	0.118	0.396	0.500	0.452	N/A	N/A
	Left		0.238	/	/	/	0.238	0.238	0.238	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.259	/	/	/	0.259	0.259	0.259	N/A	N/A
	Front	50%RB	0.303	0.039	0.160	0.118	0.342	0.463	0.421	N/A	N/A
	Back		0.292	0.062	0.166	0.118	0.354	0.458	0.410	N/A	N/A
	Left		0.206	/	/	/	0.206	0.206	0.206	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.229	/	/	/	0.229	0.229	0.229	N/A	N/A
LTE Band 4 QPSK (20MHz)	Front	1RB	0.479	0.039	0.160	0.118	0.518	0.639	0.597	N/A	N/A
	Back		0.474	0.062	0.166	0.118	0.536	0.640	0.592	N/A	N/A
	Left		0.406	/	/	/	0.406	0.406	0.406	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.250	/	/	/	0.250	0.250	0.250	N/A	N/A
	Front	50%RB	0.494	0.039	0.160	0.118	0.533	0.654	0.612	N/A	N/A
	Back		0.482	0.062	0.166	0.118	0.544	0.648	0.600	N/A	N/A
	Left		0.411	/	/	/	0.411	0.411	0.411	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.257	/	/	/	0.257	0.257	0.257	N/A	N/A
LTE Band 5 QPSK (10MHz)	Front	1RB	0.202	0.039	0.160	0.118	0.241	0.362	0.320	N/A	N/A
	Back		0.209	0.062	0.166	0.118	0.271	0.375	0.327	N/A	N/A
	Left		0.199	/	/	/	0.199	0.199	0.199	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.173	/	/	/	0.173	0.173	0.173	N/A	N/A

	Front	50%RB	0.131	0.039	0.160	0.118	0.170	0.291	0.249	N/A	N/A
	Back		0.135	0.062	0.166	0.118	0.197	0.301	0.253	N/A	N/A
	Left		0.127	/	/	/	0.127	0.127	0.127	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.112	/	/	/	0.112	0.112	0.112	N/A	N/A
LTE Band 12 QPSK (10MHz)	Front	1RB	0.204	0.039	0.160	0.118	0.243	0.364	0.322	N/A	N/A
	Back		0.208	0.062	0.166	0.118	0.270	0.374	0.326	N/A	N/A
	Left		0.199	/	/	/	0.199	0.199	0.199	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.168	/	/	/	0.168	0.168	0.168	N/A	N/A
	Front	50%RB	0.206	0.039	0.160	0.118	0.245	0.366	0.324	N/A	N/A
	Back		0.209	0.062	0.166	0.118	0.271	0.375	0.327	N/A	N/A
	Left		0.191	/	/	/	0.191	0.191	0.191	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.165	/	/	/	0.165	0.165	0.165	N/A	N/A
LTE Band 17 QPSK (10MHz)	Front	1RB	0.179	0.039	0.160	0.118	0.218	0.339	0.297	N/A	N/A
	Back		0.185	0.062	0.166	0.118	0.247	0.351	0.303	N/A	N/A
	Left		0.159	/	/	/	0.159	0.159	0.159	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.133	/	/	/	0.133	0.133	0.133	N/A	N/A
	Front	50%RB	0.178	0.039	0.160	0.118	0.217	0.338	0.296	N/A	N/A
	Back		0.181	0.062	0.166	0.118	0.243	0.347	0.299	N/A	N/A
	Left		0.157	/	/	/	0.157	0.157	0.157	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.127	/	/	/	0.127	0.127	0.127	N/A	N/A
LTE Band 30 QPSK (10MHz)	Front	1RB	0.085	0.039	0.160	0.118	0.124	0.245	0.203	N/A	N/A
	Back		0.079	0.062	0.166	0.118	0.141	0.245	0.197	N/A	N/A
	Left		0.070	/	/	/	0.070	0.070	0.070	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.056	/	/	/	0.056	0.056	0.056	N/A	N/A
	Front	50%RB	0.083	0.039	0.160	0.118	0.122	0.243	0.201	N/A	N/A
	Back		0.077	0.062	0.166	0.118	0.139	0.243	0.195	N/A	N/A
	Left		0.067	/	/	/	0.067	0.067	0.067	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.066	/	/	/	0.066	0.066	0.066	N/A	N/A
LTE Band 66 QPSK (20MHz)	Front	1RB	0.567	0.039	0.160	0.118	0.606	0.727	0.685	N/A	N/A
	Back		0.558	0.062	0.166	0.118	0.620	0.724	0.676	N/A	N/A
	Left		0.494	/	/	/	0.494	0.494	0.494	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.467	/	/	/	0.467	0.467	0.467	N/A	N/A
	Front	50%RB	0.564	0.039	0.160	0.118	0.603	0.724	0.682	N/A	N/A
	Back		0.553	0.062	0.166	0.118	0.615	0.719	0.671	N/A	N/A
	Left		0.487	/	/	/	0.487	0.487	0.487	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.462	/	/	/	0.462	0.462	0.462	N/A	N/A
LTE Band 71 QPSK (20MHz)	Front	1RB	0.149	0.039	0.160	0.118	0.188	0.309	0.267	N/A	N/A
	Back		0.151	0.062	0.166	0.118	0.213	0.317	0.269	N/A	N/A
	Left		0.134	/	/	/	0.134	0.134	0.134	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.131	/	/	/	0.131	0.131	0.131	N/A	N/A
	Front	50%RB	0.146	0.039	0.160	0.118	0.185	0.306	0.264	N/A	N/A
	Back		0.149	0.062	0.166	0.118	0.211	0.315	0.267	N/A	N/A
	Left		0.129	/	/	/	0.129	0.129	0.129	N/A	N/A
	Right		/	0.049	0.147	0.118	0.049	0.147	0.118	N/A	N/A
	Top		/	0.036	0.163	0.118	0.036	0.163	0.118	N/A	N/A
	Bottom		0.144	/	/	/	0.144	0.144	0.144	N/A	N/A

13. Test Equipment List

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
E-Field Probe	MVG	SSE2	04/22 EPG0365	2023/02/06	2024/02/05
6 1/2 Digital Multimeter	Keithley	DMM6500	4527164	2022/11/24	2023/11/23
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	161997	2022/11/24	2023/11/23
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2022/11/24	2023/11/23
E-Series Avg. Power Sensor	KEYSIGHT	E9300A	MY55050017	2023/03/25	2024/03/24
EPM Series Power Meter	KEYSIGHT	E4418B	MY41293435	2023/03/25	2024/03/24
10dB Attenuator	MIDWEST MICROWAVE	263-10dB	/	2023/03/25	2024/03/24
Coupler	MERRIMAC	CWM-10R-10.8G	LOT-83391	2023/03/25	2024/03/24
750MHz Validation Dipole	MVG	SID750	07/22 DIP 0G835-655	2023/02/06	2024/02/05
835MHz Validation Dipole	MVG	SID835	07/22 DIP 0G835-656	2023/02/06	2024/02/05
1800MHz Validation Dipole	MVG	SID1800	07/22 DIP 1G800-657	2023/02/06	2024/02/05
1900MHz Validation Dipole	MVG	SID1900	07/22 DIP 1G900-658	2023/02/06	2024/02/05
2450MHz Validation Dipole	MVG	SID2450	07/22 DIP 2G450-662	2023/02/06	2024/02/05
2600MHz Validation Dipole	MVG	SID2600	07/22 DIP 2G600-663	2023/02/06	2024/02/05
5200MHz-5800MHz Validation Dipole	MVG	SID5000	07/22 DIP5G000-670	2023/02/06	2024/02/05
LIMESAR Dielectric Probe	MVG	SCLMP	06/22 OCPG88	/	/
ENA Series Network Analyzer	Agilent	E5071B	MY42301221	2022/11/24	2023/11/23
Thermometer	Riters	DT-232	21A11	2023/03/25	2024/03/24
Antenna network emulator	MVG	ANTA 74	07/22 ANTA 74	/	/
SAM Phantom	MVG	SAM	07/22 SAM149	/	/
Mobile Phone Positioning System	MVG	MSH 118	07/22 MSH 118	/	/
Mechanical Calibration Kit	PNA	/	/	/	/
Open SAR test software	MVG	/	V5.3.5	/	/
Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria: 1. There is no physical damage on the dipole; 2. System validation with specific dipole is within 10% of calibrated value; 3. Return-loss in within 20% of calibrated measurement. 4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.					

ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Dielectric performance of tissue simulating liquid									
Frequency (MHz)	ϵ_r		σ (s/m)		Delta (ϵ_r)	Delta (σ)	Limit	Temp (°C)	Date
	Target	Measured	Target	Measured					
750	41.90	41.80	0.89	0.86	0.24%	3.37%	±5%	20.0	27/6/2023
835	41.50	41.41	0.90	0.87	0.22%	3.33%	±5%	20.0	27/6/2023
1800	40.00	39.91	1.40	1.37	0.23%	2.14%	±5%	20.0	28/6/2023
1900	40.00	39.88	1.40	1.41	0.30%	-0.71%	±5%	20.0	28/6/2023
2450	39.20	39.08	1.80	1.81	0.31%	-0.56%	±5%	20.0	29/6/2023
2600	39.00	38.88	1.96	1.97	0.31%	-0.51%	±5%	20.0	29/6/2023
5200	36.00	35.88	4.66	4.70	0.33%	-0.86%	±5%	20.0	29/6/2023
5400	35.80	35.68	4.86	4.90	0.34%	-0.82%	±5%	20.0	29/6/2023
5800	35.30	35.18	5.27	5.31	0.34%	-0.76%	±5%	20.0	29/6/2023

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %(for 10 g).

Frequency (MHz)	Input Power (mW)	1g SAR (W/Kg)	10g SAR (W/Kg)	1g SAR 1W input power normalized (W/Kg)	10g SAR 1W input power normalized (W/Kg)	1g SAR Standard target (1W) (W/Kg)	10g SAR Standard target (1W) (W/Kg)	1g SAR Deviation	10g SAR Deviation
750	16	0.138	0.092	8.63	5.75	8.25	5.38	4.55%	6.88%
835	16	0.163	0.106	10.19	6.63	9.79	6.17	4.06%	7.37%
1800	16	0.588	0.312	36.75	19.50	39.33	20.61	-6.56%	-5.39%
1900	16	0.630	0.322	39.38	20.13	40.97	20.7	-3.89%	-2.78%
2450	16	0.793	0.352	49.56	22.00	54.4	23.86	-8.89%	-7.80%
2600	16	0.866	0.421	54.13	26.31	57.14	24.48	-5.28%	7.49%
5200	13	0.998	0.294	76.77	22.62	73.88	21.29	3.91%	6.23%
5400	13	1.120	0.327	86.15	25.15	81.47	23.23	5.75%	8.28%
5800	13	1.023	0.280	78.69	21.54	74.21	21.50	6.04%	0.18%

System Performance Check Data (750 MHz)

System check at 750 MHz

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	750.000
Relative permittivity (real part)	41.800
Relative permittivity (imaginary part)	21.460
Conductivity (S/m)	0.860

C. SAR Surface and Volume




Maximum location: X=0.00, Y=9.00 ; SAR Peak: 0.20 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.092
SAR 1g (W/Kg)	0.138
Variation (%)	-2.190
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.287	0.142	0.092	0.073	0.042



F. 3D Image



System Performance Check Data (835 MHz)

System check at 835 MHz

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	835.000
Relative permittivity (real part)	41.410
Relative permittivity (imaginary part)	19.490
Conductivity (S/m)	0.870

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=-3.00 ; SAR Peak: 0.26 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.106
SAR 1g (W/Kg)	0.163
Variation (%)	-3.390
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.059	0.173	0.115	0.061	0.072



F. 3D Image



System Performance Check Data (1800 MHz)

System check at 1800 MHz

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1800.000
Relative permittivity (real part)	39.910
Relative permittivity (imaginary part)	14.090
Conductivity (S/m)	1.370

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.00 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.312
SAR 1g (W/Kg)	0.588
Variation (%)	-0.250
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.003	0.638	0.356	0.204	0.127



F. 3D Image



System Performance Check Data (1900 MHz)

System check at 1900 MHz

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	1900.000
Relative permittivity (real part)	39.880
Relative permittivity (imaginary part)	13.380
Conductivity (S/m)	1.410

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.18 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.322
SAR 1g (W/Kg)	0.630
Variation (%)	-2.080
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.201	0.759	0.402	0.239	0.156



F. 3D Image



System Performance Check Data (2450 MHz)

System check at 2450 MHz

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2450.000
Relative permittivity (real part)	39.080
Relative permittivity (imaginary part)	13.340
Conductivity (S/m)	1.810

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.47 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.352
SAR 1g (W/Kg)	0.793
Variation (%)	-2.570
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.466	0.900	0.477	0.261	0.158



F. 3D Image



System Performance Check Data (2600 MHz)

System check at 2600 MHz

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.40
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	2600.000
Relative permittivity (real part)	38.880
Relative permittivity (imaginary part)	12.690
Conductivity (S/m)	1.970

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-1.00 ; SAR Peak: 1.02 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.421
SAR 1g (W/Kg)	0.866
Variation (%)	2.980
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.020	0.655	0.359	0.187	0.091



F. 3D Image



System Performance Check Data (5200 MHz)

System check at 5200 MHz

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5200.000
Relative permittivity (real part)	35.880
Relative permittivity (imaginary part)	16.250
Conductivity (S/m)	4.700

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.294
SAR 1g (W/Kg)	0.998
Variation (%)	-3.400
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.268	1.889	1.021	0.523	0.266	0.142	0.085	0.060	0.052



F. 3D Image



System Performance Check Data (5400 MHz)

System check at 5400 MHz

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.12
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5400.000
Relative permittivity (real part)	35.800
Relative permittivity (imaginary part)	16.200
Conductivity (S/m)	4.860

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 3.78 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.327
SAR 1g (W/Kg)	1.120
Variation (%)	-4.610
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.660	2.141	1.177	0.614	0.317	0.169	0.098	0.065	0.050



F. 3D Image



System Performance Check Data (5800 MHz)

System check at 5800 MHz

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	dx=8mm dy=8mm, Adaptive 1 max
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=5mm, Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW

B. Permittivity

Frequency (MHz)	5800.000
Relative permittivity (real part)	35.180
Relative permittivity (imaginary part)	16.480
Conductivity (S/m)	5.310

C. SAR Surface and Volume




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 4.17 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.280
SAR 1g (W/Kg)	1.023
Variation (%)	0.490
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	3.948	2.037	0.915	0.361	0.135	0.055	0.033	0.037	0.059



F. 3D Image



ANNEX C Test Data

1-Head with front position in dist. 0mm on Channel 190 in GSM850 voice

SAR Measurement at GSM850 (Cheek, Right)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	GSM850
Channels	Middle (190)
Signal	TDMA (GSM)
Modulation	GMSK

B. Permittivity

Frequency (MHz)	836.600
Relative permittivity (real part)	41.408
Relative permittivity (imaginary part)	19.492
Conductivity (S/m)	0.871

C. SAR Surface and Volume



Maximum location: X=-48.00, Y=-47.00 ; SAR Peak: 0.40 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.219
SAR 1g (W/Kg)	0.308
Variation (%)	2.980
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.389	0.305	0.226	0.172	0.135


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China



F. 3D Image



2-Body with back position in dist. 10mm on Channel 190 in GPRS850+4slots

SAR Measurement at GPRS850 (Body, Validation Plane)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS850
Channels	Middle (190)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	836.600
Relative permittivity (real part)	41.408
Relative permittivity (imaginary part)	19.492
Conductivity (S/m)	0.871

C. SAR Surface and Volume




Maximum location: X=-15.00, Y=43.00 ; SAR Peak: 0.65 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.373
SAR 1g (W/Kg)	0.504
Variation (%)	1.950
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.925	0.488	0.343	0.293	0.200



F. 3D Image



3-Head with front position in dist. 0mm on Channel 810 in GSM1900 voice

SAR Measurement at GSM1900 (Cheek, Right)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	GSM1900
Channels	Higher (810)
Signal	TDMA (GSM)
Modulation	GMSK

B. Permittivity

Frequency (MHz)	1909.800
Relative permittivity (real part)	39.866
Relative permittivity (imaginary part)	13.394
Conductivity (S/m)	1.417

C. SAR Surface and Volume




Maximum location: X=-64.00, Y=-32.00 ; SAR Peak: 0.24 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.102
SAR 1g (W/Kg)	0.159
Variation (%)	1.800
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.234	0.166	0.107	0.071	0.049



F. 3D Image



4- Body with front position in dist. 10mm on Channel 810 in GPRS1900+4slots

SAR Measurement at GPRS1900 (Body, Validation Plane)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	GPRS1900
Channels	Higher (810)
Signal	TDMA (GPRS)
Modulation	GMSK (CS-1)
TX-slots	4

B. Permittivity

Frequency (MHz)	1909.800
Relative permittivity (real part)	39.866
Relative permittivity (imaginary part)	13.394
Conductivity (S/m)	1.417

C. SAR Surface and Volume




Maximum location: X=0.00, Y=-1.00 ; SAR Peak: 0.81 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.336
SAR 1g (W/Kg)	0.533
Variation (%)	1.930
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.807	0.553	0.341	0.213	0.137



F. 3D Image



5-Head with front position in dist. 0mm on Channel 9400 in WCDMA Band 2

SAR Measurement at Band 2 (1900) (Cheek, Right)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	Band 2 (1900)
Channels	Middle (9400)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	1880.000
Relative permittivity (real part)	39.909
Relative permittivity (imaginary part)	13.351
Conductivity (S/m)	1.395

C. SAR Surface and Volume




Maximum location: X=-57.00, Y=-24.00 ; SAR Peak: 0.33 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.169
SAR 1g (W/Kg)	0.249
Variation (%)	3.380
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.331	0.259	0.191	0.142	0.106



F. 3D Image



6-Body with front position in dist. 10mm on Channel 9400 in WCDMA Band 2

SAR Measurement at Band 2 (1900) (Body, Validation Plane)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band 2 (1900)
Channels	Middle (9400)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	1880.000
Relative permittivity (real part)	39.909
Relative permittivity (imaginary part)	13.351
Conductivity (S/m)	1.395

C. SAR Surface and Volume



Maximum location: X=15.00, Y=16.00 ; SAR Peak: 0.33 W/kg


D. SAR 1g & 10g

SAR 10g (W/Kg)	0.162
SAR 1g (W/Kg)	0.235
Variation (%)	1.780
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
--------	------	------	------	-------	-------

SAR (W/Kg)	0.332	0.242	0.165	0.117	0.089
------------	-------	-------	-------	-------	-------



F. 3D Image



7-Head with front position in dist. 0mm on Channel 1312 in WCDMA Band 4

SAR Measurement at Band 4 (1700) (Cheek, Right)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	Band 4 (1700)
Channels	Lower (1312)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	1712.400
Relative permittivity (real part)	40.046
Relative permittivity (imaginary part)	13.954
Conductivity (S/m)	1.325

C. SAR Surface and Volume




Maximum location: X=-58.00, Y=-22.00 ; SAR Peak: 0.46 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.191
SAR 1g (W/Kg)	0.295
Variation (%)	-2.120
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.453	0.307	0.193	0.133	0.105



F. 3D Image



8-Body with front position in dist. 10mm on Channel 1312 in WCDMA Band 4

SAR Measurement at Band 4 (1700) (Body, Validation Plane)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band 4 (1700)
Channels	Lower (1312)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	1712.400
Relative permittivity (real part)	40.046
Relative permittivity (imaginary part)	13.954
Conductivity (S/m)	1.325

C. SAR Surface and Volume




Maximum location: X=14.00, Y=9.00 ; SAR Peak: 0.45 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.211
SAR 1g (W/Kg)	0.318
Variation (%)	1.360
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.453	0.330	0.220	0.146	0.097



F. 3D Image



9-Head with front position in dist. 0mm on Channel 4132 in WCDMA Band 5

SAR Measurement at Band 5 (850) (Cheek, Right)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPGO365
ConvF	1.68
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	Band 5 (850)
Channels	Lower (4132)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	826.400
Relative permittivity (real part)	41.423
Relative permittivity (imaginary part)	19.477
Conductivity (S/m)	0.866

C. SAR Surface and Volume



Maximum location: X=-49.00, Y=-47.00 ; SAR Peak: 0.27 W/kg


D. SAR 1g & 10g

SAR 10g (W/Kg)	0.134
SAR 1g (W/Kg)	0.190
Variation (%)	-2.350
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
--------	------	------	------	-------	-------

SAR (W/Kg)	0.272	0.189	0.124	0.090	0.075
------------	-------	-------	-------	-------	-------



F. 3D Image



10-Body with back position in dist. 10mm on Channel 4132 in WCDMA Band 5

SAR Measurement at Band 5 (850) (Body, Validation Plane)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Band 5 (850)
Channels	Lower (4132)
Signal	WCDMA
Mode	Release 99
Connection Type	RMC, 12.2 kbps

B. Permittivity

Frequency (MHz)	826.400
Relative permittivity (real part)	41.423
Relative permittivity (imaginary part)	19.477
Conductivity (S/m)	0.866

C. SAR Surface and Volume




Maximum location: X=16.00, Y=-16.00 ; SAR Peak: 0.23 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.112
SAR 1g (W/Kg)	0.153
Variation (%)	-3.390
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.577	0.159	0.067	0.078	0.040



F. 3D Image



11-Head with front position in dist. 0mm on Channel 18900 in LTE band 2

SAR Measurement at LTE band 2 (Cheek, Right)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 2
Channels	Middle (18900)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	49
RB size	1

B. Permittivity

Frequency (MHz)	1879.910
Relative permittivity (real part)	39.909
Relative permittivity (imaginary part)	13.351
Conductivity (S/m)	1.395

C. SAR Surface and Volume




Maximum location: X=-57.00, Y=-26.00 ; SAR Peak: 0.40 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.165
SAR 1g (W/Kg)	0.257
Variation (%)	-1.510
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/kg)	0.395	0.271	0.173	0.121	0.096



F. 3D Image



12-Body with front position in dist. 10mm on Channel 18700 in LTE Band 2

SAR Measurement at LTE band 2 (Body, Validation Plane)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 2
Channels	Middle (18900)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	49
RB size	1

B. Permittivity

Frequency (MHz)	1879.910
Relative permittivity (real part)	39.909
Relative permittivity (imaginary part)	13.351
Conductivity (S/m)	1.395

C. SAR Surface and Volume




Maximum location: X=15.00, Y=1.00 ; SAR Peak: 0.45 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.190
SAR 1g (W/Kg)	0.304
Variation (%)	0.650
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.337	0.319	0.102	0.141	0.047



F. 3D Image



13-Head with front position in dist. 0mm on Channel 20050 in LTE band 4

SAR Measurement at LTE band 4 (Cheek, Right)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 4
Channels	Lower (20050)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Frequency (MHz)	1711.090
Relative permittivity (real part)	40.048
Relative permittivity (imaginary part)	13.952
Conductivity (S/m)	1.324

C. SAR Surface and Volume



Maximum location: X=-64.00, Y=-23.00 ; SAR Peak: 0.40 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.188
SAR 1g (W/Kg)	0.276
Variation (%)	0.630
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/kg)	0.392	0.285	0.193	0.138	0.106



F. 3D Image



14-Body with Front position in dist. 10mm on Channel 20050 in LTE Band 4

SAR Measurement at LTE band 4 (Body, Validation Plane)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 4
Channels	Lower (20050)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Frequency (MHz)	1711.090
Relative permittivity (real part)	40.048
Relative permittivity (imaginary part)	13.952
Conductivity (S/m)	1.324

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.302
SAR 1g (W/Kg)	0.470
Variation (%)	-0.580
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.679	0.488	0.318	0.208	0.136



F. 3D Image



15-Head with front position in dist. 0mm on Channel 20450 in LTE band 5

SAR Measurement at LTE band 5 (Cheek, Right)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 5
Channels	Lower (20450)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	828.910
Relative permittivity (real part)	41.419
Relative permittivity (imaginary part)	19.481
Conductivity (S/m)	0.867

C. SAR Surface and Volume




Maximum location: X=-56.00, Y=-39.00 ; SAR Peak: 0.29 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.141
SAR 1g (W/Kg)	0.193
Variation (%)	-1.230
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.326	0.196	0.129	0.095	0.069



F. 3D Image



16-Body with back position in dist. 10mm on Channel 20450 in LTE Band 5

SAR Measurement at LTE band 5 (Body, Validation Plane)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.68
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 5
Channels	Lower (20450)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	828.910
Relative permittivity (real part)	41.419
Relative permittivity (imaginary part)	19.481
Conductivity (S/m)	0.867

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.091
SAR 1g (W/Kg)	0.124
Variation (%)	-2.060
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.174	0.128	0.091	0.069	0.058



F. 3D Image



17-Head with front position in dist. 0mm on Channel 23130 in LTE band 12

SAR Measurement at LTE band 12 (Cheek, Right)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 12
Channels	Higher (23130)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	710.910
Relative permittivity (real part)	41.603
Relative permittivity (imaginary part)	19.297
Conductivity (S/m)	0.806

C. SAR Surface and Volume




Maximum location: X=-64.00, Y=-40.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.079
SAR 1g (W/Kg)	0.107
Variation (%)	-3.700
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.155	0.107	0.073	0.059	0.058



F. 3D Image



18-Body with back position in dist. 10mm on Channel 23130 in LTE Band 12

SAR Measurement at LTE band 12 (Body, Validation Plane)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 12
Channels	Higher (23130)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	710.910
Relative permittivity (real part)	41.603
Relative permittivity (imaginary part)	19.297
Conductivity (S/m)	0.806

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.150
SAR 1g (W/Kg)	0.204
Variation (%)	-2.200
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.371	0.206	0.136	0.108	0.079



F. 3D Image



19-Head with front position in dist. 0mm on Channel 23780 in LTE band 17

SAR Measurement at LTE band 17 (Cheek, Right)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 17
Channels	Lower (23780)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	708.910
Relative permittivity (real part)	41.606
Relative permittivity (imaginary part)	19.294
Conductivity (S/m)	0.805

C. SAR Surface and Volume




Maximum location: X=-63.00, Y=-48.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.077
SAR 1g (W/Kg)	0.104
Variation (%)	-1.860
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.485	0.109	0.049	0.070	0.028



F. 3D Image



20-Body with back position in dist. 10mm on Channel 23780 in LTE Band 17

SAR Measurement at LTE band 17 (Body, Validation Plane)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 17
Channels	Lower (23780)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	708.910
Relative permittivity (real part)	41.606
Relative permittivity (imaginary part)	19.294
Conductivity (S/m)	0.805

C. SAR Surface and Volume




Maximum location: X=17.00, Y=-34.00 ; SAR Peak: 0.25 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.118
SAR 1g (W/Kg)	0.166
Variation (%)	-2.260
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.192	0.174	0.116	0.080	0.074



F. 3D Image



21-Head with front position in dist. 0mm on Channel 27710 in LTE band 30

SAR Measurement at LTE band 30 (Cheek, Right)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 30
Channels	Middle (27710)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	24
RB size	1

B. Permittivity

Frequency (MHz)	2309.910
Relative permittivity (real part)	39.267
Relative permittivity (imaginary part)	13.947
Conductivity (S/m)	1.661

C. SAR Surface and Volume



Maximum location: X=-61.00, Y=-22.00 ; SAR Peak: 0.18 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.083
SAR 1g (W/Kg)	0.113
Variation (%)	-1.900
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/kg)	0.121	0.114	0.101	0.083	0.063



F. 3D Image



22-Body with front position in dist. 0mm on Channel 27710 in LTE band 30

SAR Measurement at LTE band 30 (Body, Validation Plane)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 30
Channels	Middle (27710)
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Frequency (MHz)	2305.590
Relative permittivity (real part)	39.273
Relative permittivity (imaginary part)	13.966
Conductivity (S/m)	1.656

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.070
SAR 1g (W/Kg)	0.077
Variation (%)	-1.940
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 112 of 142


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.068	0.064	0.040	0.035	0.046



F. 3D Image



23-Head with front position in dist. 0mm on Channel 132072 in LTE band 66

SAR Measurement at LTE band 66 (Cheek, Right)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 66
Channels	Lower (132072)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	49
RB size	1

B. Permittivity

Frequency (MHz)	1719.910
Relative permittivity (real part)	40.034
Relative permittivity (imaginary part)	13.966
Conductivity (S/m)	1.329

C. SAR Surface and Volume



Maximum location: X=-61.00, Y=-25.00 ; SAR Peak: 0.52 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.241
SAR 1g (W/Kg)	0.359
Variation (%)	-4.780
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/kg)	0.516	0.377	0.258	0.186	0.144



F. 3D Image



24 - Body with front position in dist. 10mm on Channel 132072 in LTE Band 66

SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 28/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.96
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels	Lower (132072)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	1720.090
Relative permittivity (real part)	40.034
Relative permittivity (imaginary part)	13.966
Conductivity (S/m)	1.329

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.335
SAR 1g (W/Kg)	0.538
Variation (%)	-0.520
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.824	0.561	0.345	0.219	0.147



F. 3D Image



25-Head with front position in dist. 0mm on Channel 133222 in LTE band 71

SAR Measurement at LTE band 71 (Cheek, Right)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 71
Channels	Lower (133222)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	673.090
Relative permittivity (real part)	41.662
Relative permittivity (imaginary part)	19.238
Conductivity (S/m)	0.786

C. SAR Surface and Volume



Maximum location: X=-64.00, Y=-40.00 ; SAR Peak: 0.14 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.067
SAR 1g (W/Kg)	0.091
Variation (%)	-1.050
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 118 of 142


BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.294	0.094	0.046	0.047	0.028



F. 3D Image



26-Body with back position in dist. 10mm on Channel 133222 in LTE band 71

SAR Measurement at LTE band 71 (Body, Validation Plane)

Date of measurement: 27/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	1.65
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 71
Channels	Lower (133222)
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1

B. Permittivity

Frequency (MHz)	673.090
Relative permittivity (real part)	41.662
Relative permittivity (imaginary part)	19.238
Conductivity (S/m)	0.786

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.098
SAR 1g (W/Kg)	0.141
Variation (%)	-4.540
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.217	0.133	0.088	0.068	0.052



F. 3D Image



27-Head with front position in dist. 0mm on Channel 1 in IEEE 802.11b ISM

SAR Measurement at IEEE 802.11b ISM (Cheek, Right)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11b ISM
Channels	Lower (1)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	2412.000
Relative permittivity (real part)	39.131
Relative permittivity (imaginary part)	13.505
Conductivity (S/m)	1.769

C. SAR Surface and Volume




Maximum location: X=-22.00, Y=3.00 ; SAR Peak: 0.25 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.073
SAR 1g (W/Kg)	0.133
Variation (%)	-1.090
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.251	0.141	0.069	0.040	0.033



F. 3D Image



28-Body with back position in dist. 10mm on Channel 1 in 802.11b ISM

SAR Measurement at IEEE 802.11b ISM (Body, Validation Plane)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11b ISM
Channels	Lower (1)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	2412.000
Relative permittivity (real part)	39.131
Relative permittivity (imaginary part)	13.505
Conductivity (S/m)	1.769

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.040
SAR 1g (W/Kg)	0.057
Variation (%)	-1.330
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.074	0.062	0.049	0.037	0.028



F. 3D Image



29-Head with front position in dist. 0mm on Channel 46 in 802.11n U-NII

SAR Measurement at IEEE 802.11n U-NII (Cheek, Right)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n U-NII
Channels	Lower (46)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5230.000
Relative permittivity (real part)	35.850
Relative permittivity (imaginary part)	16.280
Conductivity (S/m)	4.730

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=1.00 ; SAR Peak: 0.39 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.123
SAR 1g (W/Kg)	0.201
Variation (%)	-1.350
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	7.00	12.00	17.00
SAR (W/Kg)	0.258	0.204	0.099	0.060	0.075



F. 3D Image



30-Body with back position in dist. 10mm on Channel 46 in 802.11n U-NII

SAR Measurement at IEEE 802.11n U-NII (Body, Validation Plane)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11n U-NII
Channels	Lower (46)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5230.000
Relative permittivity (real part)	35.850
Relative permittivity (imaginary part)	16.280
Conductivity (S/m)	4.730

C. SAR Surface and Volume




Maximum location: X=10.00, Y=8.00 ; SAR Peak: 0.25 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.085
SAR 1g (W/Kg)	0.152
Variation (%)	-1.870
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	7.00	12.00	17.00
SAR (W/Kg)	0.244	0.192	0.125	0.085	0.044



F. 3D Image



31-Head with front position in dist. 0mm on Channel 60 in 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Cheek, Right)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a U-NII
Channels	Lower (60)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5300.000
Relative permittivity (real part)	35.780
Relative permittivity (imaginary part)	16.350
Conductivity (S/m)	4.800

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=7.00 ; SAR Peak: 0.65 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.144
SAR 1g (W/Kg)	0.278
Variation (%)	-3.030
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	7.00	12.00	17.00
SAR (W/Kg)	0.430	0.272	0.077	0.036	0.057



F. 3D Image



32-Body with back position in dist. 10mm on Channel 60 in 802.11a U-NII

SAR Measurement at IEEE 802.11a U-NII (Body, Validation Plane)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.24
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11a U-NII
Channels	Lower (60)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5300.000
Relative permittivity (real part)	35.780
Relative permittivity (imaginary part)	16.350
Conductivity (S/m)	4.800

C. SAR Surface and Volume




Maximum location: X=8.00, Y=7.00 ; SAR Peak: 0.20 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.058
SAR 1g (W/Kg)	0.099
Variation (%)	3.920
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	7.00	12.00	17.00
SAR (W/Kg)	0.181	0.133	0.056	0.022	0.008



F. 3D Image



33-Head with front position in dist. 0mm on Channel 151 in 802.11n U-NII

SAR Measurement at IEEE 802.11n U-NII (Cheek, Right)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11n U-NII
Channels	Higher (151)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5755.000
Relative permittivity (real part)	35.225
Relative permittivity (imaginary part)	16.575
Conductivity (S/m)	5.265

C. SAR Surface and Volume




Maximum location: X=-6.00, Y=7.00 ; SAR Peak: 0.38 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.093
SAR 1g (W/Kg)	0.188
Variation (%)	-2.160
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	7.00	12.00	17.00
SAR (W/Kg)	0.283	0.208	0.095	0.050	0.037



F. 3D Image



34-Body with back position in dist. 10mm on Channel 151 in 802.11n U-NII

SAR Measurement at IEEE 802.11n U-NII (Body, Validation Plane)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.04
Area Scan	surf_sam_plan.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Validation plane
Device Position	Body
Band	IEEE 802.11n U-NII
Channels	Higher (151)
Signal	IEEE 802.11

B. Permittivity

Frequency (MHz)	5755.000
Relative permittivity (real part)	35.225
Relative permittivity (imaginary part)	16.575
Conductivity (S/m)	5.265

C. SAR Surface and Volume




Maximum location: X=8.00, Y=8.00 ; SAR Peak: 0.21 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.088
SAR 1g (W/Kg)	0.144
Variation (%)	3.540
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	2.00	7.00	12.00	17.00
SAR (W/Kg)	0.206	0.177	0.122	0.083	0.057



F. 3D Image



35-Head with front position in dist. 0mm on Channel 78 in Bluetooth

SAR Measurement at Bluetooth (Cheek, Right)

Date of measurement: 29/6/2023


A. Experimental conditions.

Probe	SN 04/22 EPG0365
ConvF	2.36
Area Scan	sam_direct_droit2_surf8mm.txt
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete
Phantom	Right head
Device Position	Cheek
Band	Bluetooth
Channels	Higher (78)
Signal	Bluetooth

B. Permittivity

Frequency (MHz)	2440.000
Relative permittivity (real part)	39.093
Relative permittivity (imaginary part)	13.383
Conductivity (S/m)	1.799

C. SAR Surface and Volume




Maximum location: X=-24.00, Y=-1.00 ; SAR Peak: 0.12 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.050
SAR 1g (W/Kg)	0.072
Variation (%)	-1.650
Horizontal validation criteria: minimum distance (mm)	0.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	0.000000

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.203	0.078	0.034	0.036	0.036



F. 3D Image



ANNEX D SAR Test Setup Photos

Reference Photo: simulation liquid depth 15cm




Reference Photos



Left Head - Cheek




Left Head - Tilt



Right Head - Cheek




Right Head - Tilt




Hotspot Front (dist. 10mm)



Hotspot Back (dist. 10mm)



Hotspot Left (dist. 10mm)



Hotspot Right (dist. 10mm)



Hotspot Top (dist. 10mm)



Hotspot Bottom (dist. 10mm)

ANNEX E EUT External and Internal Photos

Please refer to RF Report.

ANNEX F Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--