

# TEST REPORT



**Dt&C Co., Ltd.**

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042  
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2404-0039

2. Customer

• Name (FCC) : DHAUTOWARE Co.,Ltd.

• Address (FCC) : 278, Beotkkot-ro, Geumcheon-gu Seoul South Korea 08511

3. Use of Report : FCC Original Grant

4. Product Name / Model Name : 24MY BN7 8inch AVN / DM-S12101A  
FCC ID : 2BDNYJCHBN700AVNC

5. FCC Regulation(s): Part 15.247

Test Method used: KDB558074 D01v05r02, ANSI C63.10-2013

6. Date of Test : 2024.03.05 ~ 2024.03.18

7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : SeokHo Han (Signature)	Name : JaeJin Lee (Signature)

2024 . 04 . 09 .

**Dt&C Co., Ltd.**

If this report is required to confirmation of authenticity, please contact to [report@dtnc.net](mailto:report@dtnc.net)

## Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2404-0039	Apr, 09. 2024	Initial issue	SeokHo Han	JaeJin Lee

# Table of Contents

<b>1. General Information .....</b>	<b>4</b>
1.1. Description of EUT .....	4
1.2. Declaration by the applicant / manufacturer .....	4
1.3. Testing Laboratory .....	5
1.4. Testing Environment.....	5
1.5. Measurement Uncertainty.....	5
1.6. Test Equipment List .....	6
<b>2. Test Methodology .....</b>	<b>7</b>
2.1. EUT Configuration.....	7
2.2. EUT Exercise.....	7
2.3. General Test Procedures .....	7
2.4. Instrument Calibration .....	7
2.5. Description of Test Modes.....	8
<b>3. Antenna Requirements .....</b>	<b>9</b>
<b>4. Summary of Test Result .....</b>	<b>10</b>
<b>5. Test Result .....</b>	<b>11</b>
5.1. Unwanted Emissions (Radiated).....	11
5.1.1. Test Setup.....	12
5.1.2. Test Procedures .....	12
5.1.3. Test Results.....	13
5.3. AC Power-Line Conducted Emissions .....	15
5.3.1. Test Setup.....	15
5.3.2. Test Procedures .....	15
5.3.3. Test Results.....	15
<b>APPENDIX I .....</b>	<b>16</b>
<b>APPENDIX II .....</b>	<b>17</b>
<b>APPENDIX III .....</b>	<b>19</b>
<b>APPENDIX IIII .....</b>	<b>27</b>

## 1. General Information

### 1.1. Description of EUT

Equipment Class	Digital Transmission System (DTS)
Product Name	24MY BN7 8inch AVN
Model Name	DM-S12101A
Add Model Name	JCHBN700AVNC
EUT Serial Number	Conducted: 000024021613202600C8, Radiated: 000024021613300500CB
Power Supply	DC 14.4 V
Modulation Technique	<ul style="list-style-type: none"><li>▪ 802.11b: CCK, DSSS</li><li>▪ 802.11g/n: OFDM</li></ul>
Antenna Specification	Antenna Type: PCB Antenna Gain: 2.30 dBi (PK)

### 1.2. Declaration by the applicant / manufacturer

N/A

### 1.3. Testing Laboratory

<b>Dt&amp;C Co., Ltd.</b>		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of Part 2.948 according to ANSI C63.4-2014.		
- FCC & IC MRA Designation No. : KR0034		
- ISED#: 5740A		
<a href="http://www.dtnet.net">www.dtnet.net</a>		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

### 1.4. Testing Environment

Ambient Condition	
▪ Temperature	+20 °C ~ +23 °C
▪ Relative Humidity	+40 % ~ +43 %

### 1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Antenna-port conducted emission	1.0 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (1 GHz Below)	5.0 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (1 GHz ~ 18 GHz)	4.8 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (18 GHz Above)	5.7 dB (The confidence level is about 95 %, $k = 2$ )

## 1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	23/12/15	24/12/15	MY48010133
Spectrum Analyzer	Agilent Technologies	N9020A	23/06/23	24/06/23	US47360812
Spectrum Analyzer	Agilent Technologies	N9020A	23/06/23	24/06/23	MY46471622
Receiver	Rohde Schwarz	ESC13	23/06/23	24/06/23	100798
DC Power Supply	Agilent Technologies	66332A	23/06/23	24/06/23	US37474125
DC Power Supply	SM techno	SDP30-5D	23/06/23	24/06/23	305DMG288
Multimeter	FLUKE	17B+	23/12/15	24/12/15	36390701WS
Signal Generator	Rohde Schwarz	SMBV100A	23/12/15	24/12/15	255571
Signal Generator	ANRITSU	MG3695C	23/12/15	24/12/15	173501
Thermohygrometer	BODYCOM	BJ5478	23/12/15	24/12/15	120612-1
Thermohygrometer	BODYCOM	BJ5478	23/12/15	24/12/15	120612-2
Thermohygrometer	BODYCOM	BJ5478	23/06/23	24/06/23	N/A
Loop Antenna	ETS-Lindgren	6502	23/11/09	24/11/09	00060496
Hybrid Antenna	Schwarzbeck	VULB 9160	23/12/15	24/12/15	3362
Horn Antenna	ETS-Lindgren	3117	23/06/23	24/06/23	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	23/06/23	24/06/23	155
PreAmplifier	tsj	MLA-0118-B01-40	23/12/15	24/12/15	1852267
PreAmplifier	tsj	MLA-1840-J02-45	23/06/23	24/06/23	16966-10728
PreAmplifier	H.P	8447D	23/12/15	24/12/15	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	23/06/23	24/06/23	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	23/06/23	24/06/23	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	23/06/23	24/06/23	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	23/06/23	24/06/23	16012202
Attenuator	Aeroflex/Weinschel	56-3	23/06/23	24/06/23	Y2370
Attenuator	SMAJK	SMAJK-2-3	23/06/23	24/06/23	3
Attenuator	SMAJK	SMAJK-2-3	23/06/23	24/06/23	2
Attenuator	Aeroflex/Weinschel	86-10-11	23/06/23	24/06/23	408
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A MA2411B	23/12/15	24/12/15	1338004 1911481
Cable	Dt&C	Cable	24/01/03	25/01/03	G-2
Cable	HUBER+SUHNER	SUCOFLEX 100	24/01/03	25/01/03	G-3
Cable	Dt&C	Cable	24/01/03	25/01/03	G-4
Cable	OMT	YSS21S	24/01/03	25/01/03	G-5
Cable	Junkosha	MWX241	24/01/03	25/01/03	mmW-1
Cable	Junkosha	MWX241	24/01/03	25/01/03	mmW-4
Cable	HUBER+SUHNER	SUCOFLEX100	24/01/03	25/01/03	M-01
Cable	HUBER+SUHNER	SUCOFLEX100	24/01/03	25/01/03	M-02
Cable	JUNFLON	MWX241/B	24/01/03	25/01/03	M-03
Cable	JUNFLON	J12J101757-00	24/01/03	25/01/03	M-07
Cable	HUBER+SUHNER	SUCOFLEX106	24/01/03	25/01/03	M-09
Cable	Radiall	TESTPRO3	24/01/03	25/01/03	RFC-70
Test Software (Radiated)	tsj	EMI Measurement	NA	NA	Version 2.00.0185

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by Dt&C itself.

## 2. Test Methodology

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB558074 D01v05r02 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB558074 D01v05r02. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the test mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.

So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

#### Radiated Emissions

Basically the radiated tests were performed with KDB558074 D01v05r02. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on section 12.1 of the KDB558074 D01v05r02.

The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

### 2.4. Instrument Calibration

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

## 2.5. Description of Test Modes

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting.

### EUT Operation test setup

- Test Software: Tera Term 4.104.0.0

### Test Mode

Test mode	Worst case data rate	Tested Frequency (MHz)		
TM 1	802.11b 11 Mbps	2 412	2 437	2 462
TM 2	802.11g 6 Mbps	2 412	2 437	2 462
TM 3	802.11n(HT20) MCS 0	2 412	2 437	2 462

Note1: The worst case data rate was determined based on the certified module report.



### 3. Antenna Requirements

■ **According to Part 15.203**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

**The antenna is attached on the PCB by means of unique connector.  
Therefore this E.U.T complies with the requirement of Part 15.203**

## 4. Summary of Test Result

FCC part section(s)	Test Description	Limit	Test Condition	Status Note 1
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	<b>NT</b> Note 2
15.247(b)	Maximum Peak Output Power	< 1 Watt		<b>NT</b> Note 2
15.247(d)	Unwanted Emissions(Conducted)	20 dBc in any 100 kHz BW		<b>NT</b> Note 2
15.247(e)	Power Spectral Density	< 8 dBm / 3 kHz		<b>NT</b> Note 2
15.247(d) 15.205 15.209	Unwanted Emissions(Radiated)	Part 15.209 limits (Refer to section 5.2)	Radiated	<b>C</b>
15.207	AC Power-Line Conducted Emissions	Part 15.207 limits (Refer to section 5.3)	AC Line Conducted	<b>NA</b> Note 3
15.203	Antenna Requirements	Part 15.203 (Refer to section 3)	-	<b>C</b>
<p>Note 1: <b>C</b>=Comply   <b>NC</b>=Not Comply   <b>NT</b>=Not Tested   <b>NA</b>=Not Applicable</p> <p>Note 2: This device uses the certified module. (FCC ID: 2ADQJ-YSP88459SM) Please refer to the module test for conducted signal test items. The conducted output power was verified to be the same as module.</p> <p>Note 3: This device is installed in a car. Therefore the power source is a battery of car.</p>				

## 5. Test Result

### 5.1. Unwanted Emissions (Radiated)

#### ■ Test Requirements and limit,

#### Part 15.247(d), Part 15.205, Part 15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of Part 15.247 the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### - Part 15.209: General requirement

Frequency (MHz)	FCC Limit (uV/m)	Measurement Distance (m)
0.009 – 0.490	2 400 / F (kHz)	300
0.490 – 1.705	24 000 / F (kHz)	30
1.705 – 30.0	30	30

Frequency (MHz)	FCC Limit (uV/m)	Measurement Distance (m)
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

#### - Part 15.205(a): Restricted band of operation

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.414 25 ~ 8.414 75	108 ~ 121.94	1 300 ~ 1 427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1 435 ~ 1 626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.173 5 ~ 2.190 5	12.519 75 ~ 12.520 25	149.9 ~ 150.05	1 645.5 ~ 1 646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.576 75 ~ 12.577 25	156.524 75 ~ 156.525 25	1 660 ~ 1 710	8.025 ~ 8.5	22.01 ~ 23.12
4.177 25 ~ 4.177 75	13.36 ~ 13.41	156.7 ~ 156.9	1 718.8 ~ 1 722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.207 25 ~ 4.207 75	16.42 ~ 16.423	162.012 5 ~ 167.17	2 200 ~ 2 300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.694 75 ~ 16.695 25	167.72 ~ 173.2	2 310 ~ 2 390	10.6 ~ 12.7	36.43 ~ 36.5
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	240 ~ 285	2 483.5 ~ 2 500	13.25 ~ 13.4	Above 38.6
6.311 75 ~ 6.312 25	25.5 ~ 25.67	322 ~ 335.4	2 655 ~ 2 900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3 260 ~ 3 267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3 332 ~ 3 339		
8.376 25 ~ 8.386 75	74.8 ~ 75.2	960 ~ 1 240	3 345.8 ~ 3 358		
			3 600 ~ 4 400		

### 5.1.1. Test Setup

Refer to the APPENDIX I.

### 5.1.2. Test Procedures

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm.  
For emission measurements above 1 GHz, the table height is 1.5 m.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1 m to 4 m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

#### Note: Measurement Instrument Setting for Radiated Emission Measurements.

- KDB558074 D01v05r02 - Section 8.6
- ANSI C63.10-2013 – Section 11.12

#### 1. Frequency Range Below 1 GHz

RBW = 100 or 120 kHz, VBW = 3 x RBW, Detector = Peak or Quasi Peak

#### 2. Frequency Range > 1 GHz

Peak Measurement > 1 GHz

RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes

Average Measurement > 1 GHz

1. RBW = 1 MHz (unless otherwise specified).
2. VBW  $\geq$  3 x RBW.
3. Detector = RMS (Number of points  $\geq$  2 x Span / RBW)
4. Averaging type = power (i.e., RMS).
5. Sweep time = auto.
6. Perform a trace average of at least 100 traces.
7. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (RMS) mode was used in step 4, then the applicable correction factor is  $10 \log(1/D)$ , where D is the duty cycle.
  - 2) If linear voltage averaging mode was used in step 4, then the applicable correction factor is  $20 \log(1/D)$ , where D is the duty cycle.
  - 3) If a specific emission is demonstrated to be continuous ( $\geq$  98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

#### Duty Cycle Correction factor

Test Mode	Date rate	T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	D = T <sub>on</sub> / (T <sub>on+off</sub> )	DCCF = 10 log(1/D) (dB)
TM 1	11 Mbps	1.206	1.302	0.926 3	0.33
TM 2	6 Mbps	2.063	2.165	0.952 9	0.21
TM 3	MCS 0	1.919	2.021	0.949 5	0.23

Note1: Where, T= Transmission duration / D= Duty cycle

Note2: Please refer to the appendix II for duty cycle plots.

### 5.1.3. Test Results

#### - Test Notes

1. The radiated emissions were investigated 9 kHz to 25 GHz. And no other spurious and harmonic emissions were found below listed frequencies.
2. Information of Distance Correction Factor  
For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.  
In this case, the distance factor is applied to the result.  
- Calculation of distance correction factor  
At frequencies below 30 MHz =  $40 \log(\text{tested distance} / \text{specified distance})$   
At frequencies at or above 30 MHz =  $20 \log(\text{tested distance} / \text{specified distance})$   
When distance factor is "N/A", the measurements were performed at the specified distance and distance factor is not applied.
3. Sample Calculation.  
 $\text{Margin} = \text{Limit} - \text{Result}$  /  $\text{Result} = \text{Reading} + \text{TF} + \text{DCCF} + \text{DCF}$  /  $\text{TF} = \text{AF} + \text{CL} + \text{HL} + \text{AL} - \text{AG}$   
Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain, HL = High pass filter Loss, AL = Attenuator Loss, DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor

### Radiated Emissions data(9 kHz ~ 25 GHz) : TM 1

Tested Frequency (MHz)	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)
2 412	2 389.36	H	X	PK	51.91	4.48	N/A	N/A	56.39	74.00	17.61
	2 389.75	H	X	AV	42.21	4.48	0.33	N/A	47.02	54.00	6.98
	4 823.64	H	X	PK	51.50	1.61	N/A	N/A	53.11	74.00	20.89
	4 823.99	H	X	AV	41.27	1.61	0.33	N/A	43.21	54.00	10.79
	7 235.88	V	X	PK	51.01	7.25	N/A	N/A	58.26	74.00	15.74
	7 235.12	V	X	AV	41.14	7.24	0.33	N/A	48.71	54.00	5.29
2 437	4 873.83	H	X	PK	51.65	1.54	N/A	N/A	53.19	74.00	20.81
	4 873.69	H	X	AV	41.04	1.54	0.33	N/A	42.91	54.00	11.09
	7 309.20	V	X	PK	50.28	6.78	N/A	N/A	57.06	74.00	16.94
	7 309.89	V	X	AV	40.36	6.77	0.33	N/A	47.46	54.00	6.54
2 462	2 488.43	H	X	PK	52.33	5.08	N/A	N/A	57.41	74.00	16.59
	2 488.06	H	X	AV	42.19	5.07	0.33	N/A	47.59	54.00	6.41
	4 923.90	H	X	PK	50.17	2.25	N/A	N/A	52.42	74.00	21.58
	4 923.98	H	X	AV	39.93	2.25	0.33	N/A	42.51	54.00	11.49
	7 384.84	V	X	PK	48.10	7.16	N/A	N/A	55.26	74.00	18.74
	7 384.42	V	X	AV	37.80	7.16	0.33	N/A	45.29	54.00	8.71

**Radiated Emissions data(9 kHz ~ 25 GHz) : TM 2**

Tested Frequency (MHz)	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)
2 412	2 389.13	H	X	PK	54.64	4.48	N/A	N/A	59.12	74.00	14.88
	2 389.57	H	X	AV	44.18	4.48	0.21	N/A	48.87	54.00	5.13
	4 823.39	H	X	PK	51.17	1.61	N/A	N/A	52.78	74.00	21.22
	4 822.94	H	X	AV	40.76	1.61	0.21	N/A	42.58	54.00	11.42
	7 238.50	V	X	PK	51.65	7.27	N/A	N/A	58.92	74.00	15.08
	7 236.74	V	X	AV	40.12	7.26	0.21	N/A	47.59	54.00	6.41
2 437	4 873.22	H	X	PK	51.39	1.54	N/A	N/A	52.93	74.00	21.07
	4 873.46	H	X	AV	40.69	1.54	0.21	N/A	42.44	54.00	11.56
	7 310.22	V	X	PK	50.11	6.76	N/A	N/A	56.87	74.00	17.13
	7 308.40	V	X	AV	39.90	6.79	0.21	N/A	46.90	54.00	7.10
2 462	2 484.23	H	X	PK	55.67	4.99	N/A	N/A	60.66	74.00	13.34
	2 483.82	H	X	AV	44.32	4.98	0.21	N/A	49.51	54.00	4.49
	4 922.99	H	X	PK	49.73	2.24	N/A	N/A	51.97	74.00	22.03
	4 922.89	H	X	AV	39.52	2.24	0.21	N/A	41.97	54.00	12.03
	7 380.79	V	X	PK	49.31	7.13	N/A	N/A	56.44	74.00	17.56
	7 381.38	V	X	AV	37.77	7.13	0.21	N/A	45.11	54.00	8.89

**Radiated Emissions data(9 kHz ~ 25 GHz) : TM 3**

Tested Frequency (MHz)	Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin(dB)
2 412	2 388.61	H	X	PK	53.64	4.47	N/A	N/A	58.11	74.00	15.89
	2 389.09	H	X	AV	43.96	4.48	0.23	N/A	48.67	54.00	5.33
	4 823.07	H	X	PK	51.23	1.61	N/A	N/A	52.84	74.00	21.16
	4 823.32	H	X	AV	40.89	1.61	0.23	N/A	42.73	54.00	11.27
	7 235.28	V	X	PK	53.44	7.25	N/A	N/A	60.69	74.00	13.31
	7 234.81	V	X	AV	41.09	7.24	0.23	N/A	48.56	54.00	5.44
2 437	4 874.17	H	X	PK	50.94	1.55	N/A	N/A	52.49	74.00	21.51
	4 874.28	H	X	AV	40.65	1.55	0.23	N/A	42.43	54.00	11.57
	7 309.00	V	X	PK	50.90	6.78	N/A	N/A	57.68	74.00	16.32
	7 308.59	V	X	AV	39.48	6.78	0.23	N/A	46.49	54.00	7.51
2 462	2 485.38	H	X	PK	55.19	5.01	N/A	N/A	60.20	74.00	13.80
	2 485.21	H	X	AV	44.28	5.01	0.23	N/A	49.52	54.00	4.48
	4 922.55	H	X	PK	49.78	2.24	N/A	N/A	52.02	74.00	21.98
	4 922.37	H	X	AV	39.78	2.24	0.23	N/A	42.25	54.00	11.75
	7 382.94	V	X	PK	48.00	7.14	N/A	N/A	55.14	74.00	18.86
	7 383.13	V	X	AV	37.78	7.15	0.23	N/A	45.16	54.00	8.84

### 5.3. AC Power-Line Conducted Emissions

#### ■ Test Requirements and limit, Part 15.207

An intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5.0	56	46
5 ~ 30	60	50

\* Decreases with the logarithm of the frequency

#### 5.3.1. Test Setup

NA

#### 5.3.2. Test Procedures

Conducted emissions from the EUT were measured according to the ANSI C63.10-2013.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.


#### 5.3.3. Test Results

NA


## APPENDIX I

### Test set up diagrams

#### ▪ Radiated Measurement



#### ▪ Conducted Measurement



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	10.77	15	11.88
1	11.05	20	12.16
2.402 & 2.440 & 2.480	11.18	25	12.94
5	11.32	-	-
10	11.70	-	-


Note 1: The path loss from EUT to Spectrum analyzer was measured and used for test.  
Path loss (S/A's correction factor) = Cable A + Attenuator






## Duty Cycle

TM 2 &amp; 2 437 MHz



## Duty Cycle

TM 3 &amp; 2 437 MHz




## APPENDIX III

### Unwanted Emissions (Radiated) Test Plot


TM 1 & 2 412 & X axis & Hor

Detector Mode : PK




TM 1 & 2 412 & X axis & Hor

Detector Mode : AV




TM 1 &amp; 2 462 &amp; X axis &amp; Hor

Detector Mode : PK




TM 1 &amp; 2 462 &amp; X axis &amp; Hor


Detector Mode : AV



**Detector Mode : PK**




**Detector Mode : AV**



TM 2 &amp; 2 462 &amp; X axis &amp; Hor

Detector Mode : PK




TM 2 &amp; 2 462 &amp; X axis &amp; Hor

Detector Mode : AV




TM 3 &amp; 2 412 &amp; X axis &amp; Hor

Detector Mode : PK



TM 3 &amp; 2 412 &amp; X axis &amp; Hor


Detector Mode : AV





TM 3 &amp; 2 462 &amp; X axis &amp; Hor

Detector Mode : PK



TM 3 &amp; 2 462 &amp; X axis &amp; Hor


Detector Mode : AV






TM 1 &amp; 2 437 &amp; X axis &amp; Ver

Detector Mode : AV




TM 2 &amp; 2 412&amp; X axis &amp; Ver

Detector Mode : AV



TM 3 &amp; 2 412&amp; X axis &amp; Ver


Detector Mode : AV



## APPENDIX III

### Output power verification

#### Test Setup



#### Test Procedure

- KDB558074 D01v05r02 - Section 8.3.1.3
- ANSI C63.10-2013 – Section 11.9.1.3

#### RBW ≥ DTSPKPM1 Peak-reading power meter method

The maximum conducted output powers were measured using a broadband peak RF power meter which has greater video bandwidth than DUT's DTS bandwidth and utilize a fast-responding diode detector.

- KDB558074 D01v05r02 - Section 8.3.2.3
- ANSI C63.10-2013 – Section 11.9.2.3

#### Method AVGPM-G

The average conducted output powers were measured using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Mode	Data Rate	Tested Frequency (MHz)	Average Output Power (dBm)	Peak Output Power (dBm)
802.11g	6 Mbps	2 412	10.99	21.18
		2 437	10.92	21.26
		2 462	10.93	21.50

All mode were measured and the worst-case results are reported.