

EV Charging Clean Energy Technology Co., Ltd.

Model Difference Declaration

We, EV Charging Clean Energy Technology Co., Ltd. declare:

Atlas All-in-One DC charger: Atlas D80-US, Atlas D120-US, Atlas D160-US, Atlas D160-US-PRO

FCC ID: 2BETU-ATLASD160US

IC: 31984-ATLASD160US

Atlas D80-US, Atlas D120-US and Atlas D160-US are electrically identical except the rated power. The difference between Atlas D160-US and Atlas D160-US-PRO is Atlas D160-US-PRO has liquid cooling while Atlas D160-US doesn't.

Atlas D80-US: Input: 480VAC, 60Hz, 117A Max

Output 1/2: 200-1000VDC, 200A Max, 80kW Max

Atlas D120-US: Input: 480VAC, 60Hz, 174A Max

Output 1/2: 200-1000VDC, 200A Max, 120kW Max

Atlas D160-US: Input: 480VAC, 60Hz, 231A Max

Output 1/2: 200-1000VDC, 200A Max, 160kW Max

Atlas D160-US-PRO: Input: 480VAC, 60Hz, 232A Max

Output 1: 200-1000VDC, 500A Max, 160kW Max

Output 2: 200-1000VDC, 200A Max, 160kW Max

Xianhong Yan

Xianhong Yan

Date: August 30, 2024