RF Test Report

FCC ID: 2BLEP-FTT100

Test Report No……..:	EMC240802004-02-002
Product(s) Name……...:	Touchscreen Computer
Model(s)……..:	FTT100
Trade Mark……....:	PlayReplay
Applicant……..…:	PLAYREPLAY AB
Address……..…...:	co Kjellander SjOberg Rosenlundsgatan 40 11853 Stockholm Sweden
Receipt Date……..:	2024.08.12
Test Date……....:	2024.08.14~2024.09.20
Issued Date……..…:	2024.09.24
Standards……..:	47 CFR FCC Part 15, Subpart C(Section 15.247) ANSI C63.10:2013
Testing Laboratory……:	Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Black Ding	Tim Zhang	Misue Su	Shenzhen Haiyun Standard Technical Co., Ltd. HAIYUN Report Seal
Black Ding	Tim.zhang	Misue Su	

Table of Contents

REPORT ISSUED HISTORY 4

1 . SUMMARY OF TEST RESULTS 5

1.1 TEST FACILITY 6

1.2 MEASUREMENT UNCERTAINTY 6

1.3 TEST ENVIRONMENT CONDITIONS 6

2 . GENERAL INFORMATION 7

2.1 GENERAL DESCRIPTION OF EUT 7

2.2 DESCRIPTION OF TEST MODES 8

2.3 PARAMETERS OF TEST SOFTWARE 9

2.4 SUPPORT UNITS 9

3 . AC POWER LINE CONDUCTED EMISSIONS 10

3.1 LIMIT 10

3.2 TEST PROCEDURE 10

3.3 DEVIATION FROM TEST STANDARD 10

3.4 TEST SETUP 11

3.5 EUT OPERATING CONDITIONS 11

3.6 TEST RESULTS 11

4 . RADIATED EMISSIONS 12

4.1 LIMIT 12

4.2 TEST PROCEDURE 13

4.3 DEVIATION FROM TEST STANDARD 14

4.4 TEST SETUP 14

4.5 EUT OPERATING CONDITIONS 15

4.6 TEST RESULT - 9 KHZ TO 30 MHZ 15

4.7 TEST RESULT - 30 MHZ TO 1000 MHZ 15

4.8 TEST RESULT - ABOVE 1000 MHZ 15

5 . BANDWIDTH 16

5.1 LIMIT 16

5.2 TEST PROCEDURE 16

5.3 DEVIATION FROM STANDARD 16

5.4 TEST SETUP 16

5.5 EUT OPERATION CONDITIONS 16

5.6 TEST RESULTS 16

6 . MAXIMUM OUTPUT POWER 17

6.1 LIMIT 17
6.2 TEST PROCEDURE 17
6.3 DEVIATION FROM STANDARD 17
6.4 TEST SETUP 17
6.5 EUT OPERATION CONDITIONS 17
6.6 TEST RESULTS 17
7 . CONDUCTED SPURIOUS EMISSION 18
7.1 LIMIT 18
7.2 TEST PROCEDURE 18
7.3 DEVIATION FROM STANDARD 18
7.4 TEST SETUP 18
7.5 EUT OPERATION CONDITIONS 18
7.6 TEST RESULTS 18
8 . POWER SPECTRAL DENSITY 19
8.1 LIMIT 19
8.2 TEST PROCEDURE 19
8.3 DEVIATION FROM STANDARD 19
8.4 TEST SETUP 19
8.5 EUT OPERATION CONDITIONS 19
8.6 TEST RESULTS 19
9 . MEASUREMENT INSTRUMENTS LIST 20
10 . ANTENNA REQUIREMENT 21
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS 22
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ 27
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ 28
APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ 33
APPENDIX E - BANDWIDTH 44
APPENDIX F - MAXIMUM OUTPUT POWER 53
APPENDIX G - CONDUCTED SPURIOUS EMISSION 58
APPENDIX H - POWER SPECTRAL DENSITY 70

REPORT ISSUED HISTORY

Original Report Issue Date: 2024.09.24

● No additional attachment

○ Additional attachments were issued following record

Attachment No.	Issue Date	Description

1.. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	**Test Item**	**Test Result**	**Judgment**	**Remark**
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	------
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	------
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	------
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	------
15.247(d)	Conducted Spurious Emission	APPENDIX G	PASS	------
15.247(e)	Power Spectral Density	APPENDIX H	PASS	------
15.203	Antenna Requirement	------	PASS	Note(2)

Note:

(1) “N/A” denotes test is not applicable to this device.

(2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.

1.1. TEST FACILITY

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier	CN0145
A2LA Certificate Number	6823.01
Telephone:	0755-26024411

1.2. MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Uncertainty	
Parameter	Uncertainty
Occupied Channel Bandwidth	±102kHz
Power Spectral Density	±0.743dB
Conducted Spurious Emission	±1.328dB
RF power conducted	±0.377dB
Conducted emission(9kHz~30MHz) AC main	±2.68dB
Radiated emission(9kHz~30MHz)	±2.74dB
Radiated emission (30MHz~1GHz)	±4.22dB
Radiated emission (1GHz~18GHz)	±5.06dB
Radiated emission (18GHz~40GHz)	±4.98dB

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3. TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	23.5°C	49%	AC 120V/60Hz	Freedom Zhuo
Radiated Emissions-9 kHz to 30 MHz	23.4°C	53%	AC 120V/60Hz	Freedom Zhuo
Radiated Emissions-30 MHz to 1000 MHz	23.4°C	53%	AC 120V/60Hz	Freedom Zhuo
Radiated Emissions-Above 1000 MHz	23.4°C	53%	AC 120V/60Hz	Freedom Zhuo
Bandwidth	23.6°C	50%	DC 12V	Albert Fan
Maximum Output Power	23.6°C	50%	DC 12V	Albert Fan
Conducted Spurious Emission	23.6°C	50%	DC 12V	Albert Fan
Power Spectral Density	23.6°C	50%	DC 12V	Albert Fan

Note: Adapter supply voltage AC 120V/60Hz.

2.. GENERAL INFORMATION

2.1. GENERAL DESCRIPTION OF EUT

Product No.	POC240802004-S001
Product Name	Touchscreen Computer
Model Name	FTT100
Trade Mark	PlayReplay
Power Supply	DC 12V from adapter or POE 48V
Operation Frequency	2402 MHz ~ 2480 MHz
Modulation Type	GFSK
Bit Rate of Transmitter	1Mbps, 2Mbps
Max. Output Power	0.89 dBm (0.0012W)
Antenna gain	1.09dBi
Antenna type	External Antenna

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

2.2. DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39
Mode 2	TX Mode_2Mbps Channel 00/19/39
Mode 3	TX Mode_1Mbps Channel 00

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 3	TX Mode_1Mbps Channel 00

Radiated emissions test – Below 1GHz	
Final Test Mode	Description
Mode 3	TX Mode_1Mbps Channel 00

Radiated emissions test – Above 1GHz	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39
Mode 2	TX Mode_2Mbps Channel 00/19/39

Conducted test	
Final Test Mode	Description
Mode 1	TX Mode_1Mbps Channel 00/19/39
Mode 2	TX Mode_2Mbps Channel 00/19/39

Note:

(1) For radiated emission above 1 GHz test, the spurious points of 1GHz~18GHz and 18GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.

(2) For AC power line conducted emissions and radiated emissions below 1 GHz test, the TX Mode_1Mbps Channel 00 is found to be the worst case and recorded.

2.3. PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	cmd.exe		
Frequency (MHz)	2402	2440	2480
1Mbps	default	default	default
2Mbps	default	default	default

2.4. SUPPORT UNITS

No.	Equipment	Model	Manufacturer	Series No
1	POE	G0545-530-060-PSE1000	GOSPE DIGITAL	/
2	SWITCHING ADAPTER	GQ48-120500-E1	GangQi	/
3	Earphone	E1	Xiaomi	/
4	Flat Panel Monitor	S2721QS	DELL	/

3.. AC POWER LINE CONDUCTED EMISSIONS

3.1. LIMIT

Frequency of Emission (MHz)	Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

Note:

(1) The tighter limit applies at the band edges.
(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2. TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.3. DEVIATION FROM TEST STANDARD

No deviation.

3.4. TEST SETUP



3.5. EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.6. TEST RESULTS

Please refer to the APPENDIX A.

Remark:

(1) All readings are QP Mode value unless otherwise stated AVG in column of『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform.In this case, a " * " marked in AVG Mode column of Interference Voltage Measured.

(2) Measuring frequency range from 150 kHz to 30 MHz.

4.. RADIATED EMISSIONS

4.1. LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2. TEST PROCEDURE

a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn‘t perform. (below 1 GHz)
h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn‘t perform. (above 1 GHz)
i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5 GHz for PK/AVG detector

4.3. DEVIATION FROM TEST STANDARD

No deviation.

4.4. TEST SETUP

9 kHz to 30 MHz



30 MHz to 1 GHz



Above 1 GHz



4.5. EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6. TEST RESULT - 9 kHz TO 30 MHz

Please refer to the APPENDIX B.

Remark:

(1) Distance extrapolation factor = 40 log (specific distance / test distance) (dB).
(2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7. TEST RESULT - 30 MHz TO 1000 MHz

Please refer to the APPENDIX C.

4.8. TEST RESULT - ABOVE 1000 MHz

Please refer to the APPENDIX D.

Remark:

(1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5.. BANDWIDTH

5.1. LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6 dB Bandwidth	>= 500 kHz
	99% Emission Bandwidth	-

5.2. TEST PROCEDURE

a. The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span Frequency	> Measurement Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span Frequency	Between 1.5 times and 5.0 times the OBW
RBW	1% to 5% of the OBW
VBW	approximately three times RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.3. DEVIATION FROM STANDARD

No deviation.

5.4. TEST SETUP



5.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6. TEST RESULTS

Please refer to the APPENDIX E.

6.. MAXIMUM OUTPUT POWER

6.1. LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Output Power	1.0000 watt or 30.00 dBm

6.2. TEST PROCEDURE

a. The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	≥ 3×RBW
RBW	2 MHz
VBW	6 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3. DEVIATION FROM STANDARD

No deviation.

6.4. TEST SETUP



6.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6. TEST RESULTS

Please refer to the APPENDIX F.

7.. CONDUCTED SPURIOUS EMISSION

7.1. LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

7.2. TEST PROCEDURE

a. The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.
b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3. DEVIATION FROM STANDARD

No deviation.

7.4. TEST SETUP



7.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6. TEST RESULTS

Please refer to the APPENDIX G.

8.. POWER SPECTRAL DENSITY

8.1. LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

8.2. TEST PROCEDURE

a. The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.

b. The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	2 MHz
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3. DEVIATION FROM STANDARD

No deviation.

8.4. TEST SETUP



8.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6. TEST RESULTS

Please refer to the APPENDIX H.

9.. MEASUREMENT INSTRUMENTS LIST

Radiated Emissions							
No.	Equipment	Manufacturer	Type No.	Serial No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal. Due date (yyyy/mm/dd)
1	Test receiver	Rohde&Schwarz	ESU	100184	JLE011	2024/4/24	2025/4/23
2	Log periodic antenna	Schwarzbeck	VULB 9168	1151	JLE012	2024/4/20	2025/4/19
3	Low frequency amplifier	/	LNA 0920N	2014	JLE023	2024/4/24	2025/4/23
4	High frequency amplifier	Schwarzbeck	BBV 9718	284	JLE024	2024/4/24	2025/4/23
5	Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1273	JLE028	2024/4/20	2025/4/19
6	Temp&Humidity Recorder	Meideshi	JR900	/	JLE021	2024/4/24	2025/4/23
7	Horn Antenna	SCHWARZBECK	BBHA 9170	9170#685	JLE029	2024/7/15	2025/7/14
8	Loop Antenna	SCHWARZBECK	FMZB1519B	00029	JLE030	2024/7/15	2025/7/14
9	Broadband preamplifier	Schwarzbeck	BBV9721	9721-019	JLE025	2024/4/24	2025/4/23
10	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
Conducted Emission							
1	LISN	Rohde&Schwarz	ENV216	100075	JLE002	2024/4/24	2025/4/23
2	ISN	Schwarzbeck	CATE 5 8158	#171	JLE003	2024/4/24	2025/4/23
3	Test receiver	Rohde&Schwarz	ESCI	100718	JLE010	2024/4/24	2025/4/23
4	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	JLE047	2024/4/24	2025/4/23
5	Temp&Humidity Recorder	Meideshi	JR900	/	JLE020	2024/4/24	2025/4/23
6	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
RF Conducted Emission							
1	MXA Signal Analyzer	Keysight	N9021B	MY60080169	JLE050	2024/4/20	2025/4/19
2	RF Control Unit	dsusoft	JS0806-2	21G8060449	JLE053	2024/4/20	2025/4/19
3	power supply unit	dsusoft	JS0806-4ADC	N/A	JLE055	2024/4/20	2025/4/19
4	VXG Signal Generator	Keysight	M9384B	MY61270787	JLE051	2024/4/20	2025/4/19
5	EXG Analog Signal Generator	Keysight	N5173B	MY59101282	JLE052	2024/4/20	2025/4/19
6	Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	1201.0002K50-116064-Dt	JLE054	2024/4/20	2025/4/19
7	Test software	dsusoft	JS1120-3 Ver.3.2.22.0				

10.. ANTENNA REQUIREMENT

Test standard: FCC part 15.203

According to the manufacturer declared, the EUT has an external antenna, the antenna gain is 1.09dBi and the antenna connector is designed RP-SMA antenna interface.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

POE power supply

Test Mode	TX Mode_1Mbps Channel 00	Phase	Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1660	19.99	20.14	40.13	65.16	-25.03	QP	
2		0.1660	3.69	20.14	23.83	55.16	-31.33	AVG	
3		0.2580	28.81	20.02	48.83	61.50	-12.67	QP	
4		0.2580	21.05	20.02	41.07	51.50	-10.43	AVG	
5		0.4660	27.41	20.25	47.66	56.58	-8.92	QP	
6		0.4660	12.53	20.25	32.78	46.58	-13.80	AVG	
7	*	0.6500	27.48	20.03	47.51	56.00	-8.49	QP	
8		0.6500	15.05	20.03	35.08	46.00	-10.92	AVG	
9		11.2940	21.83	20.24	42.07	60.00	-17.93	QP	
10		11.2940	12.68	20.24	32.92	50.00	-17.08	AVG	
11		25.9060	10.33	20.23	30.56	60.00	-29.44	QP	
12		25.9060	4.45	20.23	24.68	50.00	-25.32	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_1Mbps Channel 00	Phase	Neutral

Conducted Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1780	26.70	20.30	47.00	64.58	-17.58	QP	
2		0.1780	10.77	20.30	31.07	54.58	-23.51	AVG	
3		0.2620	29.58	20.10	49.68	61.37	-11.69	QP	
4		0.2620	21.03	20.10	41.13	51.37	-10.24	AVG	
5		0.3340	26.39	20.09	46.48	59.35	-12.87	QP	
6		0.3340	17.72	20.09	37.81	49.35	-11.54	AVG	
7		0.4700	27.68	20.08	47.76	56.51	-8.75	QP	
8		0.4700	10.00	20.08	30.08	46.51	-16.43	AVG	
9	*	0.6420	28.42	20.20	48.62	56.00	-7.38	QP	
10		0.6420	16.33	20.20	36.53	46.00	-9.47	AVG	
11		10.3900	18.78	20.13	38.91	60.00	-21.09	QP	
12		10.3900	10.18	20.13	30.31	50.00	-19.69	AVG	

Adapter power supply

Test Mode	TX Mode_1Mbps Channel 00	Phase	Line



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1620	29.89	20.13	50.02	65.36	-15.34	QP	
2		0.1620	13.93	20.13	34.06	55.36	-21.30	AVG	
3		0.2500	16.52	20.00	36.52	61.76	-25.24	QP	
4		0.2500	1.68	20.00	21.68	51.76	-30.08	AVG	
5		0.6060	10.74	20.04	30.78	56.00	-25.22	QP	
6		0.6060	1.75	20.04	21.79	46.00	-24.21	AVG	
7		2.4740	9.01	20.04	29.05	56.00	-26.95	QP	
8		2.4740	3.37	20.04	23.41	46.00	-22.59	AVG	
9		7.5940	9.20	20.02	29.22	60.00	-30.78	QP	
10		7.5940	4.00	20.02	24.02	50.00	-25.98	AVG	
11		16.8340	13.26	20.16	33.42	60.00	-26.58	QP	
12		16.8340	5.00	20.16	25.16	50.00	-24.84	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_1Mbps Channel 00	Phase	Neutral

Conducted Emission Measurement



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1580	31.66	20.22	51.88	65.57	-13.69	QP	
2		0.1580	13.70	20.22	33.92	55.57	-21.65	AVG	
3		0.1780	27.60	20.17	47.77	64.58	-16.81	QP	
4		0.1780	10.30	20.17	30.47	54.58	-24.11	AVG	
5		0.5900	16.39	19.98	36.37	56.00	-19.63	QP	
6		0.5900	6.80	19.98	26.78	46.00	-19.22	AVG	
7		1.7220	9.22	20.21	29.43	56.00	-26.57	QP	
8		1.7220	1.85	20.21	22.06	46.00	-23.94	AVG	
9		5.9500	7.86	20.06	27.92	60.00	-32.08	QP	
10		5.9500	2.87	20.06	22.93	50.00	-27.07	AVG	
11		16.6820	15.11	20.30	35.41	60.00	-24.59	QP	
12		16.6820	7.34	20.30	27.64	50.00	-22.36	AVG	

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ

Radiated emission: 9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ

POE power supply

Test Mode	TX Mode_1Mbps Channel 00	Polarization	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.1797	44.35	-10.97	33.38	40.00	-6.62	peak			
2		43.3534	41.58	-9.65	31.93	40.00	-8.07	peak			
3	!	82.0704	48.34	-13.61	34.73	40.00	-5.27	peak			
4	!	250.3010	51.92	-11.78	40.14	46.00	-5.86	peak			
5	!	375.9384	49.28	-8.20	41.08	46.00	-4.92	peak			
6	*	625.0780	44.30	-2.93	41.37	46.00	-4.63	peak			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_1Mbps Channel 00	Polarization	Horizontal

Radiated Emission

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		39.5756	39.13	-9.93	29.20	40.00	-10.80	peak			
2		78.9651	46.52	-13.32	33.20	40.00	-6.80	peak			
3		162.6105	42.32	-8.97	33.35	43.50	-10.15	peak			
4	*	250.3010	53.81	-11.78	42.03	46.00	-3.97	peak			
5		375.9384	47.43	-8.20	39.23	46.00	-6.77	peak			
6	!	501.1790	46.30	-5.04	41.26	46.00	-4.74	peak			

Adapter power supply

Test Mode	TX Mode_1Mbps Channel 00	Polarization	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		43.3534	43.58	-9.65	33.93	40.00	-6.07	peak			
2		78.9651	46.77	-13.32	33.45	40.00	-6.55	peak			
3		89.2762	50.83	-13.86	36.97	43.50	-6.53	peak			
4		250.3010	51.42	-11.78	39.64	46.00	-6.36	peak			
5	!	375.9384	49.78	-8.20	41.58	46.00	-4.42	peak			
6	*	501.1790	47.72	-5.04	42.68	46.00	-3.32	peak			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

Test Mode	TX Mode_1Mbps Channel 00	Polarization	Horizontal

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		41.8594	37.55	-9.71	27.84	40.00	-12.16	peak			
2	*	79.8002	48.75	-13.49	35.26	40.00	-4.74	peak			
3	!	125.0065	47.86	-10.33	37.53	43.50	-5.97	peak			
4		191.0738	44.98	-12.11	32.87	43.50	-10.63	peak			
5		250.3010	51.31	-11.78	39.53	46.00	-6.47	peak			
6	!	501.1790	45.80	-5.04	40.76	46.00	-5.24	peak			

REMARKS:
(1) Measurement Value = Reading Level + Correct Factor.
(2) Margin Level = Measurement Value - Limit Value.

APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ

Test Mode	TX 2402 MHz_1Mbps	Polarization	Vertical

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4804.000	32.85	16.01	48.86	74.00	-25.14	peak			

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	46.61	-1.78	44.83	74.00	-29.17	peak			
2		2390.000	45.39	-1.54	43.85	74.00	-30.15	peak			

Test Mode	TX 2402 MHz_1Mbps	Polarization	Horizontal

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4804.000	32.98	16.01	48.99	74.00	-25.01	peak			

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2310.000	44.87	-1.78	43.09	74.00	-30.91	peak			
2	*	2390.000	44.70	-1.54	43.16	74.00	-30.84	peak			

Test Mode	TX 2440 MHz_1Mbps	Polarization	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4880.000	34.07	15.40	49.47	74.00	-24.53	peak			

Test Mode	TX 2440 MHz_1Mbps	Polarization	Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4880.000	33.01	15.40	48.41	74.00	-25.59	peak			

Test Mode	TX 2480 MHz_1Mbps	Polarization	Vertical

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4960.000	34.02	14.93	48.95	74.00	-25.05	peak			

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2483.500	51.24	-0.90	50.34	74.00	-23.66	peak			
2		2500.000	43.82	-0.74	43.08	74.00	-30.92	peak			

Test Mode	TX 2480 MHz_1Mbps	Polarization	Horizontal

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4960.000	34.01	14.93	48.94	74.00	-25.06	peak			

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2483.500	52.71	-0.90	51.81	74.00	-22.19	peak			
2		2500.000	43.79	-0.74	43.05	74.00	-30.95	peak			

Test Mode	TX 2402 MHz_2Mbps	Polarization	Vertical

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	4808.000	34.44	15.97	50.41	74.00	-23.59	peak			

Radiated Emission



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2310.000	32.88	10.19	43.07	74.00	-30.93	peak			
2		2390.000	32.64	10.41	43.05	74.00	-30.95	peak			