

RF Exposure / SAR Statement

No. : 30EE0164-YK-01-D

Applicant : **Alpine Electronics, Inc.**
Type of Equipment : **Bluetooth Module**
Model No. : **PF240028**
FCC ID : **A269ZUA131**

Alpine Electronics, Inc. declares that Model : Bluetooth Module complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "PF240028" has 1.79 mW of conducted Peak Output power and 3.66 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "PF240028" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 1.79 mW (Maximum peak output power)
G = 2.04 Numerical Antenna gain; equal 3.10 dBi
r = 20.0 cm

For: PF240028

$$S = 0.00073 \text{ mW/cm}^2$$

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112