

## MPE REPORT

---

Report No.: SRTC2020-9004(F)-20050903(I)

Product Name: UNIT ASSY, Display Audio

Product Model: G10\_AO

Applicant: ALPS ALPINE CO.,LTD.

Manufacturer: ALPS ALPINE CO.,LTD.

Specification: FCC Part §2.1091, §2.1093, §1.1307(b), §1.1310

FCC ID: A269ZUA166

The State Radio\_monitoring\_center Testing Center (SRTC)

15th Building, No.30, Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183 Fax: 86-10-57996388

## CONTENTS

<b>1 GENERAL INFORMATION .....</b>	<b>2</b>
1.1 NOTES OF THE TEST REPORT .....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY .....	2
1.3 APPLICANT'S DETAILS .....	2
1.4 MANUFACTURER'S DETAILS .....	2
<b>2 DESCRIPTION OF THE DEVICE UNDER TEST .....</b>	<b>3</b>
2.1 FINAL EQUIPMENT BUILD STATUS .....	3
<b>4 RESULT SUMMARY .....</b>	<b>4</b>
<b>5 TEST RESULTS .....</b>	<b>5</b>
5.1 AVERAGE POWER OUTPUT .....	5
5.2 SAR TEST EXCLUSION THRESHOLDS .....	7

## **1 GENERAL INFORMATION**

### **1.1 Notes of the test report**

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### **1.2 Information about the testing laboratory**

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

### **1.3 Applicant's details**

Company:	ALPS ALPINE CO.,LTD.
Address:	20-1 Yoshima Industrial Park,Iwaki,Fukushima Japan
City:	Iwaki, Fukushima
Country or Region:	Japan
Contacted person:	Kenji Nagase
Tel:	+81-246-36-4111 Ext: 4170
Fax:	+81-246-36-6090
Email:	ALJP_SMB_00436@alpsalpine.com

### **1.4 Manufacturer's details**

Company:	ALPS ALPINE CO.,LTD.
Address:	20-1 Yoshima Industrial Park,Iwaki,Fukushima Japan
City:	Iwaki, Fukushima
Country or Region:	Japan
Contacted person:	Kenji Nagase
Tel:	+81-246-36-4111 Ext: 4170
Fax:	+81-246-36-6090
Email:	ALJP_SMB_00436@alpsalpine.com

## **2 DESCRIPTION OF THE DEVICE UNDER TEST**

### **2.1 Final Equipment Build Status**

Bluetooth




Frequency Range	2.402GHz~2.480GHz
Number of Channel	79
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK
Duplex Mode	TDD
Channel Spacing	1MHz
Data Rate	1Mbps, 2 Mbps, 3 Mbps
Antenna Type	Fixed Internal Antenna
Antenna Gain	-0.5dBi
Power Supply	13.2VDC
HW Version	2wk
SW Version	00.875.000

## **3 REFERENCE SPECIFICATION**

Specification	Version	Title
2.1091	2021	Radiofrequency radiation exposure evaluation: mobile devices.
2.1093	2021	Radiofrequency radiation exposure evaluation: portable devices.
1.1307(b)	2021	Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
1.1310	2021	Radiofrequency radiation exposure limits.
KDB447498	October 23, 2015	RF exposure procedures and equipment authorization policies for mobile and portable devices

**4 RESULT SUMMARY**

No.	Test case	FCC reference
1	MPE Calculation	FCC Part §2.1091, FCC Part §2.1093, FCC Part §1.1307(b) FCC Part §1.1310 KDB 447498

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Miss Jin Wanqing 	Issued date:  20211231

## 5 Test Results

### 5.1 Average Power Output

#### 5.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

#### 5.1.2 Test Description

A transmitter antenna terminal of EUT is connected to the power meter. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

#### 5.1.3 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v04 – Section 9.2.3

#### 5.1.4 Test Settings

The maximum average conducted output power may be measured using a broadband average RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.

2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.

3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.


b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.

c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

d) Adjust the measurement in dBm by adding  $10\log(1/x)$ , where x is the duty cycle to the measurement result.

#### 5.1.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



### 5.1.6 Test Result

#### BT output power

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2441MHz (Ch39)	2480MHz (Ch78)
GFSK	-1.63	-0.71	-1.03
$\pi/4$ DQPSK	-3.11	-2.22	-2.52
8DPSK	-3.12	-2.25	-2.54

#### Tune-up tolerance

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2441MHz (Ch39)	2480MHz (Ch78)
GFSK	-4~0	-4~0	-4~0
$\pi/4$ DQPSK	-4~0	-4~0	-4~0
8DPSK	-4~0	-4~0	-4~0

## 5.2 SAR Test Exclusion Thresholds

According to the KDB447498 4.3.1(a)

For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

Summary of Transmitters

Mode/Band	Freq (GHz)	Max. power of channel, including tune-up tolerance, (dBm)	Max. power of channel, including tune-up tolerance, (mW)	Min. test separation distance, (mm)	The calculation results (1g)	SAR test exclusion Threshold (1g)	SAR Required
Bluetooth	2.402	0	1	0	0.310	$\leq 3.0$	No
Bluetooth	2.440	0	1	0	0.312	$\leq 3.0$	No
Bluetooth	2.480	0	1	0	0.315	$\leq 3.0$	No

---End of Test Report---