

TEST REPORT

Report No.: HK12090539-1

ALCO Electronics Ltd.

Class II Permissive Change

Application
For
Certification

(FCC ID: A2HPA5075U-1SPA)

Transceiver

Prepared and Checked by:

Approved by:

Signed On File
Wong Cheuk Ho, Herbert
Engineer

Chan Chi Hung, Terry
Assistant Supervisor
Date: September 24, 2012

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

INTERTEK TESTING SERVICES

GENERAL INFORMATION

ALCO Electronics Ltd.
BRAND NAME: TOSHIBA, MODEL: PA5075U-1SPA

FCC ID: A2HPA5075U-1SPA

Grantee:	ALCO Electronics Ltd.
Grantee Address:	11/F., Zung Fu Industrial Building, 1067 King's Road, Quarry Bay, Hong Kong.
Contact Person:	Peggy Suen
Tel:	852-2562 6121
Fax:	852-2597 5201
e-mail:	peggy@alco.com.hk
Manufacturer:	Dongguan Houjie Alco Electronics General Factory
Manufacturer Address:	The 3 rd Industrial District, Houjie, Dongguan, Guangdong, P.R.C.
Buyer:	Toshiba America Information Systems, Inc.
Buyer Address:	9740 Irvine Boulevard, Irvine, CA92618-608, United States.
Brand Name:	TOSHIBA
Model:	PA5075U-1SPA (Consisting of Sound Bar:PA5075E-1SPB and Passive Subwoofer:PA5075E-1SPW)
Type of EUT:	Transceiver
Description of EUT:	Mini 3D Soundbar with Subwoofer
Serial Number:	1209116887002
FCC ID:	A2HPA5075U-1SPA
Date of Sample Submitted:	September 17, 2012
Date of Test:	September 19, 2012
Report No.:	HK12090539-1
Report Date:	September 24, 2012
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

ALCO Electronics Ltd.
BRAND NAME: TOSHIBA, MODEL: PA5075U-1SPA

FCC ID: A2HPA5075U-1SPA

TEST SPECIFICATION	REFERENCE	RESULTS
Transmitter Power Line Conducted Emissions	15.207	Pass
Transmitter Field Strength and Bandwidth Requirement	15.249	Pass

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	1
1.1	Product Description	1
1.2	Purpose of Change	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	<u>System Test Configuration</u>	2
2.1	Justification	2
2.2	EUT Exercising Software	2
2.3	Special Accessories	2
2.4	Equipment Modification	2
2.5	Measurement Uncertainty	2
2.6	Support Equipment List and Description	2
3.0	<u>Emission Results</u>	3
3.1	Field Strength Calculation	3
3.2	Radiated Emission Configuration Photograph	4
3.3	Radiated Emission Data	4
3.4	Conducted Emission Configuration Photograph	4
3.5	Conducted Emission Data	4
4.0	<u>Equipment Photographs</u>	11
5.0	<u>Product Labelling</u>	11
6.0	<u>Technical Specifications</u>	11
7.0	<u>Instruction Manual</u>	11
8.0	<u>Miscellaneous Information</u>	12
8.1	Measured Bandwidth	12
8.2	Discussion of Pulse Desensitization	13
8.3	Calculation of Average Factor	13
8.4	Emissions Test Procedures	13
9.0	<u>Equipment List</u>	15

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is Mini 3D Soundbar with a passive Subwoofer. It can accept both analog input sources (RCA aux-in and 3.5mm phone-jack line-in), digital input sources (optical and coaxial) and wireless Bluetooth device. The Bluetooth module in the EUT operating in the frequency range from 2402MHz to 2480MHz (79 channels with 1MHz channel spacing). The audio signal is amplified and fed to the built-in stereo loudspeakers. The separate passive Subwoofer unit is driven by the internal subwoofer power amplifier. The EUT is powered by 19VDC from an AC/DC adaptor. The AC/DC adaptor can accept universal AC input voltage (100V-240VAC).

The RF output power setting of the Bluetooth module is -8dBm during test.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

The Mini 3D Sound Bar with Subwoofer with model no.: PA5075U-1SPA consists of the following units:

- Mini 3D Sound Bar with model no.: PA5075U-1SPB
- Passive Subwoofer with model no.: PA5075U-1SPW

1.2 Purpose of Change

The Schematic and PCB Layout has been changed. However RF portion (hardware, firmware and output power setting) remains unchanged.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by 120VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by ALCO Electronics Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

1. IBM ThinkPad – Type: 2371 (MIS-1486)
2. Software: Broadcom BlueTool Version 1.4.4.9
3. Audio cable with 1 metre long.
4. Adaptor Model: DA65A19, Input: 100-240VAC 50-60Hz, Output: 19VDC 3.42A (Provided by Applicant)

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB μ V/m
- RR = RA - AG - AV in dB μ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V/m	
AF = 7.4 dB	RR = 18.0 dB μ V
CF = 1.6 dB	LF = 9.0 dB
AG = 29.0 dB	
AV = 5.0 dB	
FS = RR + LF	
FS = 18 + 9 = 27 dB μ V/m	

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 4804.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 2.4 dB

3.4 Conducted Emission Configuration Photograph

The worst case in line-conducted emission was found at 0.425 MHz

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by 11.6 dB

INTERTEK TESTING SERVICES

Applicant: ALCO Electronics Ltd.
 Model: PA5075U-1SPA
 Worst-Case Operating Mode: Transmitting

Date of Test: August 07, 2012

Table 1

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
H	1.3	60	2402.000	87.5	33	29.4	83.9	0	83.9	94.0	-10.1
H	1.6	120	4804.000	49.7	33	34.9	51.6	0	51.6	54.0	-2.4
H	1.5	90	7206.000	43.3	33	37.9	48.2	0	48.2	54.0	-5.8
H	1.1	80	9608.000	40.6	33	40.4	48.0	0	48.0	54.0	-6.0
H	1.2	100	12010.000	42.9	33	40.5	50.4	0	50.4	54.0	-3.6
H	1.3	160	14412.000	44.0	33	40.0	51.0	0	51.0	54.0	-3.0

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
H	1.3	60	2402.000	87.5	33	29.4	83.9	114.0	-30.1
H	1.6	120	4804.000	49.7	33	34.9	51.6	74.0	-22.4
H	1.5	90	7206.000	43.3	33	37.9	48.2	74.0	-25.8
H	1.1	80	9608.000	40.6	33	40.4	48.0	74.0	-26.0
H	1.2	100	12010.000	42.9	33	40.5	50.4	74.0	-23.6
H	1.3	160	14412.000	44.0	33	40.0	51.0	74.0	-23.0

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: ALCO Electronics Ltd.
 Model: PA5075U-1SPA
 Worst-Case Operating Mode: Transmitting

Date of Test: August 07, 2012

Table 2

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
H	1.3	60	2442.000	87.4	33	29.4	83.8	0	83.8	94.0	-10.2
H	1.6	120	4884.000	49.1	33	34.9	51.0	0	51.0	54.0	-3.0
H	1.5	90	7326.000	43.4	33	37.9	48.3	0	48.3	54.0	-5.7
H	1.1	80	9768.000	40.7	33	40.4	48.1	0	48.1	54.0	-5.9
H	1.2	100	12210.000	42.7	33	40.5	50.2	0	50.2	54.0	-3.8
H	1.3	160	14652.000	45.5	33	38.4	50.9	0	50.9	54.0	-3.1

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
H	1.3	60	2442.000	87.4	33	29.4	83.8	114.0	-30.2
H	1.6	120	4884.000	49.1	33	34.9	51.0	74.0	-23.0
H	1.5	90	7326.000	43.4	33	37.9	48.3	74.0	-25.7
H	1.1	80	9768.000	40.7	33	40.4	48.1	74.0	-25.9
H	1.2	100	12210.000	42.7	33	40.5	50.2	74.0	-23.8
H	1.3	160	14652.000	45.5	33	38.4	50.9	74.0	-23.1

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: ALCO Electronics Ltd.
 Model: PA5075U-1SPA
 Worst-Case Operating Mode: Transmitting

Date of Test: August 07, 2012

Table 3

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Average Factor (dB)	Calculated at 3m (dBµV/m)	Average Limit at 3m (dBµV/m)	Margin (dB)
H	1.3	60	2480.000	86.8	33	29.4	83.2	0	83.2	94.0	-10.8
H	1.6	120	4960.000	49.4	33	34.9	51.3	0	51.3	54.0	-2.7
H	1.5	90	7440.000	44.0	33	37.9	48.9	0	48.9	54.0	-5.1
H	1.1	80	9920.000	40.8	33	40.4	48.2	0	48.2	54.0	-5.8
H	1.2	100	12400.000	42.7	33	40.5	50.2	0	50.2	54.0	-3.8
H	1.3	160	14880.000	45.2	33	38.4	50.6	0	50.6	54.0	-3.4

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBµV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBµV/m)	Peak Limit at 3m (dBµV/m)	Margin (dB)
H	1.3	60	2480.000	86.8	33	29.4	83.2	114.0	-30.8
H	1.6	120	4960.000	49.4	33	34.9	51.3	74.0	-22.7
H	1.5	90	7440.000	44.0	33	37.9	48.9	74.0	-25.1
H	1.1	80	9920.000	40.8	33	40.4	48.2	74.0	-25.8
H	1.2	100	12400.000	42.7	33	40.5	50.2	74.0	-23.8
H	1.3	160	14880.000	45.2	33	38.4	50.6	74.0	-23.4

- NOTES: 1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: ALCO Electronics Ltd.
 Model: PA5075U-1SPA
 Worst-Case Operating Mode: Transmitting

Date of Test: August 07, 2012

Table 4

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	1.4	190	2402.000	84.8	33	29.4	81.2	0	81.2	94.0	-12.8
V	1.5	60	4804.000	49.3	33	34.9	51.2	0	51.2	54.0	-2.8
V	1.4	275	7206.000	43.5	33	37.9	48.4	0	48.4	54.0	-5.6
V	1.2	80	9608.000	40.8	33	40.4	48.2	0	48.2	54.0	-5.8
V	1.3	140	12010.000	42.7	33	40.5	50.2	0	50.2	54.0	-3.8
V	1.2	160	14412.000	43.9	33	40.0	50.9	0	50.9	54.0	-3.1

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	1.4	190	2402.000	84.8	33	29.4	81.2	114.0	-32.8
V	1.5	60	4804.000	49.3	33	34.9	51.2	74.0	-22.8
V	1.4	275	7206.000	43.5	33	37.9	48.4	74.0	-25.6
V	1.2	80	9608.000	40.8	33	40.4	48.2	74.0	-25.8
V	1.3	140	12010.000	42.7	33	40.5	50.2	74.0	-23.8
V	1.2	160	14412.000	43.9	33	40.0	50.9	74.0	-23.1

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: ALCO Electronics Ltd.
 Model: PA5075U-1SPA
 Worst-Case Operating Mode: Transmitting

Date of Test: August 07, 2012

Table 5

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	1.4	190	2442.000	84.9	33	29.4	81.3	0	81.3	94.0	-12.7
V	1.5	60	4884.000	49.1	33	34.9	51.0	0	51.0	54.0	-3.0
V	1.4	275	7326.000	44.0	33	37.9	48.9	0	48.9	54.0	-5.1
V	1.2	80	9768.000	41.0	33	40.4	48.4	0	48.4	54.0	-5.6
V	1.3	140	12210.000	42.8	33	40.5	50.3	0	50.3	54.0	-3.7
V	1.2	160	14652.000	45.4	33	38.4	50.8	0	50.8	54.0	-3.2

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	1.4	190	2442.000	84.9	33	29.4	81.3	114.0	-32.7
V	1.5	60	4884.000	49.1	33	34.9	51.0	74.0	-23.0
V	1.4	275	7326.000	44.0	33	37.9	48.9	74.0	-25.1
V	1.2	80	9768.000	41.0	33	40.4	48.4	74.0	-25.6
V	1.3	140	12210.000	42.8	33	40.5	50.3	74.0	-23.7
V	1.2	160	14652.000	45.4	33	38.4	50.8	74.0	-23.2

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: ALCO Electronics Ltd.
 Model: PA5075U-1SPA
 Worst-Case Operating Mode: Transmitting

Date of Test: August 07, 2012

Table 6

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (dB)	Calculated at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	1.4	190	2480.000	84.7	33	29.4	81.1	0	81.1	94.0	-12.9
V	1.5	60	4960.000	49.3	33	34.9	51.2	0	51.2	54.0	-2.8
V	1.4	275	7440.000	43.7	33	37.9	48.6	0	48.6	54.0	-5.4
V	1.2	80	9920.000	40.8	33	40.4	48.2	0	48.2	54.0	-5.8
V	1.3	140	12400.000	42.7	33	40.5	50.2	0	50.2	54.0	-3.8
V	1.2	160	14880.000	44.6	33	38.4	50.0	0	50.0	54.0	-4.0

Polarization	Height (m)	Angle (°)	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	1.4	190	2480.000	84.7	33	29.4	81.1	114.0	-32.9
V	1.5	60	4960.000	49.3	33	34.9	51.2	74.0	-22.8
V	1.4	275	7440.000	43.7	33	37.9	48.6	74.0	-25.4
V	1.2	80	9920.000	40.8	33	40.4	48.2	74.0	-25.8
V	1.3	140	12400.000	42.7	33	40.5	50.2	74.0	-23.8
V	1.2	160	14880.000	44.6	33	38.4	50.0	74.0	-24.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth.

8.1 Measured Bandwidth

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2009) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

INTERTEK TESTING SERVICES

8.2 Discussion Pulse Desensitvity

Pulse desensitvity is not applicable for this device. Since the transmitter transmits the RF signal continuously.

8.3 Calculation of Average Factor

The average factor is not applicable for this device as the transmitted signal is a continuously signal.

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 (2009). A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

9.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer	Double Ridged Guide Antenna
Registration No.	EW-2500	EW-1792	EW-1015
Manufacturer	R&S	R&S	EMCO
Model No.	ESCI	FSP40	3115
Calibration Date	Feb. 24, 2012	Sep. 28, 2011	Aug. 24, 2011
Calibration Due Date	Feb. 24, 2013	Sep. 28, 2012	Feb. 24, 2013

Equipment	Log Periodic Antenna	Biconical Antenna
Registration No.	EW-0572	EW-0954
Manufacturer	EMCO	EMCO
Model No.	3146	3104C
Calibration Date	Nov. 15, 2012	Oct. 18, 2011
Calibration Due Date	May. 15, 2013	Apr. 18, 2013

2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN
Registration No.	EW-2500	EW-2041
Manufacturer	R&S	KYORITSU
Model No.	ESCI	KNW-403D
Calibration Date	Feb. 24, 2012	Jan. 05, 2012
Calibration Due Date	Feb. 24, 2013	Dec. 31, 2012

3) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-1792
Manufacturer	R&S
Model No.	FSP40
Calibration Date	Sep. 28, 2011
Calibration Due Date	Sep. 28, 2012