

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

--f(GHz) is the RF channel transmit frequency in GHz

--Power and distance are rounded to the nearest mW and mm before calculation

--The result is rounded to one decimal place for comparison

$$\text{EIRP} = p_t \times g_t = (\text{EXd})^2 / 30$$

Where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unit less),

E = electric field strength in V/m, ---  $10^{((\text{dBuV/m})/20)} / 10^6$

d = measurement distance in meters (m) ---3m

$$\text{So } p_t = (\text{Exd})^2 / 30 \times g_t$$

Field strength = 97.35 dBuV/m @3m

Ant gain =2dBi, so Ant numeric gain= 1.58

$$\text{So } p_t = \{ [10^{(97.35/20)} / 10^6 \times 3]^2 / 30 \times 1.58 \} \times 1000 \text{ mW} = 1.031 \text{ mW}$$

$$\text{So } (1.031 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.48} = 0.325 < 3$$

Then SAR evaluation is not required