



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM140100029303

Page : 1 of 19

FCC REPORT

Application No. : SZEM1401000293IT (SGS HK No.:HKES1401000159IT)
Applicant: ALCO Electronics Ltd.
Dongguan Houjie Alco Electronics General Factory Gong
Ye Xi Road, Houjie Technology Industrial Park, Houjie,
**Manufacturer/
Supplier:** Dongguan, Guangdong, P.R.C.
Postal Code:523960
Product Name: 7" Tablet
Model No.(EUT): Alt. Model: RCT6272W23 (Brand name: RCA)
Add Model No.: Basic Model: CT9272W23 (Brand name: VENTURER)
FCC ID: A2HRCT6272W23
Standards: 47 CFR Part 15B (2013)
Date of Receipt: 2014-01-22
Date of Test: 2014-01-24 to 2014-03-06
Date of Issue: 2014-04-08

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang

EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



2 Test Summary

Test Item	Test Requirement	Test method	Result
Radiated Emission (30MHz to 5GHz)§	47 CFR Part 15B	ANSI C63.4 (2009)	PASS
Conducted Emission (150KHz to 30MHz)	47 CFR Part 15B	ANSI C63.4 (2009)	PASS

Remark:

Model No.: Basic Model: CT9272W23 (Brand name: VENTURER)

Alt. Model: RCT6272W23 (Brand name: RCA)

Only the model RCT6272W23 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only different on trade mark and model number.

§ If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz.



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST ENVIRONMENT AND MODE	4
4.4 DESCRIPTION OF SUPPORT UNITS	5
4.5 TEST LOCATION	5
4.6 TEST FACILITY	6
4.7 DEVIATION FROM STANDARDS	6
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4.10 EQUIPMENT LIST	7
5 TEST RESULTS AND MEASUREMENT DATA	9
5.1 CONDUCTED EMISSIONS	9
5.2 RADIATED EMISSION	13
6 PHOTOGRAPHS - EUT TEST SETUP	18
6.1 CONDUCTED EMISSION	18
6.2 RADIATED EMISSION	18
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	19

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only

4 General Information

4.1 Client Information

Applicant:	ALCO Electronics Ltd.
Address of Applicant:	11/F, Zung Fu Industrial Building, 1067 King's Road, Quarry Bay, Hong Kong
Manufacturer/ Supplier:	Dongguan Houjie Alco Electronics General Factory
Address of Manufacturer/ Supplier:	Gong Ye Xi Road, Houjie Technology Industrial Park, Houjie, Dongguan, Guangdong, P.R.C. Postal Code: 523960

4.2 General Description of EUT

Product Name:	7" Tablet	
Model No.:	Basic Model: CT9272W23 (Brand name: VENTURER) Alt. Model: RCT6272W23 (Brand name: RCA)	
Sample Type:	Portable production	
The Highest Frequency:	1GHz	
Antenna Type:	Integral	
Antenna Gain:	2dBi	
Power Supply:	AC Adapter:	Model: STC-A515B-Z Input: 100-120V~ 50/60Hz 0.3A Output: 5V = 1.5A
	Battery:	Internal rechargeable battery: MLP3867103 DC 3.7V 2600mAh 9.62Wh
Test Voltage:	AC 120V 60Hz	
DC cable:	90cm(Unshielded with one ferrite core)	

4.3 Test Environment and Mode

Operating Environment:	
Temperature:	23.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1025mbar
Test mode:	
Play mode:	The EUT play the video .
R&W Int memory and TF card mode:	The EUT exchange the data with PC.
AC charge+Play mode:	The EUT play the video and AC charge it.
AC charge+ R&W Int memory and TF card mode:	The EUT exchange the data with PC and AC charge it.



4.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
PC	DELL	DCSM
LCD-displaying	DELL	SP2208WFPt
KEYBOARD	DELL	SK-8115
MOUSE	Lenovo	MO28UOL
PC	IBM	8172
LCD-displaying	Lenovo	L1711pC
KEYBOARD	IBM	SK-8115
MOUSE	Lenovo	MO28UOA
TF card	kingston	2GB
Earphone	Supply by client	120cm unshielded
USB cable	Supply by client	100cm shielded with two ferrite core

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Equipment List

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2014-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2014-05-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	Coaxial cable	SGS	N/A	SEL0027	2014-05-29
5	Coaxial cable	SGS	N/A	SEL0189	2014-05-29
6	Coaxial cable	SGS	N/A	SEL0121	2014-05-29
7	Coaxial cable	SGS	N/A	SEL0178	2014-05-29
8	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-10-24
9	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2014-10-24
10	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2014-05-16
11	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2014-10-24
12	Barometer	ChangChun	DYM3	SEL0088	2014-05-24
13	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
14	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2014-10-24
15	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2014-10-24
16	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2014-05-16
17	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2014-06-04



Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2014-06-10
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2014-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2014-05-16
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2014-11-10
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2014-11-10
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2014-11-10
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2014-05-16
8	Coaxial Cable	SGS	N/A	SEL0025	2014-05-29
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2014-10-24
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2014-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2014-05-24


Note: The calibration interval is one year, all the instruments are valid.



5 Test results and Measurement Data

5.1 Conducted Emissions

Test Requirement:	47 CFR Part 15B		
Test Method:	ANSI C63.4: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"> 1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement. 		

<p>Test setup:</p>	
<p>Instruments Used:</p>	<p>Refer to section 4.10 for details</p>
<p>Exploratory Test Mode:</p>	<p>AC charge+Play mode, AC charge+ R&W Int memory and TF card mode</p>
<p>Final Test Mode:</p>	<p>Pretest the EUT at AC charge+Play mode, AC charge+ R&W Int memory and TF card mode and found the AC charge+Play mode which it is worse case, the test worst case mode is recorded in the report.</p>
<p>Test Results:</p>	<p>Pass</p>




Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:




Site : Shielding Room
Condition : 47 CFR PART 15 B QP CE LINE
Job No. : 0293IT
MODE : AC charge + Play

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.17600	0.02	9.70	46.40	56.12	64.67	-8.55	QP
2 @	0.17600	0.02	9.70	33.10	42.82	54.67	-11.85	Average
3	0.23533	0.02	9.70	24.61	34.33	52.26	-17.93	Average
4	0.23533	0.02	9.70	34.76	44.48	62.26	-17.78	QP
5	0.29243	0.01	9.70	19.37	29.08	50.46	-21.37	Average
6	0.29243	0.01	9.70	29.35	39.06	60.46	-21.39	QP
7	0.35201	0.01	9.76	15.37	25.14	48.91	-23.78	Average
8	0.35201	0.01	9.76	25.54	35.30	58.91	-23.61	QP
9	0.41048	0.01	9.80	21.82	31.63	57.64	-26.01	QP
10	0.41048	0.01	9.80	11.28	21.09	47.64	-26.55	Average
11	2.692	0.02	9.83	17.42	27.28	56.00	-28.72	QP
12	2.692	0.02	9.83	7.67	17.52	46.00	-28.48	Average

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Neutral Line:



Site : Shielding Room
Condition : 47 CFR PART 15 B QP CE NEUTRAL
Job No. : 0293IT
MODE : AC charge + Play

	Freq	Cable Loss	LISN Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1 @	0.17500	0.02	9.70	48.20	57.92	64.72	-6.80 QP
2 @	0.17500	0.02	9.70	34.90	44.62	54.72	-10.10 Average
3	0.23409	0.02	9.70	36.77	46.48	62.30	-15.82 QP
4	0.23409	0.02	9.70	26.37	36.09	52.30	-16.22 Average
5	0.29554	0.01	9.70	28.57	38.28	60.37	-22.09 QP
6	0.29554	0.01	9.70	18.39	28.10	50.37	-22.27 Average
7	0.35201	0.01	9.76	17.24	27.01	48.91	-21.91 Average
8	0.35201	0.01	9.76	27.17	36.93	58.91	-21.98 QP
9	0.41048	0.01	9.80	21.93	31.74	57.64	-25.89 QP
10	0.41048	0.01	9.80	11.60	21.41	47.64	-26.23 Average
11	0.46861	0.01	9.80	17.94	27.75	56.54	-28.79 QP
12	0.46861	0.01	9.80	7.69	17.50	46.54	-29.04 Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.



5.2 Radiated Emission

Test Requirement:	47 CFR Part 15B				
Test Method:	ANSI C63.4: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.</p>				




Figure 1. 30MHz to 1GHz


Figure 2. Above 1 GHz

Instruments Used:	Refer to section 4.10 for details
Exploratory Test Mode:	Play mode, R&W Int memory and TF card mode, AC charge+Play mode, AC charge+ R&W Int memory and TF card mode
Final Test Mode:	Pretest the EUT at Play mode, R&W Int memory and TF card mode, AC charge+Play mode, AC charge+ R&W Int memory and TF card mode and found the AC charge+Play mode which it is worse case, the test worst case mode is recorded in the report.
Test Results:	Pass





QP value: 30MHz~1GHz
Horizontal



Condition: 47 CFR PART 15B 3m 3142C HORIZONTAL


Job No. : 0293IT

Mode : AC charge+Play

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	78.97	1.26	5.08	25.25	51.50	32.59	-7.41
2	148.44	1.79	9.20	25.42	46.50	32.07	-11.43
3	173.21	1.99	8.31	25.35	48.46	33.41	-10.09
4	420.58	3.38	11.50	25.44	52.13	46.00	-4.43
5	470.52	3.64	13.23	26.01	43.82	34.68	-11.32
6	768.75	4.94	18.30	26.26	39.70	36.68	-9.32



Vertical



Condition: 47 CFR PART 15B 3m 3142C VERTICAL
Job No. : 0293IT
Mode : AC charge+Play

	Freq	Cable Loss	Antenna Factor	Preamplifier	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	56.39	0.99	6.37	25.81	42.50	24.05	40.00	-15.95
2	67.68	1.12	4.59	25.67	43.48	23.52	40.00	-16.48
3	78.97	1.26	5.08	25.25	46.05	27.14	40.00	-12.86
4	127.66	1.65	8.06	25.13	39.70	24.28	43.50	-19.22
5	148.44	1.79	9.20	25.42	39.44	25.01	43.50	-18.49
6	372.00	3.12	11.38	25.36	36.82	25.96	46.00	-20.04

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



Above 1GHz

Peak value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1143.830	2.29	27.45	39.20	48.37	38.91	74	-35.09	Vertical
1226.618	2.34	27.60	39.24	48.62	39.32	74	-34.68	Vertical
1780.593	2.70	30.20	39.47	45.43	38.86	74	-35.14	Vertical
2243.604	2.93	32.23	39.74	45.19	40.61	74	-33.39	Vertical
3136.610	3.42	33.34	40.40	45.34	41.70	74	-32.30	Vertical
3895.981	4.07	33.68	40.95	45.60	42.40	74	-31.60	Vertical
1072.378	2.25	27.32	39.17	48.44	38.84	74	-35.16	Horizontal
1449.030	2.49	28.01	39.33	49.50	40.67	74	-33.33	Horizontal
2011.310	2.84	31.80	39.57	44.80	39.87	74	-34.13	Horizontal
2816.900	3.21	33.14	40.17	45.20	41.38	74	-32.62	Horizontal
3725.315	3.93	33.47	40.83	45.59	42.16	74	-31.84	Horizontal
4307.183	4.36	34.69	41.26	44.96	42.75	74	-31.25	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) As shown in this section, for the investigated frequency range 1GHz to 5GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6 Photographs - EUT Test Setup

Test model No.: Alt. Model: RCT6272W23 (Brand name: RCA)

6.1 Conducted Emission



6.2 Radiatd Emission





7 Photographs - EUT Constructional Details

Test model No.: Alt. Model: RCT6272W23 (Brand name: RCA)

Refer to Report No. SZEM140100029301 for EUT external and internal photos.