




# TEST REPORT

Report No.....: **CHEW19080085** Report verification : 

Project No. ....: **SHT1907044103EW**

FCC ID.....: **A2HRCT6T06**

Applicant's name.....: **Alco Electronics Ltd**

Address.....: 11/F Metropole Square, 2 On Yiu Street, Sha Tin, New Territories, Hong Kong

Manufacturer.....: Alco Electronics Ltd

Address.....: 11/F Metropole Square, 2 On Yiu Street, Sha Tin, New Territories, Hong Kong

Test item description .....: **Tablet**

Trade Mark .....: Venturer / RCA

Model/Type reference.....: CT9T06

Listed Model(s) .....: RCT6T06

Standard .....: **FCC CFR Title 47 Part 15 Subpart C Section 15.247**

Date of receipt of test sample.....: Jul.19, 2019

Date of testing.....: Jul.19, 2019- Aug.15, 2019

Date of issue.....: Aug.16, 2019

Result.....: **PASS**

Compiled by  
( Position+Printed name+Signature): File administrators Echo Wei

Supervised by  
(Position+Printed name+Signature): Project Engineer Kiki Kong

Approved by  
(Position+Printed name+Signature): RF Manager Hans Hu

Testing Laboratory Name .....: **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address.....: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely correspond to the test sample.*

## Contents

<b>1.</b>	<b><u>TEST STANDARDS AND REPORT VERSION</u></b>	<b>3</b>
1.1.	Test Standards	3
1.2.	Report version	3
<b>2.</b>	<b><u>TEST DESCRIPTION</u></b>	<b>4</b>
<b>3.</b>	<b><u>SUMMARY</u></b>	<b>5</b>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<b>4.</b>	<b><u>TEST ENVIRONMENT</u></b>	<b>7</b>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<b>5.</b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b>11</b>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	20 dB Bandwidth	19
5.5.	Carrier Frequencies Separation	23
5.6.	Hopping Channel Number	25
5.7.	Dwell Time	27
5.8.	Pseudorandom Frequency Hopping Sequence	34
5.9.	Restricted band (radiated)	35
5.10.	Band edge and Spurious Emissions (conducted)	37
5.11.	Spurious Emissions (radiated)	53
<b>6.</b>	<b><u>TEST SETUP PHOTOS</u></b>	<b>57</b>
<b>7.</b>	<b><u>EXTERANAL AND INTERNAL PHOTOS</u></b>	<b>59</b>

# **1. TEST STANDARDS AND REPORT VERSION**

## **1.1. Test Standards**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules

## **1.2. Report version**

Revision No.	Date of issue	Description
N/A	2019-08-16	Original

## **2. TEST DESCRIPTION**

<b>Test Item</b>	<b>Section in CFR 47</b>	<b>Result</b>	<b>Test Engineer</b>
Antenna Requirement	15.203/15.247 (c)	PASS	Bruce Wong
AC Power Line Conducted Emissions	15.207	PASS	Kang Yang
Conducted Peak Output Power	15.247 (b)(1)	PASS	Bruce Wong
20 dB Bandwidth	15.247 (a)(1)	PASS	Bruce Wong
Carrier Frequencies Separation	15.247 (a)(1)	PASS	Bruce Wong
Hopping Channel Number	15.247 (a)(1)	PASS	Bruce Wong
Dwell Time	15.247 (a)(1)	PASS	Bruce Wong
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS	Bruce Wong
Restricted band	15.247(d)/15.205	PASS	Bruce Wong
Radiated Emissions	15.247(d)/15.209	PASS	Pan Xie

Note: The measurement uncertainty is not included in the test result.

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	Alco Electronics Ltd
Address:	11/F Metropole Square, 2 On Yiu Street, Sha Tin, New Territories, Hong Kong
Manufacturer:	Alco Electronics Ltd
Address:	11/F Metropole Square, 2 On Yiu Street, Sha Tin, New Territories, Hong Kong

#### 3.2. Product Description

Name of EUT:	Tablet
Trade Mark:	Venturer / RCA
Model No.:	CT9T06
Listed Model(s):	RCT6T06
Power supply:	DC 3.7V
Adapter information:	-
Hardware version:	MT8167-CT9T06-V1.0
Software version:	RCT6T06E13-ANDROID8.1-Vxx-V1.25.100-A00
<b>Bluetooth</b>	
Version:	Supported BT4.0+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	FPC Antenna
Antenna gain:	1.1dBi

### 3.3. Operation state

#### ➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
39	2441
⋮	⋮
77	2479
78	2480

#### ➤ TEST MODE

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit
For AC power line conducted emissions:
The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data recorded in the report.

### 3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

/	Manufacturer:	/
	Model No.:	/
/	Manufacturer:	/
	Model No.:	/

### 3.5. Modifications

No modifications were implemented to meet testing criteria.

## **4. TEST ENVIRONMENT**

### **4.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

### **4.2. Test Facility**

#### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### **A2LA-Lab Cert. No.: 3902.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### **FCC-Registration No.: 762235**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

#### **IC-Registration No.:5377A**

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377A.

#### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

### 4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.51 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.51 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.02 dB	(1)
Radiated Emissions below 1GHz	4.90 dB	(1)
Radiated Emissions above 1GHz	4.96 dB	(1)
Occupied Bandwidth	70 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$



#### 4.5. Equipments Used during the Test

● Conducted Emission						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	ESCI	101247	2018/10/27	2019/10/26
●	Artificial Mains	SCHWARZBECK	NNLK 8121	573	2018/10/27	2019/10/26
●	Pulse Limiter	R&S	ESH3-Z2	100499	2018/10/27	2019/10/26
●	RF Connection Cable	HUBER+SUHNER	EF400	N/A	2018/11/15	2019/11/14
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
○	Single Balanced Telecom Pair ISN	FCC	FCC-TLISN-T2-02	20371	2018/10/28	2019/10/27
○	Two Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T4-02	20373	2018/10/28	2019/10/27
○	Four Balanced Telecom Pairs ISN	FCC	FCC-TLISN-T8-02	20375	2018/10/28	2019/10/27
○	V-Network	R&S	ESH3-Z6	100211	2018/10/27	2019/10/26
○	V-Network	R&S	ESH3-Z6	100210	2018/10/27	2019/10/26
○	2-Line V-Network	R&S	ESH3-Z5	100049	2018/10/27	2019/10/26
● Radiated Emission-6th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-02	N/A	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	ESCI	100900	2018/10/28	2019/10/27
●	Loop Antenna	R&S	HFH2-Z2	100020	2017/11/20	2020/11/19
●	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	546	2017/04/05	2020/04/04
●	Pre-Amplifier	SCHWARZBECK	BBV 9742	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	N/A	N/A	2018/09/28	2019/09/27
●	RF Connection Cable	HUBER+SUHNER	SUCOFLEX104	501184/4	2018/09/28	2019/09/27
●	Test Software	R&S	ES-K1	N/A	N/A	N/A
●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A
● Radiated emission-7th test site						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	SAC-3m-01	N/A	2018/09/30	2021/09/29
●	Spectrum Analyzer	R&S	FSP40	100597	2018/10/27	2019/10/26
●	Horn Antenna	SCHWARZBECK	9120D	1011	2017/03/27	2020/03/26
●	Pre-amplifier	BONN	BLWA0160-2M	1811887	2018/11/14	2019/11/13
●	Pre-amplifier	CD	PAP-0102	12004	2018/11/14	2019/11/13
●	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	2019/04/26	2020/04/25
●	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	2018/11/15	2019/11/14
●	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	2018/11/15	2019/11/14
●	Test Software	Audix	E3	N/A	N/A	N/A
●	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
●	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

● RF Conducted Method						
Used	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	FSV40	100048	2018/10/28	2019/10/27
●	Spectrum Analyzer	Agilent	N9020A	MY50510187	2018/09/29	2019/09/28
○	Radio communication tester	R&S	CMW500	137688-Lv	2018/09/29	2019/09/28
○	Test software	Tonscend	JS1120-1(LTE)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-2(WIFI)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-3(WCDMA)	N/A	N/A	N/A
○	Test software	Tonscend	JS1120-4(GSM)	N/A	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


##### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### Test Result:

**Passed**       **Not Applicable**

The directional gain of the antenna less than 1.1 dBi, please refer to the below antenna photo.



## 5.2. Conducted Emissions (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.


### TEST RESULTS

Passed       Not Applicable

Note:

- 1) Transd= Cable lose + Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit - Level

Test Line: L



**MEASUREMENT RESULT: "GM1908125055\_fin"**

8/12/2019 2:02PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	51.30	9.9	66	14.7	QP	L1	GND
0.546000	52.10	9.9	56	3.9	QP	L1	GND
1.050000	45.90	9.9	56	10.1	QP	L1	GND
2.805000	41.90	9.9	56	14.1	QP	L1	GND
5.365500	38.90	10.0	60	21.1	QP	L1	GND
12.907500	32.90	10.1	60	27.1	QP	L1	GND

**MEASUREMENT RESULT: "GM1908125055\_fin2"**

8/12/2019 2:02PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.316500	29.60	9.9	50	20.2	AV	L1	GND
0.555000	37.30	9.9	46	8.7	AV	L1	GND
0.910500	33.90	9.9	46	12.1	AV	L1	GND
2.467500	29.40	9.9	46	16.6	AV	L1	GND
5.244000	26.20	10.0	50	23.8	AV	L1	GND
23.127000	26.70	10.3	50	23.3	AV	L1	GND

Test Line: N



**MEASUREMENT RESULT: "GM1907255031\_fin"**

7/25/2019 11:18AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	58.10	9.9	66	7.9	QP	N	GND
0.550500	49.30	9.9	56	6.7	QP	N	GND
1.698000	41.40	9.9	56	14.6	QP	N	GND
2.395500	36.70	9.9	56	19.3	QP	N	GND
5.437500	33.20	10.0	60	26.8	QP	N	GND
17.488500	30.30	10.2	60	29.7	QP	N	GND

**MEASUREMENT RESULT: "GM1907255031\_fin2"**

7/25/2019 11:18AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	41.70	9.9	56	14.3	AV	N	GND
0.528000	33.20	9.9	46	12.8	AV	N	GND
0.910500	29.50	9.9	46	16.5	AV	N	GND
2.467500	25.60	9.9	46	20.4	AV	N	GND
12.309000	20.50	10.1	50	29.5	AV	N	GND
17.515500	20.90	10.2	50	29.1	AV	N	GND


### 5.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.  
 For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
 RBW ≥ the 20 dB bandwidth of the emission being measured, VBW ≥ RBW  
 Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

#### TEST MODE:

Please refer to the clause 3.3

#### TEST RESULTS

Passed       Not Applicable

Modulation type	Channel	Peak Output power (dBm)	Average Output power (dBm)	Limit (dBm)	Result
GFSK	00	1.22	1.13	≤ 30.00	Pass
	39	0.26	0.16		
	78	2.07	1.96		
π/4DQPSK	00	1.43	0.76	≤ 21.00	Pass
	39	0.09	-0.41		
	78	2.06	1.30		
8DPSK	00	1.42	0.75	≤ 21.00	Pass
	39	0.17	-0.61		
	78	2.08	1.22		

Modulation Type: GFSK	
CH00	<p>Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz Mode Auto Sweep Count 500/500 IPK View M1[1] 1.22 dBm 2.40191320 GHz CF 2.402 GHz 691 pts Span 5.0 MHz Date: 23 Jul 2019 15:03:53</p>
CH39	<p>Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz Mode Auto Sweep Count 500/500 IPK View M1[1] 0.26 dBm 2.44092760 GHz CF 2.441 GHz 691 pts Span 5.0 MHz Date: 23 Jul 2019 15:05:10</p>
CH78	<p>Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 1 MHz Att 30 dB SWT 1 ms VBW 3 MHz Mode Auto Sweep Count 500/500 IPK View M1[1] 2.07 dBm 2.47993490 GHz CF 2.48 GHz 691 pts Span 5.0 MHz Date: 23 Jul 2019 15:40:05</p>



Modulation Type: $\pi/4$ DQPSK	
CH00	<p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 2 MHz Att 30 dB SWT 1 ms VBW 5 MHz Mode Auto Sweep Count 500/500</p> <p>IPK View</p> <p>M1[1] 1.43 dBm 2.40213750 GHz</p> <p>CF 2.402 GHz 691 pts Span 5.0 MHz</p> <p>Date: 23 JUL 2019 15:44:00</p>
CH39	<p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 2 MHz Att 30 dB SWT 1 ms VBW 5 MHz Mode Auto Sweep Count 500/500</p> <p>IPK View</p> <p>M1[1] 0.09 dBm 2.44111580 GHz</p> <p>CF 2.441 GHz 691 pts Span 5.0 MHz</p> <p>Date: 23 JUL 2019 15:44:51</p>
CH78	<p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 2 MHz Att 30 dB SWT 1 ms VBW 5 MHz Mode Auto Sweep Count 500/500</p> <p>IPK View</p> <p>M1[1] 2.06 dBm 2.47989150 GHz</p> <p>CF 2.48 GHz 691 pts Span 5.0 MHz</p> <p>Date: 23 JUL 2019 15:55:46</p>


Modulation Type: 8DPSK	
CH00	<p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 2 MHz Att 30 dB SWT 1 ms VBW 5 MHz Mode Auto Sweep Count 500/500</p> <p>IPK View</p> <p>M1[1] 1.42 dBm 2.40197110 GHz</p> <p>CF 2.402 GHz 691 pts Span 5.0 MHz</p> <p>Date: 23 JUL 2019 15:47:09</p>
CH39	<p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 2 MHz Att 30 dB SWT 1 ms VBW 5 MHz Mode Auto Sweep Count 500/500</p> <p>IPK View</p> <p>M1[1] 0.17 dBm 2.44100000 GHz</p> <p>CF 2.441 GHz 691 pts Span 5.0 MHz</p> <p>Date: 23 JUL 2019 15:48:21</p>
CH78	<p>Spectrum</p> <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 2 MHz Att 30 dB SWT 1 ms VBW 5 MHz Mode Auto Sweep Count 500/500</p> <p>IPK View</p> <p>M1[1] 2.08 dBm 2.48000000 GHz</p> <p>CF 2.48 GHz 691 pts Span 5.0 MHz</p> <p>Date: 23 JUL 2019 15:50:52</p>

## 5.4. 20 dB Bandwidth

### LIMIT

N/A

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel  
RBW  $\geq$  1% of the 20 dB bandwidth, VBW  $\geq$  RBW  
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


### TEST MODE:

Please refer to the clause 3.3


### TEST RESULTS

 Passed       Not Applicable

Modulation type	Channel	20 dB Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.93	-	Pass
	39	0.93		
	78	0.93		
$\pi/4$ DQPSK	00	1.29	-	Pass
	39	1.29		
	78	1.29		
8DPSK	00	1.28	-	Pass
	39	1.28		
	78	1.28		



Modulation Type:		$\pi/4$ DQPSK																												
CH00	<p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz                  Att 30 dB SWT 63.1 <math>\mu</math>s VBW 100 kHz Mode Auto FFT                  Count 500/500                  IPK View</p> <p>CF 2.402 GHz 1001 pts Span 2.5 MHz</p> <table border="1"> <thead> <tr> <th>Types</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td></td> <td>1</td> <td>2.4013775 GHz</td> <td>-22.97 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td></td> <td>1</td> <td>2.402175 GHz</td> <td>-2.45 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.285 MHz</td> <td>0.50 dB</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 23 Jul 2019 16:02:09</p>		Types	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.4013775 GHz	-22.97 dBm			M2		1	2.402175 GHz	-2.45 dBm			D3	M1	1	1.285 MHz	0.50 dB		
Types	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1		1	2.4013775 GHz	-22.97 dBm																										
M2		1	2.402175 GHz	-2.45 dBm																										
D3	M1	1	1.285 MHz	0.50 dB																										
CH39	<p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz                  Att 30 dB SWT 63.1 <math>\mu</math>s VBW 100 kHz Mode Auto FFT                  Count 500/500                  IPK View</p> <p>CF 2.441 GHz 1001 pts Span 2.5 MHz</p> <table border="1"> <thead> <tr> <th>Types</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td></td> <td>1</td> <td>2.4403775 GHz</td> <td>-24.35 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td></td> <td>1</td> <td>2.441175 GHz</td> <td>-3.85 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.2875 MHz</td> <td>0.35 dB</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 23 Jul 2019 16:03:44</p>		Types	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.4403775 GHz	-24.35 dBm			M2		1	2.441175 GHz	-3.85 dBm			D3	M1	1	1.2875 MHz	0.35 dB		
Types	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1		1	2.4403775 GHz	-24.35 dBm																										
M2		1	2.441175 GHz	-3.85 dBm																										
D3	M1	1	1.2875 MHz	0.35 dB																										
CH78	<p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz                  Att 30 dB SWT 63.1 <math>\mu</math>s VBW 100 kHz Mode Auto FFT                  Count 500/500                  IPK View</p> <p>CF 2.48 GHz 1001 pts Span 2.5 MHz</p> <table border="1"> <thead> <tr> <th>Types</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td></td> <td>1</td> <td>2.4793775 GHz</td> <td>-22.49 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td></td> <td>1</td> <td>2.480175 GHz</td> <td>-1.83 dBm</td> <td></td> <td></td> </tr> <tr> <td>D3</td> <td>M1</td> <td>1</td> <td>1.2875 MHz</td> <td>0.33 dB</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 23 Jul 2019 16:07:27</p>		Types	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.4793775 GHz	-22.49 dBm			M2		1	2.480175 GHz	-1.83 dBm			D3	M1	1	1.2875 MHz	0.33 dB		
Types	Ref	Trc	X-value	Y-value	Function	Function Result																								
M1		1	2.4793775 GHz	-22.49 dBm																										
M2		1	2.480175 GHz	-1.83 dBm																										
D3	M1	1	1.2875 MHz	0.33 dB																										




### 5.5. Carrier Frequencies Separation

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
 Span = wide enough to capture the peaks of two adjacent channels  
 RBW ≥ 1% of the span, VBW ≥ RBW  
 Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

#### TEST MODE:

Please refer to the clause 3.3

#### TEST RESULTS

Passed       Not Applicable

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz) *	Result
GFSK	39	1.00	≥0.93	Pass
π/4DQPSK	39	1.00	≥0.86	Pass
8DPSK	39	1.00	≥0.85	Pass

Note:

\*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the section 5.4.

π/4DQPSK limit = 2/3 \* The maximum 20 dB Bandwidth for π/4DQPSK modulation on the section 5.4.

8DPSK limit = 2/3 \* The maximum 20 dB Bandwidth for 8DPSK modulation on the section 5.4

<p>GFSK</p>	<p>Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT Count 100/100 1Pk View M1[1] -2.45 dBm D1[1] 2.44117391 GHz 0.07 dB 1.00000 MHz Start 2.44 GHz 691 pts Stop 2.443 GHz Date: 23 JUL 2019 16:17:02</p>
<p><math>\pi/4</math>DQPSK</p>	<p>Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT Count 100/100 1Pk View M1[1] -3.88 dBm D1[1] 2.44117391 GHz 0.08 dB 1.00000 MHz Start 2.44 GHz 691 pts Stop 2.443 GHz Date: 23 JUL 2019 16:20:24</p>
<p>8DPSK</p>	<p>Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 30 kHz Att 30 dB SWT 63.2 μs VBW 100 kHz Mode Auto FFT Count 100/100 1Pk View M1[1] -3.27 dBm D1[1] 2.44117391 GHz 0.12 dB 1.00000 MHz Start 2.44 GHz 691 pts Stop 2.443 GHz Date: 23 JUL 2019 16:26:28</p>




## 5.6. Hopping Channel Number

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
 Span = the frequency band of operation  
 RBW  $\geq$  1% of the span, VBW  $\geq$  RBW  
 Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.




### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS

Passed       Not Applicable

Modulation type	Channel number	Limit	Result
GFSK	79	$\geq 15.00$	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		


<p>GFSK</p>	
<p><math>\pi/4</math>DQPSK</p>	
<p>8DPSK</p>	

### 5.7. Dwell Time

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
 Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW ≥ RBW  
 Sweep = as necessary to capture the entire dwell time per hopping channel,  
 Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

#### TEST MODE:

Please refer to the clause 3.3


#### TEST RESULTS

Passed       Not Applicable


Modulation type	Channel	Burst Width [ms/hop/ch]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.38	315.00	0.12	≤ 0.40	Pass
	DH3	1.63	158.00	0.26		
	DH5	2.88	115.00	0.33		
π/4DQPSK	2DH1	0.38	316.00	0.12	≤ 0.40	Pass
	2DH3	1.63	161.00	0.26		
	2DH5	2.88	102.00	0.29		
8DPSK	3DH1	0.38	316.00	0.12	≤ 0.40	Pass
	3DH3	1.63	155.00	0.25		
	3DH5	2.89	107.00	0.31		

Modulation Type: GFSK	
DH1 Burst width	<p>Spectrum</p> <p>Ref Level 30.00 dBm   RBW 1 MHz Att 40 dB   SWT 10 ms   VBW 3 MHz</p> <p>SGL TRG:VID</p> <p>IAP Cirw</p> <p>M1[1] -5.03 dBm 0.00000000 s 3.68 dB 376.25 ps</p> <p>D1</p> <p>TRG -22.000 dBm</p> <p>CF 2.441 GHz   8001 pts   1.0 ms/</p> <p>Date: 23 JUL 2019 16:09:57</p>
DH1 Burst number	<p>Spectrum</p> <p>Ref Level 30.00 dBm   RBW 500 kHz Att 40 dB   SWT 31.6 s   VBW 3 MHz</p> <p>SGL TRG:VID</p> <p>IAP Cirw</p> <p>TRG -4.000 dBm</p> <p>CF 2.441 GHz   30001 pts   3.16 s/</p> <p>Date: 23 JUL 2019 16:00:01</p>
DH3 Burst width	<p>Spectrum</p> <p>Ref Level 30.00 dBm   RBW 1 MHz Att 40 dB   SWT 10 ms   VBW 3 MHz</p> <p>SGL TRG:VID</p> <p>IAP Cirw</p> <p>M1[1] -21.54 dBm -1.25 ps 11.61 dB 1.63250 ms</p> <p>D1</p> <p>TRG -19.000 dBm</p> <p>CF 2.441 GHz   8001 pts   1.0 ms/</p> <p>Date: 23 JUL 2019 16:01:07</p>


DH3  
Burst number






DH5  
Burst width




DH5  
Burst number




Modulation Type: $\pi/4$ DQPSK	
2DH1 Burst width	 <p>Spectrum Ref Level 30.00 dBm Att 40 dB RBW 1 MHz SGL TRG:VID IAP Cirw M1[1] -19.45 dBm D1[1] 0.00000000 s 16.21 dB 383.75 ps TRG -22.600 dBm CF 2.441 GHz 8001 pts 1.0 ms/ Date: 23 JUL 2019 16:03:47</p>
2DH1 Burst number	 <p>Spectrum Ref Level 30.00 dBm Att 40 dB RBW 500 kHz SGL TRG:VID IAP Cirw TRG -4.600 dBm CF 2.441 GHz 30001 pts 3.16 s/ Date: 23 JUL 2019 16:04:21</p>
2DH3 Burst width	 <p>Spectrum Ref Level 30.00 dBm Att 40 dB RBW 1 MHz SGL TRG:VID IAP Cirw M1[1] -15.71 dBm D1[1] 0.00000000 s -2.45 dB 1.63500 ms TRG -22.600 dBm CF 2.441 GHz 8001 pts 1.0 ms/ Date: 23 JUL 2019 16:06:15</p>


2DH3  
Burst number



2DH5  
Burst width




2DH5  
Burst number




Modulation Type: $\pi/4$ QPSK	
3DH1 Burst width	<p>Spectrum</p> <p>Ref Level 30.00 dBm Att 40 dB RBW 1 MHz SWT 10 ms VBW 3 MHz</p> <p>SGL TRG:VID IAP Cirw</p> <p>M1[1] -20.85 dBm D1[1] 383.75 ps</p> <p>TRG -22.500 dBm</p> <p>CF 2.441 GHz 8001 pts 1.0 ms/</p> <p>Date: 23 JUL 2019 16:08:28</p>
3DH1 Burst number	<p>Spectrum</p> <p>Ref Level 30.00 dBm Att 40 dB RBW 500 kHz SWT 31.6 s VBW 3 MHz</p> <p>SGL TRG:VID IAP Cirw</p> <p>TRG -4.500 dBm</p> <p>CF 2.441 GHz 30001 pts 3.16 s/</p> <p>Date: 23 JUL 2019 16:09:02</p>
3DH3 Burst width	<p>Spectrum</p> <p>Ref Level 30.00 dBm Att 40 dB RBW 1 MHz SWT 10 ms VBW 3 MHz</p> <p>SGL TRG:VID IAP Cirw</p> <p>M1[1] -19.38 dBm D1[1] 1.63375 ms</p> <p>TRG -22.400 dBm</p> <p>CF 2.441 GHz 8001 pts 1.0 ms/</p> <p>Date: 23 JUL 2019 16:09:43</p>




3DH3  
Burst number



3DH5  
Burst width



3DH5  
Burst number



### 5.8. Pseudorandom Frequency Hopping Sequence


#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5<sup>th</sup> and 9<sup>th</sup> stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter. The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


## 5.9. Restricted band (radiated)

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:  
 RBW=1 MHz, VBW=3 MHz Peak detector for Peak value  
 RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS

Passed       Not Applicable

#### Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor
- 2) Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.
- 3) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.

Test channel:				CH00			
Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
2310.000	52.54	-2.34	50.20	74.00	23.80	Horizontal	PK
2390.000	59.03	-2.41	56.62	74.00	17.38	Horizontal	PK
2310.000	53.28	-2.34	50.94	74.00	23.06	Vertical	PK
2390.000	52.64	-2.41	50.23	74.00	23.77	Vertical	PK
2310.000	42.42	-2.34	40.08	54.00	13.92	Horizontal	AV
2390.000	41.95	-2.41	39.54	54.00	14.46	Horizontal	AV
2310.000	42.42	-2.34	40.08	54.00	13.92	Vertical	AV
2390.000	42.00	-2.41	39.59	54.00	14.41	Vertical	AV


Test channel:				CH78			
Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
2483.500	58.56	-2.15	56.41	74.00	17.59	Horizontal	PK
2500.000	53.95	-2.10	51.85	74.00	22.15	Horizontal	PK
2483.500	55.46	-2.15	53.31	74.00	20.69	Vertical	PK
2500.000	52.36	-2.10	50.26	74.00	23.74	Vertical	PK
2483.500	46.84	-2.15	44.69	54.00	9.31	Horizontal	AV
2500.000	42.16	-2.10	40.06	54.00	13.94	Horizontal	AV
2483.500	45.58	-2.15	43.43	54.00	10.57	Vertical	AV
2500.000	42.20	-2.10	40.10	54.00	13.90	Vertical	AV

## 5.10. Band edge and Spurious Emissions (conducted)

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### TEST CONFIGURATION



### TEST PROCEDURE




1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:  
RBW = 100 kHz, VBW  $\geq$  RBW, scan up through 10<sup>th</sup> harmonic.  
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

### TEST MODE:


Please refer to the clause 3.3

### TEST RESULTS

Passed       Not Applicable

Test Item:	Band edge	Modulation type:	GFSK																																										
<p>CH00 No hopping mode</p>		 <table border="1" data-bbox="687 593 1334 696"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40218 GHz</td> <td>0.98 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-54.37 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-55.99 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-55.32 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.374022 GHz</td> <td>-53.31 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 23 JUL 2019 15:58:52</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	0.98 dBm			M2	1		2.4 GHz	-54.37 dBm			M3	1		2.39 GHz	-55.99 dBm			M4	1		2.31 GHz	-55.32 dBm			M5	1		2.374022 GHz	-53.31 dBm			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	0.98 dBm																																									
M2	1		2.4 GHz	-54.37 dBm																																									
M3	1		2.39 GHz	-55.99 dBm																																									
M4	1		2.31 GHz	-55.32 dBm																																									
M5	1		2.374022 GHz	-53.31 dBm																																									
<p>CH00 Hopping mode</p>		 <table border="1" data-bbox="687 1120 1334 1223"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40218 GHz</td> <td>0.81 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-55.02 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-55.16 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-53.78 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.360116 GHz</td> <td>-53.20 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 23 JUL 2019 16:08:41</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	0.81 dBm			M2	1		2.4 GHz	-55.02 dBm			M3	1		2.39 GHz	-55.16 dBm			M4	1		2.31 GHz	-53.78 dBm			M5	1		2.360116 GHz	-53.20 dBm			
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	0.81 dBm																																									
M2	1		2.4 GHz	-55.02 dBm																																									
M3	1		2.39 GHz	-55.16 dBm																																									
M4	1		2.31 GHz	-53.78 dBm																																									
M5	1		2.360116 GHz	-53.20 dBm																																									
<p>CH78 No hopping mode</p>		 <table border="1" data-bbox="687 1650 1334 1749"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.479863 GHz</td> <td>1.94 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4835 GHz</td> <td>-58.40 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.5 GHz</td> <td>-60.16 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.4892551 GHz</td> <td>-57.40 dBm</td> <td></td> <td></td> </tr> </tbody> </table> <p>Date: 23 JUL 2019 16:01:03</p>	Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.479863 GHz	1.94 dBm			M2	1		2.4835 GHz	-58.40 dBm			M3	1		2.5 GHz	-60.16 dBm			M4	1		2.4892551 GHz	-57.40 dBm										
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.479863 GHz	1.94 dBm																																									
M2	1		2.4835 GHz	-58.40 dBm																																									
M3	1		2.5 GHz	-60.16 dBm																																									
M4	1		2.4892551 GHz	-57.40 dBm																																									


CH78  
Hopping mode



Test Item:	Band edge	Modulation type:	π/4DQPSK																																										
<p>CH00 No hopping mode</p>	<table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40218 GHz</td> <td>0.01 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-51.57 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-55.09 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-55.78 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.399906 GHz</td> <td>-51.07 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	0.01 dBm			M2	1		2.4 GHz	-51.57 dBm			M3	1		2.39 GHz	-55.09 dBm			M4	1		2.31 GHz	-55.78 dBm			M5	1		2.399906 GHz	-51.07 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	0.01 dBm																																									
M2	1		2.4 GHz	-51.57 dBm																																									
M3	1		2.39 GHz	-55.09 dBm																																									
M4	1		2.31 GHz	-55.78 dBm																																									
M5	1		2.399906 GHz	-51.07 dBm																																									
<p>CH00 Hopping mode</p>	<table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.40287 GHz</td> <td>-0.05 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-53.07 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-54.79 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-55.53 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.399906 GHz</td> <td>-52.02 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40287 GHz	-0.05 dBm			M2	1		2.4 GHz	-53.07 dBm			M3	1		2.39 GHz	-54.79 dBm			M4	1		2.31 GHz	-55.53 dBm			M5	1		2.399906 GHz	-52.02 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40287 GHz	-0.05 dBm																																									
M2	1		2.4 GHz	-53.07 dBm																																									
M3	1		2.39 GHz	-54.79 dBm																																									
M4	1		2.31 GHz	-55.53 dBm																																									
M5	1		2.399906 GHz	-52.02 dBm																																									
<p>CH78 No hopping mode</p>	<table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.479863 GHz</td> <td>0.45 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4835 GHz</td> <td>-58.89 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.5 GHz</td> <td>-59.29 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.483771 GHz</td> <td>-57.45 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.479863 GHz	0.45 dBm			M2	1		2.4835 GHz	-58.89 dBm			M3	1		2.5 GHz	-59.29 dBm			M4	1		2.483771 GHz	-57.45 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.479863 GHz	0.45 dBm																																									
M2	1		2.4835 GHz	-58.89 dBm																																									
M3	1		2.5 GHz	-59.29 dBm																																									
M4	1		2.483771 GHz	-57.45 dBm																																									




CH78  
Hopping mode



Test Item:	Band edge	Modulation type:	8DPSK
<p>CH00 No hopping mode</p>			
<p>CH00 Hopping mode</p>			
<p>CH78 No hopping mode</p>			


CH78  
Hoppig mode




Date: 23 JUL 2019 16:28:57

Test Item:	SE	Modulation type:	GFSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			


CH39  
Reference level




CH39  
30MHz~1000MHz




CH39  
1GHz~26GHz




CH78  
Reference level






CH78  
30MHz~1000MHz




CH78  
1GHz~26GHz




Test Item:	SE	Modulation type:	$\pi/4$ DQPSK
CH00 Reference level		 <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 IPk Max M1[1] -1.04 dBm 2.4018260 GHz CF 2.402 GHz 691 pts Span 30.0 MHz Date: 23 JUL 2019 16:02:40</p>	
CH00 30MHz~1000MHz		 <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPk Max M1[1] -52.27 dBm 798.4890 MHz D1 -21.040 dBm Start 30.0 MHz 30001 pts Stop 1.0 GHz Date: 23 JUL 2019 16:02:56</p>	
CH00 1GHz~26GHz		 <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPk Max M1[1] -44.39 dBm 15.225833 GHz D1 -21.040 dBm Start 1.0 GHz 30001 pts Stop 26.0 GHz Date: 23 JUL 2019 16:03:12</p>	


CH39  
Reference level



CH39  
30MHz~1000MHz




CH39  
1GHz~26GHz







CH78  
Reference level






CH78  
30MHz~1000MHz




CH78  
1GHz~26GHz




Test Item:	SE	Modulation type:	8DPSK
CH00 Reference level		 <p>Ref Level 21.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 75.9 μs VBW 300 kHz Mode Auto FFT Count 100/100 IPK Max M1[1] -0.20 dBm 2.4021740 GHz CF 2.402 GHz 691 pts Span 30.0 MHz Date: 23 JUL 2019 16:00:09</p>	
CH00 30MHz~1000MHz		 <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 30.1 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPK Max M1[1] -52.79 dBm 769.5840 MHz D1 -20.200 dBm Start 30.0 MHz 30001 pts Stop 1.0 GHz Date: 23 JUL 2019 16:00:05</p>	
CH00 1GHz~26GHz		 <p>Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 250 ms VBW 300 kHz Mode Auto Sweep Count 10/10 IPK Max M1[1] -44.44 dBm 16.661667 GHz D1 -20.200 dBm Start 1.0 GHz 30001 pts Stop 26.0 GHz Date: 23 JUL 2019 16:01:01</p>	


CH39  
Reference level




CH39  
30MHz~1000MHz




CH39  
1GHz~26GHz




CH78  
Reference level



CH78  
30MHz~1000MHz



CH78  
1GHz~26GHz



### 5.11. Spurious Emissions (radiated)


#### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak

#### TEST CONFIGURATION


- Below 30 MHz



- 30 MHz ~1000 MHz



- Above 1 GHz



## TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10:2013.
2. The EUT is placed on a turn table with 0.8 meter above ground for below 1GHz, 1.5 meter above ground for above 1GHz.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1 GHz:
    - RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
    - If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - (3) From 1 GHz to 10<sup>th</sup> harmonic:
    - RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
    - RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

## TEST MODE:

Please refer to the clause 3.3

## TEST RESULTS

Passed       Not Applicable

Note:


- 1) Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3) Below 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation High channel which it was worst case, so only the worst case's data on the test report.
- 4) Above 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report
- 5) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.

### ➤ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

➤ 30 MHz ~ 1 GHz

Polarization: Vertical




**MEASUREMENT RESULT: "GM1907236057\_red"**

7/23/2019 1:46PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	36.10	-9.4	40.0	3.9	QP	100.0	213.00	VERTICAL
45.520000	32.80	-4.9	40.0	7.2	QP	100.0	360.00	VERTICAL
86.260000	24.40	-10.2	40.0	15.6	QP	100.0	172.00	VERTICAL
208.480000	30.70	-6.6	43.5	12.8	QP	100.0	77.00	VERTICAL
555.740000	29.80	3.1	46.0	16.2	QP	100.0	294.00	VERTICAL
910.760000	38.40	10.6	46.0	7.6	QP	100.0	0.00	VERTICAL

Polarization: Horizontal



**MEASUREMENT RESULT: "GM1907236058\_red"**

7/23/2019 1:48PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
45.520000	25.10	-4.9	40.0	14.9	QP	100.0	35.00	HORIZONTAL
163.860000	27.80	-9.4	43.5	15.7	QP	100.0	3.00	HORIZONTAL
183.260000	33.30	-8.1	43.5	10.2	QP	100.0	0.00	HORIZONTAL
206.540000	36.20	-6.6	43.5	7.3	QP	100.0	70.00	HORIZONTAL
357.860000	36.80	-1.8	46.0	9.2	QP	100.0	35.00	HORIZONTAL
947.620000	38.10	10.8	46.0	7.9	QP	100.0	0.00	HORIZONTAL

## ➤ 1 GHz ~ 25 GHz

CH00							
Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
2859.437	35.94	1.12	37.06	74.00	36.94	Horizontal	PK
3602.625	37.19	1.45	38.64	74.00	35.36	Horizontal	PK
4508.843	34.87	5.39	40.26	74.00	33.74	Horizontal	PK
5729.375	33.69	9.03	42.72	74.00	31.28	Horizontal	PK
2796.281	34.51	2.03	36.54	74.00	37.46	Vertical	PK
4057.937	35.55	3.15	38.70	74.00	35.30	Vertical	PK
5213.843	33.15	8.91	42.06	74.00	31.94	Vertical	PK
6703.156	31.71	13.46	45.17	74.00	28.83	Vertical	PK

CH39							
Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
1212.968	37.25	-5.80	31.45	74.00	42.55	Horizontal	PK
3141.437	36.47	0.54	37.01	74.00	36.99	Horizontal	PK
5106.625	33.69	8.81	42.50	74.00	31.50	Horizontal	PK
6578.312	31.66	13.01	44.67	74.00	29.33	Horizontal	PK
2802.156	34.31	2.05	36.36	74.00	37.64	Vertical	PK
3844.968	35.31	2.30	37.61	74.00	36.39	Vertical	PK
5141.875	32.77	8.88	41.65	74.00	32.35	Vertical	PK
7036.562	31.37	15.27	46.64	74.00	27.36	Vertical	PK

CH78							
Freq. [MHz]	Reading [dB $\mu$ V/m]	Factor [dB]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Polarity	Detector
3188.437	36.01	0.78	36.79	74.00	37.21	Horizontal	PK
4657.187	33.15	6.12	39.27	74.00	34.73	Horizontal	PK
5127.187	32.21	8.85	41.06	74.00	32.94	Horizontal	PK
6678.187	31.75	13.40	45.15	74.00	28.85	Horizontal	PK
3154.656	37.14	0.60	37.74	74.00	36.26	Vertical	PK
3814.125	35.75	2.09	37.84	74.00	36.16	Vertical	PK
5152.156	33.04	8.89	41.93	74.00	32.07	Vertical	PK
6227.281	31.84	10.91	42.75	74.00	31.25	Vertical	PK

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dB $\mu$ V/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.




## 6. TEST SETUP PHOTOS

Conducted Emissions (AC Mains)






Radiated Emissions










## 7. EXTERANAL AND INTERNAL PHOTOS


External Photos














Internal Photos


















-----End of Report-----