

FCC TEST REPORT

Report No. : EMI00-016
 Tested Date: May/18/00

Test Performed By
 Philips Electronics Industries (Taiwan) Ltd.
 Business Electronics
 EMC Lab.
 No. 5, Tze Chiang 1 Road,
 Chungli, Taoyuan, Taiwan, R.O.C.
 Tel.: + 886-3-454-9862 Fax.: +886-3-454-9887

Manufacturer : Philips Business Electronics

Tested System:

- | | | | |
|---------------|---|-----------------------------|----------------------|
| 1. EUT | : | AMT-15B070-CN color monitor | s/n: TY0005126 |
| | : | FCC ID | : A3KM078 |
| 2. Computer | : | IBM V66XA | s/n: S14AA00072 |
| | : | FCC ID | : FCC Logo |
| 3. Keyboard | : | IBM KB-7959 | s/n: 10422 |
| | : | FCC ID | : FCC Logo |
| 4. Mouse | : | IBM M-S34 | s/n: 457249 |
| | : | FCC ID | : DZL211029 |
| 5. Modem | : | USRoboties 268 | s/n: 002680559278575 |
| | : | FCC ID | : CJE-0318 |
| 6. Printer | : | HP2225C | s/n: 3123S97227 |
| | : | FCC ID | : DSI6XU2225 |
| 7. Video Card | : | METABYTE | s/n: 10105 |
| | : | FCC ID | : I27MM-VS03A |

Note: Test was performed in according with FCC measurement procedure ANSI C63.4-1992
 "AMERICAN NATIONAL STANDARD FOR MEASUREMENT OF RADIO-NOISE
 EMISSION FROM LOW-VOLTAGE ELECTRONIC EQUIPMENT IN THE RANGE
 OF 9KHz TO 40GHz"

Monitor was connected to floor mounted AC outlet.
 68.7KHz mode (1024X768/85Hz) was tested.
 D-sub I/F cable with one ferrite core was used.
 Non-shield power cord was used during test.
 The test equipment used for testing please refer to the list as attached.

Deviation: None

Radiated RF Level – Peak Value

Frequency (MHz)	Horizontal (dBuv/m)	Vertical (dBuv/m)	FCC/B Limit (dBuv/m)
66.03	27.28	28.98	40.0
114.05	31.54	34.14	43.5
119.95	33.5	30.9	43.5

FCC ID: A3KM078

126.07	27.08	28.38	43.5
215.9	32.58	31.88	43.5
222.09	33.74	34.74	46.0
228.1	33.86	33.56	46.0
231.1	33.95	33.05	46.0
234.1	35.5	34.3	46.0
246.1	37.04	34.34	46.0
270.12	37.4	35.1	46.0
306.13	33.02	33.62	46.0
318.13	32.17	32.67	46.0
324.14	31.09	31.59	46.0
330.14	32.22	31.52	46.0
335.83	31.16	29.86	46.0
346.18	32.9	30.91	46.0
354.16	31.6	32.0	46.0
366.16	31.4	31.3	46.0

Spectrum Analyzer Setting:

RBW: 100KHz

VBW: 100KHz

Quasi-peak Values were taken with Rohde & Schwarz ESVS 30 EMI Test receiver.

Radiated RF Level – Quasi-Peak Value

Frequency (MHz)	Horizontal (dB _V /m)	Vertical (dB _V /m)	FCC/B Limit (dB _V /m)
71.97	29.66	32.56	40.0
167.92	41.04	38.04	43.5

The spectrum was scanned from 30MHz to 1000MHz and the significant emissions were recorded.

Test distance between device under test and receiving antenna was 3-meter.

Sample of calculation:

$$\text{Final value (dB_V/m)} = \text{Antenna Factor (dB)} + \text{Cable Loss (dB)} + \text{Reading value (dB_V/m)}$$

Tested by:

C.C.Wu

Checked by:

K.J.Hsu – EMC Engineer
NVLAP Signatory





