



RF EXPOSURE REPORT

REPORT NO.: SA110504E03

MODEL NO.: 5903-003285

FCC ID: A3L-DRMODEMZ1

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Samsung Electronics Co., Ltd.

ADDRESS: 416 Maetan-dong, Young-Tong gu, Suwon, Korea
442-742

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110504E03	Original release	June 03, 2011



1.CERTIFICATION

PRODUCT: DR-Ready Modem
BRAND NAME: SAMSUNG
MODEL NO.: 5903-003285
TEST SAMPLE: MASS-PRODUCTION
APPLICANT: Samsung Electronics Co., Ltd.
STANDARDS: IEEE C95.1

The above equipment (Model: 5903-003285) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : *Amanda Chu* , **DATE:** June 03, 2011
(Amanda Chu, Deputy Manager)

APPROVED BY : *May Chen* , **DATE:** June 03, 2011
(May Chen, Deputy Manager)

2.RF Exposure Limit

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3.MPE calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4.Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. calculation result of maximum conducted power

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm ²)	LIMIT (mW/cm ²)
2405-2480	4.2	0	20	0.001	1.00

--- END ---