

TEST REPORT

FCC MPE Test for AT1H04-A10

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2109-FC041

DATE OF ISSUE
September 28, 2021

Tested by
Kwang Il Yoon



Technical Manager
Jong Seok Lee



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO

HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

**TEST
REPORT**
FCC MPE Test for
AT1H04-A10

REPORT NO.
HCT-RF-2109-FC041

DATE OF ISSUE
September 28, 2021

Additional Model
-

Applicant

SAMSUNG Electronics Co., Ltd.

129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea

Product Name

AU (AT1H04)

Model Name

AT1H04-A10

FCC ID

A3LAT1H04-A10

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	September 28, 2021	Initial Release

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr

RF Exposure Statement

1. Limit

According to § 1.1310 RF exposure is calculated.

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz, * = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. Results

- The EUT duty cycle is calculated according to ANSI C63.26 - 5.2.4.3.4.
 Duty Cycle = On-time / Transmitter period = 74.3 %
 (By manufacturer's declaration, this EUT has a duty cycle of up to 74.3%)
 Duty Correction = $10 \log (1/\text{duty cycle}) = 10 \log (1/0.743) = 1.29 \text{ dB}$
- Max. EIRP (40 dBm) – Duty Correction (1.29 dB) + tolerance (4 dB) = Total (42.71 dBm)

-Wall installation-

EIRP[Radiated Power]	42.71	dBm
EIRP[Radiated Power]	18663.80	mW
Prediction distance	40.00	cm
Prediction frequency	37 000 ~ 40 000	MHz
Power density at prediction frequency (S)	0.9283	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm ²

-Pole installation-

EIRP[Radiated Power]	42.71	dBm
EIRP[Radiated Power]	18663.80	mW
Prediction distance	40.00	cm
Prediction frequency	37 000 ~ 40 000	MHz
Power density at prediction frequency (S)	0.9283	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm ²

-Ceiling installation-

EIRP[Radiated Power]	38.71	dBm
EIRP[Radiated Power]	7430.19	mW
Prediction distance	25.00	cm
Prediction frequency	37 000 ~ 40 000	MHz
Power density at prediction frequency (S)	0.9460	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm ²