

TEST REPORT

FCC MPE Test for AT1K08d-A00

APPLICANT
SAMSUNG Electronics Co., Ltd.

REPORT NO.
HCT-RF-2210-FC005

DATE OF ISSUE
October 14, 2022

Tested by
Kyung Soo Kang



Technical Manager
Kwon Jeong



HCT CO., LTD.
Bongjai Huh
BongJai Huh / CEO



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401

**TEST
REPORT**
FCC MPE Test for
AT1K08d-A00

REPORT NO.
HCT-RF-2210-FC005

DATE OF ISSUE
October 14, 2022

Additional Model
-

Applicant	SAMSUNG Electronics Co., Ltd. 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
Product Name	AU(AT1K08d)
Model Name	AT1K08d-A00
FCC ID	A3LAT1K08D-A00

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test results were applied only to the test methods required by the standard.

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	October 14, 2022	Initial Release

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

If this report is required to confirmation of authenticity, please contact to www.hct.co.kr

RF Exposure Statement

1. Limit

According to § 1.1310 RF exposure is calculated.

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz, * = Plane-wave equivalent power density

2. Maximum Permissible Exposure Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = Power input to antenna

G = Power gain to the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

3. Results

- The EUT duty cycle is calculated according to ANSI C63.26 - 5.2.4.3.4.
 Duty Cycle = On-time / Transmitter period = 73.17 %
 Duty Correction = $10 \log (1/\text{duty cycle}) = 10 \log (1/0.7317) = 1.3569 \text{ dB}$
- MIMO Max. EIRP (66 dBm) – Duty Correction (1.3569 dB) + tolerance (3 dB) = Total (67.64 dBm)

EIRP[Radiated Power]	67.64	dBm
EIRP[Radiated Power]	5807644.18	mW
Prediction distance	690.00	cm
Prediction frequency	27 500 ~ 28 350 37 600 ~ 39 300	MHz
Power density at prediction frequency (S)	0.9707	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.00	mW/cm ²