FCC and IC Certification

Maximum Permissible Exposure

RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the Environmental of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm ²)	(Minutes)
	(A) Limits for	occupational / Cor	ntral Exposure	
30 - 300	61.4	0.163	1	6
300 - 1500			F/300	6
1500 - 100000	•••		5	6
(E	B) Limits for Gener	ral Population / Un	controlled Exposu	ıre
30 - 300	27.5	0.073	0.2	30
300 - 1500			F/1500	30
1500 - 100000			1	30

F = Frequency (MHz)

Fries formula

Fries transmission formula : Pd = (Pout * G) / (4 * π * r²)

 $r = \sqrt{((Pout * G) / 4 * \pi * Pd))}$

Where

Pd = Power density in mW/cm²

Pout = Output power to antenna in mW

G = Gain of antenna in linear scale

 π = 3.1416

r = Distance between observation point center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the Maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the Maximum distance r where the MPE limit is reached and Power density at prediction frequency.



Test Report No.: NK-16-R-063

FCC and IC Certification

Test Result : DTS (2GHz Band)

The maximum antenna gain is 2.7 dBi or 1.86(Numeric).

Maximum peak output power at antenna input terminal: 21.00 (dBm)

Maximum peak output power at antenna input terminal: 125.89 (mW)

Antenna gain(typical): 2.70 (dBi)

Maximum antenna gain: 1.86 (numeric)

Prediction distance: 20 (cm)

Prediction frequency: 2462 (MHz)

MPE limit for uncontrolled exposure at prediction frequency:

1 (mW/cm^2)

Power density at prediction frequency: 0.046637 (mW/cm^2)

Test result: PASS

The MPE was calculated with maximum permitted output level add to positive power tolerance. According to the operational description submitted by manufacturer, maximum permitted output power is 21 dBm including positive tolerance.

Samsung Electronics Co., Ltd.
FCC ID: A3LATKM052000 / IC:649E-ATKM052000



Test Report No.: NK-16-R-063

FCC and IC Certification

Test Result : UNII (5GHz Band)

The maximum antenna gain is **2.7 dBi**.

Maximum peak output power at antenna input terminal: 16.00 (dBm)

Maximum peak output power at antenna input terminal: 39.81 (mW)

Antenna gain(typical): 2.70 (dBi)

Maximum antenna gain: 1.86 (numeric)

Prediction distance: 20 (cm)

Prediction frequency: 5260 (MHz)

MPE limit for uncontrolled exposure at prediction frequency:

1 (mW/cm^2)

Power density at prediction frequency: 0.014748 (mW/cm^2)

Test result: PASS

Note(s)

The MPE was calculated with maximum permitted output level add to positive power tolerance. According to the operational description submitted by manufacturer, maximum permitted output power is 16 dBm including positive tolerance.

Samsung Electronics Co., Ltd. FCC ID: A3LATKM052000 / IC:649E-ATKM052000