

Appendix A. Calibration certificate
Appendix A.1 Probe Calibration certificate (EX3DV4_7840)

Calibration Laboratory of
 Schmid & Partner
 Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client	Eurofins KCTL Gyeonggi-do, Republic of Korea	Certificate No.	EX-7840_Aug23
--------	--	-----------------	----------------------

CALIBRATION CERTIFICATE

Object: EX3DV4 - SN:7840

Calibration procedure(s): QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6, QA CAL-25.v8
 Calibration procedure for dosimetric E-field probes

Calibration date: August 25, 2023



This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3) °C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP2	SN: 104778	30-Mar-23 (No. 217-03804/03805)	Mar-24
Power sensor NRP-Z91	SN: 103244	30-Mar-23 (No. 217-03804)	Mar-24
OCP DAK-3.5 (weighted)	SN: 1249	20-Oct-22 (OCP-DAK3.5-1249_Oct22)	Oct-23
OCP DAK-12	SN: 1016	20-Oct-22 (OCP-DAK12-1016_Oct22)	Oct-23
Reference 20 dB Attenuator	SN: CC2552 (20x)	30-Mar-23 (No. 217-03809)	Mar-24
DAE4	SN: 660	16-Mar-23 (No. DAE4-660_Mar23)	Mar-24
Reference Probe ES3DV2	SN: 3013	06-Jan-23 (No. ES3-3013_Jan23)	Jan-24

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-22)	In house check: Jun-24
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-22)	In house check: Oct-24

Calibrated by	Name: Joanna Lleshaj	Function: Laboratory Technician	Signature: 
Approved by	Name: Sven Kühn	Function: Technical Manager	Signature: 

Issued: August 25, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

EX3DV4 - SN:7840

August 25, 2023

Parameters of Probe: EX3DV4 - SN:7840

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k = 2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.71	0.60	0.65	±10.1%
DCP (mV) ^B	110.0	106.5	106.5	±4.7%

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB/ $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Max Unc ^E k = 2
0	CW	X	0.00	0.00	1.00	0.00	141.5	±1.4%	±4.7%
		Y	0.00	0.00	1.00		118.2		
		Z	0.00	0.00	1.00		131.8		
10352	Pulse Waveform (200Hz, 10%)	X	1.61	61.04	6.49	10.00	60.0	±3.1%	±9.6%
		Y	1.44	60.06	5.75		60.0		
		Z	1.46	60.29	6.10		60.0		
10353	Pulse Waveform (200Hz, 20%)	X	0.85	60.00	4.98	6.99	80.0	±2.6%	±9.6%
		Y	0.79	60.00	4.41		80.0		
		Z	0.80	60.00	4.81		80.0		
10354	Pulse Waveform (200Hz, 40%)	X	0.47	60.00	3.93	3.98	95.0	±2.6%	±9.6%
		Y	0.03	127.87	0.31		95.0		
		Z	0.26	152.07	1.54		95.0		
10355	Pulse Waveform (200Hz, 60%)	X	0.31	60.00	3.20	2.22	120.0	±1.5%	±9.6%
		Y	0.01	159.99	0.58		120.0		
		Z	6.79	158.42	19.98		120.0		
10387	QPSK Waveform, 1 MHz	X	0.93	72.32	17.30	1.00	150.0	±3.4%	±9.6%
		Y	0.41	62.75	11.55		150.0		
		Z	0.57	64.93	13.28		150.0		
10388	QPSK Waveform, 10 MHz	X	1.69	69.96	16.31	0.00	150.0	±1.0%	±9.6%
		Y	1.17	65.67	13.12		150.0		
		Z	1.39	66.75	14.44		150.0		
10396	64-QAM Waveform, 100 kHz	X	1.92	66.96	17.20	3.01	150.0	±1.1%	±9.6%
		Y	1.73	65.40	16.33		150.0		
		Z	1.62	63.83	15.66		150.0		
10399	64-QAM Waveform, 40 MHz	X	2.99	67.51	15.91	0.00	150.0	±2.2%	±9.6%
		Y	2.68	66.37	15.00		150.0		
		Z	2.83	66.44	15.25		150.0		
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.94	66.74	15.79	0.00	150.0	±3.6%	±9.6%
		Y	3.74	66.82	15.46		150.0		
		Z	3.93	66.64	15.64		150.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Linearization parameter uncertainty for maximum specified field strength.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4 - SN:7840

August 25, 2023

Parameters of Probe: EX3DV4 - SN:7840

Sensor Model Parameters

	C1 fF	C2 fF	α V ⁻¹	T1 msV ⁻²	T2 msV ⁻¹	T3 ms	T4 V ⁻²	T5 V ⁻¹	T6
x	9.8	69.82	32.52	5.33	0.00	4.90	0.77	0.00	1.00
y	7.6	55.22	33.45	1.66	0.00	4.90	0.55	0.00	1.00
z	9.6	69.20	33.50	2.95	0.00	4.90	0.06	0.06	1.00

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle	-76.0°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Note: Measurement distance from surface can be increased to 3-4 mm for an Area Scan job.

EX3DV4 - SN:7840

August 25, 2023

Parameters of Probe: EX3DV4 - SN:7840

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k = 2)
750	41.9	0.89	9.09	9.31	9.19	0.40	1.27	±12.0%
850	41.5	0.92	8.63	8.86	8.60	0.40	1.27	±12.0%
900	41.5	0.97	8.50	8.29	8.53	0.40	1.27	±12.0%
1750	40.1	1.37	7.72	7.63	7.71	0.27	1.27	±12.0%
1900	40.0	1.40	7.27	7.27	7.26	0.30	1.27	±12.0%
2300	39.5	1.67	6.99	6.98	7.02	0.32	1.27	±12.0%
2450	39.2	1.80	6.80	6.79	6.85	0.31	1.27	±12.0%
2600	39.0	1.96	6.79	6.78	6.83	0.30	1.27	±12.0%
5250	35.9	4.71	5.33	5.34	5.33	0.31	1.72	±14.0%
5600	35.5	5.07	4.59	4.57	4.57	0.39	1.67	±14.0%
5800	35.3	5.27	4.72	4.69	4.74	0.35	1.87	±14.0%

^C Frequency validity above 300 MHz of ±100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–9 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10%. If TSL with deviations from the target of less than ±5% are used, the calibration uncertainties are 11.1% for 0.7 - 3 GHz and 13.1% for 3 - 6 GHz.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4 - SN:7840

August 25, 2023

Parameters of Probe: EX3DV4 - SN:7840

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k = 2)
6500	34.5	6.07	4.96	5.00	5.05	0.20	2.00	±18.6%
7000	33.9	6.65	5.26	5.29	5.28	0.20	2.00	±18.6%

^C Frequency validity at 6.5 GHz is -600/+700 MHz, and ±700 MHz at or above 7 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±10%.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz; below ±2% for frequencies between 3–6 GHz; and below ±4% for frequencies between 6–10 GHz at any distance larger than half the probe tip diameter from the boundary.




EX3DV4 - SN:7840

August 25, 2023

Frequency Response of E-Field

(TEM-Cell:ifi1110 EXX, Waveguide:R22)




Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

EX3DV4 - SN:7840

August 25, 2023

Receiving Pattern (ϕ), $\theta = 0^\circ$




EX3DV4 - SN:7840

August 25, 2023

Dynamic Range f(SAR_{head})

(TEM cell, f_{eval} = 1900MHz)




Uncertainty of Linearity Assessment: ±0.6% (k=2)

EX3DV4 - SN:7840


August 25, 2023

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), f = 900 MHz



EX3DV4 - SN:7840

August 25, 2023

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^k k = 2
0		CW	CW	0.00	±4.7
10010	CAB	SAR Validation (Square, 100 ms, 10 ms)	Test	10.00	±9.6
10011	CAC	UMTS-FDD (WCDMA)	WCDMA	2.91	±9.6
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	±9.6
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	±9.6
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	±9.6
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	±9.6
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	±9.6
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	±9.6
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	±9.6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	±9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	±9.6
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	±9.6
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	±9.6
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	±9.6
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	±9.6
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	±9.6
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	±9.6
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	±9.6
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	±9.6
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	±9.6
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	±9.6
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	±9.6
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	±9.6
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	±9.6
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	±9.6
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	±9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	±9.6
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	±9.6
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	±9.6
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	±9.6
10062	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.88	±9.6
10063	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.83	±9.6
10064	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	±9.6
10065	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	±9.6
10066	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	±9.6
10067	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	±9.6
10068	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	±9.6
10069	CAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	±9.6
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	±9.6
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.82	±9.6
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	±9.6
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	±9.6
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	±9.6
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	±9.6
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	±9.6
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	±9.6
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	±9.6
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	±9.6
10097	CAC	UMTS-FDD (HSDPA)	WCDMA	3.98	±9.6
10098	CAC	UMTS-FDD (HSUPA, Subiest 2)	WCDMA	3.98	±9.6
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	±9.6
10100	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	±9.6
10101	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10102	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10103	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	±9.6
10104	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	±9.6
10105	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	±9.6
10108	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	±9.6
10109	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10110	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	±9.6
10111	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^F k = 2
10112	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	±9.6
10113	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10114	CAD	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	±9.6
10115	CAD	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	±9.6
10116	CAD	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	±9.6
10117	CAD	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	±9.6
10118	CAD	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	±9.6
10119	CAD	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	±9.6
10140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	±9.6
10142	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10143	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	±9.6
10144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	±9.6
10145	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	±9.6
10146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	±9.6
10147	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	±9.6
10149	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10150	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10151	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TDD	9.28	±9.6
10152	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10153	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	±9.6
10154	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	±9.6
10155	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10156	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	±9.6
10157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	±9.6
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	±9.6
10161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FDD	6.58	±9.6
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	±9.6
10167	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	±9.6
10168	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	±9.6
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.6
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10171	AAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	±9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9.21	±9.6
10173	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10174	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10175	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-FDD	5.72	±9.6
10176	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10177	CAJ	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	±9.6
10178	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10179	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10180	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10181	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	±9.6
10182	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10183	AAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10184	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10185	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	±9.6
10186	AAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10187	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	±9.6
10188	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10189	AAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10193	CAD	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9.6
10194	CAD	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	±9.6
10195	CAD	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	±9.6
10196	CAD	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	±9.6
10197	CAD	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	±9.6
10198	CAD	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	±9.6
10219	CAD	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	±9.6
10220	CAD	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	±9.6
10221	CAD	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	±9.6
10222	CAD	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	±9.6
10223	CAD	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	±9.6
10224	CAD	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10225	CAC	UMTS-FDD (HSPA+)	WCDMA	5.97	±9.6
10226	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.49	±9.6
10227	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	±9.6
10228	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	±9.6
10229	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10230	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10231	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9.19	±9.6
10232	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10233	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10234	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	±9.6
10235	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10236	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10237	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	±9.6
10238	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10239	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10240	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TDD	9.21	±9.6
10241	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	±9.6
10242	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TDD	9.86	±9.6
10243	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	±9.6
10244	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10245	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.06	±9.6
10246	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	9.30	±9.6
10247	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TDD	9.91	±9.6
10248	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TDD	10.09	±9.6
10249	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	±9.6
10250	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	±9.6
10251	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TDD	10.17	±9.6
10252	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	±9.6
10253	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	±9.6
10254	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	±9.6
10255	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	±9.6
10256	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	±9.6
10257	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	±9.6
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	±9.6
10259	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	±9.6
10260	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9.6
10261	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9.6
10262	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	±9.6
10263	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TDD	10.16	±9.6
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	±9.6
10265	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	±9.6
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	±9.6
10268	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10269	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	±9.6
10270	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TDD	9.58	±9.6
10274	CAC	UMTS-FDD (HSUPA, Sublest 5, 3GPP Rel8.10)	WCDMA	4.87	±9.6
10275	CAC	UMTS-FDD (HSUPA, Sublest 5, 3GPP Rel8.4)	WCDMA	3.96	±9.6
10277	CAA	PHS (QPSK)	PHS	11.81	±9.6
10278	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.5)	PHS	11.81	±9.6
10279	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.38)	PHS	12.18	±9.6
10290	AAB	CDMA2000, RC1, SQ55, Full Rate	CDMA2000	3.91	±9.6
10291	AAB	CDMA2000, RC3, SQ55, Full Rate	CDMA2000	3.46	±9.6
10292	AAB	CDMA2000, RC3, SQ32, Full Rate	CDMA2000	3.39	±9.6
10293	AAB	CDMA2000, RC3, SQ3, Full Rate	CDMA2000	3.50	±9.6
10295	AAB	CDMA2000, RC1, SQ3, 1/8th Rate 25 fr.	CDMA2000	12.49	±9.6
10297	AAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	±9.6
10298	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	±9.6
10299	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.6
10300	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10301	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)	WiMAX	12.03	±9.6
10302	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	±9.6
10303	AAA	IEEE 802.16e WiMAX (31:15, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	12.52	±9.6
10304	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	11.86	±9.6
10305	AAA	IEEE 802.16e WiMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)	WiMAX	15.24	±9.6
10306	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)	WiMAX	14.67	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^F k = 2
10307	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	±9.6
10308	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)	WiMAX	14.46	±9.6
10309	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.59	±9.6
10310	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, AMC 2x3, 18 symbols)	WiMAX	14.57	±9.6
10311	AAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	±9.6
10313	AAA	iDEN 1:3	iDEN	10.51	±9.6
10314	AAA	iDEN 1:6	iDEN	13.48	±9.6
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	±9.6
10316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10317	AAD	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.6
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.6
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	±9.6
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	±9.6
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	±9.6
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	±9.6
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	±9.6
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	±9.6
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	±9.6
10400	AAE	IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	±9.6
10401	AAE	IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	±9.6
10402	AAE	IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	±9.6
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	±9.6
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	±9.6
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5.22	±9.6
10410	AAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	±9.6
10414	AAA	WLAN CCF, 64-QAM, 40 MHz	Generic	8.54	±9.6
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	±9.6
10416	AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10417	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	WLAN	8.14	±9.6
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	WLAN	8.19	±9.6
10422	AAC	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	±9.6
10423	AAC	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	±9.6
10424	AAC	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	±9.6
10425	AAC	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	±9.6
10426	AAC	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	±9.6
10427	AAC	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	±9.6
10430	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	±9.6
10431	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	±9.6
10432	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10433	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10434	AAB	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	±9.6
10435	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10447	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	±9.6
10448	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.53	±9.6
10449	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	±9.6
10450	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	±9.6
10451	AAB	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	±9.6
10453	AAE	Validation (Square, 10 ms, 1 ms)	Test	10.00	±9.6
10456	AAC	IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	±9.6
10457	AAB	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	±9.6
10458	AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	6.55	±9.6
10459	AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	±9.6
10460	AAB	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	±9.6
10461	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10462	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.30	±9.6
10463	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10464	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10465	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10466	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10467	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10468	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10469	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10470	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10471	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ⁵ k = 2
10472	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10473	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10474	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10475	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10477	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10478	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10479	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10480	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	±9.6
10481	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10482	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.71	±9.6
10483	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	±9.6
10484	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	±9.6
10485	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.59	±9.6
10486	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.38	±9.6
10487	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.60	±9.6
10488	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	±9.6
10489	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10490	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.41	±9.6
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10494	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10495	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	±9.6
10496	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10497	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10498	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.40	±9.6
10499	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.88	±9.6
10500	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10501	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	±9.6
10502	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	±9.6
10503	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	±9.6
10504	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10505	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10506	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10507	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	±9.6
10508	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10509	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.99	±9.6
10510	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.49	±9.6
10511	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.51	±9.6
10512	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10513	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.42	±9.6
10514	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10516	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	±9.6
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10518	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10519	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.39	±9.6
10520	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	±9.6
10521	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	±9.6
10522	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10523	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.08	±9.6
10524	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	±9.6
10525	AAC	IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.36	±9.6
10526	AAC	IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.42	±9.6
10527	AAC	IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.21	±9.6
10528	AAC	IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.36	±9.6
10529	AAC	IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.36	±9.6
10531	AAC	IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.43	±9.6
10532	AAC	IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10533	AAC	IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.38	±9.6
10534	AAC	IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.45	±9.6
10535	AAC	IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.45	±9.6
10536	AAC	IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.32	±9.6
10537	AAC	IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
10538	AAC	IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.54	±9.6
10540	AAC	IEEE 802.11ac WiFi (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.39	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10541	AAC	IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.46	±9.6
10542	AAC	IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.65	±9.6
10543	AAC	IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.65	±9.6
10544	AAC	IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.47	±9.6
10545	AAC	IEEE 802.11ac WiFi (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10546	AAC	IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.35	±9.6
10547	AAC	IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.49	±9.6
10548	AAC	IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.37	±9.6
10550	AAC	IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.38	±9.6
10551	AAC	IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.50	±9.6
10552	AAC	IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.42	±9.6
10553	AAC	IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.45	±9.6
10554	AAD	IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.48	±9.6
10555	AAD	IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
10556	AAD	IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.50	±9.6
10557	AAD	IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.52	±9.6
10558	AAD	IEEE 802.11ac WiFi (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.61	±9.6
10560	AAD	IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.73	±9.6
10561	AAD	IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.56	±9.6
10562	AAD	IEEE 802.11ac WiFi (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.69	±9.6
10563	AAD	IEEE 802.11ac WiFi (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.77	±9.6
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	±9.6
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	±9.6
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	±9.6
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	±9.6
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	±9.6
10570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.30	±9.6
10571	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10572	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10574	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10575	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10576	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10578	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10581	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10582	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10583	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10584	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10585	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10586	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10587	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10588	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10589	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10590	AAC	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10591	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)	WLAN	8.63	±9.6
10592	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10593	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 90pc duty cycle)	WLAN	8.64	±9.6
10594	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10595	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)	WLAN	8.74	±9.6
10596	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)	WLAN	8.71	±9.6
10597	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)	WLAN	8.72	±9.6
10598	AAC	IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)	WLAN	8.50	±9.6
10599	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)	WLAN	8.79	±9.6
10600	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10601	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 90pc duty cycle)	WLAN	8.82	±9.6
10602	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)	WLAN	8.94	±9.6
10603	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)	WLAN	9.03	±9.6
10604	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)	WLAN	8.76	±9.6
10605	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)	WLAN	8.97	±9.6
10606	AAC	IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10607	AAC	IEEE 802.11ac WiFi (20 MHz, MCS0, 90pc duty cycle)	WLAN	8.64	±9.6
10608	AAC	IEEE 802.11ac WiFi (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.77	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10609	AAC	IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.57	±9.6
10610	AAC	IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.78	±9.6
10611	AAC	IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10612	AAC	IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10613	AAC	IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.94	±9.6
10614	AAC	IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.59	±9.6
10615	AAC	IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10616	AAC	IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.82	±9.6
10617	AAC	IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.81	±9.6
10618	AAC	IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.58	±9.6
10619	AAC	IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.86	±9.6
10620	AAC	IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.87	±9.6
10621	AAC	IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10622	AAC	IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.68	±9.6
10623	AAC	IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10624	AAC	IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.96	±9.6
10625	AAC	IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.96	±9.6
10626	AAC	IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10627	AAC	IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10628	AAC	IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.71	±9.6
10629	AAC	IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10630	AAC	IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.72	±9.6
10631	AAC	IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.81	±9.6
10632	AAC	IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10633	AAC	IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.83	±9.6
10634	AAC	IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.80	±9.6
10635	AAC	IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6
10636	AAD	IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10637	AAD	IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10638	AAD	IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.86	±9.6
10639	AAD	IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10640	AAD	IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)	WLAN	8.98	±9.6
10641	AAD	IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)	WLAN	9.06	±9.6
10642	AAD	IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)	WLAN	9.06	±9.6
10643	AAD	IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.89	±9.6
10644	AAD	IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)	WLAN	9.05	±9.6
10645	AAD	IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)	WLAN	9.11	±9.6
10646	AAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10647	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10648	AAA	CDMA2000 (1x Advanced)	CDMA2000	3.45	±9.6
10652	AAF	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.91	±9.6
10653	AAF	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	±9.6
10654	AAE	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	±9.6
10655	AAF	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	±9.6
10658	AAB	Pulse Waveform (200Hz, 10%)	Test	10.00	±9.6
10659	AAB	Pulse Waveform (200Hz, 20%)	Test	6.99	±9.6
10660	AAB	Pulse Waveform (200Hz, 40%)	Test	3.98	±9.6
10661	AAB	Pulse Waveform (200Hz, 60%)	Test	2.22	±9.6
10662	AAB	Pulse Waveform (200Hz, 80%)	Test	0.97	±9.6
10670	AAA	Bluetooth Low Energy	Bluetooth	2.19	±9.6
10671	AAC	IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.09	±9.6
10672	AAC	IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.57	±9.6
10673	AAC	IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.78	±9.6
10674	AAC	IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10675	AAC	IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.90	±9.6
10676	AAC	IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10677	AAC	IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.73	±9.6
10678	AAC	IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.78	±9.6
10679	AAC	IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.89	±9.6
10680	AAC	IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)	WLAN	8.80	±9.6
10681	AAC	IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)	WLAN	8.62	±9.6
10682	AAC	IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)	WLAN	8.83	±9.6
10683	AAC	IEEE 802.11ax (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10684	AAC	IEEE 802.11ax (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.26	±9.6
10685	AAC	IEEE 802.11ax (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10686	AAC	IEEE 802.11ax (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.28	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^F k = 2
10687	AAC	IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.45	±9.6
10688	AAC	IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)	WLAN	8.29	±9.6
10689	AAC	IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.55	±9.6
10690	AAC	IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10691	AAC	IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.25	±9.6
10692	AAC	IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)	WLAN	8.29	±9.6
10693	AAC	IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle)	WLAN	8.25	±9.6
10694	AAC	IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle)	WLAN	8.57	±9.6
10695	AAC	IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.78	±9.6
10696	AAC	IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.91	±9.6
10697	AAC	IEEE 802.11ax (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.61	±9.6
10698	AAC	IEEE 802.11ax (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.89	±9.6
10699	AAC	IEEE 802.11ax (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.82	±9.6
10700	AAC	IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.73	±9.6
10701	AAC	IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.86	±9.6
10702	AAC	IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.70	±9.6
10703	AAC	IEEE 802.11ax (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10704	AAC	IEEE 802.11ax (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.56	±9.6
10705	AAC	IEEE 802.11ax (40 MHz, MCS10, 90pc duty cycle)	WLAN	8.69	±9.6
10706	AAC	IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle)	WLAN	8.66	±9.6
10707	AAC	IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.32	±9.6
10708	AAC	IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10709	AAC	IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10710	AAC	IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.29	±9.6
10711	AAC	IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.39	±9.6
10712	AAC	IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)	WLAN	8.67	±9.6
10713	AAC	IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.33	±9.6
10714	AAC	IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.26	±9.6
10715	AAC	IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.45	±9.6
10716	AAC	IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.30	±9.6
10717	AAC	IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle)	WLAN	8.48	±9.6
10718	AAC	IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle)	WLAN	8.24	±9.6
10719	AAC	IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.81	±9.6
10720	AAC	IEEE 802.11ax (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.87	±9.6
10721	AAC	IEEE 802.11ax (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.76	±9.6
10722	AAC	IEEE 802.11ax (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.55	±9.6
10723	AAC	IEEE 802.11ax (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10724	AAC	IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.90	±9.6
10725	AAC	IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10726	AAC	IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.72	±9.6
10727	AAC	IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.66	±9.6
10728	AAC	IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.65	±9.6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle)	WLAN	8.64	±9.6
10730	AAC	IEEE 802.11ax (80 MHz, MCS11, 90pc duty cycle)	WLAN	8.67	±9.6
10731	AAC	IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10732	AAC	IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.46	±9.6
10733	AAC	IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.40	±9.6
10734	AAC	IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.25	±9.6
10735	AAC	IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.33	±9.6
10736	AAC	IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)	WLAN	8.27	±9.6
10737	AAC	IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.36	±9.6
10738	AAC	IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.42	±9.6
10739	AAC	IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.29	±9.6
10740	AAC	IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.48	±9.6
10741	AAC	IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle)	WLAN	8.40	±9.6
10742	AAC	IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle)	WLAN	8.43	±9.6
10743	AAC	IEEE 802.11ax (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.94	±9.6
10744	AAC	IEEE 802.11ax (160 MHz, MCS1, 90pc duty cycle)	WLAN	9.16	±9.6
10745	AAC	IEEE 802.11ax (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.93	±9.6
10746	AAC	IEEE 802.11ax (160 MHz, MCS3, 90pc duty cycle)	WLAN	9.11	±9.6
10747	AAC	IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle)	WLAN	9.04	±9.6
10748	AAC	IEEE 802.11ax (160 MHz, MCS5, 90pc duty cycle)	WLAN	8.93	±9.6
10749	AAC	IEEE 802.11ax (160 MHz, MCS6, 90pc duty cycle)	WLAN	8.90	±9.6
10750	AAC	IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.79	±9.6
10751	AAC	IEEE 802.11ax (160 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10752	AAC	IEEE 802.11ax (160 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10753	AAC	IEEE 802.11ax (160 MHz, MCS10, 90pc duty cycle)	WLAN	9.00	±9.6
10754	AAC	IEEE 802.11ax (160 MHz, MCS11, 90pc duty cycle)	WLAN	8.94	±9.6
10755	AAC	IEEE 802.11ax (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.64	±9.6
10756	AAC	IEEE 802.11ax (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.77	±9.6
10757	AAC	IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.77	±9.6
10758	AAC	IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.69	±9.6
10759	AAC	IEEE 802.11ax (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.58	±9.6
10760	AAC	IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle)	WLAN	8.49	±9.6
10761	AAC	IEEE 802.11ax (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.58	±9.6
10762	AAC	IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.49	±9.6
10763	AAC	IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.53	±9.6
10764	AAC	IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.54	±9.6
10765	AAC	IEEE 802.11ax (160 MHz, MCS10, 99pc duty cycle)	WLAN	8.54	±9.6
10766	AAC	IEEE 802.11ax (160 MHz, MCS11, 99pc duty cycle)	WLAN	8.51	±9.6
10767	AAE	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	7.99	±9.6
10768	AAD	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10769	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10770	AAD	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10771	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10772	AAD	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.23	±9.6
10773	AAD	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.03	±9.6
10774	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10775	AAD	5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10776	AAD	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10777	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10778	AAD	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.34	±9.6
10779	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.42	±9.6
10780	AAD	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10781	AAD	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10782	AAD	5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.43	±9.6
10783	AAE	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10784	AAD	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.29	±9.6
10785	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.40	±9.6
10786	AAD	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.35	±9.6
10787	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.44	±9.6
10788	AAD	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10789	AAD	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.37	±9.6
10790	AAD	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10791	AAE	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.83	±9.6
10792	AAD	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.92	±9.6
10793	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.95	±9.6
10794	AAD	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10795	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.84	±9.6
10796	AAD	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10797	AAD	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.01	±9.6
10798	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10799	AAD	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10801	AAD	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10802	AAD	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.87	±9.6
10803	AAD	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10805	AAD	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10806	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.37	±9.6
10809	AAD	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10810	AAD	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10812	AAD	5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10817	AAE	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10818	AAD	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10819	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.33	±9.6
10820	AAD	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.30	±9.6
10821	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10822	AAD	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10823	AAD	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.36	±9.6
10824	AAD	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.39	±9.6
10825	AAD	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10827	AAD	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.42	±9.6
10828	AAD	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.43	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10829	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.40	±9.6
10830	AAD	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.63	±9.6
10831	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.73	±9.6
10832	AAD	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.74	±9.6
10833	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10834	AAD	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.75	±9.6
10835	AAD	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10836	AAD	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.66	±9.6
10837	AAD	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.68	±9.6
10839	AAD	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10840	AAD	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.67	±9.6
10841	AAD	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.71	±9.6
10843	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.49	±9.6
10844	AAD	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10846	AAD	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10854	AAD	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10855	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10856	AAD	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10857	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.35	±9.6
10858	AAD	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10859	AAD	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10860	AAD	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10861	AAD	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.40	±9.6
10863	AAD	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10864	AAD	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10865	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10866	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10868	AAD	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.89	±9.6
10869	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10870	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.86	±9.6
10871	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10872	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.52	±9.6
10873	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10874	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10875	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10876	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.39	±9.6
10877	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	7.95	±9.6
10878	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10879	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.12	±9.6
10880	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.38	±9.6
10881	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10882	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.96	±9.6
10883	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.57	±9.6
10884	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.53	±9.6
10885	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10886	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10887	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10888	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.35	±9.6
10889	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.02	±9.6
10890	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.40	±9.6
10891	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.13	±9.6
10892	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10897	AAC	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.66	±9.6
10898	AAB	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10899	AAB	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10900	AAB	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10901	AAB	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10902	AAB	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10903	AAB	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10904	AAB	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10905	AAB	5G NR (DFT-s-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10906	AAB	5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10907	AAC	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.78	±9.6
10908	AAB	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10909	AAB	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.96	±9.6
10910	AAB	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^κ κ = 2
10911	AAB	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10912	AAB	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10913	AAB	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10914	AAB	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.85	±9.6
10915	AAB	5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6
10916	AAB	5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10917	AAB	5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10918	AAC	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10919	AAB	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10920	AAB	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10921	AAB	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10922	AAB	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.82	±9.6
10923	AAB	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10924	AAB	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10925	AAB	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.95	±9.6
10926	AAB	5G NR (DFT-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10927	AAB	5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10928	AAC	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10929	AAC	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10930	AAC	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10931	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10932	AAC	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10933	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10934	AAC	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10935	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10936	AAC	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10937	AAC	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.77	±9.6
10938	AAC	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10939	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.82	±9.6
10940	AAC	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.89	±9.6
10941	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10942	AAC	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10943	AAD	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.95	±9.6
10944	AAC	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.81	±9.6
10945	AAC	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10946	AAC	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10947	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10948	AAC	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10949	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10950	AAC	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10951	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.92	±9.6
10952	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.25	±9.6
10953	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.15	±9.6
10954	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.23	±9.6
10955	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.42	±9.6
10956	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.14	±9.6
10957	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.31	±9.6
10958	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.61	±9.6
10959	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.33	±9.6
10960	AAC	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.32	±9.6
10961	AAB	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.36	±9.6
10962	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.40	±9.6
10963	AAB	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.55	±9.6
10964	AAC	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.29	±9.6
10965	AAB	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.37	±9.6
10966	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.55	±9.6
10967	AAB	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.42	±9.6
10968	AAB	5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.49	±9.6
10972	AAB	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	11.59	±9.6
10973	AAB	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	9.06	±9.6
10974	AAB	5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)	5G NR FR1 TDD	10.28	±9.6
10978	AAA	ULLA BDR	ULLA	1.16	±9.6
10979	AAA	ULLA HDR4	ULLA	8.58	±9.6
10980	AAA	ULLA HDR8	ULLA	10.32	±9.6
10981	AAA	ULLA HDRp4	ULLA	3.19	±9.6
10982	AAA	ULLA HDRp8	ULLA	3.43	±9.6

EX3DV4 - SN:7840

August 25, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10983	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.31	±9.6
10984	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.42	±9.6
10985	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.54	±9.6
10986	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.50	±9.6
10987	AAA	5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.53	±9.6
10988	AAA	5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.38	±9.6
10989	AAA	5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.33	±9.6
10990	AAA	5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.52	±9.6
11003	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	10.24	±9.6
11004	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	10.73	±9.6
11005	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.70	±9.6
11006	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.55	±9.6
11007	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.46	±9.6
11008	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.51	±9.6
11009	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.78	±9.6
11010	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.95	±9.6
11011	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.96	±9.6
11012	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.88	±9.6
11013	AAA	IEEE 802.11be (320 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
11014	AAA	IEEE 802.11be (320 MHz, MCS2, 99pc duty cycle)	WLAN	8.45	±9.6
11015	AAA	IEEE 802.11be (320 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
11016	AAA	IEEE 802.11be (320 MHz, MCS4, 99pc duty cycle)	WLAN	8.44	±9.6
11017	AAA	IEEE 802.11be (320 MHz, MCS5, 99pc duty cycle)	WLAN	8.41	±9.6
11018	AAA	IEEE 802.11be (320 MHz, MCS6, 99pc duty cycle)	WLAN	8.40	±9.6
11019	AAA	IEEE 802.11be (320 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
11020	AAA	IEEE 802.11be (320 MHz, MCS8, 99pc duty cycle)	WLAN	8.27	±9.6
11021	AAA	IEEE 802.11be (320 MHz, MCS9, 99pc duty cycle)	WLAN	8.46	±9.6
11022	AAA	IEEE 802.11be (320 MHz, MCS10, 99pc duty cycle)	WLAN	8.36	±9.6
11023	AAA	IEEE 802.11be (320 MHz, MCS11, 99pc duty cycle)	WLAN	8.09	±9.6
11024	AAA	IEEE 802.11be (320 MHz, MCS12, 99pc duty cycle)	WLAN	8.42	±9.6
11025	AAA	IEEE 802.11be (320 MHz, MCS13, 99pc duty cycle)	WLAN	8.37	±9.6
11026	AAA	IEEE 802.11be (320 MHz, MCS0, 99pc duty cycle)	WLAN	8.39	±9.6

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Appendix A.2 Probe Calibration certificate (EUmmWV4 9489)

Calibration Laboratory of
 Schmid & Partner
 Engineering AG
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Eurofins KCTL**
 Gyeonggi-do, Republic of Korea

Certificate No. **EUmm-9489_Jun23**

CALIBRATION CERTIFICATE

Object	EUmmWV4 - SN:9489
Calibration procedure(s)	QA CAL-02.v9, QA CAL-25.v8, QA CAL-42.v3 Calibration procedure for E-field probes optimized for close near field evaluations in air
Calibration date	June 20, 2023

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22±3) °C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power sensor NRP110T	SN: 101244	12-Apr-23 (No. 0001A300692178)	Apr-24
Spectrum analyzer FSV40	SN: 101832	23-Jan-23 (No. 4030-315005314)	Jan-24
Ref. Probe EUmmWV3	SN: 9374	22-May-23 (No. EUmm-9374_May23)	May-24
DAE4ip	SN: 1662	13-Feb-23 (No. DAE4ip-1662_Feb23)	Feb-24

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Generator APSIN26G	SN: 669	28-Mar-17 (in house check May-23)	In house check: May-24
Generator Agilent E8251A	SN: US41140111	28-Mar-17 (in house check May-23)	In house check: May-24

	Name	Function	Signature
Calibrated by	Jeton Kastrati	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: July 04, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of
 Schmid & Partner
 Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (BAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

NORM_{x,y}	sensitivity in free space
DCP	diode compression point
CF	crest factor (1/full_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement position), i.e. $\theta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system
Sensor Angles	sensor deviation from the probe axis, used to calculate the field orientation and polarization
k	is the wave propagation direction

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1309-2005, "IEEE Standard for Calibration of Electromagnetic Field Sensors and Probes, excluding Antennas, from 9 kHz to 40 GHz", December 2005

Methods Applied and Interpretation of Parameters:

- **NORM_{x,y}**: Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). For frequencies > 6 GHz, the far field in front of waveguide horn antennas is measured for a set of frequencies in various waveguide bands up to 110 GHz.
- **DCP_{x,y}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
 Note: As the field is measured with a diode detector sensor, it is warranted that the probe response is linear (E^2) below the documented lowest calibrated value.
- **PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- The frequency sensor model parameters are determined prior to calibration based on a frequency sweep (sensor model involving resistors R, R_{in} , inductance L and capacitors C, C_0).
- **A_{x,y}, B_{x,y}, C_{x,y}, D_{x,y}, V_{fix,y}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- **Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerances required.
- **Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).
- **Equivalent Sensor Angle**: The two probe sensors are mounted in the same plane at different angles. The angles are assessed using the information gained by determining the NORM_x (no uncertainty required).
- **Spherical isotropy (3D deviation from isotropy)**: in a locally homogeneous field realized using an open waveguide / horn setup.

EUmmWV4 - SN:9489

June 20, 2023

Parameters of Probe: EUmmWV4 - SN:9489

Basic Calibration Parameters

	Sensor X	Sensor Y	Unc (k=2)
Norm ($\mu W/(V/m)^2$)	0.02177	0.02395	-10.1%
DCP (mV) [§]	105.0	101.5	±4.7%
Equivalent Sensor Angle	-61.5	36.4	

Calibration Results for Frequency Response (750 MHz – 110 GHz)

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc (k=2) dB
0.75	77.2	-0.03	-0.11	±0.43
1.0	140.4	-0.01	-0.02	+0.43
2.0	133.0	0.12	0.16	±0.43
2.2	124.8	0.07	-0.05	±0.43
2.5	123.0	0.07	0.10	±0.43
3.5	256.2	-0.23	-0.24	±0.43
3.7	249.8	-0.04	0.07	±0.43
5.6	74.7	-0.07	-0.29	-0.98
8.0	87.2	-0.10	-0.16	±0.98
10.0	66.2	0.01	-0.04	-0.98
15.0	51.2	0.13	0.19	±0.98
25.6	112.6	0.18	0.19	±0.98
30.0	121.9	0.01	-0.00	-0.98
35.0	121.3	-0.14	0.16	±0.98
40.0	102.3	-0.24	-0.25	±0.98
50.0	81.5	0.06	0.02	±0.98
55.0	75.9	0.04	0.04	-0.98
60.0	80.5	-0.01	-0.00	±0.98
65.0	77.1	0.07	0.05	+0.98
70.0	74.3	0.09	0.07	±0.98
75.0	74.8	0.01	0.00	±0.98
75.0	96.6	0.01	0.01	±0.98
80.0	95.4	-0.11	-0.07	+0.98
85.0	58.0	-0.03	0.06	±0.98
90.0	84.0	0.00	0.01	±0.98
92.0	83.9	0.04	0.00	+0.98
95.0	76.2	0.01	-0.03	±0.98
97.0	69.1	0.02	-0.01	±0.98
100.0	66.8	0.06	0.10	±0.98
105.0	67.2	-0.23	-0.14	±0.98
110.0	78.1	0.14	0.06	+0.98

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

§ Uncertainty parameter uncertainty for maximum specification strength.

EUMmWV4 - SN:9489

June 20, 2023

Parameters of Probe: EUMmWV4 - SN:9489

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB/√PV	C	D dB	VR mV	Max dev.	Max Unc ^E k = 2
0	CW	X	0.00	0.00	1.00	0.00	135.4	-2.7%	
		Y	0.00	0.00	1.00		71.4		±4.7%
10352	Pulse Waveform (200Hz, 10%)	X	1.99	60.00	14.26	0.00	6.0	±1.4%	±9.6%
		Y	1.54	60.00	15.59		6.0		
10353	Pulse Waveform (200Hz, 20%)	X	1.38	60.00	13.06	5.99	12.0	+0.6%	±9.6%
		Y	1.29	60.00	14.52		12.0		
10354	Pulse Waveform (200Hz, 40%)	X	0.83	60.00	11.72	5.98	23.0	+1.9%	±9.6%
		Y	0.70	60.00	13.17		23.0		
10355	Pulse Waveform (200Hz, 60%)	X	0.50	60.00	10.91	2.22	27.0	+1.0%	±9.6%
		Y	0.54	60.00	11.64		27.0		
10387	QPSK Waveform, 1 MHz	X	1.09	60.00	11.48	1.00	22.0	±1.7%	±9.6%
		Y	1.27	60.00	11.40		22.0		
10388	QPSK Waveform, 10 MHz	X	1.29	60.00	11.50	0.00	22.0	+1.0%	±9.6%
		Y	1.56	60.00	11.41		22.0		
10396	64-QAM Waveform, 100 kHz	X	2.26	62.22	14.72	3.01	17.0	+0.6%	±9.6%
		Y	2.52	63.25	15.36		17.0		
10399	64-QAM Waveform, 40 MHz	X	2.13	60.00	12.14	0.00	19.0	±1.1%	±9.6%
		Y	2.36	60.00	12.07		19.0		
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.24	60.00	12.61	0.00	12.0	±0.7%	±9.6%
		Y	3.53	60.00	12.52		12.0		

Note: For details on UID parameters see Appendix

^E Uncertainty is determined using the max. deviation from IEEE resource data (no rectangular distribution) and is expressed for the square of the field (e.g.)

EUmmWV4 - SN:9489

June 20, 2023

Parameters of Probe: EUmmWV4 - SN:9489

Calibration Results for Linearity Response

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc (k=2) dB
0.9	50.0	0.03	0.10	±0.2
0.9	100.0	-0.00	0.04	±0.2
0.9	500.0	0.03	0.00	±0.2
0.9	1000.0	0.05	0.03	±0.2
0.9	1500.0	0.04	0.04	±0.2
0.9	2100.0	-0.00	0.03	±0.2

Sensor Frequency Model Parameters (750 MHz – 55 GHz)

	Sensor X	Sensor Y
R (Ω)	95.68	101.74
R ₀ (Ω)	97.62	156.81
L (nH)	0.06289	0.09756
C (pF)	0.2020	0.1761
C ₀ (pF)	0.0551	0.0556

Sensor Frequency Model Parameters (55 GHz – 110 GHz)

	Sensor X	Sensor Y
R (Ω)	39.65	21.00
R ₀ (Ω)	174.53	88.38
L (nH)	0.07975	0.04077
C (pF)	0.2591	0.1202
C ₀ (pF)	0.0658	0.1235

Sensor Model Parameters


	C1 fF	C2 fF	α V ⁻¹	T1 ms V ⁻²	T2 ms V ⁻¹	T3 ms	T4 V ⁻²	T5 V ⁻¹	T6
x	38.5	250.73	33.79	0.92	4.03	6.01	0.00	1.03	1.01
y	57.4	270.39	33.38	0.92	3.18	6.04	0.00	1.25	1.01

Other Probe Parameters

Sensor Arrangement	Rectangular
Connector Angle	144.0°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	320 mm
Probe Body Diameter	8 mm
Tip Length	23 mm
Tip Diameter	8.0 mm
Probe Tip to Sensor X Calibration Point	1.5 mm
Probe Tip to Sensor Y Calibration Point	1.5 mm

EUMmWV4 - SN:9489

June 20, 2023



Probe isotropy for E_{201} : probe rotated $\omega = 0^\circ$ to 360° , filled from field propagation direction \bar{x}
 Parallel to the field propagation ($\psi = 0^\circ - 90^\circ$) at 30 GHz: deviation within ± 0.32 dB
 Parallel to the field propagation ($\psi = 0^\circ - 90^\circ$) at 80 GHz: deviation within ± 0.43 dB

EUmmWV4 - SN:9489

June 20, 2023

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ¹ k - 2
10010	CAB	SAN Multicast (Square, 100ms, 10ms)	ISW	0.00	+4.7
10011	CAC	JMTC-FDD (WCDMA)	ISW	0.00	+9.6
10012	CAD	IEEE 802.11b WiFi 2.4GHz (DSSS, 1Mbps)	WLAN	1.87	+9.6
10013	CAD	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 8Mbps)	WLAN	5.46	+9.6
10021	DAC	GSM FDD (TDMA, GMSK)	GSM	5.55	+9.6
10023	DAC	GPRS FDD (TDMA, GMSK, TN 0)	GSM	5.57	+9.6
10024	DAC	GPRS FDD (TDMA, GMSK, TN 0-1)	GSM	5.56	+9.6
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.65	+9.6
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	5.55	+9.6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0 - 2)	GSM	4.80	+9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0 - 2-3)	GSM	3.00	+9.6
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0 - 2)	GSM	7.78	+9.6
10030	CAA	IEEE 802.10 Bluetooth (GFSK, DH1)	Bluetooth	5.80	+9.6
10031	CAA	IEEE 802.10 Bluetooth (GFSK, DH3)	Bluetooth	1.87	+9.6
10032	CAA	IEEE 802.15 Bluetooth (GFSK, DHS)	Bluetooth	1.76	+9.6
10033	CAA	IEEE 802.15 Bluetooth (FM-DQPSK, DH1)	Bluetooth	7.74	+9.6
10034	CAA	IEEE 802.15 Bluetooth (FM-DQPSK, DHS)	Bluetooth	4.80	+9.6
10035	CAA	IEEE 802.15 Bluetooth (FM-DQPSK, DHS)	Bluetooth	3.80	+9.6
10036	CAA	IEEE 802.15 Bluetooth (DPSK, DH1)	Bluetooth	3.01	+9.6
10037	CAA	IEEE 802.15 Bluetooth (DPSK, DHS)	Bluetooth	4.77	+9.6
10038	CAA	IEEE 802.15 Bluetooth (DPSK, DHS)	Bluetooth	4.10	+9.6
10039	CAD	CDMA2000 (1XRTT, R01)	CDMA2000	4.57	+9.6
10042	CAB	IS 34/38 IS6 FDD (TDM/FDM, FM-DQPSK, Full Rate)	AMPS	7.78	+9.6
10044	CAA	IS 95/A-TIA 808 FDD (FDMA, FM)	AMPS	0.00	+9.6
10045	CAA	DECT (TDD, TDM/FDM, GFSK, Full Set, 24)	DECT	10.80	+9.6
10049	CAA	DECT (TDD, TDM/FDM, GFSK, Double Set, 12)	DECT	10.78	+9.6
10058	CAA	UMTS-FDD (TD-SCDMA, 1.28 Mbps)	TD-SCDMA	11.01	+9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0 - 2)	GSM	0.00	+9.6
10059	CAB	IEEE 802.11b WiFi 2.4GHz (DSSS, 2Mbps)	WLAN	2.12	+9.6
10060	CAB	IEEE 802.11b WiFi 2.4GHz (DSSS, 5.5Mbps)	WLAN	2.88	+9.6
10061	CAB	IEEE 802.11b WiFi 2.4GHz (DSSS, 11Mbps)	WLAN	3.60	+9.6
10062	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 3Mbps)	WLAN	3.88	+9.6
10063	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 6Mbps)	WLAN	3.83	+9.6
10064	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 12Mbps)	WLAN	3.09	+9.6
10065	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 18Mbps)	WLAN	3.99	+9.6
10066	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 24Mbps)	WLAN	3.38	+9.6
10067	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 36Mbps)	WLAN	10.12	+9.6
10068	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 48Mbps)	WLAN	10.24	+9.6
10069	CAD	IEEE 802.11a WiFi 5GHz (OFDM, 54Mbps)	WLAN	10.59	+9.6
10071	CAB	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 9Mbps)	WLAN	3.83	+9.6
10072	CAB	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 12Mbps)	WLAN	3.82	+9.6
10073	CAB	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 18Mbps)	WLAN	3.90	+9.6
10074	CAB	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 24Mbps)	WLAN	10.00	+9.6
10075	CAB	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 36Mbps)	WLAN	10.77	+9.6
10076	CAB	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 48Mbps)	WLAN	10.84	+9.6
10077	CAD	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 54Mbps)	WLAN	11.00	+9.6
10081	CAB	CDMA2000 (1XRTT, R02)	CDMA2000	3.97	+9.6
10082	CAB	IS 54/58 IS6 FDD (TDM/FDM, FM-DQPSK, Full Rate)	AMPS	0.77	+9.6
10083	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	5.55	+9.6
10087	CAC	UMTS-FDD (IS-DPA)	WCDMA	3.98	+9.6
10088	CAC	UMTS-FDD (IS-DPA, Subtest 2)	WCDMA	3.98	+9.6
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	+9.6
10100	CA-	LTE-FDD (SC-FDMA, 100% RB, 20MHz, QPSK)	LTE-FDD	5.87	+9.6
10101	CA-	LTE-FDD (SC-FDMA, 100% RB, 20MHz, 16-QAM)	LTE-FDD	6.12	+9.6
10102	CA-	LTE-FDD (SC-FDMA, 100% RB, 20MHz, 64-QAM)	LTE-FDD	6.80	+9.6
10103	CA-F	LTE-TDD (SC-FDMA, 100% RB, 20MHz, QPSK)	LTE-TDD	9.28	+9.6
10104	CA-F	LTE-TDD (SC-FDMA, 100% RB, 20MHz, 16-QAM)	LTE-TDD	9.97	+9.6
10105	CA-F	LTE-TDD (SC-FDMA, 100% RB, 20MHz, 64-QAM)	LTE-TDD	10.01	+9.6
10109	CA-F	LTE-FDD (SC-FDMA, 100% RB, 10MHz, QPSK)	LTE-FDD	5.80	+9.6
10109	CA-F	LTE-FDD (SC-FDMA, 100% RB, 10MHz, 16-QAM)	LTE-FDD	6.10	+9.6
10110	CA-F	LTE-FDD (SC-FDMA, 100% RB, 5MHz, QPSK)	LTE-FDD	5.75	+9.6
10111	CA-F	LTE-FDD (SC-FDMA, 100% RB, 5MHz, 16-QAM)	LTE-FDD	6.44	+9.6

EUmmWV4 - SN:9469

June 20, 2023

UID	Rev	Communication System Name	Group	RAI(dB)	UncF k -2
10112	CAH	LTE-FDD (SC-FDMA, 100% RB, 10MHz, 64-QAM)	LTE-FDD	6.28	-9.9
10113	CAH	LTE-FDD (SC-FDMA, 100% RB, 5MHz, 64-QAM)	LTE-FDD	6.09	-9.9
10114	CAD	IEEE 802.11n (HT Greenfield, 13.5Mbps, BPSK)	WLAN	8.0	-3.9
10115	CAD	IEEE 802.11n (HT Greenfield, 31Mbps, 16-QAM)	WLAN	8.46	-3.9
10119	CAD	IEEE 802.11n (HT Greenfield, 135Mbps, 64-QAM)	WLAN	8.5	-3.9
10117	CAD	IEEE 802.11n (HT Mixed, 13.5Mbps, BPSK)	WLAN	8.07	-3.9
10118	CAD	IEEE 802.11n (HT Mixed, 31Mbps, 16-QAM)	WLAN	8.59	-3.9
10119	CAD	IEEE 802.11n (HT Mixed, 135Mbps, 64-QAM)	WLAN	8.19	-3.9
10140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15MHz, 16-QAM)	LTE-FDD	6.36	-9.9
10141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15MHz, 64-QAM)	LTE-FDD	6.88	-9.9
10142	CAF	LTE-FDD (SC-FDMA, 100% RB, 3MHz, QPSK)	LTE-FDD	5.79	-9.9
10143	CAF	LTE-FDD (SC-FDMA, 100% RB, 3MHz, 16-QAM)	LTE-FDD	6.35	-9.9
10144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3MHz, 64-QAM)	LTE-FDD	6.65	-9.9
10145	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4MHz, QPSK)	LTE-FDD	5.70	-9.9
10146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4MHz, 16-QAM)	LTE-FDD	6.47	-9.9
10147	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4MHz, 64-QAM)	LTE-FDD	6.72	-9.9
10149	CAF	LTE-FDD (SC-FDMA, 50% RB, 20MHz, 16-QAM)	LTE-FDD	6.42	-9.9
10150	CAF	LTE-FDD (SC-FDMA, 50% RB, 20MHz, 64-QAM)	LTE-FDD	6.60	-9.9
10151	CAF	LTE-FDD (SC-FDMA, 50% RB, 20MHz, QPSK)	LTE-FDD	6.28	-9.9
10152	CAH	LTE-TDD (SC-FDMA, 50% RB, 20MHz, 16-QAM)	LTE-TDD	6.50	-9.9
10153	CAH	LTE-TDD (SC-FDMA, 50% RB, 20MHz, 64-QAM)	LTE-TDD	11.05	-9.9
10154	CAH	LTE-FDD (SC-FDMA, 50% RB, 10MHz, QPSK)	LTE-FDD	5.73	-9.9
10155	CAH	LTE-FDD (SC-FDMA, 50% RB, 10MHz, 16-QAM)	LTE-FDD	6.43	-9.9
10156	CAH	LTE-FDD (SC-FDMA, 50% RB, 5MHz, QPSK)	LTE-FDD	5.79	-9.9
10157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5MHz, 16-QAM)	LTE-FDD	5.49	-9.9
10158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10MHz, 64-QAM)	LTE-FDD	6.62	-9.9
10159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5MHz, 64-QAM)	LTE-FDD	5.65	-9.9
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, QPSK)	LTE-FDD	5.82	-9.9
10161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, 16-QAM)	LTE-FDD	6.43	-9.9
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15MHz, 64-QAM)	LTE-FDD	6.59	-9.9
10163	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4MHz, QPSK)	LTE-FDD	5.72	-9.9
10164	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4MHz, 16-QAM)	LTE-FDD	6.21	-9.9
10165	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4MHz, 64-QAM)	LTE-FDD	6.79	-9.9
10166	CAF	LTE-FDD (SC-FDMA, 1 RB, 20MHz, 16-QAM)	LTE-FDD	5.73	-9.9
10167	CAF	LTE-FDD (SC-FDMA, 1 RB, 20MHz, 64-QAM)	LTE-FDD	6.02	-9.9
10168	CAF	LTE-FDD (SC-FDMA, 1 RB, 20MHz, QPSK)	LTE-FDD	5.40	-9.9
10169	CAH	LTE-TDD (SC-FDMA, 1 RB, 20MHz, QPSK)	LTE-TDD	3.21	-9.9
10170	CAH	LTE-TDD (SC-FDMA, 1 RB, 20MHz, 16-QAM)	LTE-TDD	3.48	-9.9
10171	CAH	LTE-TDD (SC-FDMA, 1 RB, 20MHz, 64-QAM)	LTE-TDD	13.05	-9.9
10172	CAF	LTE-FDD (SC-FDMA, 1 RB, 10MHz, QPSK)	LTE-FDD	5.72	-9.9
10173	CAF	LTE-FDD (SC-FDMA, 1 RB, 10MHz, 16-QAM)	LTE-FDD	6.52	-9.9
10174	CAF	LTE-FDD (SC-FDMA, 1 RB, 10MHz, 64-QAM)	LTE-FDD	6.52	-9.9
10175	CAF	LTE-FDD (SC-FDMA, 1 RB, 5MHz, QPSK)	LTE-FDD	5.71	-9.9
10176	CAF	LTE-FDD (SC-FDMA, 1 RB, 5MHz, 16-QAM)	LTE-FDD	5.92	-9.9
10177	CAF	LTE-FDD (SC-FDMA, 1 RB, 5MHz, 64-QAM)	LTE-FDD	6.52	-9.9
10178	CAH	LTE-FDD (SC-FDMA, 1 RB, 5MHz, QPSK)	LTE-FDD	5.73	-9.9
10179	CAH	LTE-FDD (SC-FDMA, 1 RB, 5MHz, 16-QAM)	LTE-FDD	6.01	-9.9
10180	CAH	LTE-FDD (SC-FDMA, 1 RB, 5MHz, 64-QAM)	LTE-FDD	6.60	-9.9
10181	CAF	LTE-FDD (SC-FDMA, 1 RB, 15MHz, QPSK)	LTE-FDD	5.78	-9.9
10182	CAF	LTE-FDD (SC-FDMA, 1 RB, 15MHz, 16-QAM)	LTE-FDD	6.59	-9.9
10183	CAF	LTE-FDD (SC-FDMA, 1 RB, 15MHz, 64-QAM)	LTE-FDD	6.59	-9.9
10184	CAD	IEEE 802.11n (HT Greenfield, 6.5Mbps, BPSK)	WLAN	8.09	-9.9
10185	CAD	IEEE 802.11n (HT Greenfield, 13.5Mbps, 16-QAM)	WLAN	8.12	-9.9
10186	CAD	IEEE 802.11n (HT Greenfield, 31Mbps, 64-QAM)	WLAN	8.2	-9.9
10187	CAD	IEEE 802.11n (HT Mixed, 6.5Mbps, BPSK)	WLAN	8.10	-9.9
10188	CAD	IEEE 802.11n (HT Mixed, 13.5Mbps, 16-QAM)	WLAN	8.13	-9.9
10189	CAD	IEEE 802.11n (HT Mixed, 31Mbps, 64-QAM)	WLAN	8.27	-9.9
10190	CAD	IEEE 802.11n (HT Mixed, 135Mbps, BPSK)	WLAN	8.03	-9.9
10191	CAD	IEEE 802.11n (HT Mixed, 135Mbps, 16-QAM)	WLAN	8.12	-9.9
10192	CAD	IEEE 802.11n (HT Mixed, 135Mbps, 64-QAM)	WLAN	8.27	-9.9
10193	CAD	IEEE 802.11n (HT Mixed, 135Mbps, BPSK)	WLAN	8.08	-9.9
10194	CAD	IEEE 802.11n (HT Mixed, 135Mbps, 16-QAM)	WLAN	8.48	-9.9
10195	CAD	IEEE 802.11n (HT Mixed, 135Mbps, 64-QAM)	WLAN	8.08	-9.9

Certificate No: EUmm-9488 Jun23

Page 8 of 13

EUmmWV4 - SN 9499

June 20, 2023

UID	Rev	Communication System Name	Group	PAR [dB]	Unc ² k = 2
10225	CAC	UMTS-FDD (HSPA+)	WCDMA	5.37	-58.0
10226	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.43	-58.0
10227	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.28	-58.0
10228	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	3.22	-58.0
10229	CAB	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.18	-58.0
10230	CAB	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	13.25	-58.0
10231	CAB	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	3.19	-58.0
10232	CAH	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.43	-58.0
10233	CAH	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	13.25	-58.0
10234	CAH	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	3.21	-58.0
10235	CAH	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.48	-58.0
10236	CAH	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	13.25	-58.0
10237	CAH	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	3.21	-58.0
10238	CAG	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.48	-58.0
10239	CAG	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	13.25	-58.0
10240	CAG	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	3.21	-58.0
10241	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	3.82	-58.0
10242	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	8.80	-58.0
10243	CAC	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	3.45	-58.0
10244	CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.05	-58.0
10245	CAB	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.05	-58.0
10246	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	3.30	-58.0
10247	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	3.91	-58.0
10248	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.09	-58.0
10249	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	3.29	-58.0
10250	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	3.31	-58.0
10251	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.17	-58.0
10252	CAH	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	3.24	-58.0
10253	CAG	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	3.90	-58.0
10254	CAG	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.14	-58.0
10255	CAG	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	3.20	-58.0
10256	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.98	-58.0
10257	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	-58.0
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	3.31	-58.0
10259	CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	3.99	-58.0
10260	CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	-58.0
10261	CAB	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	3.24	-58.0
10262	CAH	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	3.88	-58.0
10263	CAH	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	10.18	-58.0
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	3.25	-58.0
10265	CAB	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	3.92	-58.0
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.07	-58.0
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	3.30	-58.0
10268	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	10.06	-58.0
10269	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.18	-58.0
10270	CAB	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	3.58	-58.0
10271	CAC	UMTS-FDD (HSPA, Subtest 5, 3GPP Rel. 10)	WCDMA	4.87	-58.0
10272	CAC	UMTS-FDD (HSPA, Subtest 5, 3GPP Rel. 10)	WCDMA	5.96	-58.0
10273	CAA	PHS (QPSK)	PHS	11.81	-58.0
10274	CAA	PHS (QPSK, BW 884MHz, RollOff 0.5)	PHS	11.81	-58.0
10275	CAA	PHS (QPSK, BW 884MHz, RollOff 0.39)	PHS	12.18	-58.0
10280	AA4	CDMA2000, RC3, SCSS, Full Rate	CDMA2000	3.91	-58.0
10281	AA4	CDMA2000, RC3, SCSS, Full Rate	CDMA2000	3.48	-58.0
10282	AA4	CDMA2000, RC3, SCSS, Full Rate	CDMA2000	3.30	-58.0
10283	AA4	CDMA2000, RC3, SCSS, Full Rate	CDMA2000	3.50	-58.0
10284	AA4	CDMA2000, RC3, SCSS, Full Rate	CDMA2000	12.49	-58.0
10287	AA4	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	3.81	-58.0
10288	AA4	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	3.72	-58.0
10289	AA4	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.90	-58.0
10800	AA4	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	8.80	-58.0
10801	AAA	IEEE 802.16e WMAX (20-18, 5-ns, 10MHz, QPSK, PUSC)	WMAX	12.03	-58.0
10802	AAA	IEEE 802.16e WMAX (20-18, 5-ns, 10MHz, QPSK, PUSC, J-CTRL symbol)	WMAX	12.07	-58.0
10803	AAA	IEEE 802.16e WMAX (20-18, 5-ns, 10MHz, 64QAM, PUSC)	WMAX	12.32	-58.0
10804	AAA	IEEE 802.16e WMAX (20-18, 5-ns, 10MHz, 64QAM, PUSC)	WMAX	11.88	-58.0
10805	AAA	IEEE 802.16e WMAX (20-18, 5-ns, 10MHz, 64QAM, PUSC, 15 symbol)	WMAX	15.24	-58.0
10806	AAA	IEEE 802.16e WMAX (20-18, 5-ns, 10MHz, 64QAM, PUSC, 15 symbol)	WMAX	14.67	-58.0

EUmmWV4 - SN:9489

June 26, 2023

UID	Rev	Communication System Name	Group	PAR (dB)	$U_{\text{eq}}^2 \text{ @ } z$
10307	AAA	IEEE 802.11e WLAN (20MHz, 10ms, 10MHz, QPSK, PUSC, 16 symbols)	WLAN	14.43	-45.0
10308	AAA	IEEE 802.11e WLAN (20MHz, 10ms, 10MHz, 16QAM, PUSC)	WLAN	14.48	-45.0
10309	AAA	IEEE 802.11e WLAN (20MHz, 10ms, 10MHz, 16QAM, AMC 2cs, 16 symbols)	WLAN	14.59	-45.0
10310	AAA	IEEE 802.11e WLAN (20MHz, 10ms, 10MHz, QPSK, AMC 2cs, 16 symbols)	WLAN	14.57	-45.0
10311	AAC	LTE FDD (SC-FDMA, 10MHz, 10MHz, OFDM)	LTE FDD	8.33	-45.6
10312	AAA	IDEN 1.8	IDEN	13.51	-45.6
10313	AAA	IDEN 1.8	IDEN	13.59	-45.6
10314	AAA	IDEN 1.8	IDEN	13.59	-45.6
10315	AAE	IEEE 802.11n WiFi 2.4GHz (DSSS, 6Mbps, 80ps duty cycle)	WLAN	1.71	-45.6
10316	AAE	IEEE 802.11n WiFi 2.4GHz (ERP OFDM, 6Mbps, 80ps duty cycle)	WLAN	8.35	-45.6
10317	AAE	IEEE 802.11n WiFi 2.4GHz (OFDM, 6Mbps, 80ps duty cycle)	WLAN	8.35	-45.6
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	-48.8
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	8.00	-48.8
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.00	-48.8
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.00	-48.8
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	1.00	-48.8
10392	AAA	QPSK Waveform, 1MHz	Generic	5.10	-49.8
10393	AAA	QPSK Waveform, 10MHz	Generic	5.22	-49.8
10394	AAA	64-QAM Waveform, 100kHz	Generic	0.21	-49.8
10395	AAA	64-QAM Waveform, 40MHz	Generic	0.21	-49.8
10400	AAF	IEEE 802.11ac WiFi (80MHz, 64-QAM, 80ps duty cycle)	WLAN	8.67	-49.8
10401	AAF	IEEE 802.11ac WiFi (80MHz, 64-QAM, 80ps duty cycle)	WLAN	8.60	-49.8
10402	AAF	IEEE 802.11ac WiFi (80MHz, 64-QAM, 80ps duty cycle)	WLAN	8.58	-49.8
10403	AAB	CDMA2000 1X-EV-DO, Rev. A)	CDMA2000	5.76	-49.8
10404	AAB	CDMA2000 1X-EV-DO, Rev. A)	CDMA2000	5.77	-49.8
10405	AAB	CDMA2000 1X-EV-DO, Rev. A)	CDMA2000	5.72	-49.8
10410	AAH	LTE TDD (SC-FDMA, 1RB, 10MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Cont=4)	LTE TDD	7.82	-49.8
10411	AAH	WLAN SCDF 64-QAM, 40MHz	Generic	6.54	-49.8
10412	AAA	IEEE 802.11e WiFi 2.4GHz (DSSS, 1Mbps, 80ps duty cycle)	WLAN	1.54	-49.8
10413	AAA	IEEE 802.11g WiFi 2.4GHz (ERP OFDM, 6Mbps, 80ps duty cycle)	WLAN	8.28	-49.8
10414	AAC	IEEE 802.11g WiFi 2.4GHz (OFDM, 6Mbps, 80ps duty cycle)	WLAN	8.28	-49.8
10415	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 6Mbps, 80ps duty cycle, Long preamble)	WLAN	8.14	-49.8
10416	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-OFDM, 6Mbps, 80ps duty cycle, Short preamble)	WLAN	8.15	-49.8
10422	AAC	IEEE 802.11n (HT Greenfield), 7.2Mbps, 80ps)	WLAN	8.52	-49.8
10423	AAC	IEEE 802.11n (HT Greenfield), 15.2Mbps, 16-QAM)	WLAN	8.17	-49.8
10424	AAC	IEEE 802.11n (HT Greenfield), 15.2Mbps, 64-QAM)	WLAN	8.10	-49.8
10425	AAC	IEEE 802.11n (HT Greenfield), 15Mbps, 80ps)	WLAN	8.41	-49.8
10426	AAC	IEEE 802.11n (HT Greenfield), 30Mbps, 16-QAM)	WLAN	8.46	-49.8
10427	AAC	IEEE 802.11n (HT Greenfield), 15Mbps, 64-QAM)	WLAN	8.41	-49.8
10430	AAF	LTE-FDD (OFDMA, 5MHz, E-TM 3.1)	LTE-FDD	8.58	-49.8
10431	AAC	LTE-FDD (OFDMA, 10MHz, E-TM 3.1)	LTE-FDD	8.58	-49.8
10432	AAD	LTE-FDD (OFDMA, 15MHz, E-TM 3.1)	LTE-FDD	8.54	-49.8
10433	AAD	LTE-FDD (OFDMA, 20MHz, E-TM 3.1)	LTE-FDD	8.34	-49.8
10434	AAE	WCDMA (R5 Test Model) T1-C4 (FDD)	WCDMA	8.80	-49.8
10435	AAE	LTE-TDD (SC-FDMA, 1RB, 10MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.92	-49.8
10447	AAF	LTE-FDD (OFDMA, 5MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.59	-49.8
10448	AAF	LTE-FDD (OFDMA, 10MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.59	-49.8
10449	AAD	LTE-FDD (OFDMA, 15MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	-49.8
10450	AAD	LTE-FDD (OFDMA, 20MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	-49.8
10451	AAE	WCDMA (R5 Test Model) T1-C4 (FDD)	WCDMA	7.59	-49.8
10452	AAE	Waveform (Square, 10ms, 1ms)	3G	10.00	-49.8
10456	AAC	IEEE 802.11ac WiFi (160MHz, 64-QAM, 80ps duty cycle)	WLAN	8.83	-49.8
10457	AAF	UMTS-FDD (DC-HSDPA)	WCDMA	8.62	-49.8
10458	AAA	CDMA2000 1X-EV-DO, Rev. B, 3 carriers)	CDMA2000	8.55	-49.8
10459	AAA	CDMA2000 1X-EV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	-49.8
10460	AAH	UMTS FDD (WCDMA, AMR)	WCDMA	7.39	-49.8
10461	AAC	LTE-TDD (SC-FDMA, 1RB, 1.4MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.92	-49.8
10462	AAC	LTE-TDD (SC-FDMA, 1RB, 1.4MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.20	-49.8
10463	AAC	LTE-TDD (SC-FDMA, 1RB, 1.4MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.50	-49.8
10464	AAC	LTE-TDD (SC-FDMA, 1RB, 3MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	-49.8
10465	AAC	LTE-TDD (SC-FDMA, 1RB, 3MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	-49.8
10466	AAD	LTE-TDD (SC-FDMA, 1RB, 3MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	-49.8
10467	AAE	LTE-TDD (SC-FDMA, 1RB, 5MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.92	-49.8
10468	AAE	LTE-TDD (SC-FDMA, 1RB, 5MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	-49.8
10469	AAC	LTE-TDD (SC-FDMA, 1RB, 5MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	-49.8
10470	AAC	LTE-TDD (SC-FDMA, 1RB, 10MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	-49.8
10471	AAE	LTE-TDD (SC-FDMA, 1RB, 10MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	-49.8

FUMmWV4 - SN:3488

June 20, 2023

UID	REV	Communication System Name	Group	PAF (dB)	Line # - 2
10472	AAJ	LTE-TDD (SC-FDMA) 7 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.57	-29.8
10473	AAJ	LTE-TDD (SC-FDMA) 7 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.82	-29.8
10474	AAJ	LTE-TDD (SC-FDMA) 7 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.82	-29.8
10475	AAJ	LTE-TDD (SC-FDMA) 7 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.87	-29.8
10476	AAJ	LTE-TDD (SC-FDMA) 7 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.32	-29.8
10478	AAJ	LTE-TDD (SC-FDMA) 7 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.57	-29.8
10479	AAJ	LTE-TDD (SC-FDMA) 80% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.74	-29.8
10480	AAJ	LTE-TDD (SC-FDMA) 80% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.16	-29.8
10481	AAJ	LTE-TDD (SC-FDMA) 80% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	9.26	-29.8
10482	AAJ	LTE-TDD (SC-FDMA) 80% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.71	-29.8
10483	AAJ	LTE-TDD (SC-FDMA) 80% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.38	-29.8
10484	AAJ	LTE-TDD (SC-FDMA) 80% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.47	-29.8
10485	AAJ	LTE-TDD (SC-FDMA) 80% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.99	-29.8
10486	AAJ	LTE-TDD (SC-FDMA) 80% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.33	-29.8
10487	AAJ	LTE-TDD (SC-FDMA) 80% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.80	-29.8
10488	AAJ	LTE-TDD (SC-FDMA) 80% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.79	-29.8
10489	AAJ	LTE-TDD (SC-FDMA) 80% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.31	-29.8
10490	AAJ	LTE-TDD (SC-FDMA) 80% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.84	-29.8
10491	AAJ	LTE-TDD (SC-FDMA) 80% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.84	-29.8
10492	AAJ	LTE-TDD (SC-FDMA) 80% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	6.74	-29.8
10493	AAJ	LTE-TDD (SC-FDMA) 80% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.41	-29.8
10494	AAJ	LTE-TDD (SC-FDMA) 80% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.95	-29.8
10495	AAJ	LTE-TDD (SC-FDMA) 80% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.74	-29.8
10496	AAJ	LTE-TDD (SC-FDMA) 80% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.37	-29.8
10497	AAJ	LTE-TDD (SC-FDMA) 80% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.54	-29.8
10498	AAJ	LTE-TDD (SC-FDMA) 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.67	-29.8
10499	AAJ	LTE-TDD (SC-FDMA) 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.46	-29.8
10500	AAJ	LTE-TDD (SC-FDMA) 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.84	-29.8
10501	AAJ	LTE-TDD (SC-FDMA) 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.07	-29.8
10502	AAJ	LTE-TDD (SC-FDMA) 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.44	-29.8
10503	AAJ	LTE-TDD (SC-FDMA) 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.82	-29.8
10504	AAJ	LTE-TDD (SC-FDMA) 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.72	-29.8
10505	AAJ	LTE-TDD (SC-FDMA) 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.37	-29.8
10506	AAJ	LTE-TDD (SC-FDMA) 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.54	-29.8
10507	AAJ	LTE-TDD (SC-FDMA) 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.74	-29.8
10508	AAJ	LTE-TDD (SC-FDMA) 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.35	-29.8
10509	AAJ	LTE-TDD (SC-FDMA) 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.93	-29.8
10510	AAJ	LTE-TDD (SC-FDMA) 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.07	-29.8
10511	AAJ	LTE-TDD (SC-FDMA) 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.44	-29.8
10512	AAJ	LTE-TDD (SC-FDMA) 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.82	-29.8
10513	AAJ	LTE-TDD (SC-FDMA) 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9	LTE-TDD	7.74	-29.8
10514	AAJ	LTE-TDD (SC-FDMA) 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.37	-29.8
10515	AAJ	LTE-TDD (SC-FDMA) 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9	LTE-TDD	8.95	-29.8
10516	AAA	IEEE 802.11b WiFi (2.4 GHz, DSSS, 2Mbps, 99% duty cycle)	WLAN	7.59	-29.8
10517	AAA	IEEE 802.11b WiFi (2.4 GHz, DSSS, 5.5Mbps, 99% duty cycle)	WLAN	7.67	-29.8
10518	AAA	IEEE 802.11b WiFi (2.4 GHz, DSSS, 11Mbps, 99% duty cycle)	WLAN	7.87	-29.8
10519	AAA	IEEE 802.11g WiFi (2.4 GHz, OFDM, 6Mbps, 99% duty cycle)	WLAN	8.39	-29.8
10520	AAA	IEEE 802.11g WiFi (2.4 GHz, OFDM, 12Mbps, 99% duty cycle)	WLAN	8.89	-29.8
10521	AAA	IEEE 802.11g WiFi (2.4 GHz, OFDM, 18Mbps, 99% duty cycle)	WLAN	8.97	-29.8
10522	AAA	IEEE 802.11n WiFi (5 GHz, OFDM, 30Mbps, 99% duty cycle)	WLAN	8.95	-29.8
10523	AAA	IEEE 802.11n WiFi (5 GHz, OFDM, 45Mbps, 99% duty cycle)	WLAN	9.16	-29.8
10524	AAA	IEEE 802.11n WiFi (5 GHz, OFDM, 60Mbps, 99% duty cycle)	WLAN	9.27	-29.8
10525	AAA	IEEE 802.11ac WiFi (20 MHz, MCS0, 99% duty cycle)	WLAN	8.86	-29.8
10526	AAA	IEEE 802.11ac WiFi (20 MHz, MCS1, 99% duty cycle)	WLAN	8.42	-29.8
10527	AAA	IEEE 802.11ac WiFi (20 MHz, MCS2, 99% duty cycle)	WLAN	8.27	-29.8
10528	AAA	IEEE 802.11ac WiFi (20 MHz, MCS3, 99% duty cycle)	WLAN	8.36	-29.8
10529	AAA	IEEE 802.11ac WiFi (20 MHz, MCS4, 99% duty cycle)	WLAN	8.48	-29.8
10530	AAA	IEEE 802.11ac WiFi (20 MHz, MCS5, 99% duty cycle)	WLAN	8.48	-29.8
10531	AAA	IEEE 802.11ac WiFi (20 MHz, MCS6, 99% duty cycle)	WLAN	8.29	-29.8
10532	AAA	IEEE 802.11ac WiFi (20 MHz, MCS7, 99% duty cycle)	WLAN	8.38	-29.8
10533	AAA	IEEE 802.11ac WiFi (40 MHz, MCS0, 99% duty cycle)	WLAN	8.45	-29.8
10534	AAA	IEEE 802.11ac WiFi (40 MHz, MCS1, 99% duty cycle)	WLAN	8.95	-29.8
10535	AAA	IEEE 802.11ac WiFi (40 MHz, MCS2, 99% duty cycle)	WLAN	9.32	-29.8
10536	AAA	IEEE 802.11ac WiFi (40 MHz, MCS3, 99% duty cycle)	WLAN	9.44	-29.8
10537	AAA	IEEE 802.11ac WiFi (40 MHz, MCS4, 99% duty cycle)	WLAN	8.54	-29.8
10538	AAA	IEEE 802.11ac WiFi (40 MHz, MCS5, 99% duty cycle)	WLAN	8.54	-29.8
10539	AAA	IEEE 802.11ac WiFi (40 MHz, MCS6, 99% duty cycle)	WLAN	8.39	-29.8

Certificate No: EUMmWV4-Jun23

Page 11 of 18

Eurofins KCTL Co.,Ltd.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-70-5008-1021 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR23-SPF0049-A
Page (97) of (131)



KCTL

EUMmWv4 - SN:9489

June 20, 2023

UID	Rev	Communication System Name	Group	FAR (dB)	MinE _g -3
10541	AAC	IEEE 802.11ac WiFi (40MHz, MCS7, 90pc duty cycle)	WLAN	8.48	-3.8
10542	AAC	IEEE 802.11ac WiFi (40MHz, MCS8, 90pc duty cycle)	WLAN	8.55	-3.8
10543	AAC	IEEE 802.11ac WiFi (40MHz, MCS9, 90pc duty cycle)	WLAN	8.63	-3.8
10544	AAC	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	WLAN	8.47	-3.8
10545	AAC	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	WLAN	8.55	-3.8
10546	AAC	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	WLAN	8.63	-3.8
10547	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	WLAN	8.49	-3.8
10548	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	WLAN	8.57	-3.8
10550	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	WLAN	8.65	-3.8
10551	AAC	IEEE 802.11ac WiFi (80MHz, MCS7, 90pc duty cycle)	WLAN	8.50	-3.8
10552	AAC	IEEE 802.11ac WiFi (80MHz, MCS8, 90pc duty cycle)	WLAN	8.58	-3.8
10553	AAC	IEEE 802.11ac WiFi (80MHz, MCS9, 90pc duty cycle)	WLAN	8.66	-3.8
10554	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	WLAN	8.48	-3.8
10555	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	WLAN	8.57	-3.8
10556	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	WLAN	8.65	-3.8
10557	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	WLAN	8.50	-3.8
10558	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	WLAN	8.58	-3.8
10559	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	WLAN	8.66	-3.8
10560	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	WLAN	8.50	-3.8
10561	AAC	IEEE 802.11ac WiFi (160MHz, MCS8, 90pc duty cycle)	WLAN	8.58	-3.8
10562	AAC	IEEE 802.11ac WiFi (160MHz, MCS9, 90pc duty cycle)	WLAN	8.66	-3.8
10563	AAC	IEEE 802.11ac WiFi (160MHz, MCS7, 90pc duty cycle)	WLAN	8.77	-3.8
10564	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 6Mbps, 90pc duty cycle)	WLAN	8.25	-3.8
10565	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 12Mbps, 90pc duty cycle)	WLAN	8.45	-3.8
10566	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 18Mbps, 90pc duty cycle)	WLAN	8.73	-3.8
10567	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 24Mbps, 90pc duty cycle)	WLAN	8.77	-3.8
10568	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 36Mbps, 90pc duty cycle)	WLAN	8.87	-3.8
10569	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 48Mbps, 90pc duty cycle)	WLAN	8.70	-3.8
10570	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 54Mbps, 90pc duty cycle)	WLAN	8.90	-3.8
10571	AAA	IEEE 802.11b WiFi 2.4GHz (DSSS, 1Mbps, 90pc duty cycle)	WLAN	1.99	-3.8
10572	AAA	IEEE 802.11b WiFi 2.4GHz (DSSS, 2Mbps, 90pc duty cycle)	WLAN	1.99	-3.8
10573	AAA	IEEE 802.11b WiFi 2.4GHz (DSSS, 5.5Mbps, 90pc duty cycle)	WLAN	1.98	-3.8
10574	AAA	IEEE 802.11b WiFi 2.4GHz (DSSS, 11Mbps, 90pc duty cycle)	WLAN	1.98	-3.8
10575	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 6Mbps, 90pc duty cycle)	WLAN	8.59	-3.8
10576	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 9Mbps, 90pc duty cycle)	WLAN	8.60	-3.8
10577	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 12Mbps, 90pc duty cycle)	WLAN	8.70	-3.8
10578	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 18Mbps, 90pc duty cycle)	WLAN	8.78	-3.8
10579	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 24Mbps, 90pc duty cycle)	WLAN	8.90	-3.8
10580	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 36Mbps, 90pc duty cycle)	WLAN	8.75	-3.8
10581	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 48Mbps, 90pc duty cycle)	WLAN	8.95	-3.8
10582	AAA	IEEE 802.11g WiFi 2.4GHz (DSSS-CFDM, 54Mbps, 90pc duty cycle)	WLAN	8.87	-3.8
10583	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 8Mbps, 90pc duty cycle)	WLAN	8.50	-3.8
10584	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 9Mbps, 90pc duty cycle)	WLAN	8.60	-3.8
10585	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 18Mbps, 90pc duty cycle)	WLAN	8.70	-3.8
10586	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 18Mbps, 90pc duty cycle)	WLAN	8.79	-3.8
10587	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 24Mbps, 90pc duty cycle)	WLAN	8.66	-3.8
10588	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 36Mbps, 90pc duty cycle)	WLAN	8.75	-3.8
10589	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 48Mbps, 90pc duty cycle)	WLAN	8.85	-3.8
10590	AAC	IEEE 802.11ah WiFi 5GHz (OFDM, 54Mbps, 90pc duty cycle)	WLAN	8.87	-3.8
10591	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	WLAN	8.63	-3.8
10592	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS1, 90pc duty cycle)	WLAN	8.79	-3.8
10593	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS2, 90pc duty cycle)	WLAN	8.91	-3.8
10594	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS3, 90pc duty cycle)	WLAN	8.74	-3.8
10595	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS4, 90pc duty cycle)	WLAN	8.74	-3.8
10596	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS5, 90pc duty cycle)	WLAN	8.71	-3.8
10597	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS6, 90pc duty cycle)	WLAN	8.72	-3.8
10598	AAC	IEEE 802.11r (HT Mixed, 20MHz, MCS7, 90pc duty cycle)	WLAN	8.50	-3.8
10599	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	WLAN	8.79	-3.8
10600	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS1, 90pc duty cycle)	WLAN	8.88	-3.8
10601	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS2, 90pc duty cycle)	WLAN	8.82	-3.8
10602	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS3, 90pc duty cycle)	WLAN	8.84	-3.8
10603	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS4, 90pc duty cycle)	WLAN	8.73	-3.8
10604	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS5, 90pc duty cycle)	WLAN	8.73	-3.8
10605	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS6, 90pc duty cycle)	WLAN	8.97	-3.8
10606	AAC	IEEE 802.11r (HT Mixed, 40MHz, MCS7, 90pc duty cycle)	WLAN	8.92	-3.8
10607	AAC	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	WLAN	8.94	-3.8
10608	AAC	IEEE 802.11ac WiFi (20MHz, MCS1, 90pc duty cycle)	WLAN	8.73	-3.8

Certificate No: EUMm-0488_Jun23

Page 12 of 18

EUMmWV4 - SN:9469

June 20, 2025

UID	Rev	Communication System Name	Group	FAR (dB)	Unc ² R=2
10600	AAC	IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.57	-3.6
10610	AAC	IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.78	-3.8
10611	AAC	IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	-3.8
10612	AAC	IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	-3.8
10613	AAC	IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.94	-3.8
10614	AAC	IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.93	-3.8
10615	AAC	IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.92	-3.8
10616	AAC	IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.92	-3.8
10617	AAC	IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.91	-3.8
10618	AAC	IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.99	-3.8
10619	AAC	IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.95	-3.8
10620	AAC	IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.93	-3.8
10621	AAC	IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.75	-3.8
10622	AAC	IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.88	-3.8
10623	AAC	IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.89	-3.8
10624	AAC	IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.98	-3.8
10625	AAC	IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.82	-3.8
10626	AAC	IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.89	-3.8
10627	AAC	IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.89	-3.8
10628	AAC	IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.77	-3.8
10629	AAC	IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.86	-3.8
10630	AAC	IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.72	-3.8
10631	AAC	IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.7	-3.8
10632	AAC	IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.85	-3.8
10633	AAC	IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.85	-3.8
10634	AAC	IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.74	-3.8
10635	AAC	IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)	WLAN	8.82	-3.8
10636	AAC	IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.82	-3.8
10637	AAC	IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)	WLAN	8.87	-3.8
10638	AAC	IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)	WLAN	8.85	-3.8
10639	AAC	IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)	WLAN	8.79	-3.8
10640	AAC	IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)	WLAN	8.85	-3.8
10641	AAC	IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.85	-3.8
10642	AAC	IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)	WLAN	9.03	-3.8
10643	AAC	IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)	WLAN	9.03	-3.8
10644	AAC	IEEE 802.11ac WiFi (160 MHz, MCS10, 90pc duty cycle)	WLAN	9.05	-3.8
10645	AAC	IEEE 802.11ac WiFi (160 MHz, MCS11, 90pc duty cycle)	WLAN	9.11	-3.8
10646	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.95	-3.8
10647	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.95	-3.8
10648	AAG	CDMA2000 1X Advanced	CDMA2000	9.45	-3.8
10652	AAP	LTE-TDC (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	8.81	-3.8
10653	AAP	LTE-TDC (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	-3.8
10654	AAL	LTE-TDC (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.98	-3.8
10655	AAL	LTE-TDC (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.81	-3.8
10656	AAL	Pulse Waveform (200Hz, 10%)	Test	6.00	-3.8
10659	AAL	Pulse Waveform (200Hz, 20%)	Test	6.55	-3.8
10660	AAL	Pulse Waveform (200Hz, 40%)	Test	6.68	-3.8
10661	AAL	Pulse Waveform (200Hz, 50%)	Test	6.22	-3.8
10662	AAL	Pulse Waveform (200Hz, 50%)	Test	6.87	-3.8
10670	AAV	Bluetooth Low Energy	Bluetooth	7.15	-3.8
10671	AAC	IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.05	-3.8
10672	AAC	IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.7	-3.8
10673	AAC	IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.75	-3.8
10674	AAC	IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	-3.8
10675	AAC	IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.90	-3.8
10676	AAC	IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	-3.8
10677	AAC	IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.73	-3.8
10678	AAC	IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.78	-3.8
10679	AAC	IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.89	-3.8
10680	AAC	IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)	WLAN	8.80	-3.8
10681	AAC	IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)	WLAN	8.89	-3.8
10682	AAC	IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)	WLAN	8.93	-3.8
10683	AAC	IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.02	-3.8
10684	AAC	IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	9.25	-3.8
10685	AAC	IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.83	-3.8
10686	AAC	IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.88	-3.8

EUMWV4 - SN:9489

June 20, 2025

UID	Rev	Communication System Name	Group	PAI1 (dB)	Unc ² K - 2
10687	AAC	IEEE 802.11ax (20 MHz, MCS8, 90ps duty cycle)	WLAN	8.40	-9.6
10688	AAC	IEEE 802.11ax (20 MHz, MCS8, 90ps duty cycle)	WLAN	8.29	-9.6
10689	AAC	IEEE 802.11ax (20 MHz, MCS8, 90ps duty cycle)	WLAN	8.50	-9.6
10690	AAC	IEEE 802.11ax (20 MHz, MCS7, 90ps duty cycle)	WLAN	8.29	-9.6
10691	AAC	IEEE 802.11ax (20 MHz, MCS8, 90ps duty cycle)	WLAN	8.25	-9.6
10692	AAC	IEEE 802.11ax (20 MHz, MCS8, 90ps duty cycle)	WLAN	8.29	-9.6
10693	AAC	IEEE 802.11ax (20 MHz, MCS11, 90ps duty cycle)	WLAN	8.25	-9.6
10694	AAC	IEEE 802.11ax (20 MHz, MCS11, 90ps duty cycle)	WLAN	8.57	-9.6
10695	AAC	IEEE 802.11ax (20 MHz, MCS9, 90ps duty cycle)	WLAN	8.73	-9.6
10696	AAC	IEEE 802.11ax (20 MHz, MCS11, 90ps duty cycle)	WLAN	8.91	-9.6
10697	AAC	IEEE 802.11ax (20 MHz, MCS8, 90ps duty cycle)	WLAN	8.81	-9.6
10698	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	9.39	-9.6
10699	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	9.32	-9.6
10700	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	9.23	-9.6
10701	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	9.85	-9.6
10702	AAC	IEEE 802.11ax (40 MHz, MCS7, 90ps duty cycle)	WLAN	8.70	-9.6
10703	AAC	IEEE 802.11ax (40 MHz, MCS9, 90ps duty cycle)	WLAN	8.82	-9.6
10704	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	8.68	-9.6
10705	AAC	IEEE 802.11ax (40 MHz, MCS10, 90ps duty cycle)	WLAN	8.88	-9.6
10706	AAC	IEEE 802.11ax (40 MHz, MCS11, 90ps duty cycle)	WLAN	8.88	-9.6
10707	AAC	IEEE 802.11ax (40 MHz, MCS9, 90ps duty cycle)	WLAN	8.32	-9.6
10708	AAC	IEEE 802.11ax (40 MHz, MCS11, 90ps duty cycle)	WLAN	8.55	-9.6
10709	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	8.23	-9.6
10710	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	8.26	-9.6
10711	AAC	IEEE 802.11ax (40 MHz, MCS4, 90ps duty cycle)	WLAN	8.59	-9.6
10712	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	8.67	-9.6
10713	AAC	IEEE 802.11ax (40 MHz, MCS9, 90ps duty cycle)	WLAN	8.35	-9.6
10714	AAC	IEEE 802.11ax (40 MHz, MCS7, 90ps duty cycle)	WLAN	8.26	-9.6
10715	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	8.45	-9.6
10716	AAC	IEEE 802.11ax (40 MHz, MCS8, 90ps duty cycle)	WLAN	8.50	-9.6
10717	AAC	IEEE 802.11ax (40 MHz, MCS10, 90ps duty cycle)	WLAN	8.48	-9.6
10718	AAC	IEEE 802.11ax (40 MHz, MCS11, 90ps duty cycle)	WLAN	8.24	-9.6
10719	AAC	IEEE 802.11ax (40 MHz, MCS9, 90ps duty cycle)	WLAN	8.81	-9.6
10720	AAC	IEEE 802.11ax (80 MHz, MCS4, 90ps duty cycle)	WLAN	8.87	-9.6
10721	AAC	IEEE 802.11ax (80 MHz, MCS2, 90ps duty cycle)	WLAN	8.75	-9.6
10722	AAC	IEEE 802.11ax (80 MHz, MCS8, 90ps duty cycle)	WLAN	8.55	-9.6
10723	AAC	IEEE 802.11ax (80 MHz, MCS4, 90ps duty cycle)	WLAN	8.79	-9.6
10724	AAC	IEEE 802.11ax (80 MHz, MCS8, 90ps duty cycle)	WLAN	8.30	-9.6
10725	AAC	IEEE 802.11ax (80 MHz, MCS8, 90ps duty cycle)	WLAN	8.71	-9.6
10726	AAC	IEEE 802.11ax (80 MHz, MCS7, 90ps duty cycle)	WLAN	9.72	-9.6
10727	AAC	IEEE 802.11ax (80 MHz, MCS8, 90ps duty cycle)	WLAN	8.98	-9.6
10728	AAC	IEEE 802.11ax (80 MHz, MCS9, 90ps duty cycle)	WLAN	8.85	-9.6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 90ps duty cycle)	WLAN	8.54	-9.6
10730	AAC	IEEE 802.11ax (80 MHz, MCS11, 90ps duty cycle)	WLAN	8.67	-9.6
10731	AAC	IEEE 802.11ax (90 MHz, MCS9, 90ps duty cycle)	WLAN	8.42	-9.6
10732	AAC	IEEE 802.11ax (90 MHz, MCS11, 90ps duty cycle)	WLAN	8.48	-9.6
10733	AAC	IEEE 802.11ax (90 MHz, MCS9, 90ps duty cycle)	WLAN	8.40	-9.6
10734	AAC	IEEE 802.11ax (90 MHz, MCS8, 90ps duty cycle)	WLAN	8.26	-9.6
10735	AAC	IEEE 802.11ax (90 MHz, MCS4, 90ps duty cycle)	WLAN	8.88	-9.6
10736	AAC	IEEE 802.11ax (90 MHz, MCS8, 90ps duty cycle)	WLAN	8.27	-9.6
10737	AAC	IEEE 802.11ax (90 MHz, MCS6, 90ps duty cycle)	WLAN	8.58	-9.6
10738	AAC	IEEE 802.11ax (90 MHz, MCS7, 90ps duty cycle)	WLAN	8.40	-9.6
10739	AAC	IEEE 802.11ax (90 MHz, MCS8, 90ps duty cycle)	WLAN	8.28	-9.6
10740	AAC	IEEE 802.11ax (90 MHz, MCS8, 90ps duty cycle)	WLAN	8.45	-9.6
10741	AAC	IEEE 802.11ax (90 MHz, MCS10, 90ps duty cycle)	WLAN	8.40	-9.6
10742	AAC	IEEE 802.11ax (90 MHz, MCS11, 90ps duty cycle)	WLAN	8.43	-9.6
10743	AAC	IEEE 802.11ax (110 MHz, MCS9, 90ps duty cycle)	WLAN	8.94	-9.6
10744	AAC	IEEE 802.11ax (110 MHz, MCS11, 90ps duty cycle)	WLAN	9.19	-9.6
10745	AAC	IEEE 802.11ax (110 MHz, MCS2, 90ps duty cycle)	WLAN	8.83	-9.6
10746	AAC	IEEE 802.11ax (110 MHz, MCS8, 90ps duty cycle)	WLAN	8.11	-9.6
10747	AAC	IEEE 802.11ax (110 MHz, MCS4, 90ps duty cycle)	WLAN	9.04	-9.6
10748	AAC	IEEE 802.11ax (110 MHz, MCS8, 90ps duty cycle)	WLAN	8.03	-9.6
10749	AAC	IEEE 802.11ax (110 MHz, MCS9, 90ps duty cycle)	WLAN	8.93	-9.6
10750	AAC	IEEE 802.11ax (110 MHz, MCS7, 90ps duty cycle)	WLAN	8.73	-9.6
10751	AAC	IEEE 802.11ax (110 MHz, MCS8, 90ps duty cycle)	WLAN	9.92	-9.6
10752	AAC	IEEE 802.11ax (110 MHz, MCS9, 90ps duty cycle)	WLAN	9.91	-9.6

EUmmWVA - SN9489

June 20, 2023

UID	Rev	Communication System Name	Group	PAR [dB]	Unc ² [k=2]
10733	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.08	-29.6
10734	AAR	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.26	-29.6
10735	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.81	-29.6
10736	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.77	-29.6
10737	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.77	-29.6
10738	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.59	-29.6
10739	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.88	-29.6
10740	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.48	-29.6
10741	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.58	-29.6
10742	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.49	-29.6
10743	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.58	-29.6
10744	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.56	-29.6
10745	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.56	-29.6
10746	AAC	FDD 502.11ax 160MHz, MCS 0, 8000 duty cycle	WLAN	8.51	-29.6
10747	AAC	EG NR (CF-OFDM) 1 RB, 5MHz, QPSK, 15kHz	5G NR FRI TDD	7.88	-29.0
10748	AAD	EG NR (CF-OFDM) 1 RB, 10MHz, QPSK, 15kHz	5G NR FRI TDD	8.01	-29.6
10749	AAD	EG NR (CF-OFDM) 1 RB, 15MHz, QPSK, 15kHz	5G NR FRI TDD	8.01	-29.6
10750	AAD	EG NR (CF-OFDM) 1 RB, 20MHz, QPSK, 15kHz	5G NR FRI TDD	8.02	-29.6
10751	AAD	EG NR (CF-OFDM) 1 RB, 25MHz, QPSK, 15kHz	5G NR FRI TDD	8.02	-29.6
10752	AAD	EG NR (CF-OFDM) 1 RB, 30MHz, QPSK, 15kHz	5G NR FRI TDD	8.02	-29.6
10753	AAD	EG NR (CF-OFDM) 1 RB, 40MHz, QPSK, 15kHz	5G NR FRI TDD	8.02	-29.6
10754	AAD	EG NR (CF-OFDM) 1 RB, 50MHz, QPSK, 15kHz	5G NR FRI TDD	8.02	-29.6
10755	AAD	EG NR (CF-OFDM) 50% RB, 5MHz, QPSK, 15kHz	5G NR FRI TDD	8.2	-29.6
10756	AAD	EG NR (CF-OFDM) 50% RB, 10MHz, QPSK, 15kHz	5G NR FRI TDD	8.26	-29.6
10757	AAC	EG NR (CF-OFDM) 50% RB, 15MHz, QPSK, 15kHz	5G NR FRI TDD	8.26	-29.6
10758	AAD	EG NR (CF-OFDM) 50% RB, 20MHz, QPSK, 15kHz	5G NR FRI TDD	8.24	-29.6
10759	AAC	EG NR (CF-OFDM) 50% RB, 25MHz, QPSK, 15kHz	5G NR FRI TDD	8.48	-29.6
10760	AAD	EG NR (CF-OFDM) 50% RB, 30MHz, QPSK, 15kHz	5G NR FRI TDD	8.88	-29.6
10761	AAD	EG NR (CF-OFDM) 50% RB, 40MHz, QPSK, 15kHz	5G NR FRI TDD	8.58	-29.6
10762	AAD	EG NR (CF-OFDM) 50% RB, 50MHz, QPSK, 15kHz	5G NR FRI TDD	8.49	-29.6
10763	AAC	EG NR (CF-OFDM) 100% RB, 5MHz, QPSK, 15kHz	5G NR FRI TDD	8.2	-29.6
10764	AAD	EG NR (CF-OFDM) 100% RB, 10MHz, QPSK, 15kHz	5G NR FRI TDD	8.28	-29.6
10765	AAD	EG NR (CF-OFDM) 100% RB, 15MHz, QPSK, 15kHz	5G NR FRI TDD	8.46	-29.6
10766	AAD	EG NR (CF-OFDM) 100% RB, 20MHz, QPSK, 15kHz	5G NR FRI TDD	8.26	-29.6
10767	AAD	EG NR (CF-OFDM) 100% RB, 25MHz, QPSK, 15kHz	5G NR FRI TDD	8.44	-29.6
10768	AAD	EG NR (CF-OFDM) 100% RB, 30MHz, QPSK, 15kHz	5G NR FRI TDD	8.88	-29.6
10769	AAD	EG NR (CF-OFDM) 100% RB, 40MHz, QPSK, 15kHz	5G NR FRI TDD	8.57	-29.6
10770	AAD	EG NR (CF-OFDM) 100% RB, 50MHz, QPSK, 15kHz	5G NR FRI TDD	8.49	-29.6
10771	AAC	EG NR (CF-OFDM) 1 RB, 5MHz, QPSK, 30kHz	5G NR FRI TDD	7.88	-29.6
10772	AAD	EG NR (CF-OFDM) 1 RB, 10MHz, QPSK, 30kHz	5G NR FRI TDD	7.92	-29.6
10773	AAD	EG NR (CF-OFDM) 1 RB, 15MHz, QPSK, 30kHz	5G NR FRI TDD	7.92	-29.6
10774	AAD	EG NR (CF-OFDM) 1 RB, 20MHz, QPSK, 30kHz	5G NR FRI TDD	7.92	-29.6
10775	AAD	EG NR (CF-OFDM) 1 RB, 25MHz, QPSK, 30kHz	5G NR FRI TDD	7.94	-29.6
10776	AAD	EG NR (CF-OFDM) 1 RB, 30MHz, QPSK, 30kHz	5G NR FRI TDD	7.92	-29.6
10777	AAD	EG NR (CF-OFDM) 1 RB, 40MHz, QPSK, 30kHz	5G NR FRI TDD	8.0	-29.6
10778	AAD	EG NR (CF-OFDM) 1 RB, 50MHz, QPSK, 30kHz	5G NR FRI TDD	7.99	-29.6
10779	AAD	EG NR (CF-OFDM) 1 RB, 60MHz, QPSK, 30kHz	5G NR FRI TDD	7.99	-29.6
10780	AAD	EG NR (CF-OFDM) 1 RB, 80MHz, QPSK, 30kHz	5G NR FRI TDD	7.99	-29.6
10781	AAD	EG NR (CF-OFDM) 1 RB, 100MHz, QPSK, 30kHz	5G NR FRI TDD	7.99	-29.6
10805	AAD	EG NR (CF-OFDM) 50% RB, 10MHz, QPSK, 30kHz	5G NR FRI TDD	8.34	-29.6
10806	AAD	EG NR (CF-OFDM) 50% RB, 15MHz, QPSK, 30kHz	5G NR FRI TDD	8.37	-29.6
10807	AAD	EG NR (CF-OFDM) 50% RB, 20MHz, QPSK, 30kHz	5G NR FRI TDD	8.34	-29.6
10810	AAD	EG NR (CF-OFDM) 50% RB, 40MHz, QPSK, 30kHz	5G NR FRI TDD	8.34	-29.6
10812	AAD	EG NR (CF-OFDM) 50% RB, 60MHz, QPSK, 30kHz	5G NR FRI TDD	8.35	-29.6
10817	AAC	EG NR (CF-OFDM) 100% RB, 5MHz, QPSK, 30kHz	5G NR FRI TDD	8.35	-29.6
10818	AAD	EG NR (CF-OFDM) 100% RB, 10MHz, QPSK, 30kHz	5G NR FRI TDD	8.34	-29.6
10819	AAD	EG NR (CF-OFDM) 100% RB, 15MHz, QPSK, 30kHz	5G NR FRI TDD	8.35	-29.6
10820	AAD	EG NR (CF-OFDM) 100% RB, 20MHz, QPSK, 30kHz	5G NR FRI TDD	8.39	-29.6
10821	AAD	EG NR (CF-OFDM) 100% RB, 25MHz, QPSK, 30kHz	5G NR FRI TDD	8.41	-29.6
10822	AAD	EG NR (CF-OFDM) 100% RB, 30MHz, QPSK, 30kHz	5G NR FRI TDD	8.41	-29.6
10823	AAD	EG NR (CF-OFDM) 100% RB, 40MHz, QPSK, 30kHz	5G NR FRI TDD	8.39	-29.6
10824	AAD	EG NR (CF-OFDM) 100% RB, 50MHz, QPSK, 30kHz	5G NR FRI TDD	8.39	-29.6
10825	AAD	EG NR (CF-OFDM) 100% RB, 60MHz, QPSK, 30kHz	5G NR FRI TDD	8.41	-29.6
10827	AAD	EG NR (CF-OFDM) 100% RB, 80MHz, QPSK, 30kHz	5G NR FRI TDD	8.43	-29.6
10828	AAD	EG NR (CF-OFDM) 100% RB, 90MHz, QPSK, 30kHz	5G NR FRI TDD	8.43	-29.6

EUmmWV4 - SN9489

June 20, 2023

UID	Rev	Communication System Name	Group	FAR (dB)	UncF A = 2
10858	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	8.43	-18.6
10859	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.68	-18.6
10860	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.93	-18.6
10861	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.74	-18.6
10862	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.70	-18.6
10863	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.75	-18.6
10864	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.70	-18.6
10865	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.66	-18.6
10866	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.60	-18.6
10867	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.70	-18.6
10868	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.67	-18.6
10869	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.71	-18.6
10870	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.69	-18.6
10871	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10872	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10873	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10874	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10875	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10876	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10877	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10878	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10879	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10880	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10881	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10882	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10883	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10884	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10885	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10886	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10887	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10888	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10889	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10890	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10891	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10892	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10893	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10894	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10895	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10896	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10897	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10898	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10899	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10900	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10901	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10902	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10903	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10904	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10905	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10906	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10907	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10908	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10909	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6
10910	AAD	5G NR (CP-OFDM, 1 RB, 10MHz, QPSK, 20kHz)	5G NR FR1 TDD	7.64	-18.6

EUMmWV4 -SNS480

June 20, 2024

UID	Rev	Communication System Name	Group	PAR(dB)	Unc ² K = 2
10911	AAB	5G NR (DFT-s-OFDM, 30% RB, 25MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.95	-9.8
10912	AAB	5G NR (DFT-s-OFDM, 30% RB, 25MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.84	-9.8
10913	AAB	5G NR (DFT-s-OFDM, 30% RB, 40MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.84	-9.8
10914	AAB	5G NR (DFT-s-OFDM, 30% RB, 25MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.85	-9.8
10915	AAB	5G NR (DFT-s-OFDM, 30% RB, 40MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.85	-9.8
10916	AAB	5G NR (DFT-s-OFDM, 30% RB, 40MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.87	-9.8
10917	AAB	5G NR (DFT-s-OFDM, 30% RB, 40MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.94	-9.8
10918	AAC	5G NR (DFT-s-OFDM, 100% RB, 10MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.35	-9.8
10919	AAB	5G NR (DFT-s-OFDM, 100% RB, 10MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.35	-9.8
10920	AAB	5G NR (DFT-s-OFDM, 100% RB, 15MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.37	-9.8
10921	AAB	5G NR (DFT-s-OFDM, 100% RB, 20MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.41	-9.8
10922	AAB	5G NR (DFT-s-OFDM, 100% RB, 25MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.42	-9.8
10923	AAB	5G NR (DFT-s-OFDM, 100% RB, 30MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.44	-9.8
10924	AAB	5G NR (DFT-s-OFDM, 100% RB, 40MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.44	-9.8
10925	AAB	5G NR (DFT-s-OFDM, 100% RB, 50MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.45	-9.8
10926	AAB	5G NR (DFT-s-OFDM, 100% RB, 60MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.46	-9.8
10927	AAB	5G NR (DFT-s-OFDM, 100% RB, 80MHz, QPSK, 30kHz)	5G NR-FR1-TDD	5.46	-9.8
10928	AAC	5G NR (DFT-s-OFDM, 1 RB, 5MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10929	AAC	5G NR (DFT-s-OFDM, 1 RB, 10MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10930	AAC	5G NR (DFT-s-OFDM, 1 RB, 15MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10931	AAC	5G NR (DFT-s-OFDM, 1 RB, 20MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.51	-9.8
10932	AAC	5G NR (DFT-s-OFDM, 1 RB, 25MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.51	-9.8
10933	AAC	5G NR (DFT-s-OFDM, 1 RB, 30MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.51	-9.8
10934	AAC	5G NR (DFT-s-OFDM, 1 RB, 40MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.51	-9.8
10935	AAC	5G NR (DFT-s-OFDM, 1 RB, 50MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.51	-9.8
10936	AAC	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.50	-9.8
10937	AAC	5G NR (DFT-s-OFDM, 50% RB, 10MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10938	AAC	5G NR (DFT-s-OFDM, 50% RB, 15MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10939	AAC	5G NR (DFT-s-OFDM, 50% RB, 20MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10940	AAC	5G NR (DFT-s-OFDM, 50% RB, 25MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.52	-9.8
10941	AAC	5G NR (DFT-s-OFDM, 50% RB, 30MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.53	-9.8
10942	AAC	5G NR (DFT-s-OFDM, 50% RB, 40MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.53	-9.8
10943	AAC	5G NR (DFT-s-OFDM, 50% RB, 50MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.53	-9.8
10944	AAC	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.51	-9.8
10945	AAC	5G NR (DFT-s-OFDM, 100% RB, 10MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.53	-9.8
10946	AAC	5G NR (DFT-s-OFDM, 100% RB, 15MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.53	-9.8
10947	AAC	5G NR (DFT-s-OFDM, 100% RB, 20MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.57	-9.8
10948	AAC	5G NR (DFT-s-OFDM, 100% RB, 25MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.56	-9.8
10949	AAC	5G NR (DFT-s-OFDM, 100% RB, 30MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.57	-9.8
10950	AAC	5G NR (DFT-s-OFDM, 100% RB, 40MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.54	-9.8
10951	AAC	5G NR (DFT-s-OFDM, 100% RB, 50MHz, QPSK, 15kHz)	5G NR-FR1-FDD	5.54	-9.8
10952	AAA	5G NR DL (CP-OFDM, TM 3.1, 5MHz, 64-QAM, 15kHz)	5G NR-FR1-FDD	6.25	-9.8
10953	AAA	5G NR DL (CP-OFDM, TM 3.1, 10MHz, 64-QAM, 15kHz)	5G NR-FR1-FDD	6.23	-9.8
10954	AAA	5G NR DL (CP-OFDM, TM 3.1, 15MHz, 64-QAM, 15kHz)	5G NR-FR1-FDD	6.12	-9.8
10955	AAA	5G NR DL (CP-OFDM, TM 3.1, 20MHz, 64-QAM, 15kHz)	5G NR-FR1-FDD	6.12	-9.8
10956	AAA	5G NR DL (CP-OFDM, TM 3.1, 5MHz, 64-QAM, 30kHz)	5G NR-FR1-FDD	6.14	-9.8
10957	AAA	5G NR DL (CP-OFDM, TM 3.1, 10MHz, 64-QAM, 30kHz)	5G NR-FR1-FDD	6.1	-9.8
10958	AAA	5G NR DL (CP-OFDM, TM 3.1, 15MHz, 64-QAM, 30kHz)	5G NR-FR1-FDD	6.6	-9.8
10959	AAA	5G NR DL (CP-OFDM, TM 3.1, 20MHz, 64-QAM, 30kHz)	5G NR-FR1-FDD	6.88	-9.8
10960	AAC	5G NR DL (CP-OFDM, TM 3.1, 5MHz, 64-QAM, 15kHz)	5G NR-FR1-TDD	6.32	-9.8
10961	AAB	5G NR DL (CP-OFDM, TM 3.1, 10MHz, 64-QAM, 15kHz)	5G NR-FR1-TDD	6.38	-9.8
10962	AAB	5G NR DL (CP-OFDM, TM 3.1, 15MHz, 64-QAM, 15kHz)	5G NR-FR1-TDD	6.40	-9.8
10963	AAB	5G NR DL (CP-OFDM, TM 3.1, 20MHz, 64-QAM, 15kHz)	5G NR-FR1-TDD	6.36	-9.8
10964	AAC	5G NR DL (CP-OFDM, TM 3.1, 5MHz, 64-QAM, 30kHz)	5G NR-FR1-TDD	6.29	-9.8
10965	AAB	5G NR DL (CP-OFDM, TM 3.1, 10MHz, 64-QAM, 30kHz)	5G NR-FR1-TDD	6.37	-9.8
10966	AAB	5G NR DL (CP-OFDM, TM 3.1, 15MHz, 64-QAM, 30kHz)	5G NR-FR1-TDD	6.55	-9.8
10967	AAD	5G NR DL (CP-OFDM, TM 3.1, 20MHz, 64-QAM, 30kHz)	5G NR-FR1-TDD	6.72	-9.8
10968	AAB	5G NR DL (CP-OFDM, TM 3.1, 5MHz, 64-QAM, 50kHz)	5G NR-FR1-TDD	6.73	-9.8
10969	AAB	5G NR (CP-OFDM, 1 RB, 20MHz, QPSK, 15kHz)	5G NR-FR1-TDD	11.53	-9.8
10970	AAB	5G NR (CP-OFDM, 1 RB, 100MHz, QPSK, 30kHz)	5G NR-FR1-TDD	8.08	-9.8
10971	AAB	5G NR (CP-OFDM, 100% RB, 100MHz, 256-QAM, 30kHz)	5G NR-FR1-TDD	11.28	-9.8
10972	AAA	UL-LA RDL	UL-LA	1.18	-9.8
10973	AAA	UL-LA HD31	UL-LA	6.50	-9.8
10974	AAA	UL-LA HD38	UL-LA	10.32	-9.8
10975	AAA	UL-LA HD34	UL-LA	8.16	-9.8
10976	AAA	UL-LA HD38	UL-LA	8.48	-9.8

ELmmWV4 - SN-3489

June 20, 2023

UID	Rev	Communication System Name	Group	FAH (dB)	Unc ^F (r-2)
10983	AAA	5G NR DL (CP-OFDM, TM3, 40MHz, 54-QAM, 15kHz)	5G NR FR1 TDD	9.31	-18.6
10984	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 15kHz)	5G NR FR1 TDD	9.42	-18.6
10985	AAA	5G NR DL (CP-OFDM, TM3, 40MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	9.54	-18.6
10986	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	9.59	-18.6
10987	AAA	5G NR DL (CP-OFDM, TM3, 60MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	9.55	-18.6
10988	AAA	5G NR DL (CP-OFDM, TM3, 70MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	9.33	-18.6
10989	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	9.33	-18.6
10990	AAA	5G NR DL (CP-OFDM, TM3, 60MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	9.52	-18.6
11000	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 15kHz)	5G NR FR1 TDD	10.39	-18.6
11001	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 TDD	10.73	-18.6
11002	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 15kHz)	5G NR FR1 FDD	9.60	-18.6
11003	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 15kHz)	5G NR FR1 FDD	9.65	-18.6
11004	AAA	5G NR DL (CP-OFDM, TM3, 40MHz, 54-QAM, 15kHz)	5G NR FR1 FDD	9.49	-18.6
11005	AAA	5G NR DL (CP-OFDM, TM3, 60MHz, 54-QAM, 15kHz)	5G NR FR1 FDD	9.51	-18.6
11006	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 FDD	9.76	-18.6
11007	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 FDD	9.76	-18.6
11008	AAA	5G NR DL (CP-OFDM, TM3, 40MHz, 54-QAM, 30kHz)	5G NR FR1 FDD	9.98	-18.6
11009	AAA	5G NR DL (CP-OFDM, TM3, 60MHz, 54-QAM, 30kHz)	5G NR FR1 FDD	9.98	-18.6
11010	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 FDD	9.98	-18.6
11011	AAA	5G NR DL (CP-OFDM, TM3, 80MHz, 54-QAM, 30kHz)	5G NR FR1 FDD	9.98	-18.6
11012	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.27	-18.6
11013	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.45	-18.6
11014	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.44	-18.6
11015	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.41	-18.6
11016	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.29	-18.6
11017	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.27	-18.6
11018	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.28	-18.6
11019	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.28	-18.6
11020	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.27	-18.6
11021	AAA	IEEE 802.11be (80MHz, MCS9, 80ps duty cycle)	WLAN	9.28	-18.6
11022	AAA	IEEE 802.11be (80MHz, MCS10, 80ps duty cycle)	WLAN	9.38	-18.6
11023	AAA	IEEE 802.11be (80MHz, MCS10, 80ps duty cycle)	WLAN	9.38	-18.6
11024	AAA	IEEE 802.11be (80MHz, MCS10, 80ps duty cycle)	WLAN	9.42	-18.6
11025	AAA	IEEE 802.11be (80MHz, MCS10, 80ps duty cycle)	WLAN	9.37	-18.6
11026	AAA	IEEE 802.11be (80MHz, MCS10, 80ps duty cycle)	WLAN	9.39	-18.6

^F Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Appendix A.3 System Calibration certificate (5G Verification Source 10 GHz 1023)

**Calibration Laboratory of
 Schmid & Partner
 Engineering AG**
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Eurofins KCTL (Dymstec)**

Certificate No: **5G-Veri10-1023_Jan23**

CALIBRATION CERTIFICATE			
Object	5G Verification Source 10 GHz - SN: 1023		
Calibration procedure(s)	QA CAL-45.v4 Calibration procedure for sources in air above 6 GHz		
Calibration date:	January 20, 2023		
This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.			
All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.			
Calibration Equipment used (M&TE critical for calibration)			
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Reference Probe EUmmWV3	SN: 9374	2023-01-03(No. EUmmWV3-9374_Jan23)	Jan-24
DAE4ip	SN: 1602	2022-06-27 (No. DAE4ip-1602_Jun22)	Jun-23
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator R&S SMF100A	SN: 100184	19-May-22 (in house check Nov-22)	In house check: Nov-23
Power sensor R&S NRP18S-10	SN: 101258	31-May-22 (in house check Nov-22)	In house check: Nov-23
Calibrated by:	Name Leif Klynsner	Function Laboratory Technician	Signature 
Approved by:	Sven Kühn	Technical Manager	
			Issued: February 8, 2023
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

CW Continuous wave

Calibration is Performed According to the Following Standards

- Internal procedure QA CAL-45, Calibration procedure for sources in air above 6 GHz.
- IEC/IEEE 63195-1, "Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz)", May 2022

Methods Applied and Interpretation of Parameters

- *Coordinate System:* z-axis in the waveguide horn boresight, x-axis is in the direction of the E-field, y-axis normal to the others in the field scanning plane parallel to the horn flare and horn flange.
- *Measurement Conditions:* (1) 10 GHz: The radiated power is the forward power to the horn antenna minus ohmic and mismatch loss. The forward power is measured prior and after the measurement with a power sensor. During the measurements, the horn is directly connected to the cable and the antenna ohmic and mismatch losses are determined by far-field measurements. (2) 30, 45, 60 and 90 GHz: The verification sources are switched on for at least 30 minutes. Absorbers are used around the probe cub and at the ceiling to minimize reflections.
- *Horn Positioning:* The waveguide horn is mounted vertically on the flange of the waveguide source to allow vertical positioning of the EUMmW probe during the scan. The plane is parallel to the phantom surface. Probe distance is verified using mechanical gauges positioned on the flare of the horn.
- *E-field distribution:* E field is measured in two x-y-plane (10mm, 10mm + $\lambda/4$) with a vectorial E-field probe. The E-field value stated as calibration value represents the E-field-maxima and the averaged (1cm² and 4cm²) power density values at 10mm in front of the horn.
- *Field polarization:* Above the open horn, linear polarization of the field is expected. This is verified graphically in the field representation.

Calibrated Quantity

- Local peak E-field (V/m) and average of peak spatial components of the poynting vector (W/m²) averaged over the surface area of 1 cm² and 4cm² at the nominal operational frequency of the verification source. Both square and circular averaging results are listed.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module mmWave	V3.2
Phantom	5G Phantom	
Distance Horn Aperture - plane	10 mm	
XY Scan Resolution	dx, dy = 7.5 mm	
Number of measured planes	2 (10mm, 10mm + $\lambda/4$)	
Frequency	10 GHz \pm 10 MHz	

Calibration Parameters, 10 GHz

Circular Averaging

Distance Horn Aperture to Measured Plane	<i>Prad'</i> (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Avg Power Density Avg (psPDn+, psPDtot+, psPDmod+) (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	86.1	152	1.27 dB	59.8	55.7	1.28 dB

Distance Horn Aperture to Measured Plane	<i>Prad'</i> (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Power Density psPDn+, psPDtot+, psPDmod+ (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	86.1	152	1.27 dB	59.5, 59.8, 60.0	55.3, 55.7, 56.0	1.28 dB

Square Averaging

Distance Horn Aperture to Measured Plane	<i>Prad'</i> (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Avg Power Density Avg (psPDn+, psPDtot+, psPDmod+) (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	86.1	152	1.27 dB	59.8	55.6	1.28 dB

Distance Horn Aperture to Measured Plane	<i>Prad'</i> (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Power Density psPDn+, psPDtot+, psPDmod+ (W/m ²)		Uncertainty (k = 2)
				1 cm ²	4 cm ²	
10 mm	86.1	152	1.27 dB	59.5, 59.8, 60.0	55.2, 55.6, 55.9	1.28 dB

Max Power Density

Distance Horn Aperture to Measured Plane	<i>Prad'</i> (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Max Power Density Sn, Stot, Stot (W/m ²)	Uncertainty (k = 2)
				61.1, 61.3, 61.4	
10 mm	86.1	152	1.27 dB		1.28 dB

¹ Assessed ohmic and mismatch loss plus numerical offset: 0.55 dB

DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1023	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-01-03	DAE4ip Sn1602, 2022-06-27


Scan Setup

Grid Extents [mm]
 Grid Steps [lambda]
 Sensor Surface [mm]
 MAIA

5G Scan
 120.0 x 120.0
 0.25 x 0.25
 10.0
 MAIA not used

Measurement Results

Date	5G Scan
2023-01-20, 14:35	2023-01-20, 14:35
Avg. Area [cm ²]	1.00
Avg. Type	Circular Averaging
psPDn+ [W/m ²]	59.5
psPDtot+ [W/m ²]	59.8
psPDmod+ [W/m ²]	60.0
Max(Sn) [W/m ²]	61.1
Max(Stot) [W/m ²]	61.3
Max(Stot) [W/m ²]	61.4
E _{max} [V/m]	152
Power Drift [dB]	-0.01



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1023	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-01-03	DAE4jp Sn1602, 2022-06-27


Scan Setup

Grid Extents [mm]
 Grid Steps [lambda]
 Sensor Surface [mm]
 MAIA

5G Scan
 120.0 x 120.0
 0.25 x 0.25
 10.0
 MAIA not used

Measurement Results

	5G Scan
Date	2023-01-20, 14:35
Avg. Area [cm ²]	4.00
Avg. Type	Circular Averaging
psPDn+ [W/m ²]	55.3
psPDtot+ [W/m ²]	55.7
psPDmod+ [W/m ²]	56.0
Max(Sn) [W/m ²]	61.1
Max(Stot) [W/m ²]	61.3
Max(Stot) [W/m ²]	61.4
E _{max} [V/m]	152
Power Drift [dB]	-0.01



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1023	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-01-03	DAE4ip Sn1602, 2022-06-27


Scan Setup

Grid Extents [mm]
 Grid Steps [lambda]
 Sensor Surface [mm]
 MAIA

5G Scan
 120.0 x 120.0
 0.25 x 0.25
 10.0
 MAIA not used

Measurement Results

Date	5G Scan
2023-01-20, 14:35	2023-01-20, 14:35
Avg. Area [cm ²]	1.00
Avg. Type	Square Averaging
psPDn+ [W/m ²]	59.5
psPDtot+ [W/m ²]	59.8
psPDmod+ [W/m ²]	60.0
Max(Sn) [W/m ²]	61.1
Max(Stot) [W/m ²]	61.3
Max(Stot) [W/m ²]	61.4
E _{max} [V/m]	152
Power Drift [dB]	-0.01



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000 (10000.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1023	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group,	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW	10000.0, 10000	1.0

Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom - 1002	Air	EUmmWV3 - SN9374_F1-55GHz, 2023-01-03	DAE4ip Sn1602, 2022-06-27


Scan Setup

Grid Extents [mm]
 Grid Steps [lambda]
 Sensor Surface [mm]
 MAIA

5G Scan
 120.0 x 120.0
 0.25 x 0.25
 10.0
 MAIA not used

Measurement Results

	5G Scan
Date	2023-01-20, 14:35
Avg. Area [cm ²]	4.00
Avg. Type	Square Averaging
psPDn+ [W/m ²]	55.2
psPDtot+ [W/m ²]	55.6
psPDmod+ [W/m ²]	55.9
Max(Sn) [W/m ²]	61.1
Max(Stot) [W/m ²]	61.3
Max(Stot) [W/m ²]	61.4
E _{max} [V/m]	152
Power Drift [dB]	-0.01



Appendix A.4 Dipole Calibration certificate (D6.5GHzV2_1005)

**Calibration Laboratory of
 Schmid & Partner
 Engineering AG**
 Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Eurofins KCTL**
 Gyeonggi-do, Republic of Korea

Certificate No. **D6.5GHzV2-1005_Sep23**

CALIBRATION CERTIFICATE			
Object	D6.5GHzV2 - SN:1005		
Calibration procedure(s)	QA CAL-22.v7 Calibration Procedure for SAR Validation Sources between 3-10 GHz		
Calibration date:	September 21, 2023		
<p>This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.</p> <p>All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.</p> <p>Calibration Equipment used (M&TE critical for calibration)</p>			
Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power sensor R&S NRP33T	SN: 100967	03-Apr-23 (No. 217-03806)	Apr-24
Reference 20 dB Attenuator	SN: BH9394 (20k)	30-Mar-23 (No. 217-03809)	Mar-24
Mismatch combination	SN: 84224 / 360D	03-Apr-23 (No. 217-03812)	Apr-24
Reference Probe EX3DV4	SN: 7405	12-Jun-23 (No. EX3-7405_Jun23)	Jun-24
DAE4	SN: 908	03-Jul-23 (No. DAE4-908_Jul23)	Jul-24
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator Anapico APSIN20G	SN: 827	18-Dec-18 (in house check Dec-21)	In house check: Dec-23
Power sensor NRP-Z23	SN: 100169	10-Jan-19 (in house check Nov-22)	In house check: Nov-23
Power sensor NRP-18T	SN: 100950	28-Sep-22 (in house check Nov-22)	In house check: Nov-23
Network Analyzer Keysight E5063A	SN:MY54504221	31-Oct-19 (in house check Oct-22)	In house check: Oct-25
Calibrated by:	Name Jeton Kastrati	Function Laboratory Technician	Signature 
Approved by:	Name Sven Kühn	Function Technical Manager	Signature 
			Issued: September 25, 2023
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Glossary:

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORM x,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range Of 4 MHz To 10 GHz)", October 2020.

Additional Documentation:

- b) DASY System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The Return Loss ensures low reflected power. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.
- *The absorbed power density (APD):* The absorbed power density is evaluated according to Samaras T, Christ A, Kuster N, "Compliance assessment of the epithelial or absorbed power density above 6 GHz using SAR measurement systems", Bioelectromagnetics, 2021 (submitted). The additional evaluation uncertainty of 0.55 dB (rectangular distribution) is considered.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY6	V16.2
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	5 mm	with Spacer
Zoom Scan Resolution	dx, dy = 3.4 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	6500 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	34.5	6.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	33.3 ± 6 %	6.09 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	---	---

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	29.3 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	291 W/kg ± 24.7 % (k=2)

SAR averaged over 8 cm ³ (8 g) of Head TSL	Condition	
SAR measured	100 mW input power	6.61 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	65.5 W/kg ± 24.4 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	5.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	53.6 W/kg ± 24.4 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.5 Ω - 2.0 jΩ
Return Loss	- 26.5 dB

APD (Absorbed Power Density)

APD averaged over 1 cm ²	Condition	
APD measured	100 mW input power	290 W/m ²
APD measured	normalized to 1W	2900 W/m² ± 29.2 % (k=2)

APD averaged over 4 cm ²	condition	
APD measured	100 mW input power	132 W/m ²
APD measured	normalized to 1W	1320 W/m² ± 28.9 % (k=2)

*The reported APD values have been derived using the psSAR1g and psSAR8g.

General Antenna Parameters and Design

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

DASY6 Validation Report for Head TSL

Measurement Report for D6.5GHz-1005, UID 0 -, Channel 6500 (6500.0MHz)

Device under Test Properties

Name, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D6.5GHz	10.0 x 10.0 x 10.0	SN: 1005	-

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz]	Conversion Factor	TSL Cond. [S/m]	TSL Permittivity
Flat, HSL	5.00	Band	CW,	6500	5.50	6.09	33.3

Hardware Setup

Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center - 1182	HBBL600-10000V6	EX3DV4 - SN7405, 2023-06-12	DAE4 Sn908, 2023-07-03

Scan Setup


Grid Extents [mm]
 Grid Steps [mm]
 Sensor Surface [mm]
 Graded Grid
 Grading Ratio
 MAIA
 Surface Detection
 Scan Method

Zoom Scan
 22.0 x 22.0 x 22.0
 3.4 x 3.4 x 1.4
 1.4
 Yes
 1.4
 N/A
 VMS + 6p
 Measured


Measurement Results

Date
 psSAR1g [W/Kg]
 psSAR8g [W/Kg]
 psSAR10g [W/Kg]
 Power Drift [dB]
 Power Scaling
 Scaling Factor [dB]
 TSL Correction
 M2/M1 [%]
 Dist 3dB Peak [mm]

Zoom Scan
 2023-09-21, 13:39
 29.3
 6.61
 5.41
 -0.01
 Disabled
 No correction
 50.8
 4.8



Impedance Measurement Plot for Head TSL



Appendix B. Power Reduction Verification


Proximity Sensor Triggering Distance (KDB 616217 §6.2)

Rear of the DUT was placed directly below the flat phantom. The DUT was moved toward the phantom in accordance with the steps outlined in KDB 616217 §6.2 to determine the trigger distance for enabling power reduction. The DUT was moved away from the phantom to determine the trigger distance for resuming full power.



The DUT featured a visual indicator on its display that showed the status of the proximity sensor (Triggered or not triggered). This was used to determine the status of the sensor during the proximity sensor assessment as monitoring the output power directly was not practical without affecting the measurement.

It was confirmed separately that the output power was altered according to the proximity sensor status indication. This was achieved by observing the proximity sensor status at the same time as monitoring the conducted power contains both the full and reduced conducted power measurements.





LEGEND

-  Direction of DUT travel for determination of power reduction triggering point
-  Direction of DUT travel for determination of full power resumption triggering point

Resulting test positions for SAR measurements

Tissue simulating liquid	Band	Trigger distance – Rear		
		Moving toward phantom	Moving from phantom	Worst case distance for SAR
6500 Head	WLAN Main	10 mm	10 mm	9 mm

Proximity Sensor Triggering Distance Measurement Results – Rear Side (Main)

DUT Moving Toward (Trigger) to the Phantom

Distance to DUT Output Power (dBm)										
Distance (mm)	15	14	13	12	11	10	9	8	7	6
6.5 GHz 802.11ax 80MHz	10.04	9.99	10.05	10.09	9.98	7.51	7.51	7.49	7.61	7.54
6.5 GHz 802.11ax 160MHz	12.58	12.41	12.59	12.55	12.61	7.37	7.42	7.45	7.29	7.38



DUT Moving Away (Release) from the Phantom

Distance to DUT Output Power (dBm)										
Distance (mm)	6	7	8	9	10	11	12	13	14	15
6.5 GHz 802.11ax 80MHz	7.62	7.53	7.55	7.51	7.59	10.01	10.16	10.13	10.06	10.11
6.5 GHz 802.11ax 160MHz	7.25	7.36	7.27	7.28	7.35	12.52	12.41	12.58	12.60	12.60

Hall Effect and Gravity Sensor Guidance (Nov. 2019 TCB Workshop Notes)

The Power verification was performed according to the following procedure:

- Step 1)** With the lid is in closed mode (0 degrees), open the screen in 10 degree steps until laptop mode or tablet mode is obtained.
- Step 2)** Lower the screen 5 degrees. Closed mode should be reobtained. If not keep lowering in 5 degree steps.
- Step 3)** Open the screen in 1 degree steps until laptop mode or tablet mode is reobtained. Continue opening the screen in 1 degree steps until at least 5 degrees past where laptop mode or tablet mode (90 degree) was obtained.
- Step 4)** Then continue opening the screen in 10 degree steps until tablet mode or laptop mode is obtained.
- Step 5)** Power measurements should be taken at each step.



Laptop Mode / Antenna 1(Aux)					
Degrees	Band	U-NII-5	U-NII-6	U-NII-7	U-NII-8
	Mode	802.11ax(BW 160)			
Step 1) With the lid is in closed mode (0 degrees), open the screen in 10 degree steps until laptop mode is obtained.					
0	Notebook	Closed Mode			
10					
20					
30					
40		7.29	7.30	7.30	7.40
50		7.24	7.37	7.37	7.40
60		7.37	7.24	7.36	7.30
70		7.25	7.27	7.35	7.42
80		7.29	7.37	7.31	7.30
90		7.39	7.34	7.36	7.41
100		7.32	7.25	7.32	7.34
110		7.24	7.33	7.33	7.39
120		7.23	7.37	7.42	7.40
130		7.26	7.25	7.41	7.44
140		7.38	7.26	7.39	7.41
150		7.36	7.33	7.31	7.29
160		7.34	7.38	7.31	7.41
170		7.39	7.33	7.34	7.39
180		7.26	7.26	7.32	7.34
190		7.34	7.34	7.40	7.33
200	7.28	7.34	7.41	7.32	
210	Tablet	12.43	12.57	12.44	12.47
Step 2) Lower the screen 5 degrees. Closed mode should be reobtained. If not keep lowering in 5 degree steps.					
210	Tablet	12.42	12.53	12.38	12.37
205		12.41	12.56	12.39	12.43
200~40	Notebook	7.33	7.28	7.36	7.38
35~0		Closed Mode			
Step 3) Continue opening the screen in 1 degree steps until at least 5 degrees past where laptop mode was obtained.					
0~39	Notebook	Closed Mode			
40~200		7.37	7.38	7.33	7.44
201	Tablet	12.42	12.56	12.32	12.48
202		12.31	12.53	12.34	12.48
203		12.28	12.61	12.46	12.52
204		12.29	12.59	12.42	12.41
205		12.32	12.48	12.40	12.51
206		12.41	12.47	12.41	12.49
Step 4) Then continue opening the screen in 10 degree steps until tablet mode is obtained.					
210	Tablet	12.35	12.56	12.37	12.48
220		12.37	12.48	12.30	12.50
230		12.37	12.55	12.40	12.44
240		12.29	12.57	12.30	12.40
255		12.28	12.55	12.46	12.37
260		12.28	12.58	12.40	12.44
270		12.28	12.62	12.38	12.40
280		12.40	12.47	12.36	12.53
290		12.32	12.57	12.31	12.43
300		12.42	12.47	12.32	12.45
310		12.36	12.48	12.42	12.52
320		12.43	12.48	12.40	12.47
330		12.34	12.51	12.33	12.45
340		12.37	12.62	12.33	12.38
350		12.36	12.49	12.45	12.37
360		12.37	12.54	12.37	12.38

Tablet Mode / Antenna 1(Aux)						
Degrees	Band Mode	U-NII-5	U-NII-6	U-NII-7	U-NII-8	
		802.11ax(BW 160)				
Step 1) With the lid is in closed mode (0 degrees), open the screen in 10 degree steps until laptop mode is obtained.						
0	Tablet	12.40	12.52	12.46	12.47	
10		12.33	12.60	12.31	12.46	
20		12.30	12.46	12.46	12.50	
30		12.43	12.52	12.36	12.49	
40		12.28	12.62	12.40	12.53	
50		12.32	12.56	12.40	12.38	
60		12.30	12.47	12.34	12.50	
70		12.40	12.52	12.36	12.52	
80		12.29	12.46	12.33	12.43	
90		12.29	12.46	12.46	12.48	
100		12.43	12.56	12.40	12.38	
110		12.43	12.51	12.34	12.46	
120		12.32	12.59	12.33	12.47	
130		12.40	12.56	12.41	12.53	
140		12.40	12.54	12.33	12.38	
150	12.37	12.49	12.38	12.52		
160	Notebook	7.23	7.22	7.36	7.39	
Step 2) Lower the screen 5 degrees. Closed mode should be reobtained. If not keep lowering in 5 degree steps.						
160	Notebook	7.34	7.30	7.29	7.44	
155	Tablet	12.30	12.49	12.39	12.47	
150		12.33	12.54	12.32	12.46	
145~0		12.34	12.54	12.36	12.45	
Step 3) Continue opening the screen in 1 degree steps until at least 5 degrees past where laptop mode was obtained.						
0~157	Tablet	12.29	12.60	12.39	12.41	
158		12.34	12.54	12.42	12.48	
159	Notebook	7.38	7.30	7.26	7.36	
160		7.27	7.28	7.36	7.34	
161		7.25	7.24	7.32	7.39	
162		7.39	7.37	7.30	7.28	
163		7.37	7.33	7.30	7.32	
164		7.33	7.29	7.37	7.30	
Step 4) Then continue opening the screen in 10 degree steps until tablet mode is obtained.						
170	Notebook	7.25	7.38	7.35	7.35	
180		7.32	7.37	7.30	7.36	
190		7.36	7.22	7.39	7.36	
200		7.26	7.26	7.31	7.39	
210		7.37	7.24	7.31	7.36	
220		7.27	7.23	7.31	7.31	
230		7.30	7.32	7.40	7.43	
240		7.28	7.31	7.37	7.32	
250		7.25	7.23	7.34	7.44	
260		7.25	7.34	7.26	7.39	
270		7.38	7.30	7.38	7.39	
280		7.38	7.28	7.37	7.40	
290		7.36	7.32	7.42	7.29	
300		7.34	7.26	7.30	7.42	
310		7.27	7.29	7.40	7.29	
320		7.23	7.32	7.29	7.28	
330		Closed Mode				
340						
350						
360						