



# TEST REPORT

## KCTL KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,  
Suwon-si, Gyeonggi-do, 16677, Korea  
TEL: 82-31-285-0894 FAX: 82-505-299-8311  
[www.kctl.co.kr](http://www.kctl.co.kr)

Report No.:  
KR21-SRF0012-B

Page (1) of (12)

# KCTL

### 1. Client

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2020-09-21

2. Use of Report : Certification

3. Name of Product / Model : Wi-Fi/BLE combo module / CCAR210R

4. Manufacturer / Country of Origin : Samsung Electronics Co., Ltd. / Korea

5. FCC ID : A3LCCAR210R

6. IC Certification No. : 649E-CCAR210R

7. Date of Test : 2020-12-21 to 2021-01-06

8. Location of Test :  Permanent Testing Lab  On Site Testing (Address: Address of testing location)

9. Test Standards : 47 CRF Part 1.1310  
RSS-102 Issue 5 Mar 2015

10. Test Results : Refer to the test result in the test report

Affirmation	Tested by	Technical Manager
	Name : Hosung Lee (Signature)	Name : Heesu Ahn (Signature)

2021-01-21

## KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

**REPORT REVISION HISTORY**

Date	Revision	Page No
2021-01-14	Originally issued	-
2021-01-19	Updated	11
2021-01-21	Updated	4

*This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.*

Note. The report No. KR21-SRF0012-A is superseded by the report No. KR21-SRF0012-B.

**General remarks for test reports**

Nothing significant to report.

## CONTENTS

1.	General information .....	4
2.	Device information .....	4
2.1.	Frequency/channel operations.....	4
3.	Measurement uncertainty .....	6
4.	RF Exposure.....	7
4.1.	Test results.....	10
5.	Measurement Equipment.....	12

## 1. General information

Client : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
Manufacturer : Samsung Electronics Co., Ltd.  
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea  
Laboratory : KCTL Inc.  
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea  
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132  
VCCI Registration No. : R-20080, G-20078, C-20059, T-20056  
Industry Canada Registration No. : 8035A  
KOLAS No.: KT231

## 2. Device information

Equipment under test : Wi-Fi/BLE combo module  
Model : CCAR210R  
Frequency range : 2 402 MHz ~ 2 480 MHz (Bluetooth(BLE))  
2 412 MHz ~ 2 462 MHz (802.11b/g/n HT20)  
2 422 MHz ~ 2 452 MHz (802.11n HT40)  
Modulation technique : Bluetooth(BLE)\_GFSK  
WIFI(802.11b/g/n HT20/40)\_DSSS, OFDM  
Number of channels : Bluetooth(BLE)\_40 ch  
2.4 GHz band: 11 ch (20 MHz), 7 ch (40 MHz),  
Power source : DC 5.0 V, DC 12.0 V  
Antenna type : Metal Antenna  
Antenna gain : Bluetooth(BLE) 0.5 dBi  
2.4 GHz band 0.5 dBi  
Software version : v1.0  
Hardware version : v1.0  
Operation temperature : -20 °C ~ 85 °C

## 2.1. Frequency/channel operations

This device contains the following capabilities:

802.11b/g/n HT20/40, Bluetooth Low Energy

Ch.	Frequency (MHz)
00	2 402
.	.
19	2 440
.	.
39	2 480

Table 2.1.1. Bluetooth Low Energy

Ch.	Frequency (MHz)
01	2 412
.	.
06	2 437
.	.
11	2 462

Table 2.1.2. 802.11b/g/n\_HT20 mode

Ch.	Frequency (MHz)
03	2 422
.	.
06	2 437
.	.
09	2 452

Table 2.1.3. 802.11n\_HT40 mode

### 3. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty ( $\pm$ )
Conducted RF power	1.3 dB

## 4. RF Exposure

### FCC

#### Regulation

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Table 1 – Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm <sup>2</sup> ]	Averaging Time [minute]
(A) Limits for Occupational / Controlled Exposure				
0.3 ~ 3.0	614	1.63	*100	6
3.0 ~ 30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30 ~ 300	61.4	0.163	1.0	6
300 ~ 1 500	/	/	f/300	6
1 500 ~ 15 000	/	/	5	6
(B) Limits for General Population / Uncontrolled Exposure				
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19/f	*180/f <sup>2</sup>	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1 500	/	/	f/1 500	30
1 500 ~ 15 000	/	/	1.0	30

*f*=frequency in MHz, \*=*plane-wave equivalent power density*

Per the guidance of KDB 680106, the E-field and H-field limits shown in the table above are extended down to 100 kHz

**IC****RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)**

According to RSS-102 Issue 5, Paragraph "4. Exposure Limits", Industry of Canada has adopted the RF field strength limits established in Health Canada's RF exposure guideline, Safety code 6:

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-10 <sup>21</sup>	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> <sup>0.5</sup>	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> <sup>0.25</sup>	0.1540/ <i>f</i> <sup>0.25</sup>	8.944/ <i>f</i> <sup>0.5</sup>	6
48-300	22.06	0.05852	1.291	6
<u>300-6000</u>	<u>3.142 <i>f</i><sup>0.3417</sup></u>	<u>0.008335 <i>f</i><sup>0.3417</sup></u>	<u>0.02619 <i>f</i><sup>0.6834</sup></u>	<u>6</u>
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> <sup>1.2</sup>
150000-300000	0.158 <i>f</i> <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> <i>f</i>	616000/ <i>f</i> <sup>1.2</sup>
<p><b>Note:</b> <i>f</i> is frequency in MHz.  *Based on nerve stimulation (NS).  ** Based on specific absorption rate (SAR).</p>				



**Exemption Limits for Routine Evaluation – RF Exposure Evaluation**

According to RSS-102 Issue 5 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- Below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1W (adjusted for tune-up tolerance);
- At or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- At or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;
- At or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance.)

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

## 4.1. Test results

### FCC

#### MPE (Maximum Permissible Exposure) Prediction

Prediction of MPE limit at a given distance: Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2 \quad (\Rightarrow R = \sqrt{PG/4\pi S})$$

S = power density [mW/cm<sup>2</sup>]

P = Power input to antenna [mW]

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna [cm]

### IC

#### RF Exposure evaluation

At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz;

**Calculation Result of RF exposure (FCC)**

Maximum tune-up tolerance (Worst Case)

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Ant Gain [dBi]	Power density at 20 cm [mW/cm <sup>2</sup> ]	Limit [mW/cm <sup>2</sup> ]
BLE 1 Mbps	2 402	7.5	0.50	0.001 26	1.00
BLE 2 Mbps	2 402	7.5	0.50	0.001 26	1.00
802.11b	2 462	18.5	0.50	0.015 80	1.00
802.11g	2 437	17	0.50	0.011 19	1.00
802.11n_HT20	2 437	17	0.50	0.011 19	1.00
802.11n_HT40	2 452	16	0.50	0.008 89	1.00

**Calculation Results of RF exposure (IC)**

Maximum tune-up tolerance (Worst Case)

Mode	Frequency [MHz]	Max Tune-up Power [dBm]	Ant Gain [dBi]	E.I.R.P		Limit [mW]
				[dBm]	[mW]	
BLE 1 Mbps	2 402	7.5	0.50	8.00	6.31	2 676.42
BLE 2 Mbps	2 402	7.5	0.50	8.00	6.31	2 676.42
802.11b	2 462	18.5	0.50	19.00	79.43	2 721.93
802.11g	2 437	17	0.50	17.50	56.23	2 703.01
802.11n_HT20	2 437	17	0.50	17.50	56.23	2 703.01
802.11n_HT40	2 452	16	0.50	16.50	44.67	2 714.37

## 5. Measurement Equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
DC Power Supply	AGILENT	E3632A	KR94907664	21.05.11
Power Sensor	R&S	NRP-Z81	1137.9009.02-106223-bB	21.05.25
Attenuator	R&S	DNF Dämpfungsglied 10 dB in N-50 Ohm	31212	21.05.11

**End of test report**