

## 1.2 Detail Information related product

### 1.2.1 Specification

| Items             |                                  | Maple  | Remarks       |
|-------------------|----------------------------------|--|---------------|
| General           | Major Features                   | As Standalone: Copier, Printer, Scan, Scan to USB<br>As Network connected: Network Print, Scan to E-mail | -             |
|                   | Size (W*D*H)                     | 413.6W×353.2D ×333.4H mm<br>(16.26*13.9*12.12 inch)  | -             |
|                   | Net Weight(Inc. Toner Cartridge) | 20.5 Kg (45.2 lbs)   | -             |
| Power Consumption | Ready                            | Less than 160W   | -             |
|                   | AVG.                             | Less than 350W<br>(Currency:5A(110V)/3A(220V))   | -             |
|                   | Max/Peak                         | 700W/1KW   | -             |
|                   | Sleep/Power off                  | Less than 30W  | -             |
| Power Supply      | Input Voltage                    | Low Voltage : 110 ~ 127VAC   | -             |
|                   | Input Frequency                  | 50 / 60Hz(+/- 3Hz)   | -             |
| Warm Up Time      | from Cold Status                 | Less than 35 seconds   | Rated Voltage |
| EMI Approval      |                                  | Class B  | -             |
| Device Memory     | Standard / Max.                  | 128MB / 128MB(Std./Max)  | -             |
|                   | Type                             | SDRAM  | -             |
| PRINT             | Print Speed                      | B&W :17ppm/Letter<br>16ppm/A4<br>Color : 4ppm/A4.Letter  | -             |
|                   | Print Emulation                  | SPL-C  | -             |

#### Operating Frequency

Main Clock = 12MHz  
 Main CPU core Clock = 300MHz  
 USB Clock = 6MHz  
 SD Memory Clock = 100MHz  
 MAC Clock = 25MHz