

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification	Remarks
Processor	Chorus3 (360Mhz)	-
Standard System memory	256MB DDR2 SDRAM	-
Resolution	Up to 2400X600dpi Class (Default 1200x600 dpi) Optical: 600x600 Dpi	-
Copy Quality mode	Text : 600x600dpi(Optical: 300x300dpi) Mixed : 600x600dpi(Optical: 300x300dpi) Photo : 600x600dpi(Optical: 300x300dpi)(ADF) , 1200x1200dpi(Optical: 600x600dpi) (Platen)	-
Paper Handling	Paper Tray(standard) 150 Sheets	-
Power Rating	110~127 VAC, 5.5A, 50/60 Hz	-
Power Consumption	Average : 350W Sleep/Power off : Less than 6W/0.45W	-
Printer Language	SPL-C, PCL-6 (CLX-3185N/FN/FW only)	-
PC Interfaces	USB2.0, Ethernet 10/100 Tx Base, 802.11b/g/n(Wireless model only)	-
OS compatibility	Microsoft Windows: 2000/XP(Include 64bit) Vista Linux OS: Red Hat 8~9, Fedora Core 1~4 Mandrake 9.2~10.1 SuSE 8.2~9.2	-
Modes of Operation	USB Printing, Network Printing, Copy , FAX (FAX model only) Wireless network printing (Wireless model only)	-
Intended Class for Emissions	Class B	-