

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification	Remarks
Processor	CHORUS3N (533MHz)	-
Standard System memory	512MB DDR3 on all configurations (Default) 1GB(max) Customer Installable Option	-
Resolution	True 1200x600dpi (Effective 2400 x 1200dpi)	-
Copy Quality mode	mono : 600x600dpi(ADF) ,600x600dpi (Platen) color : 300x300dpi(ADF) ,600x600dpi (Platen)	-
Paper Handling	Paper Tray(standard) 250 Sheets 2nd Tray(optional) 520 Sheets Bypass Tray 50 Sheets	-
Power Rating	110~127 VAC, 8A	-
Power Consumption	Power save mode : 1.5 Watts Stand by mode : 12 Watts Printing simplex : 850 Watts ADF Copy mode (1-1 copy, Tray2) : 850 Watts	-
Printer Language	SPLC, PCL5Ce, PCL6C, PS3, PDF V1.7	-
Interfaces	USB2.0, Network, FAX, WI-FI	-
OS compatibility	Windows 95/98/2000/NT4.0/Win-ME/XP/Longhorn/XP 64bit/ Citrix MAC OS 8, 9, X 10.2, X 10.3 & Higher Unix/Linux	-
Modes of Operation	USB Printing, ADF Scan, Duplex ADF Copy, 1200dpi Printing, Fax RX, Fax TX, Network Printing, Duplex Printing, PC Scan	-
Intended Class for Emissions	Class B	

3.6 Clock Frequencies

Kind of Clocks	Frequency [MHz]	Kind of Clocks	Frequency [MHz]
Main Source	12	Video	27.3
CPU Internal	533	DDR3	377
USB Device	12	OPE	800
CIS	8.4		