




TEST REPORT

KCTL Inc. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR19-SRF0089-A Page (1) of (100)	
---	---	---

1. Client

- Name : Samsung Electronics Co., Ltd.
- Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Rep. of Korea
- Date of Receipt : 2019-03-26

2. Use of Report : -

3. Name of Product and Model : WiFi Module / CWAP210M

4. Manufacturer and Country of Origin : Samsung Electronics Co., Ltd. / Korea

5. FCC ID : A3LCWAP210M

6. IC Certificate No. : 649E-CWAP210M

7. Date of Test : 2019-07-12 to 2019-07-15

8. Test Standards : FCC Part 15 Subpart C, 15.247 RSS-247 Issue 2 February 2017 RSS GEN Issue 5 March 2019

9. Test Results : Refer to the test result in the test report

Affirmation	Tested by 	Technical Manager 
	Name : Euijung Kim (Signature)	Name : Jaehyong Lee (Signature)

2019-08-02

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (2) of (100)

**Report revision history**

Date	Revision	Page No
2019-07-18	Initial report	-
2019-08-02	Updated KDB version	9, 12, 15

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KOLAS accreditation.



CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Accessory information	4
2.2.	Frequency/channel operations.....	5
2.3.	Duty Cycle Correction Factor	5
3.	Antenna requirement	8
4.	Summary of tests	9
5.	Measurement uncertainty	10
6.	Measurement results explanation example	11
7.	Test results	12
7.1.	Maximum peak output power.....	12
7.2.	Peak Power Spectral Density	15
7.3.	6 dB Bandwidth(DTS Channel Bandwidth)	21
7.4.	Spurious Emission, Band Edge and Restricted bands.....	32
7.5.	Conducted Spurious Emission.....	88
7.6.	AC Conducted emission	97
8.	Measurement equipment	100

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (4) of (100)

KCTL

1. General information

Client : Samsung Electronics Co., Ltd.
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,
Rep. of Korea
Manufacturer : Samsung Electronics Co., Ltd.
Address : 129, Samsung-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677,
Rep. of Korea
Laboratory : KCTL Inc.
Address : 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea
Accreditations : FCC Site Designation No: KR0040, FCC Site Registration No: 687132
VCCI Registration No. : R-3327, G-198, C-3706, T-1849
Industry Canada Registration No. : 8035A
KOLAS No.: KT231

2. Device information

Equipment under test : WiFi Module
Model : CWAP210M
Frequency range : 2 412 MHz ~ 2 462 MHz (802.11b/g/n HT20)
2 422 MHz ~ 2 452 MHz (802.11n HT40)
Modulation technique : DSSS (802.11b), OFDM (802.11g/n HT20/HT40)
Number of channels : 11 ch (802.11b/g/n HT20), 7 ch (802.11n HT40)
Power source : DC 5 V, 12 V
Antenna specification : Metal Antenna
Antenna gain : 1 dBi
Software version : REV1.0
Hardware version : REV1.0
Test device serial No. : N/A
Operation temperature : -20 °C ~ 70 °C

2.1. Accessory information

Equipment	Manufacturer	Model	Serial No.	Power source
N/A	-	-	-	-

2.2. Frequency/channel operations

This device contains the following capabilities:
WIFI(802.11b/g/n(HT20/HT40))

Ch.	Frequency (MHz)
01	2 412
⋮	⋮
07	2 437
⋮	⋮
11	2 462


Table 2.2.1. 802.11b/g/n HT20 mode

Ch.	Frequency (MHz)
03	2 422
⋮	⋮
07	2 437
⋮	⋮
09	2 452

Table 2.2.2. 802.11n HT40 mode

2.3. Duty Cycle Correction Factor

- 802.11b




Note₁) : Period : 112.46 ms, On time : 85.80 ms

Note₂) : DCCF = $10 \log(1 / x) = 10 \log(1/0.763) = 1.175 \text{ dB}$, $x = 85.80/112.46 = 0.763$ (76.3%)

Note₃) : 802.11b is a non-continuous transmission (duty cycle < 98 %)

- 802.11g




Note₁) : Period : 16.15 ms, On time : 15.40 ms

Note₂) : DCCF = $10 \log(1 / x) = 10 \log(1/0.953) = 0.208 \text{ dB}$, $x = 15.40/16.15 = 0.953 (95.3\%)$

Note₃) : 802.11g is a non-continuous transmission (duty cycle < 98 %)

- 802.11n HT20



Note₁) : Period : 16.15 ms, On time : 14.31 ms

Note₂) : DCCF = $10 \log(1 / x) = 10 \log(1/0.886) = 0.256 \text{ dB}$, $x = 14.31/16.15 = 0.886 (88.6\%)$

Note₃) : 802.11n HT20 is a non-continuous transmission (duty cycle < 98 %)

- 802.11n HT40

Note₁) : Period : 15.94 ms, On time : 7.79 ms

Note₂) : $DCCF = 10 \log(1/x) = 10 \log(1/0.489) = 3.108 \text{ dB}$, $x = 7.79/15.94 = 0.489$ (48.9%)

Note₃) : 802.11n HT20 is a non-continuous transmission (duty cycle < 98%)

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Requirement of RSS-GEN Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

- The transmitter has permanently attached Metal Antenna (internal antenna) on board.
- The E.U.T Complies with the requirement of §15.203, §15.247.

4. Summary of tests

FCC Part section(s)	IC Rule Reference	Parameter	Test results
15.247(b)(3)	RSS-247 (5.4)(d)	Maximum Peak Output Power	Pass
15.247(e)	RSS-247 (5.2)(b)	Peak Power Spectral Density	Pass
15.247(a)(2)	RSS-247 (5.2)(a)	6 dB Channel Bandwidth	Pass
-	RSS-Gen (6.7)	Occupied Bandwidth	Pass
15.247(d), 15.205(a), 15.209(a)	RSS-Gen (8.9), (8.10) RSS-247(5.5)	Spurious emission	Pass
		Band-edge, restricted band	Pass
15.207(a)	RSS-Gen (8.8)	Conducted Emissions	Pass

Notes:

- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that X orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in X orientation
- The test procedure(s) in this report were performed in accordance as following.
 - ANSI C63.10-2013
 - KDB 558074 D01 V05r02
- The worst-case data rate were:
 - 802.11b mode : 1Mbps
 - 802.11g mode : 6Mbps
 - 802.11n HT20 mode : MCS0
 - 802.11n HT40 mode : MCS0

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty	
Conducted RF power	1.76 dB	
Conducted spurious emissions	4.03 dB	
Radiated spurious emissions	9 kHz ~ 30 MHz:	2.28 dB
	30 MHz ~ 300 MHz	4.98 dB
	300 MHz ~ 1 000 MHz	5.14 dB
	1 GHz ~ 6 GHz	6.70 dB
	Above 6 GHz	6.60 dB
Conducted emissions	9 kHz ~ 150 kHz	3.66 dB
	150 kHz ~ 30 MHz	3.26 dB

KCTL

6. Measurement results explanation example

The offset level is set in the spectrum analyzer to compensate the RF cable loss factor between EUT conducted output port and spectrum analyzer.

With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Frequency (MHz)	Factor(dB)	Frequency (MHz)	Factor(dB)
30	10.22	9 000	12.34
100	10.32	10 000	12.74
200	10.41	11 000	12.77
300	10.48	12 000	12.48
400	10.55	13 000	13.02
500	10.62	14 000	12.81
600	10.65	15 000	13.20
700	10.68	16 000	12.89
800	10.74	17 000	13.51
900	10.71	18 000	13.46
1 000	10.75	19 000	13.29
2 000	11.04	20 000	13.39
3 000	11.31	21 000	13.55
4 000	11.68	22 000	13.79
5 000	11.56	23 000	13.74
6 000	11.98	24 000	13.72
7 000	12.06	25 000	13.74
8 000	12.46	26 000	13.81


Note.

Offset(dB) = RF cable loss(dB) + Attenuator(dB)

7. Test results

7.1. Maximum peak output power

Test setup



Limit

According to §15.247(b)(3), RSS-247(5.4) For systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

According to RSS-247 5.4(d), For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

Test procedure

ANSI C63.10-2013 - Section 11.9

KDB 558074 D01 V05r02 - Section 8.3

Test settings

General

Section 15.247 permits the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for demonstrating compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth (see ANSI C63.10 for measurement guidance).

When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW to set a bin-to-bin spacing of \leq RBW/2 so that narrowband signals are not lost between frequency bins.

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level. The intent is to test at 100 % duty cycle; however a small reduction in duty cycle (to no lower than 98 %) is permitted, if required by the EUT for amplitude control

purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

If continuous transmission (or at least 98 % duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

Maximum peak conducted output power

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW \geq DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW \geq [3 \times RBW].
- c) Set span \geq [3 \times RBW].
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

Measurement using a power meter (PM)

Method AVGPM is a measurement using an RF average power meter, as follows:

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:
 - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.
- c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- d) Adjust the measurement in dBm by adding [10 log(1/D)], where D is the duty cycle.

Notes:

A peak responding power sensor is used, where the power sensor system video bandwidth is greater than the occupied bandwidth of the EUT.

Test results

This test report shall not be reproduced, except in full, without the written approval

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (14) of (100)

KCTL**DC 5 V**

Test mode	Frequency (MHz)	Conducted output power (dBm)		Conducted Power Limit (dBm)	Ant. Gain (dBi)	Max. e.i.r.p.(dB m)		Max. e.i.r.p. Limit (dBm)
		Peak	Average			Peak	Average	
802.11b	2 412	18.48	16.70	30.00	1.00	19.48	17.70	36.02
	2 437	18.68	16.89		1.00	19.68	17.89	
	2 462	19.28	17.52		1.00	20.28	18.52	
802.11g	2 412	25.49	16.13	30.00	1.00	26.49	17.13	36.02
	2 437	24.99	16.18		1.00	25.99	17.18	
	2 462	25.19	16.48		1.00	26.19	17.48	
802.11 n HT20	2 412	25.09	15.90	30.00	1.00	26.09	16.90	36.02
	2 437	25.09	16.02		1.00	26.09	17.02	
	2 462	25.19	16.45		1.00	26.19	17.45	
802.11 n HT40	2 422	24.19	14.48	30.00	1.00	25.19	15.48	36.02
	2 437	24.49	14.66		1.00	25.49	15.66	
	2 452	24.39	14.98		1.00	25.39	15.98	

DC 12 V

Test mode	Frequency (MHz)	Conducted output power (dBm)		Conducted Power Limit (dBm)	Ant. Gain (dBi)	Max. e.i.r.p.(dB m)		Max. e.i.r.p. Limit (dBm)
		Peak	Average			Peak	Average	
802.11b	2 412	18.78	16.80	30.00	1.00	19.78	17.80	36.02
	2 437	19.08	17.15		1.00	20.08	18.15	
	2 462	19.18	17.54		1.00	20.18	18.54	
802.11g	2 412	24.89	16.12	30.00	1.00	25.89	17.12	36.02
	2 437	25.19	16.22		1.00	26.19	17.22	
	2 462	24.99	16.56		1.00	25.99	17.56	
802.11 n HT20	2 412	25.09	16.09	30.00	1.00	26.09	17.09	36.02
	2 437	25.19	16.20		1.00	26.19	17.20	
	2 462	25.29	16.53		1.00	26.29	17.53	
802.11 n HT40	2 422	24.29	14.69	30.00	1.00	25.29	15.69	36.02
	2 437	24.49	14.63		1.00	25.49	15.63	
	2 452	24.29	14.82		1.00	25.29	15.82	


Notes:

1. e.i.r.p. Calculation:

$$\text{e.i.r.p. (dB m)} = \text{Conducted output power (dB m)} + \text{Antenna gain (dB i)}$$

7.2. Peak Power Spectral Density

Test setup



Limit

According to §15.247(e), RSS-247(5.2) for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test procedure

ANSI C63.10-2013 - Section 11.10.2
KDB 558074 D01 V05r02 - Section 8.4

Test settings

Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4) Set the VBW $\geq 3 \times \text{RBW}$.
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (16) of (100)

KCTL**Test results****DC 5 V**


Test mode	Frequency(MHz)	Result(dBm) (RBW = 3 kHz)	Limit(dBm/ 3kHz)
802.11b	2 412	5.30	8.00
	2 437	5.40	
	2 462	5.84	
802.11g	2 412	-9.55	
	2 437	-9.07	
	2 462	-8.12	
802.11n HT20	2 412	-7.92	
	2 437	-8.28	
	2 462	-7.40	
802.11n HT40	2 422	-11.37	
	2 437	-12.00	
	2 452	-12.35	

DC 12 V


Test mode	Frequency(MHz)	Result(dBm) (RBW = 3 kHz)	Limit(dBm/ 3kHz)
802.11b	2 412	5.60	8.00
	2 437	5.50	
	2 462	6.01	
802.11g	2 412	-8.39	
	2 437	-8.71	
	2 462	-8.28	
802.11n HT20	2 412	-8.80	
	2 437	-8.82	
	2 462	-8.89	
802.11n HT40	2 422	-13.04	
	2 437	-13.46	
	2 452	-13.56	

DC 5 V


802.11b / Low ch.




802.11g / Low ch.




802.11b / Mid ch.




802.11g / Mid ch.



802.11b / High ch.



802.11g / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (18) of (100)




802.11n HT20 / Low ch




802.11n HT40 / Low ch




802.11n HT20 / Mid ch




802.11n HT40 / Mid ch



802.11n HT20 / High ch



802.11n HT40 / High ch



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (19) of (100)




DC 12 V


802.11b / Low ch.




802.11g / Low ch.




802.11b / Mid ch.




802.11g / Mid ch.



802.11b / High ch.



802.11g / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (20) of (100)




802.11n HT20 / Low ch




802.11n HT40 / Low ch




802.11n HT20 / Mid ch




802.11n HT40 / Mid ch



802.11n HT20 / High ch




802.11n HT40 / High ch



7.3. 6 dB Bandwidth(DTS Channel Bandwidth)

Test setup



Limit

According to §15.247(a)(2) RSS-247(5.2) Systems using digital modulation techniques may operate in the 902–928 MHz, 2 400–2 483.5 MHz, and 5 725–5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test procedure

ANSI C63.10-2013 - Section 11.8.2
KDB 558074 D01 v05 - Section 8.2

Test settings

DTS bandwidth

One of the following procedures may be used to determine the modulated DTS bandwidth.

Option 1

- 1) Set RBW = 100 kHz.
- 2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Sweep = auto couple.
- 6) Allow the trace to stabilize.
- 7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Option 2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (22) of (100)

**Test results****DC 5 V**

Test mode	Frequency(MHz)	6 dB bandwidth(MHz)	Minimum Bandwidth(MHz)
802.11b	2 412	10.04	0.5
	2 437	10.04	
	2 462	10.03	
802.11g	2 412	15.11	
	2 437	15.12	
	2 462	15.11	
802.11n HT20	2 412	15.11	
	2 437	15.11	
	2 462	15.11	
802.11n HT40	2 422	35.07	
	2 437	35.10	
	2 452	35.09	

Test mode	Frequency(MHz)	99 % bandwidth(MHz)
802.11b	2 412	14.39
	2 437	14.44
	2 462	14.39
802.11g	2 412	17.03
	2 437	17.03
	2 462	17.28
802.11n HT20	2 412	17.93
	2 437	17.88
	2 462	17.93
802.11n HT40	2 422	35.96
	2 437	36.06
	2 452	36.06

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (23) of (100)

**DC 12 V**

Test mode	Frequency(MHz)	6 dB bandwidth(MHz)	Minimum Bandwidth(MHz)
802.11b	2 412	10.01	0.5
	2 437	10.04	
	2 462	10.03	
802.11g	2 412	15.11	
	2 437	15.12	
	2 462	15.11	
802.11n HT20	2 412	15.10	
	2 437	15.12	
	2 462	15.11	
802.11n HT40	2 422	35.08	
	2 437	35.09	
	2 452	35.09	

Test mode	Frequency(MHz)	99 % bandwidth(MHz)
802.11b	2 412	14.34
	2 437	14.44
	2 462	14.39
802.11g	2 412	17.23
	2 437	17.28
	2 462	17.13
802.11n HT20	2 412	17.88
	2 437	17.88
	2 462	17.93
802.11n HT40	2 422	35.96
	2 437	36.06
	2 452	36.06

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (24) of (100)




6 dB bandwidth(MHz)

DC 5 V


802.11b / Low ch.




802.11g / Low ch.




802.11b / Mid ch.




802.11g / Mid ch.



802.11b / High ch.



802.11g / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (25) of (100)




802.11n HT20 / Low ch




802.11n HT40 / Low ch




802.11n HT20 / Mid ch




802.11n HT40 / Mid ch



802.11n HT20 / High ch



802.11n HT40 / High ch



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (26) of (100)




DC 12 V


802.11b / Low ch.




802.11g / Low ch.




802.11b / Mid ch.




802.11g / Mid ch.



802.11b / High ch.



802.11g / High ch.



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (27) of (100)




802.11n HT20 / Low ch




802.11n HT40 / Low ch




802.11n HT20 / Mid ch




802.11n HT40 / Mid ch



802.11n HT20 / High ch



802.11n HT40 / High ch



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (28) of (100)



99 % bandwidth(MHz)

DC 5 V

802.11b / Low ch.



802.11g / Low ch.



802.11b / Mid ch.



802.11g / Mid ch.



802.11b / High ch.



802.11g / High ch.



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (29) of (100)




802.11n HT20 / Low ch



802.11n HT40 / Low ch



802.11n HT20 / Mid ch




802.11n HT40 / Mid ch



802.11n HT20 / High ch



802.11n HT40 / High ch



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (30) of (100)




DC 12 V


802.11b / Low ch.



802.11g / Low ch.




802.11b / Mid ch.



802.11g / Mid ch.



802.11b / High ch.



802.11g / High ch.



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (31) of (100)



802.11n HT20 / Low ch



802.11n HT40 / Low ch



802.11n HT20 / Mid ch




802.11n HT40 / Mid ch



802.11n HT20 / High ch




802.11n HT40 / High ch




7.4. Spurious Emission, Band Edge and Restricted bands

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Limit

According to section 15.209(a), RSS-Gen(8.9) except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu\text{V}/\text{m}$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

According to section 15.205(a) and (b), RSS-Gen(8.10) only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
0.495 - 0.505	16.694 75 - 16.695 25	608 - 614	5.35 - 5.46
2.173 5 - 2.190 5	16.804 25 - 16.804 75	960 - 1 240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1 300 - 1 427	8.025 - 8.5
4.177 25 - 4.177 75	37.5 - 38.25	1 435 - 1 626.5	9.0 - 9.2
4.207 25 - 4.207 75	73 - 74.6	1 645.5 - 1 646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1 660 - 1 710	10.6 - 12.7
6.267 75 - 6.268 25	108 - 121.94	1 718.8 - 1 722.2	13.25 - 13.4
6.311 75 - 6.312 25	123 - 138	2 200 - 2 300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2 310 - 2 390	15.35 - 16.2
8.362 - 8.366	156.524 75 - 156.525	2 483.5 - 2 500	17.7 - 21.4
8.376 25 - 8.386 75	25	2 690 - 2 900	22.01 - 23.12
8.414 25 - 8.414 75	156.7 - 156.9	3 260 - 3 267	23.6 - 24.0
12.29 - 12.293	162.012 5 - 167.17	3 332 - 3 339	31.2 - 31.8
12.519 75 - 12.520 25	167.72 - 173.2	3 345.8 - 3 358	36.43 - 36.5
12.576 75 - 12.577 25	240 - 285	3 600 - 4 400	Above 38.6
13.36 - 13.41	322 - 335.4		

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in section 15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in section 15.35 apply to these measurements.

Test procedure

ANSI C63.10-2013 - Section 6.6.4.3

KDB 558074 D01 v05 - Section 8.6, 8.7

Test settings**Peak field strength measurements**

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in table
3. VBW \geq (3 \times RBW)
4. Detector = peak
5. Sweep time = auto
6. Trace mode = max hold
7. Allow sweeps to continue until the trace stabilizes

Table. RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1 000 MHz	100 kHz to 120 kHz
> 1 000 MHz	1 MHz

Average field strength measurements**Trace averaging with continuous EUT transmission at full power**

If the EUT can be configured or modified to transmit continuously ($D \geq 98\%$), then the average emission levels shall be measured using the following method (with EUT transmitting continuously):

1. RBW = 1 MHz (unless otherwise specified).
2. VBW \geq (3 \times RBW).
3. Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
4. Averaging type = power (i.e., rms):
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
5. Sweep time = auto.
6. Perform a trace average of at least 100 traces.

Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT ($D \geq 98\%$) cannot be achieved and the duty cycle is constant (duty cycle variations are less than $\pm 2\%$), then the following procedure shall be used:

1. The EUT shall be configured to operate at the maximum achievable duty cycle.
2. Measure the duty cycle D of the transmitter output signal as described in 11.6.
3. RBW = 1 MHz (unless otherwise specified).
4. VBW \geq [3 \times RBW].
5. Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq (\text{RBW} / 2)$. Satisfying this

condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.

6. Averaging type = power (i.e., rms):
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.
7. Sweep time = auto.
8. Perform a trace average of at least 100 traces.
9. A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in step f), then the applicable correction factor is $[10 \log (1 / D)]$, where D is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $[20 \log (1 / D)]$, where D is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous ($D \geq 98\%$) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1 kHz ($\geq 1/T$) for Average detection (AV) at frequency above 1 GHz. (where T = pulse width)
2. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$
Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
3. Factors(dB) = Ant. Factor(dB/m) + Cable loss(dB) + or Amp. gain(dB) + or F_d (dB)
4. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
5. Average test would be performed if the peak result were greater than the average limit.
6. ¹⁾ means restricted band.
7. According to part 15.31(f)(2), an extrapolation factor of 40 dB/decade is applied because measured distance of radiated emission is 3 m.
8. Below 30 MHz frequency range, In order to search for the worst result, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported. when the emission level was higher than 20 dB of the limit, then the following statement shall be made: "No spurious emissions were detected within 20 dB of the limit."

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A



Page (36) of (100)



Test results (Below 30 MHz) – Worst case: 802.11g / Low frequency / DC 5 V

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Ant. Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
No spurious emissions were detected within 20 dB of the limit.									

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A



Page (37) of (100)



Test results (Below 30 MHz) – Worst case: 802.11n HT20 / High frequency / DC 12 V

Frequency	Pol.	Reading	Cable Loss	Amp Gain	Ant. Factor	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
No spurious emissions were detected within 20 dB of the limit.									

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (38) of (100)



Test results (Below 1 000 MHz) – Worst case: 802.11g / Low frequency / DC 5 V

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data								
38.85	V	29.50	18.17	-30.83	-	16.84	40.00	23.16
168.95	V	22.70	18.46	-29.20	-	11.96	43.50	31.54
195.63	V	21.30	15.69	-28.92	-	8.07	43.50	35.43
450.13	H	19.90	23.00	-27.23	-	15.67	46.00	30.33
739.68	H	18.90	27.79	-25.71	-	20.98	46.00	25.02
928.10	H	18.10	29.66	-24.16	-	23.60	46.00	22.40

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (39) of (100)



Test results (Below 1 000 MHz) – Worst case: 802.11n HT20 / High frequency / DC 12 V

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Quasi peak data								
37.03	V	41.80	17.81	-30.86	-	28.75	40.00	11.25
196.72	V	22.10	15.67	-28.91	-	8.86	43.50	34.64
525.91	V	19.10	24.10	-26.84	-	16.36	46.00	29.64
626.67	H	18.80	26.20	-26.40	-	18.60	46.00	27.40
785.39	H	18.80	28.20	-25.44	-	21.56	46.00	24.44
875.96	H	18.40	29.02	-24.68	-	22.74	46.00	23.26

Horizontal/Vertical



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (40) of (100)




Test results (Above 1 000 MHz) DC 5 V

802.11b


Lowest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 339.16 ¹⁾	H	50.38	31.97	-29.92	-	52.43	74.00	21.57
4 824.03 ¹⁾	V	73.36	33.79	-56.52	-	50.63	74.00	23.37
7 235.11	V	66.99	35.50	-54.26	-	48.23	74.00	25.77
Average Data								
No spurious emissions were detected within 20 dB of the limit.								


Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (42) of (100)

KCTL**Middle Channel**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
4 874.03 ¹⁾	H	74.85	33.82	-56.64	-	52.03	74.00	21.97
7 312.59 ¹⁾	V	67.18	35.50	-54.30	-	48.38	74.00	25.62
Average Data								
4 874.03 ¹⁾	H	72.34	33.82	-56.64	1.18	50.70	54.00	3.30




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (44) of (100)




Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 486.70 ¹⁾	H	49.73	32.09	-29.89	-	51.93	74.00	22.07
4 924.11 ¹⁾	H	75.74	33.85	-56.53	-	53.06	74.00	20.94
7 386.00 ¹⁾	H	67.04	35.50	-54.33	-	48.21	74.00	25.79
Average Data								
2 486.70 ¹⁾	H	40.94	32.09	-29.89	1.18	44.32	54.00	9.68
4 924.11 ¹⁾	H	72.31	33.85	-56.53	1.18	50.81	54.00	3.19


Average data (2 486.70 MHz)




Average data (4 924.11 MHz)




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (46) of (100)




802.11g

Lowest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 389.95 ¹⁾	H	58.11	32.01	-29.79	-	60.33	74.00	13.67
4 826.30 ¹⁾	H	72.85	33.80	-56.53	-	50.12	74.00	23.88
7 231.48	V	74.22	35.50	-54.26	-	55.46	74.00	18.54
Average Data								
2 389.95 ¹⁾	H	46.35	32.01	-29.79	0.21	48.78	54.00	5.22




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (48) of (100)

KCTL**Middle Channel**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
4 870.25 ¹⁾	V	73.18	33.82	-56.64	-	50.36	74.00	23.64
7 310.38 ¹⁾	V	75.33	35.50	-54.29	-	56.54	74.00	17.46
Average Data								
7 310.38 ¹⁾	V	63.93	35.50	-54.29	0.21	45.35	54.00	8.65




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (50) of (100)




Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 483.50 ¹⁾	H	62.62	32.09	-29.88	-	64.83	74.00	9.17
4 929.53 ¹⁾	H	77.26	33.86	-56.49	-	54.63	74.00	19.37
7 385.60 ¹⁾	H	71.42	35.50	-54.33	-	52.59	74.00	21.41
Average Data								
2 483.50 ¹⁾	H	47.11	32.09	-29.88	0.21	49.53	54.00	4.47
4 929.53 ¹⁾	H	55.36	33.86	-56.49	0.21	32.94	54.00	21.06


Average data (2 483.50 MHz)




Average data (4 929.53 MHz)




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (52) of (100)




802.11n HT20

Lowest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 389.99 ¹⁾	H	59.64	32.01	-29.79	-	61.86	74.00	12.14
4 826.30 ¹⁾	H	72.22	33.80	-56.53	-	49.49	74.00	24.51
7 235.56	V	68.69	35.50	-54.26	-	49.93	74.00	24.07
Average Data								
2 389.99 ¹⁾	H	47.06	32.01	-29.79	0.53	49.81	54.00	4.19




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (54) of (100)

KCTL**Middle Channel**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
4 869.80 ¹⁾	V	70.63	33.82	-56.63	-	47.82	74.00	26.18
7 311.26 ¹⁾	H	70.81	35.50	-54.3	-	52.01	74.00	21.99
Average Data								
7 311.26 ¹⁾	H	52.23	35.50	-54.3	0.53	33.96	54.00	20.04




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (56) of (100)




Highest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 483.52 ¹⁾	H	60.78	32.09	-29.88	-	62.99	74.00	11.01
4 924.63 ¹⁾	V	73.62	33.85	-56.53	-	50.94	74.00	23.06
7 385.96 ¹⁾	H	71.27	35.50	-54.33	-	52.44	74.00	21.56
Average Data								
2 483.52 ¹⁾	H	47.83	32.09	-29.88	0.53	50.57	54.00	3.43




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (58) of (100)




802.11n HT40

Lowest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 389.71 ¹⁾	H	64.05	32.01	-29.79	-	66.27	74.00	7.73
4 844.88 ¹⁾	H	62.52	33.81	-56.57	-	39.76	74.00	34.24
Average Data								
2 389.71 ¹⁾	H	45.06	32.01	-29.79	3.11	50.39	54.00	3.61


Average data




Average data

Blank


Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (60) of (100)

KCTL**Middle Channel**

Frequency (MHz)	Pol. (V/H)	Reading (dB(μ V))	Ant. Factor (dB)	Amp. + Cable (dB)	DCCF (dB)	Result (dB(μ V/m))	Limit (dB(μ V/m))	Margin (dB)
Peak data								
4 874.33 ¹⁾	V	63.64	33.82	-56.65	-	40.81	74.00	33.19
Average Data								
No spurious emissions were detected within 20 dB of the limit.								

KCTL

KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (61) of (100)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (62) of (100)




Highest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 484.46 ¹⁾	H	58.22	32.09	-29.88	-	60.43	74.00	13.57
4 904.23 ¹⁾	H	71.37	33.84	-56.68	-	48.53	74.00	25.47
Average Data								
2 484.46 ¹⁾	H	42.99	32.09	-29.88	3.11	48.31	54.00	5.69




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (64) of (100)




Test results (Above 1 000 MHz) DC 12 V


802.11b

Lowest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 386.77 ¹⁾	H	52.87	32.01	-29.79	-	55.09	74.00	18.91
4 824.08 ¹⁾	H	73.88	33.79	-56.52	-	51.15	74.00	22.85
7 237.38	V	67.89	35.50	-54.26	-	49.13	74.00	24.87
Average Data								
2 386.77 ¹⁾	H	46.98	32.01	-29.79	1.18	50.38	54.00	12.96




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (66) of (100)

**Middle Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
Peak data								
4 874.06 ¹⁾	H	76.52	33.82	-56.64	-	53.70	74.00	20.30
7 309.88 ¹⁾	V	68.59	35.50	-54.29	-	49.80	74.00	24.20
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (67) of (100)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (68) of (100)




Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
2 487.68 ¹⁾	H	49.74	32.09	-29.89	-	51.94	74.00	22.06
4 924.00 ¹⁾	V	74.03	33.85	-56.53	-	51.35	74.00	22.65
7 385.09 ¹⁾	V	67.72	35.50	-54.33	-	48.89	74.00	25.11
Average Data								
2 487.68 ¹⁾	H	41.10	32.09	-29.89	1.18	44.48	54.00	9.52



Horizontal/Vertical for Band-edge



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (69) of (100)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (70) of (100)




802.11g

Lowest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 389.96 ¹⁾	H	60.62	32.01	-29.79	-	62.84	74.00	11.16
4 825.37 ¹⁾	V	73.99	33.80	-56.53	-	51.26	74.00	22.74
7 234.01 ¹⁾	H	72.46	35.50	-54.26	-	53.70	74.00	20.30
Average Data								
2 389.96 ¹⁾	H	48.39	32.01	-29.79	0.21	50.82	54.00	3.18




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (72) of (100)

**Middle Channel**


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μ V))	(dB)	(dB)	(dB)	(dB(μ V/m))	(dB(μ V/m))	(dB)
Peak data								
1 719.99 ¹⁾	V	65.97	29.63	-36.25	-	59.35	74.00	14.65
4 875.57 ¹⁾	V	74.39	33.83	-56.65	-	51.57	74.00	22.43
7 310.03 ¹⁾	V	73.56	35.50	-54.29	-	54.77	74.00	19.23
Average Data								
1 719.99 ¹⁾	V	44.52	29.63	-36.25	0.21	38.11	54.00	15.89




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (74) of (100)




Highest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
1 715.86	V	62.20	29.60	-36.23	-	55.57	74.00	18.43
2 483.51 ¹⁾	H	61.89	32.09	-29.88	-	64.10	74.00	9.90
4 926.19 ¹⁾	V	75.68	33.86	-56.52	-	53.02	74.00	20.98
7 387.30 ¹⁾	V	72.21	35.50	-54.33	-	53.38	74.00	20.62
Average Data								
1 715.86	V	47.49	29.60	-36.23	0.21	41.07	54.00	12.93
2 483.51 ¹⁾	H	48.45	32.09	-29.88	0.21	50.87	54.00	3.13


Average data (1 715.86 MHz)




Average data (2 483.51 MHz)




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (76) of (100)




802.11n HT20


Lowest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 389.86 ¹⁾	H	57.29	32.01	-29.79	-	59.51	74.00	14.49
4 821.31 ¹⁾	V	71.97	33.79	-56.52	-	49.24	74.00	24.76
7 237.67	V	72.78	35.50	-54.26	-	54.02	74.00	19.98
Average Data								
2 389.86 ¹⁾	H	42.39	32.01	-29.79	0.53	45.14	54.00	8.86
7 237.67	V	60.91	35.50	-54.26	0.53	42.68	54.00	11.32


Average data (2 389.86 MHz)




Average data (7 237.67 MHz)




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (78) of (100)

**Middle Channel**

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB($\mu V/m$))	(dB($\mu V/m$))	(dB)
Peak data								
4 874.36 ¹⁾	V	74.72	33.82	-56.65	-	51.89	74.00	22.11
7 310.85 ¹⁾	V	71.76	35.50	-54.30	-	52.96	74.00	21.04
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (79) of (100)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (80) of (100)




Highest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 483.79 ¹⁾	H	60.57	32.09	-29.88	-	62.78	74.00	11.22
4 924.48 ¹⁾	V	74.32	33.85	-56.53	-	51.64	74.00	22.36
7 385.37 ¹⁾	H	71.75	35.50	-54.33	-	52.92	74.00	21.08
Average Data								
2 483.79 ¹⁾	H	48.26	32.09	-29.88	0.53	51.00	54.00	3.00




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
 Suwon-si, Gyeonggi-do, 16677, Korea
 TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
 KR19-SRF0089-A


Page (82) of (100)




802.11n HT40

Lowest Channel

Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 389.89 ¹⁾	H	58.71	32.01	-29.79	-	60.93	74.00	13.07
4 848.05 ¹⁾	V	68.37	33.81	-56.58	-	45.60	74.00	28.40
Average Data								
2 389.89 ¹⁾	H	43.99	32.01	-29.79	3.11	49.32	54.00	4.68



Horizontal/Vertical for Band-edge



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (83) of (100)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (84) of (100)

**Middle Channel**

Frequency (MHz)	Pol. (V/H)	Reading (dB(μ V))	Ant. Factor (dB)	Amp. + Cable (dB)	DCCF (dB)	Result (dB(μ V/m))	Limit (dB(μ V/m))	Margin (dB)
Peak data								
3 984.39 ¹⁾	V	69.00	32.70	-56.74	-	44.96	74.00	29.04
4 867.08 ¹⁾	V	68.43	33.82	-56.63	-	45.62	74.00	28.38
Average Data								
No spurious emissions were detected within 20 dB of the limit.								



KCTL Inc.


65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A


Page (85) of (100)




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz



Horizontal/Vertical for 18 GHz ~ 26.5 GHz



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (86) of (100)




Highest Channel


Frequency	Pol.	Reading	Ant. Factor	Amp. + Cable	DCCF	Result	Limit	Margin
(MHz)	(V/H)	(dB(μV))	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
Peak data								
2 484.18 ¹⁾	H	56.59	32.09	-29.88	-	58.80	74.00	15.20
4 905.14 ¹⁾	V	67.75	33.84	-56.67	-	44.92	74.00	29.08
7 370.14 ¹⁾	H	65.29	35.50	-54.32	-	46.47	74.00	27.53
Average Data								
2 484.18 ¹⁾	H	44.33	32.09	-29.88	3.11	49.65	54.00	4.35




Horizontal/Vertical for Band-edge




Horizontal/Vertical for 1 GHz ~ 3.5 GHz



Horizontal/Vertical for 3.5 GHz ~ 18 GHz




Horizontal/Vertical for 18 GHz ~ 26.5 GHz



7.5. Conducted Spurious Emission

Test setup



Limit

According to §15.247(d), RSS-247(5.5), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operation, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation specified in §15.209(a) is not required. In addition, radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limit : 20 dBc

Test procedure

ANSI C63.10-2013 - Section 11.11.3, 14.3.3

KDB 558074 D01 v05 - Section 8.5

KDB 662911 D01 v02r01 – section (E)(3)(b)

Test settings


Establish an emission level by using the following procedure:

- 1) Set the center frequency and span to encompass frequency range to be measured.
- 2) Set the RBW = 100 kHz
- 3) Set the VBW \geq [3 x RBW]
- 4) Detector = peak
- 5) Sweep time = auto couple
- 6) Trace mode = max hold
- 7) Allow trace to fully stabilize.
- 8) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

Test results

DC 5 V 802.11b



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (90) of (100)




802.11g



Band edge



Conducted Emissions



Blank



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (91) of (100)




802.11n HT20




Band edge



Conducted Emissions



Blank



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (92) of (100)




802.11n HT40



Band edge



Conducted Emissions



Blank



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (93) of (100)




DC 12 V 802.11b



Band edge



Conducted Emissions



Blank



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (94) of (100)




802.11g



Band edge



Conducted Emissions



Blank



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (95) of (100)




802.11n HT20



Band edge



Conducted Emissions



Blank



KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr


Report No.:
KR19-SRF0089-A

Page (96) of (100)




802.11n HT40



Band edge



Conducted Emissions




Blank



7.6. AC Conducted emission

Test setup



Limit

According to 15.207(a), RSS-Gen(8.8) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequencies ranges.

Frequency of Emission (MHz)	Conducted limit (dB μ V/m)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

Test procedure


ANSI C63.10-2013 - Section 6.2

Test settings

1. The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 cm in which is located 40 cm away from the vertical wall and 1.5m away from the side wall of the shielded room.
2. Each current-carrying conductor of the EUT power cord was individually connected through a 50 Ω /50 μ H LISN, which is an input transducer to a spectrum analyzer or an EMI/Field Intensity Meter, to the input power source.
3. Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.
4. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 MHz to 30 MHz.
5. The measurements were made with the detector set to peak amplitude within a bandwidth of 10 kHz or to quasi-peak and average within a bandwidth of 9 kHz. The EUT was in transmitting mode during the measurements.

Test results

Worst case: DC 5 V / 802.11g / Low frequency



Final Result


--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.31615	22.4	4.3	9.7	32.1	14.0	59.8	49.8	27.7	35.8
2	0.4625	21.5	3.5	9.8	31.3	13.3	56.6	46.6	25.3	33.3
3	1.14522	19.8	2.4	9.7	29.5	12.1	56.0	46.0	26.5	33.9
4	2.04064	17.1	0.8	9.7	26.8	10.5	56.0	46.0	29.2	35.5
5	4.49796	16.6	0.9	9.7	26.3	10.6	56.0	46.0	29.7	35.4
6	5.85681	14.7	0.7	9.7	24.4	10.4	60.0	50.0	35.6	39.6

--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.18527	21.9	7.5	10.1	32.0	17.6	64.2	54.2	32.2	36.6
2	0.42373	36.6	20.1	9.9	46.5	30.0	57.4	47.4	10.9	17.4
3	1.0724	25.6	9.2	9.8	35.4	19.0	56.0	46.0	20.6	27.0
4	1.85226	24.8	8.5	9.8	34.6	18.3	56.0	46.0	21.4	27.7
5	2.62271	23.7	8.0	9.8	33.5	17.8	56.0	46.0	22.5	28.2
6	11.33324	14.9	0.9	10.0	24.9	10.9	60.0	50.0	35.1	39.1

Worst case: DC 12 V / 802.11n HT20 / High frequency



Final Result

--- N Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.28512	20.7	4.2	9.6	30.3	13.8	60.7	50.7	30.4	36.9
2	0.41933	31.6	12.5	9.8	41.4	22.3	57.5	47.5	16.1	25.2
3	1.01329	19.6	2.5	9.7	29.3	12.2	56.0	46.0	26.7	33.8
4	1.78107	18.8	2.1	9.7	28.5	11.8	56.0	46.0	27.5	34.2
5	4.12083	16.3	0.6	9.7	26.0	10.3	56.0	46.0	30.0	35.7
6	5.97031	15.6	1.1	9.7	25.3	10.8	60.0	50.0	34.7	39.2

--- L1 Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.30214	27.2	11.2	9.8	37.0	21.0	60.2	50.2	23.2	29.2
2	0.41676	36.3	19.9	9.9	46.2	29.8	57.5	47.5	11.3	17.7
3	1.07426	25.7	9.0	9.8	35.5	18.8	56.0	46.0	20.5	27.2
4	1.81716	24.7	8.2	9.8	34.5	18.0	56.0	46.0	21.5	28.0
5	2.61565	23.4	7.9	9.8	33.2	17.7	56.0	46.0	22.8	28.3
6	4.96081	20.2	3.9	9.8	30.0	13.7	56.0	46.0	26.0	32.3

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

Report No.:
KR19-SRF0089-A

Page (100) of (100)



8. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Spectrum Analyzer	R & S	FSV30	100810	19.08.01
Spectrum Analyzer	R & S	FSV40	100988	20.01.04
Pulse Power Meter	ANRITSU	ML2495A	1608009	19.08.02
Pulse Power Sensor	ANRITSU	MA2411B	1726174	19.08.02
ATTENUATOR	R & S	DNF Dämpfungsglied 10 dB in N-50 Ohm	31212	20.05.13
EMI TEST RECEIVER	R & S	ESC17	100732	19.08.23
Bi-Log Antenna	SCHWARZBECK	VULB 9168	583	20.05.04
Amplifier	SONOMA INSTRUMENT	310N	284608	19.08.23
COAXIAL FIXED ATTENUATOR	Agilent	8491B-003	2708A18758	20.05.04
Horn antenna	ETS.lindgren	3116	00086632	20.02.15
Horn antenna	ETS.lindgren	3117	155787	19.10.23
Broadband PreAmplifier	SCHWARZBECK	BBV9718	216	19.08.01
AMPLIFIER	L-3 Narda-MITEQ	AFS5-00101800-25-S- 5	2054571	20.02.21
AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800 -22-10P	2031196	20.02.21
AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33 -8P	2000997	19.08.02
LOOP Antenna	R & S	HFH2-Z2	100355	20.08.24
Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
Turn Table	Innco Systems	DT2000	79	-
Antenna Mast	Innco Systems	MA4000-EP	303	-
Turn Table	Innco Systems	DT2000	79	-
Highpass Filter	WT	WT-A1698-HS	WT160411001	20.05.14
TWO-LINE V - NETWORK	R & S	ENV216	101358	20.04.05
EMI TEST RECEIVER	R & S	ESCI	100001	19.08.23
Vector Signal Generator	R & S	SMBV100A	257566	20.01.04
Signal Generator	R & S	SMR40	100007	20.05.13
Cable Assembly	RadiAll	2301761768000PJ	1724.659	-
Cable Assembly	gigalane	RG-400	-	-
Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-

End of test report