

# RF EXPOSURE REPORT

**REPORT NO.:** SA991229E03

MODEL NO.: CY-SWR1100

FCC ID: A3LCYSWR1100

**ACCORDING:** FCC Guidelines for Human Exposure

**IEEE C95.1** 

APPLICANT: Samsung Electronics Co., Ltd.

ADDRESS: 416 Maetan-dong, Young-Tong gu, Suwon, Korea

442-742

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

Report No.: SA991229E03 1 Report Format Version 4.0.0



#### 1. RF EXPOSURE LIMIT

# LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)			POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)		
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

#### 2. MPE CALCULATION FORMULA

Pd = (Pout\*G) / (4\*pi\*r2)

where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

#### 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



#### 4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

### For 15.247(2.4GHz):

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm²)
2412-2462	26.2	4.24	20	0.216	1.00

## For 15.247(5GHz):

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm²)
5745-5825	27.2	4.24	20	0.556	1.00

#### For 15.407(5GHz):

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm²)	LIMIT (mW/cm²)
5180-5240	14.9	4.24	20	0.016	1.00

#### **CONCLUSION:**

Both of the 2.4GHz and 5GHz can transmit simultaneously, the formula of calculated the MPE is:

 $CPD_1/LPD_1 + CPD_2/LPD_2 + \dots etc. < 1$ 

**CPD = Calculation power density** 

**LPD** = Limit of power density

Therefore, the worst-case situation is 0.216 / 1 + 0.556 / 1 = 0.772, which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

--- END ---