



Nemko Korea CO., Ltd.

300-2, Osan-Ri, Mohyeon-Myeon, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, KOREA

TEL:+82 31 330 1700 FAX:+82 31 322 2332

FCC and IC EVALUATION REPORT FOR CERTIFICATION

Applicant :

Samsung Electronics Co., Ltd.
416, Maetan-3Dong, Yeongtong-Gu,
Suwon-Si, Gyeonggi-Do, Korea.
(Post code : 443-742)
Attn. : Mr. Jaywoo. Lee

Dates of Issue : January 5, 2012
Test Report No. : NK-11-R-284
Test Site : Nemko Korea Co., Ltd.

FCC ID
IC ID

A3LDNUBS234B
649E-DNUBS234B

Brand Name

SAMSUNG

Contact Person

Samsung Electronics Co., Ltd.
416, Maetan-3Dong, Yeongtong-Gu,
Suwon-Si, Gyeonggi-Do, Korea, 442-742.
Mr. Jaywoo. Lee
Telephone No. : +82-31-277-2569

Applied Standard: FCC 47 CFR Part 15C and IC RSS-210
Classification: FCC part 15 Spread Spectrum Transmitter
EUT Type: Wi-Fi Module

The device bearing the brand name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Jan. 5, 2012
Tested By : Jin-ha, Ko
Engineer


Jan. 05, 2012
Reviewed By : Hyunho. Kim
Manager & Chief Engineer

TABLE OF CONTENTS

1. Scope	4
2. Introduction (Site Description)	5
2.1 Test facility	5
2.2 Accreditation and listing	6
3. Test Conditions & EUT Information	7
3.1 Operation During Test	7
3.2 Support Equipment	8
3.3 Setup Drawing	8
3.4 EUT Information	9
4. Summary of Test Results	10
5. Recommendation / Conclusion	11
6. Antenna Requirements	11
7. Description of Test	12
7.1 Conducted Emissions	12
7.2 Radiated Emissions	13
7.3 6 dB Bandwidth	14
7.4 Maximum Peak Output Power	14
7.5 Peak Power Spectral Density	15
7.6 Conducted Spurious Emissions	15
8. Test Data	16
8.1 Conducted Emissions	16
8.2 Radiated Emissions	19
8.3 6 dB Modulated Bandwidth	20
8.4 Peak Power Output	30
8.5 Power Spectral Density	31
8.6 Conducted Spurious Emissions	41

8.7 Radiated Spurious Emissions	66
9 Accuracy of Measurement	92
10. Test Equipment	94
Appendix A: Labeling Requirement	95
Appendix B: Photographs of Test Set-up	96
Appendix C: EUT Photographs	98
Appendix D: Maximum Permissible Exposure	101

1. SCOPE

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission under FCC part 15 and IC RSS-210.

Responsible Party :	Samsung Electronics Co., Ltd.
Contact Person :	Mr. Jaywoo. Lee
Manufacturer :	Samsung Electronics Co., Ltd. 416 Maetan-3Dong, Yeongtong-Gu, Suwon-Si, Gyeonggi-Do, 443-742 KOREA

- FCC ID: A3LDNUBS234B
- Model: DNUB-S234B
- Brand Name: SAMSUNG
- EUT Type: Wi-Fi Module
- Classification: FCC part 15 Spread Spectrum Transmitter
- Applied Standard: FCC 47 CFR Part 15 subpart C and IC RSS-210
- Test Procedure(s): ANSI C63.4-2003 and FCC procedure dated March 23, 2005 entitled "Measurements of Digital Transmission Systems Operating Under Section 15.247".
- Dates of Test: Oct. 19, 2011 ~ Oct. 28, 2011
- Place of Tests: Nemko Korea Co., Ltd.

2. INTRODUCTION

2.1 Test facility

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2003) was used in determining radiated and conducted emissions emanating from **Samsung Electronics Co., Ltd.**

FCC ID : A3LDNUBS234B and **IC ID : 649E-DNUBS234B**

These measurement tests were conducted at **Nemko Korea Co., Ltd. EMC Laboratory**.

The site address is 300-2, Osan-Ri, Mohyeon-Myeon, Cheoin-Gu, Yongin-Si, Gyeonggi-Do, KOREA.

The area of Nemko Korea Corporation Ltd. EMC Test Site is located in a mountain area at 80 kilo-meters (48 miles) southeast and Incheon International Airport (Incheon Airport), 30 kilometers (18 miles) south-southeast from central Seoul.

It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures.

The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 2003.



Nemko Korea Co., Ltd.
EMC Lab.
300-2, Osan-Ri, Mohyeon-Myeon,
Cheoin-Gu, Yongin-Si, Gyeonggi-Do,
KOREA 449-852
Tel)+82-31-330-1700
Fax)+82-31-322-2332

Fig. 1. The map above shows the Seoul in Korea vicinity area.

The map also shows Nemko Korea Corporation Ltd. EMC Lab. and Incheon Airport.

2.2 Accreditation and listing

	Accreditation type	Accreditation number
	FCC part 15/18 Filing site	Registration No. 97992
	CAB Accreditation for DOC	Designation No. KR0026
	KOLAS Accredited Lab. (Korea Laboratory Accreditation Scheme)	Registration No. 155
	Canada IC Registered site	Site No. 2040E-1
	VCCI registration site(RE/CE/Telecom CE)	Member No. 2118
	EMC CBTL	-
	KCC(RRL)Designated Lab.	Registration No. KR0026
	SASO registered Lab and Certification Body	Registration No. 2008-15

3. TEST CONDITIONS & EUT INFORMATION

3.1 Operation During Test

The EUT is the SISO transceiver which is module supporting the 802.11b/g/n mode. It has WLAN 1 x 1 Diversity function (11b mode: 1TX, 1RX, 11g mode: 1TX, 1RX, 11N mode: 1TX, 1RX).

The EUT was tested at the lowest channel, middle channel and the highest channel with the maximum RF power and all test data recorded in the report.

During the test, the EUT was connected to laptop PC and then a test program was executed to operate EUT continuously.

The EUT is programmed with the following setting during the testing:

Test frequency		2412 MHz	2437 MHz	2462 MHz
802.11b	Programed Level	17	17	17
	Data rate (Mbps)	1	1	1
802.11g	Programed Level	14	15	15
	Data rate (Mbps)	6	6	6
802.11n(HT20)	Programed Level	13	17	15
	Data rate (Mbps)	MCS0	MCS0	MCS0


Table of test modes

Test Items	Mode	Data rate (Mbps)
Conducted Emissions	802.11n HT20	MCS0
Radiated Emissions	802.11n HT20	MCS0
6 dB Bandwidth	802.11b	1
	802.11g	6
	802.11n(HT20)	MCS0
Peak Output Power	802.11b	1
	802.11g	6
	802.11n(HT20)	MCS0
Power Spectral Density	802.11b	1
	802.11g	6
	802.11n(HT20)	MCS0
Conducted Spurious Emission, Radiated Spurious Emission, Band edge Emission	802.11b	1
	802.11g	6
	802.11n(HT20)	MCS0

3.2 Support Equipment

Wi-Fi Module (EUT)	Samsung Electronics Co., Ltd. Model : DNUB-S234B	S/N: N/A
Laptop PC	Samsung Electronics Co., Ltd. Model : NT-R520 0.3 m unshielded USB cable	FCC DOC S/N: ZK6V93FS800012Y
AC Adaptor	Chicony Power Technology Co., Ltd. Model : AD-6019R 1.2 m unshielded power cable	FCC DOC S/N: CNBA4400242A

3.3 Setup Drawing



3.4 EUT Information

The EUT is the **Samsung Wi-Fi Module FCC ID: A3LDNUBS234B, IC ID: 649E-DNUBS234B.**

Specifications:

EUT Type	Wi-Fi Module
Model Name	DNUB-S234B
Brand Name	SAMSUNG
Frequency of Operation	2412 MHz to 2462 MHz
Peak Power Output (Conducted)	802.11b Main: 21.92 dBm, Aux: 22.55 dBm 802.11g Main: 24.99 dBm , Aux: 24.86 dBm 802.11n(HT20) Main: 25.22 dBm, Aux: 25.09 dBm
Channels	802.11b,g,n(HT20) : 11 CH
TX Antenna Gain	Main : 1.87 dBi Aux : 3.86 dBi
Spreading	DSSS, OFDM
Modulations	BPSK, QPSK, 16QAM, 64QAM
Temperature Range	-10 °C ~ + 60 °C
Voltage	5.0 Vdc
Dimension(W x H x D)	36.0 mm x 5.2 mm x 25 mm
Weight	4 g
Remarks	-

4. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specification:

Name of Test	FCC Paragraph No.	IC Paragraph No.	Result	Remark
Conducted Emission	15.207	RSS-GEN 7.2.4	Complies	
Radiated Emission	15.205 15.209	RSS-GEN 7.2.2	Complies	
6 dB Bandwidth	15.247(a)(2)	RSS-210 A8.2	Complies	
Peak Power Output	15.247(b)(3)	RSS-210 A8.4	Complies	
Power Spectral Density	15.247(e)	RSS-210 A8.2	Complies	
Conducted Spurious Emission	15.247(d)	RSS-210 A8.5	Complies	
Radiated Spurious Emission	15.247(d)	RSS-210 A8.5	Complies	
Maximum Permissible Exposure	1.1307(b)	RSS-102	Complies	

5. RECOMMENDATION/CONCLUSION

The data collected shows that the **Samsung Wi-Fi Module FCC ID: A3LDNUBS234B, IC ID: 649E-DNUBS234B** is in compliance with Part 15 Subpart C 15.247 of the FCC Rules.

6. ANTENNA REQUIREMENTS

§15.203 of the FCC Rules part 15 Subpart C

: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

The antenna of the **Samsung Wi-Fi Module FCC ID: A3LDNUBS234B, IC ID: 649E-DNUBS234B** is **Permanently attached** and there are no provisions for connection to an external antenna. It complies with the requirement of §15.203.

7. DESCRIPTION OF TESTS

7.1 Conducted Emissions

The Line conducted emission test facility is located inside a 4 x 7 x 2.5 meter shielded enclosure.

It is manufactured by EM engineering. The shielding effectiveness of the shielded room is in accordance with MIL-STD-285 or NSA 65-6.

A 1 m x 1.5 m wooden table 0.8 m height is placed 0.4 m away from the vertical wall and 1.5 m away from the side of wall of the shielded room Rohde & Schwarz (ESH3-Z5) and Rohde & Schwarz (ESH2-Z5) of the 50 ohm/50 μ H Line Impedance Stabilization Network(LISN) are bonded to the shielded room.

The EUT is powered from the Rohde & Schwarz LISN (ESH3-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH2-Z5).

Power to the LISNs are filtered by high-current high insertion loss Power line filters. The purpose of filter is to attenuate ambient signal interference and this filter is also bonded to shielded enclosure. All electrical cables are shielded by tinned copper zipper tubing with inner diameter of 1 / 2 ”.

If DC power device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the LISNs, All interconnecting cables more than 1 meter were shortened by non inductive bundling (serpentine fashion) to a 1 meter length.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 150 kHz to 30 MHz with 200 ms sweep time.

The frequency producing the maximum level was re-examined using the EMI test receiver. (Rohde & Schwarz ESCS30).

The detector functions were set to CISPR quasi-peak mode & average mode.

The bandwidth of receiver was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by; switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission.

Each EME reported was calibrated using the R&S signal generator.




Fig. 2. LISN Schematic Diagram

7.2 Radiated Emissions

Preliminary measurements were made indoors at 3 meter using broad band antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The Technology configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna was note for each frequency found. The spectrum was scanned from 9 kHz to 30 MHz using Loop Antenne(EMCO, 6502) and 30 to 1000 MHz using Bi-conical log Antenna(ARA, LPB-2520/A). Above 1 GHz, Horn antenna (Schwarzbeck BBHA 9120D: up to 18 GHz , Q-par Angus QSH20S20 : 18 to 26.5 GHz, QSH22K20: up to 40 GHz) was used. Final Measurements were made outdoors at 3 or 10 m test range using Loop Antenne(EMCO, 6502) and Logbicon Super Antenna (Schwarzbeck, VULB9168) or Horn antenna.(Schwarzbeck BBHA 9120D: up to 18 GHz , Q-par Angus QSH20S20 : 18 to 26.5 GHz, QSH22K20: up to 40 GHz).

The test equipment was placed on a wooden table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was reexamined and investigated using EMI test receiver (ESCS30) & (FSP40). The detector function was set to CISPR peak mode or quasi-peak mode or average mode and the band-width of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal. The half wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT support equipment and interconnecting cables were re configured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non- metallic 1.0 m x 1.5 m table. The EUT, support equipment and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turn table containing the Technology was rotated; the antenna height was varied 1 m to 4m and stopped at the azimuth or height producing the maximum emission Each emission was maximized by : switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and of support equipment, and powering the monitor from the floor mounted outlet box and computer aux AC outlet, if applicable; whichever determined the worst case emission.

Each EME reported was calibrated using the R/S signal generator.




Fig. 3. Dimensions of Outdoor Test Site

7.3 6 dB Bandwidth

Test Setup



Test Procedure


The transmitter is set to the Low, Middle, High channels is connected to the spectrum analyzer. The RBW and VBW of spectrum analyzer are set to 100 kHz.

The sweep time is coupled.

The spectrum analyzer is set for peak detected and Max hold scan mode.

7.4 Maximum Peak Output Power

Test Setup




Test Procedure

The transmitter is set to the Low, Middle, High channels is connected to the Peak Power Meter.

7.5 Peak Power Spectral Density

Test Setup




Test Procedure

The transmitter is connected to the Spectrum analyzer.
The maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer.
The RBW of spectrum analyzer is set to 3 kHz and VBW is set to 3 kHz.
The sweep time is set to Span/3 kHz and video averaging is turned off.
The PPSD is the highest level found across the emission in any 3 kHz band.

7.6 Conducted Spurious Emissions

Test Setup



Test Procedure

The transmitter is connected to the spectrum analyzer.
The RBW of spectrum analyzer is set to 1 MHz and VBW is set to the 1 MHz.
Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the Lowest, middle and highest channels.

8. TEST DATA

8.1 Conducted Emissions

FCC §15.207, RSS-Gen 7.2.4

Frequency (MHz)	Level(dBμV)		*)Factor (dB)	**) Line	Limit(dBμV)		Margin(dB)	
	Q-Peak	Average			Q-Peak	Average	Q-Peak	Average
0.18	52.3	37.8	0.2	N	64.5	54.5	12.2	16.7
0.23	47.3	32.4	0.2	N	62.4	52.4	15.1	20.0
0.29	41.7	27.1	0.2	N	60.5	50.5	18.8	23.4
0.53	35.9	21.5	0.2	L	56.0	46.0	20.1	24.5
3.29	31.7	19.8	0.2	N	56.0	46.0	24.3	26.2
20.21	32.4	23.9	1.6	N	60.0	50.0	27.6	26.1


Line Conducted Emissions Tabulated Data

NOTES:

1. Measurements using CISPR quasi-peak mode & average mode.
2. All modes of operation were investigated and the worst -case emission were reported. See attached Plots.
3. *) Factor = LISN + Cable Loss
4. **) LINE : L = Line , N = Neutral
5. The limit is on the FCC Part section 15.207(a).


PLOTS OF EMISSIONS

- Conducted Emission at the Mains port (Line)



PLOTS OF EMISSIONS

- Conducted Emission at the Mains port (Neutral)



TEST DATA

8.2 Radiated Emissions

FCC §15.209, RSS-210 A8.5

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Antenna Heights (cm)	Turntable Angles (°)	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
40.48	49.8	V	101	40	-20.2	29.6	40.0	10.4
68.25	53.6	H	278	67	-22.4	31.2	40.0	8.8
234.52	49.7	H	164	94	-15.4	34.3	46.0	11.7
345.62	42.4	H	107	209	-13.8	28.6	46.0	17.4
833.34	43.8	H	101	146	-4.2	39.6	46.0	6.4
852.80	43.5	H	100	154	-4.2	39.3	46.0	6.7

Radiated Measurements at 3 meters




Fig. 4. Limits at 3 meters

NOTES:

1. All modes were measured and the worst-case emission was reported.

2 The radiated limits are shown on Figure 4.

Above 1 GHz the limit is 500 μ V/m.

MHz

TEST DATA

8.3 6 dB Modulated Bandwidth

FCC §15.247(a)(2), RSS-210 A8.2

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result:

802.11b mode

Channel	Frequency(MHz)	Result(MHz)		Limit(MHz)
		Main	Aux	
Low	2412	8.104	8.091	0.5
Middle	2437	8.086	8.124	0.5
High	2462	8.113	8.124	0.5

802.11g mode

Channel	Frequency(MHz)	Result(MHz)		Limit(MHz)
		Main	Aux	
Low	2412	15.105	15.110	0.5
Middle	2437	15.148	15.121	0.5
High	2462	15.322	15.464	0.5


802.11n(HT20) mode

Channel	Frequency(MHz)	Result(MHz)		Limit(MHz)
		Main	Aux	
Low	2412	15.135	15.145	0.5
Middle	2437	14.467	15.145	0.5
High	2462	15.140	15.098	0.5


PLOTS OF EMISSIONS

802.11b mode

6 dB Bandwidth, 802.11b mode, Lowest Channel (Main)




6 dB Bandwidth, 802.11b mode, Middle Channel (Main)




PLOTS OF EMISSIONS

6 dB Bandwidth, 802.11b mode, Highest Channel (Main)




6 dB Bandwidth, 802.11b mode, Lowest Channel (Aux)



PLOTS OF EMISSIONS

6 dB Bandwidth, 802.11b mode, Middle Channel (Aux)




6 dB Bandwidth, 802.11b mode, Highest Channel (Aux)




PLOTS OF EMISSIONS

802.11g mode

6 dB Bandwidth, 802.11g mode, Lowest Channel (Main)




6 dB Bandwidth, 802.11g mode, Middle Channel (Main)




PLOTS OF EMISSIONS

6 dB Bandwidth, 802.11g mode, Highest Channel (Main)




6 dB Bandwidth, 802.11g mode, Lowest Channel (Aux)




PLOTS OF EMISSIONS

6 dB Bandwidth, 802.11g mode, Middle Channel (Aux)




6 dB Bandwidth, 802.11g mode, Highest Channel (Aux)




PLOTS OF EMISSIONS

802.11n(HT20) mode

6 dB Bandwidth, 802.11n(HT20) mode, Lowest Channel (Main)




6 dB Bandwidth, 802.11n(HT20) mode, Middle Channel (Main)




PLOTS OF EMISSIONS

6 dB Bandwidth, 802.11n(HT20) mode, Highest Channel (Main)




6 dB Bandwidth, 802.11n(HT20) mode, Lowest Channel (Aux)




PLOTS OF EMISSIONS

6 dB Bandwidth, 802.11n(HT20) mode, Middle Channel (Aux)



6 dB Bandwidth, 802.11n(HT20) mode, Highest Channel (Aux)



TEST DATA

8.4 Peak Power Output

FCC §15.247(b)(3), RSS-210 A8.4

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result:

802.11b mode

Channel	Frequency(MHz)	Peak Power(dBm)		Limit(dBm)
		Main	Aux	
Low	2412	21.92	21.25	30
Middle	2437	21.84	21.99	30
High	2462	21.87	22.55	30

802.11g mode

Channel	Frequency(MHz)	Peak Power(dBm)		Limit(dBm)
		Main	Aux	
Low	2412	24.41	24.16	30
Middle	2437	24.99	24.86	30
High	2462	24.81	24.79	30

802.11n(HT20) mode

Channel	Frequency(MHz)	Peak Power(dBm)		Limit(dBm)
		Main	Aux	
Low	2412	24.21	23.63	30
Middle	2437	25.22	25.09	30
High	2462	24.83	24.72	30

TEST DATA

8.5 Power Spectral Density

FCC §15.247(e), RSS-210 A8.2

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result:

802.11b mode

Channel	Frequency(MHz)	PPSD(dBm)		Limit(dBm)
		Main	Aux	
Low	2412	-2.92	-3.69	8
Middle	2437	-3.14	-3.39	8
High	2462	-2.91	-2.86	8

802.11g mode

Channel	Frequency(MHz)	PPSD(dBm)		Limit(dBm)
		Main	Aux	
Low	2412	-10.20	-9.89	8
Middle	2437	-8.94	-8.97	8
High	2462	-9.96	-9.52	8


802.11n(HT20) mode

Channel	Frequency(MHz)	PPSD(dBm)		Limit(dBm)
		Main	Aux	
Low	2412	-11.24	-11.23	8
Middle	2437	-7.29	-6.39	8
High	2462	-8.45	-9.09	8


PLOTS OF EMISSIONS

802.11b mode

Power Spectral Density, 802.11b mode, Lowest Channel (Main)




Power Spectral Density, 802.11b mode, Middle Channel (Main)




PLOTS OF EMISSIONS

Power Spectral Density, 802.11b mode, Highest Channel (Main)




Power Spectral Density, 802.11b mode, Lowest Channel (Aux)




PLOTS OF EMISSIONS

Power Spectral Density, 802.11b mode, Middle Channel (Aux)




Power Spectral Density, 802.11b mode, Highest Channel (Aux)




PLOTS OF EMISSIONS

802.11g mode

Power Spectral Density, 802.11g mode, Lowest Channel (Main)




Power Spectral Density, 802.11g mode, Middle Channel (Main)




PLOTS OF EMISSIONS

Power Spectral Density, 802.11g mode, Highest Channel (Main)




Power Spectral Density, 802.11g mode, Lowest Channel (Aux)




PLOTS OF EMISSIONS

Power Spectral Density, 802.11g mode, Middle Channel (Aux)




Power Spectral Density, 802.11g mode, Highest Channel (Aux)




PLOTS OF EMISSIONS

802.11n(HT20) mode

Power Spectral Density, 802.11n(HT20) mode, Lowest Channel (Main)




Power Spectral Density, 802.11n(HT20) mode, Middle Channel (Main)




PLOTS OF EMISSIONS

Power Spectral Density, 802.11n(HT20) mode, Highest Channel (Main)




Power Spectral Density, 802.11n(HT20) mode, Lowest Channel (Aux)




PLOTS OF EMISSIONS

Power Spectral Density, 802.11n(HT20) mode, Middle Channel (Aux)



Power Spectral Density, 802.11n(HT20) mode, Highest Channel (Aux)



TEST DATA

8.6 Conducted Spurious Emissions

FCC §15.247(d), RSS-210 A8.5

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result:


802.11b/g/n(HT20) mode

Channel	Frequency(MHz)	Result(dBc)	Limit(dBc)
Low	2412	More than 20 dBc	20
Middle	2437	More than 20 dBc	20
High	2462	More than 20 dBc	20


PLOT OF TEST DATA

802.11b mode

Conducted Spurious Emissions, 802.11b mode, 30 MHz ~ 10 GHz, Lowest Channel (Main)




Conducted Spurious Emissions, 802.11b mode, 10 GHz ~ 25 GHz, Lowest Channel (Main)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11b mode, 30 MHz ~ 10 GHz, Middle Channel (Main)




Conducted Spurious Emissions, 802.11b mode, 10 GHz ~ 25 GHz, Middle Channel (Main)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11b mode, 30 MHz ~ 10 GHz, Highest Channel (Main)




Conducted Spurious Emissions, 802.11b mode, 10 GHz ~ 25 GHz, Highest Channel (Main)




PLOT OF TEST DATA

802.11g mode

Conducted Spurious Emissions, 802.11g mode, 30 MHz ~ 10 GHz, Lowest Channel (Main)




Conducted Spurious Emissions, 802.11g mode, 10 GHz ~ 25 GHz, Lowest Channel (Main)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11g mode, 30 MHz ~ 10 GHz, Middle Channel (Main)




Conducted Spurious Emissions, 802.11g mode, 10 GHz ~ 25 GHz, Middle Channel (Main)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11g mode, 30 MHz ~ 10 GHz, Highest Channel (Main)




Conducted Spurious Emissions, 802.11g mode, 10 GHz ~ 25 GHz, Highest Channel (Main)




PLOT OF TEST DATA

802.11n(HT20) mode

Conducted Spurious Emissions, 802.11n(HT20) mode, 30 MHz ~ 10 GHz, Lowest Channel (Main)




Conducted Spurious Emissions, 802.11n(HT20) mode, 10 GHz ~ 25 GHz, Lowest Channel (Main)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11n(HT20) mode, 30 MHz ~ 10 GHz, Middle Channel (Main)




Conducted Spurious Emissions, 802.11n(HT20) mode, 10 GHz ~ 25 GHz, Middle Channel (Main)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11n(HT20) mode, 30 MHz ~ 10 GHz, Highest Channel (Main)




Conducted Spurious Emissions, 802.11n(HT20) mode, 10 GHz ~ 25 GHz, Highest Channel (Main)




PLOT OF TEST DATA

802.11b mode

Conducted Spurious Emissions, 802.11b mode, 30 MHz ~ 10 GHz, Lowest Channel (Aux)




Conducted Spurious Emissions, 802.11b mode, 10 GHz ~ 25 GHz, Lowest Channel (Aux)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11b mode, 30 MHz ~ 10 GHz, Middle Channel (Aux)




Conducted Spurious Emissions, 802.11b mode, 10 GHz ~ 25 GHz, Middle Channel (Aux)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11b mode, 30 MHz ~ 10 GHz, Highest Channel (Aux)




Conducted Spurious Emissions, 802.11b mode, 10 GHz ~ 25 GHz, Highest Channel (Aux)




PLOT OF TEST DATA

802.11g mode

Conducted Spurious Emissions, 802.11g mode, 30 MHz ~ 10 GHz, Lowest Channel (Aux)




Conducted Spurious Emissions, 802.11g mode, 10 GHz ~ 25 GHz, Lowest Channel (Aux)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11g mode, 30 MHz ~ 10 GHz, Middle Channel (Aux)




Conducted Spurious Emissions, 802.11g mode, 10 GHz ~ 25 GHz, Middle Channel (Aux)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11g mode, 30 MHz ~ 10 GHz, Highest Channel (Aux)




Conducted Spurious Emissions, 802.11g mode, 10 GHz ~ 25 GHz, Highest Channel (Aux)




PLOT OF TEST DATA

802.11n(HT20) mode

Conducted Spurious Emissions, 802.11n(HT20) mode, 30 MHz ~ 10 GHz, Lowest Channel (Aux)




Conducted Spurious Emissions, 802.11n(HT20) mode, 10 GHz ~ 25 GHz, Lowest Channel (Aux)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11n(HT20) mode, 30 MHz ~ 10 GHz, Middle Channel (Aux)




Conducted Spurious Emissions, 802.11n(HT20) mode, 10 GHz ~ 25 GHz, Middle Channel (Aux)




PLOT OF TEST DATA

Conducted Spurious Emissions, 802.11n(HT20) mode, 30 MHz ~ 10 GHz, Highest Channel (Aux)



Conducted Spurious Emissions, 802.11n(HT20) mode, 10 GHz ~ 25 GHz, Highest Channel (Aux)




PLOT OF TEST DATA

802.11b mode

Band Edge, 802.11b mode, Lowest Channel (Main)




Band Edge, 802.11b mode Highest Channel (Main)




PLOT OF TEST DATA

802.11g mode

Band Edge, 802.11g mode, Lowest Channel (Main)




Band Edge, 802.11g mode Highest Channel (Main)




PLOT OF TEST DATA

802.11n(HT20) mode

Band Edge, 802.11n(HT20) mode, Lowest Channel (Main)



Band Edge, 802.11n(HT20) mode Highest Channel (Main)




PLOT OF TEST DATA

802.11b mode

Band Edge, 802.11b mode, Lowest Channel (Aux)




Band Edge, 802.11b mode Highest Channel (Aux)




PLOT OF TEST DATA

802.11g mode

Band Edge, 802.11g mode, Lowest Channel (Aux)




Band Edge, 802.11g mode Highest Channel (Aux)




PLOT OF TEST DATA

802.11n(HT20) mode

Band Edge, 802.11n(HT20) mode, Lowest Channel (Aux)



Band Edge, 802.11n(HT20) mode Highest Channel (Aux)



TEST DATA

8.7 Radiated Spurious Emissions

FCC §15.247(d), RSS-210 A8.5

Test Mode : Set to Lowest channel, Middle channel and Highest channel

Result:

802.11b mode

Lowest Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1498.00	48.7	H	Peak	-4.6	44.1	74.0	29.9
1498.00	37.3	H	Average	-4.6	32.7	54.0	21.3
1594.00	48.4	V	Peak	-4.3	44.1	74.0	29.9
1594.00	36.4	V	Average	-4.3	32.1	54.0	21.9
1662.00	48.1	V	Peak	-4.1	44.0	74.0	30.0
1662.00	36.5	V	Average	-4.1	32.4	54.0	21.6
2246.00	49.6	V	Peak	-2.4	47.2	74.0	26.8
2246.00	37.3	V	Average	-2.4	34.9	54.0	19.1
4824.00	41.4	V	Peak	9.3	50.7	74.0	23.3
4824.00	32.6	V	Average	9.3	41.9	54.0	12.1
7236.00	40.1	V	Peak	15.7	55.8	74.0	18.2
7236.00	28.3	V	Average	15.7	44.0	54.0	10.0

TEST DATA

Middle Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1496.00	49.1	H	Peak	-4.6	44.5	74.0	29.5
1496.00	37.5	H	Average	-4.6	32.9	54.0	21.1
1594.00	48.9	H	Peak	-4.3	44.6	74.0	29.4
1594.00	36.6	H	Average	-4.3	32.3	54.0	21.7
1661.00	53.8	V	Peak	-4.1	49.7	74.0	24.3
1661.00	36.6	V	Average	-4.1	32.5	54.0	21.5
2243.00	49.7	V	Peak	-2.5	47.2	74.0	26.8
2243.00	37.2	V	Average	-2.5	34.7	54.0	19.3
4874.00	40.8	V	Peak	9.5	50.3	74.0	23.7
4874.00	32.7	V	Average	9.5	42.2	54.0	11.8
7311.00	39.8	V	Peak	16.2	56.0	74.0	18.0
7311.00	28.8	V	Average	16.2	45.0	54.0	9.0

Highest Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1328.00	48.2	H	Peak	-5.0	43.2	74.0	30.8
1328.00	37.0	H	Average	-5.0	32.0	54.0	22.0
1496.00	50.3	V	Peak	-4.6	45.7	74.0	28.3
1496.00	37.5	V	Average	-4.6	32.9	54.0	21.1
1662.00	48.7	V	Peak	-4.1	44.6	74.0	29.4
1662.00	36.6	V	Average	-4.1	32.5	54.0	21.5
2246.00	49.5	V	Peak	-2.4	47.1	74.0	26.9
2246.00	37.4	V	Average	-2.4	35.0	54.0	19.0
4924.00	41.0	V	Peak	9.6	50.6	74.0	23.4
4924.00	31.9	V	Average	9.6	41.5	54.0	12.5
7386.00	39.9	V	Peak	16.2	56.1	74.0	17.9
7386.00	28.4	V	Average	16.2	44.6	54.0	9.4

TEST DATA

802.11g mode

Lowest Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1329.00	48.6	H	Peak	-5.0	43.6	74.0	30.4
1329.00	36.8	H	Average	-5.0	31.8	54.0	22.2
1441.00	47.8	H	Peak	-4.7	43.1	74.0	30.9
1441.00	36.6	H	Average	-4.7	31.9	54.0	22.1
1496.00	49.7	H	Peak	-4.6	45.1	74.0	28.9
1496.00	37.6	H	Average	-4.6	33.0	54.0	21.0
1594.00	48.4	V	Peak	-4.3	44.1	74.0	29.9
1594.00	36.8	V	Average	-4.3	32.5	54.0	21.5
1662.00	49.0	V	Peak	-4.1	44.9	74.0	29.1
1662.00	36.8	V	Average	-4.1	32.7	54.0	21.3
2246.00	49.4	V	Peak	-2.4	47.0	74.0	27.0
2246.00	37.6	V	Average	-2.4	35.2	54.0	18.8

TEST DATA

Middle Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1197.00	48.3	H	Peak	-5.4	42.9	74.0	31.1
1197.00	36.5	H	Average	-5.4	31.1	54.0	22.9
1330.00	48.3	H	Peak	-5.0	43.3	74.0	30.7
1330.00	37.2	H	Average	-5.0	32.2	54.0	21.8
1496.00	49.6	H	Peak	-4.6	45.0	74.0	29.0
1496.00	38.0	H	Average	-4.6	33.4	54.0	20.6
1594.00	49.8	V	Peak	-4.3	45.5	74.0	28.5
1594.00	37.5	V	Average	-4.3	33.2	54.0	20.8
1661.00	52.6	V	Peak	-4.1	48.5	74.0	25.5
1661.00	37.5	V	Average	-4.1	33.4	54.0	20.6
2245.00	49.9	V	Peak	-2.4	47.5	74.0	26.5
2245.00	38.2	V	Average	-2.4	35.8	54.0	18.2

Highest Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1328.00	47.9	H	Peak	-5.0	42.9	74.0	31.1
1328.00	36.9	H	Average	-5.0	31.9	54.0	22.1
1440.00	47.6	H	Peak	-4.7	42.9	74.0	31.1
1440.00	36.6	H	Average	-4.7	31.9	54.0	22.1
1498.00	49.9	H	Peak	-4.6	45.3	74.0	28.7
1498.00	37.9	H	Average	-4.6	33.3	54.0	20.7
1596.00	48.4	V	Peak	-4.3	44.1	74.0	29.9
1596.00	36.8	V	Average	-4.3	32.5	54.0	21.5
1663.00	49.2	V	Peak	-4.1	45.1	74.0	28.9
1663.00	36.9	V	Average	-4.1	32.8	54.0	21.2
2245.00	49.6	V	Peak	-2.4	47.2	74.0	26.8
2245.00	37.4	V	Average	-2.4	35.0	54.0	19.0

TEST DATA

802.11n(HT20) mode

Lowest Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1440.00	47.8	H	Peak	-4.7	43.1	74.0	30.9
1440.00	36.2	H	Average	-4.7	31.5	54.0	22.5
1498.00	48.4	H	Peak	-4.6	43.8	74.0	30.2
1498.00	37.2	H	Average	-4.6	32.6	54.0	21.4
1595.00	47.6	V	Peak	-4.3	43.3	74.0	30.7
1595.00	36.0	V	Average	-4.3	31.7	54.0	22.3
1661.00	48.3	V	Peak	-4.1	44.2	74.0	29.8
1661.00	36.2	V	Average	-4.1	32.1	54.0	21.9
2245.00	48.9	V	Peak	-2.4	46.5	74.0	27.5
2245.00	36.8	V	Average	-2.4	34.4	54.0	19.6
4924.00	39.2	H	Peak	9.6	48.8	74.0	25.2
4924.00	27.3	H	Average	9.6	36.9	54.0	17.1

TEST DATA

Middle Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1328.00	49.0	H	Peak	-5.0	44.0	74.0	30.0
1328.00	36.8	H	Average	-5.0	31.8	54.0	22.2
1497.00	50.4	H	Peak	-4.6	45.8	74.0	28.2
1497.00	37.9	H	Average	-4.6	33.3	54.0	20.7
1594.00	48.0	V	Peak	-4.3	43.7	74.0	30.3
1594.00	36.7	V	Average	-4.3	32.4	54.0	21.6
1661.00	50.9	V	Peak	-4.1	46.8	74.0	27.2
1661.00	36.8	V	Average	-4.1	32.7	54.0	21.3
2246.00	49.7	V	Peak	-2.4	47.3	74.0	26.7
2246.00	37.4	V	Average	-2.4	35.0	54.0	19.0
4874.00	39.8	V	Peak	9.5	49.3	74.0	24.7
4874.00	27.9	V	Average	9.5	37.4	54.0	16.6

Highest Channel (Main antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1329.00	48.1	H	Peak	-5.0	43.1	74.0	30.9
1329.00	36.7	H	Average	-5.0	31.7	54.0	22.3
1497.00	49.2	H	Peak	-4.6	44.6	74.0	29.4
1497.00	37.6	H	Average	-4.6	33.0	54.0	21.0
1594.00	48.5	V	Peak	-4.3	44.2	74.0	29.8
1594.00	36.2	V	Average	-4.3	31.9	54.0	22.1
1664.00	49.8	V	Peak	-4.1	45.7	74.0	28.3
1664.00	36.3	V	Average	-4.1	32.2	54.0	21.8
2245.00	48.3	H	Peak	-2.4	45.9	74.0	28.1
2245.00	36.8	H	Average	-2.4	34.4	54.0	19.6
4924.00	39.0	H	Peak	9.6	48.6	74.0	25.4
4924.00	27.8	H	Average	9.6	37.4	54.0	16.6

TEST DATA

802.11b mode

Lowest Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1498.00	48.8	H	Peak	-4.6	44.2	74.0	29.8
1498.00	37.5	H	Average	-4.6	32.9	54.0	21.1
1594.00	47.9	V	Peak	-4.3	43.6	74.0	30.4
1594.00	36.5	V	Average	-4.3	32.2	54.0	21.8
1662.00	48.6	V	Peak	-4.1	44.5	74.0	29.5
1662.00	36.5	V	Average	-4.1	32.4	54.0	21.6
2244.00	49.2	V	Peak	-2.5	46.7	74.0	27.3
2244.00	37.3	V	Average	-2.5	34.8	54.0	19.2
4824.00	41.4	V	Peak	9.3	50.7	74.0	23.3
4824.00	33.4	V	Average	9.3	42.7	54.0	11.3
7236.00	40.2	V	Peak	15.7	55.9	74.0	18.1
7236.00	28.4	V	Average	15.7	44.1	54.0	9.9

TEST DATA

Middle Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1329.00	47.7	H	Peak	-5.0	42.7	74.0	31.3
1329.00	36.9	H	Average	-5.0	31.9	54.0	22.1
1594.00	49.2	V	Peak	-4.3	44.9	74.0	29.1
1594.00	36.6	V	Average	-4.3	32.3	54.0	21.7
1663.00	48.4	V	Peak	-4.1	44.3	74.0	29.7
1663.00	36.4	V	Average	-4.1	32.3	54.0	21.7
2246.00	49.6	V	Peak	-2.4	47.2	74.0	26.8
2246.00	37.5	V	Average	-2.4	35.1	54.0	18.9
4874.00	41.6	V	Peak	9.5	51.1	74.0	22.9
4874.00	34.1	V	Average	9.5	43.6	54.0	10.4
7311.00	39.5	V	Peak	16.2	55.7	74.0	18.3
7311.00	28.9	V	Average	16.2	45.1	54.0	8.9

Highest Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1329.00	47.9	H	Peak	-5.0	42.9	74.0	31.1
1329.00	36.9	H	Average	-5.0	31.9	54.0	22.1
1498.00	49.0	V	Peak	-4.6	44.4	74.0	29.6
1498.00	37.5	V	Average	-4.6	32.9	54.0	21.1
1596.00	47.9	V	Peak	-4.3	43.6	74.0	30.4
1596.00	36.4	V	Average	-4.3	32.1	54.0	21.9
1663.00	48.9	V	Peak	-4.1	44.8	74.0	29.2
1663.00	36.7	V	Average	-4.1	32.6	54.0	21.4
2246.00	49.5	V	Peak	-2.4	47.1	74.0	26.9
2246.00	37.6	V	Average	-2.4	35.2	54.0	18.8
4924.00	42.1	V	Peak	9.6	51.7	74.0	22.3
4924.00	32.8	V	Average	9.6	42.4	54.0	11.6

TEST DATA

802.11g mode

Lowest Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1329.00	48.2	H	Peak	-5.0	43.2	74.0	30.8
1329.00	36.9	H	Average	-5.0	31.9	54.0	22.1
1497.00	49.0	H	Peak	-4.6	44.4	74.0	29.6
1497.00	37.9	H	Average	-4.6	33.3	54.0	20.7
1594.00	48.8	V	Peak	-4.3	44.5	74.0	29.5
1594.00	36.8	V	Average	-4.3	32.5	54.0	21.5
1661.00	48.7	V	Peak	-4.1	44.6	74.0	29.4
1661.00	36.9	V	Average	-4.1	32.8	54.0	21.2
2247.00	49.6	V	Peak	-2.4	47.2	74.0	26.8
2247.00	37.5	V	Average	-2.4	35.1	54.0	18.9
4824.00	40.5	V	Peak	9.3	49.8	74.0	24.2
4824.00	28.1	V	Average	9.3	37.4	54.0	16.6

TEST DATA

Middle Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1329.00	48.6	H	Peak	-5.0	43.6	74.0	30.4
1329.00	37.0	H	Average	-5.0	32.0	54.0	22.0
1496.00	49.9	H	Peak	-4.6	45.3	74.0	28.7
1496.00	37.7	H	Average	-4.6	33.1	54.0	20.9
1594.00	48.5	V	Peak	-4.3	44.2	74.0	29.8
1594.00	36.9	V	Average	-4.3	32.6	54.0	21.4
1662.00	48.6	V	Peak	-4.1	44.5	74.0	29.5
1662.00	37.1	V	Average	-4.1	33.0	54.0	21.0
2244.00	49.6	V	Peak	-2.5	47.1	74.0	26.9
2244.00	37.7	V	Average	-2.5	35.2	54.0	18.8
4874.00	40.5	V	Peak	9.5	50.0	74.0	24.0
4874.00	28.4	V	Average	9.5	37.9	54.0	16.1

Highest Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1332.00	48.8	H	Peak	-5.0	43.8	74.0	30.2
1332.00	37.0	H	Average	-5.0	32.0	54.0	22.0
1441.00	48.2	H	Peak	-4.7	43.5	74.0	30.5
1441.00	36.7	H	Average	-4.7	32.0	54.0	22.0
1497.00	49.3	H	Peak	-4.6	44.7	74.0	29.3
1497.00	37.7	H	Average	-4.6	33.1	54.0	20.9
1662.00	48.6	V	Peak	-4.1	44.5	74.0	29.5
1662.00	36.9	V	Average	-4.1	32.8	54.0	21.2
2243.00	49.6	V	Peak	-2.5	47.1	74.0	26.9
2243.00	37.6	V	Average	-2.5	35.1	54.0	18.9
4924.00	39.9	V	Peak	9.6	49.5	74.0	24.5
4924.00	28.2	V	Average	9.6	37.8	54.0	16.2

TEST DATA

802.11n(HT20) mode

Lowest Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1328.00	48.3	H	Peak	-5.0	43.3	74.0	30.7
1328.00	37.0	H	Average	-5.0	32.0	54.0	22.0
1497.00	49.3	H	Peak	-4.6	44.7	74.0	29.3
1497.00	37.8	H	Average	-4.6	33.2	54.0	20.8
1596.00	47.7	V	Peak	-4.3	43.4	74.0	30.6
1596.00	36.5	V	Average	-4.3	32.2	54.0	21.8
1661.00	48.6	V	Peak	-4.1	44.5	74.0	29.5
1661.00	36.7	V	Average	-4.1	32.6	54.0	21.4
2244.00	50.4	V	Peak	-2.5	47.9	74.0	26.1
2244.00	37.6	V	Average	-2.5	35.1	54.0	18.9
4824.00	39.5	V	Peak	9.3	48.8	74.0	25.2
4824.00	28.3	V	Average	9.3	37.6	54.0	16.4

TEST DATA

Middle Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1197.00	47.8	H	Peak	-5.4	42.4	74.0	31.6
1197.00	36.4	H	Average	-5.4	31.0	54.0	23.0
1328.00	49.0	H	Peak	-5.0	44.0	74.0	30.0
1328.00	37.0	H	Average	-5.0	32.0	54.0	22.0
1497.00	49.5	H	Peak	-4.6	44.9	74.0	29.1
1497.00	37.9	H	Average	-4.6	33.3	54.0	20.7
1594.00	48.2	V	Peak	-4.3	43.9	74.0	30.1
1594.00	36.6	V	Average	-4.3	32.3	54.0	21.7
1661.00	49.5	V	Peak	-4.1	45.4	74.0	28.6
1661.00	36.9	V	Average	-4.1	32.8	54.0	21.2
2243.00	49.9	V	Peak	-2.5	47.4	74.0	26.6
2243.00	37.8	V	Average	-2.5	35.3	54.0	18.7

Highest Channel (Aux antenna port)

Frequency (MHz)	Reading (dB μ V/m)	Pol* (H/V)	Detector	AF+CL+Amp (dB)**	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1441.00	47.9	H	Peak	-4.7	43.2	74.0	30.8
1441.00	36.7	H	Average	-4.7	32.0	54.0	22.0
1496.00	49.4	H	Peak	-4.6	44.8	74.0	29.2
1496.00	37.9	H	Average	-4.6	33.3	54.0	20.7
1594.00	49.2	V	Peak	-4.3	44.9	74.0	29.1
1594.00	36.6	V	Average	-4.3	32.3	54.0	21.7
1661.00	49.9	V	Peak	-4.1	45.8	74.0	28.2
1661.00	36.9	V	Average	-4.1	32.8	54.0	21.2
2245.00	49.9	V	Peak	-2.4	47.5	74.0	26.5
2245.00	37.5	V	Average	-2.4	35.1	54.0	18.9
4924.00	40.0	V	Peak	9.6	49.6	74.0	24.4
4924.00	28.3	V	Average	9.6	37.9	54.0	16.1


Note:

1. **Pol. H = Horizontal V = Vertical*
2. ***AF + CL + Amp. = Antenna Factor + Cable Loss + Amplifier.*
3. *Other spurious are 20 dB below than Fundamental.*
4. *The radiated emissions testing were made by rotating EUT through three orthogonal axes and rotating the receive antenna with horizontal, Vertical polarization.
The worst date was recorded.*
5. *For measurements the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.*
6. *The spectrum is measured from 9 kHz to 10th harmonic and the worst-case emissions are reported. No significant emissions were found beyond the 4th harmonic for this device.*


PLOT OF TEST DATA

802.11b mode

Restricted Band Spurious Emissions, 802.11b, Lowest channel Peak (Main)




Restricted Band Spurious Emissions, 802.11b, Lowest channel Average (Main)




PLOT OF TEST DATA

Restricted Band Spurious Emissions, 802.11b, Highest channel Peak (Main)




Restricted Band Spurious Emissions, 802.11b, Highest channel Average (Main)




PLOT OF TEST DATA

802.11b mode

Restricted Band Spurious Emissions, 802.11b, Lowest channel Peak (Aux)




Restricted Band Spurious Emissions, 802.11b, Lowest channel Average (Aux)




PLOT OF TEST DATA

Restricted Band Spurious Emissions, 802.11b, Highest channel Peak (Aux)




Restricted Band Spurious Emissions, 802.11b, Highest channel Average (Aux)




PLOT OF TEST DATA

802.11g mode

Restricted Band Spurious Emissions, 802.11g, Lowest channel Peak (Main)




Restricted Band Spurious Emissions, 802.11g, Lowest channel Average (Main)




PLOT OF TEST DATA

Restricted Band Spurious Emissions, 802.11g, Highest channel Peak (Main)




Restricted Band Spurious Emissions, 802.11g, Highest channel Average (Main)




PLOT OF TEST DATA

802.11g mode

Restricted Band Spurious Emissions, 802.11g, Lowest channel Peak (Aux)




Restricted Band Spurious Emissions, 802.11g, Lowest channel Average (Aux)




PLOT OF TEST DATA

Restricted Band Spurious Emissions, 802.11g, Highest channel Peak (Aux)




Restricted Band Spurious Emissions, 802.11g, Highest channel Average (Aux)




PLOT OF TEST DATA

802.11n(HT20) mode

Restricted Band Spurious Emissions, 802.11n(HT20), Lowest channel Peak (Main)




Restricted Band Spurious Emissions, 802.11n(HT20), Lowest channel Average (Main)




PLOT OF TEST DATA

Restricted Band Spurious Emissions, 802.11n(HT20), Highest channel Peak (Main)




Restricted Band Spurious Emissions, 802.11n(HT20), Highest channel Average (Main)




PLOT OF TEST DATA

802.11n(HT20) mode

Restricted Band Spurious Emissions, 802.11n(HT20), Lowest channel Peak (Aux)




Restricted Band Spurious Emissions, 802.11n(HT20), Lowest channel Average (Aux)




PLOT OF TEST DATA

Restricted Band Spurious Emissions, 802.11n(HT20), Highest channel Peak (Aux)



Restricted Band Spurious Emissions, 802.11n(HT20), Highest channel Average (Aux)



Note: For the radiated emission field strength measurements at the bandedges, the resolution bandwidth was set to 1 MHz then the video bandwidth was set to 1 MHz for peak measurements and 10 Hz for average measurements. Peak detector was used.

9. ACCURACY OF MEASUREMENT

The Measurement Uncertainties stated were calculated in accordance with the requirements of measurement uncertainty contained in CISPR 16-4-2 with the confidence level of 95%

1. Conducted Uncertainty Calculation

Source of Uncertainty	X_i	Uncertainty of X_i		Coverage factor k	$u(X_i)$ (dB)	C_i	$C_i u(X_i)$ (dB)
		Value (dB)	Probability Distribution				
Receiver reading	RI	± 0.1	normal 1	1.000	0.1	1	0.1
Attenuation AMN-Receiver	LC	± 0.08	normal 2	2.000	0.04	1	0.04
AMN Voltage division factor	LAMN	± 0.8	normal 2	2.000	0.4	1	0.4
Sine wave voltage	dVSW	± 2.00	normal 2	2.000	1.00	1	1.00
Pulse amplitude response	dVPA	± 1.50	rectangular	1.732	0.87	1	0.87
Pulse repetition rate response	dVPR	± 1.50	rectangular	1.732	0.87	1	0.87
Noise floor proximity	dVNF	± 0.00	-	-	0.00	1	0.00
AMN Impedance	dZ	± 1.80	triangular	2.449	0.73	1	0.73
Ⓐ Mismatch	M	+ 0.70	U-Shaped	1.414	0.49	1	0.49
Ⓑ Mismatch	M	- 0.80	U-Shaped	1.414	- 0.56	1	- 0.56
Measurement System Repeatability	RS	0.05	normal 1	1.000	0.05	1	0.05
Remark	Ⓐ: AMN-Receiver Mismatch : + Ⓑ: AMN-Receiver Mismatch : -						
Combined Standard Uncertainty	Normal			± 1.88			
Expanded Uncertainty U	Normal ($k = 2$)			± 3.76			

2. Radiation Uncertainty Calculation

Source of Uncertainty	X_i	Uncertainty of X_i		Coverage factor k	$u(X_i)$ (dB)	C_i	$C_i u(X_i)$ (dB)
		Value (dB)	Probability Distribution				
Receiver reading	RI	± 0.10	normal 1	1.000	0.10	1	0.10
Sine wave voltage	dVsw	± 2.00	normal 2	2.000	1.00	1	1.00
Pulse amplitude response	dVpa	± 1.50	rectangular	1.732	0.87	1	0.87
Pulse repetition rate response	dVpr	± 1.50	rectangular	1.732	0.87	1	0.87
Noise floor proximity	dVnf	± 0.50	normal 2	2.000	0.25	1	0.25
Antenna Factor Calibration	AF	± 1.50	normal 2	2.000	0.75	1	0.75
Attenuation Antenna-receiver	CL	± 0.52	normal 2	2.000	0.26	1	0.26
Antenna Directivity	AD	± 1.00	rectangular	1.732	0.58	1	0.58
Antenna Factor Height Dependence	AH	± 0.50	rectangular	1.732	0.29	1	0.29
Antenna Phase Centre Variation	AP	± 0.30	rectangular	1.732	0.17	1	0.17
Antenna Factor Frequency Interpolation	AI	± 0.30	rectangular	1.732	0.17	1	0.17
Site Imperfections	SI	± 4.00	triangular	2.449	1.63	1	1.63
Measurement Distance Variation	DV	± 0.10	rectangular	1.732	0.06	1	0.06
Antenna Balance	Dbal	± 0.90	rectangular	1.732	0.52	1	0.52
Cross Polarisation	DCross	± 0.90	rectangular	1.732	0.52	1	0.52
Ⓐ Mismatch	M	+ 0.25	U-Shaped	1.414	0.18	1	0.18
Ⓑ Mismatch	M	- 0.26	U-Shaped	1.414	- 0.18	1	- 0.18
Ⓒ Mismatch	M	+ 0.98	U-Shaped	1.414	0.69	1	0.69
Ⓓ Mismatch	M	- 1.11	U-Shaped	1.414	- 0.79	1	- 0.79
Measurement System Repeatability	RS	0.09	normal 1	1.000	0.09	1	0.09
Remark	Ⓐ: Biconical Antenna-receiver Mismatch : + (< 200 MHz) Ⓑ: Biconical Antenna-receiver Mismatch : - (< 200 MHz) Ⓒ: Log Periodic Antenna-receiver Mismatch : + (≥ 200 MHz) Ⓓ: Log Periodic Antenna-receiver Mismatch : - (≥ 200 MHz)						
Combined Standard Uncertainty	Normal			± 2.63 (< 200 MHz) ± 2.74 (≥ 200 MHz)			
Expanded Uncertainty U	Normal ($k = 2$)			± 5.26 (< 200 MHz) ± 5.48 (≥ 200 MHz)			

10. TEST EQUIPMENT

No.	Instrument	Manufacturer	Model	Serial No.	Calibration Date	Calibration Interval
1	*Test Receiver	R & S	ESCS 30	833364/020	Jan. 14 2011	1 year
2	*Test Receiver	R & S	ESCS 30	100302	Oct. 12 2011	1 year
3	*Amplifier	R & S	SCU01	10029	Apr. 06 2011	1 year
4	*Amplifier	Sonoma Instrument	310N	291916	Jul. 19 2011	1 year
5	*Amplifier	R & S	SCU-26	10011	Jun. 01 2011	1 year
6	*Pre Amplifier	HP	8449B	3008A00107	Jan. 13 2011	1 year
7	*Pre Amplifier	HP	8447F	2805A03351	Oct. 06 2011	1 year
8	Spectrum Analyzer	HP	8593E	3926A04282	Oct. 24 2011	1 year
9	*Spectrum Analyzer	Agilent	E4440A	MY44303257	Jul. 19 2011	1 year
10	Spectrum Analyzer	Agilent	N9020A	MY51110087	Apr. 16 2011	1 year
11	*Spectrum Analyzer	R & S	FSP40	100361	Jul. 19 2011	1 year
12	*Loop Antenna	EMCO	6502	8911-2436	Jan. 19 2010	2 year
13	*Power Meter	R & S	NRVS	835360/002	Jan. 13 2011	1 year
14	Peak Power Sensor	R & S	NRV-Z32	836019/028	Oct. 25 2011	1 year
15	*Biconical Log Antenna	ARA	LPB-2520/A	1180	Apr. 14 2010	2 year
16	*Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-508	Dec. 24 2010	2 year
17	*Horn Antenna	Q-par Angus	QSH20S20	8179	Apr. 12 2010	2 year
18	*Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-257	Apr. 14 2010	2 year
19	Logbicon Antenna	SCHWARZBECK	VULB9166	1067	Jul. 14 2010	2 year
20	*LISN	R & S	ESH3-Z5	833874/006	Oct. 12 2011	1 year
21	LISN	R & S	ESH2-Z5	100227	Apr. 06 2011	1 year
22	*Position Controller	DAEIL EMC	N/A	N/A	N/A	N/A
23	*Turn Table	DAEIL EMC	N/A	N/A	N/A	N/A
24	*Antenna Mast	DAEIL EMC	N/A	N/A	N/A	N/A
25	*Anechoic Chamber	EM Eng.	N/A	N/A	N/A	N/A
26	*Shielded Room	EM Eng.	N/A	N/A	N/A	N/A
27	*Position Controller	Seo-Young EMC	N/A	N/A	N/A	N/A
28	*Turn Table	Seo-Young EMC	N/A	N/A	N/A	N/A
29	*Antenna Mast	Seo-Young EMC	N/A	N/A	N/A	N/A
30	*Anechoic Chamber	Seo-Young EMC	N/A	N/A	N/A	N/A
31	*Shielded Room	Seo-Young EMC	N/A	N/A	N/A	N/A

*) Test equipment used during the test